

Python for Science and Engg: Interactive Plotting

FOSSEE

Department of Aerospace Engineering
IIT Bombay

25 September, 2010
Day 1, Session 1

Workshop Schedule: Day 1

Session 1 Sat 11:00–12:00

Session 2 Sat 12:00–13:00

Session 3 Sat 14:00–15:00

Session 4 Sat 15:10–16:10

Session 5 Thu 16:20–17:20

Workshop Schedule: Day 2

Session 1 Sun 09:00–10:00

Session 2 Sun 10:00–11:00

Session 3 Sun 11:10–12:10

Session 4 Sun 12:10–13:10

Exercises Sun 14:25–15:10

Session 5 Sun 15:20–16:20

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots

Checklist

- 1 IPython
- 2 Editor - we recommend **scite**
- 3 Data files:
 - `sslc1.txt`
 - `pendulum.txt`
 - `pos.txt`
 - `holmes.txt`
 - `anag.txt`
- 4 Python scripts:
 - `sslc_allreg.py`
 - `sslc_science.py`
- 5 Images
 - `lena.png`
 - `smoothing.gif`

About the Workshop

Intended Audience

- Engg., Mathematics and Science teachers.
- Interested students from similar streams.

Goal: Successful participants will be able to

- Use Python as plotting, computational tool.
- Understand how to use Python as a scripting and problem solving language.
- Train students for the same.

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots

Starting up ...

```
$ ipython -pylab
```

```
In []: print "Hello, World!"  
Hello, World!
```

Exiting

```
In []: ^D(Ctrl-D)  
Do you really want to exit([y]/n)? y
```

An alternative to IPython is bpython

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops**
- 4 Plotting
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots

Loops

Breaking out of loops

```
In []: while True:  
    ...:     print "Hello, World!"  
    ...:
```

Hello, World!

Hello, World! ^C (Ctrl-C)

KeyboardInterrupt


Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting**
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting**
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots

First Plot



```
In []: x = linspace(0, 2*pi, 50)  
In []: plot(x, sin(x))
```

Walkthrough

```
x = linspace(start, stop, num)
```

returns **num** evenly spaced points, in the interval **[start, stop]**.

```
x[0] = start
```

```
x[num - 1] = end
```


```
plot(x, y)
```

plots **x** and **y** using default line style and color

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting**
 - Drawing plots
 - Decoration**
 - More decoration
- 5 Multiple plots

Adding Labels



```
In []: xlabel('x')
```

```
In []: ylabel('sin(x)')
```


Another example

```
In []: clf()
```

Clears the plot area.

```
In []: y = linspace(0, 2*pi, 50)
```

```
In []: plot(y, sin(2*y))
```

```
In []: xlabel('y')
```

```
In []: ylabel('sin(2y)')
```


Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting**
 - Drawing plots
 - Decoration
 - More decoration**
- 5 Multiple plots

Title and Legends


```
In []: title('Sinusoids')
```

```
In []: legend(['sin(2y)'])
```



Legend Placement

```
In []: legend(['sin(2y)'], loc = 'center')
```



'best'
'right'
'center'

Saving & Closing

```
In []: savefig('sin.png')
```

```
In []: close()
```

Supported formats to store images:

- png
- eps - Easy to embed in LaTeX files
- emf
- pdf
- ps
- raw
- rgba
- svg

Outline

- 1 Checklist
- 2 Starting up Ipython
- 3 Loops
- 4 Plotting
 - Drawing plots
 - Decoration
 - More decoration
- 5 Multiple plots**

Overlaid Plots

```
In []: clf()  
In []: plot(y, sin(y))  
In []: plot(y, cos(y))  
In []: xlabel('y')  
In []: ylabel('f(y)')  
In []: legend(['sin(y)', 'cos(y)'])
```

By default plots would be overlaid!

Plotting separate figures


```
In []: clf()
In []: figure(1)
In []: plot(y, sin(y))
In []: figure(2)
In []: plot(y, cos(y))
In []: savefig('cosine.png')
In []: figure(1)
In []: title('sin(y)')
In []: savefig('sine.png')
In []: close()
In []: close()
```


Showing it better

```
In []: plot(y, cos(y), 'r')
```


```
In []: clf()
```

```
In []: plot(y, sin(y), 'g', linewidth=2)
```



Annotating

```
In []: annotate('local max', xy=(1.5, 1))
```



Axes lengths

Getting axes lengths

```
In []: xmin, xmax = xlim()
```


```
In []: ymin, ymax = ylim()
```

Set the axes limits

```
In []: xlim(xmin, 2*pi )
```


```
In []: ylim(ymin-0.2, ymax+0.2)
```

Axes lengths



Review Problem

- 1 Plot x , $-x$, $\sin(x)$, $x\sin(x)$ in range -5π to 5π
- 2 Add a legend
- 3 Annotate the origin
- 4 Set axes limits to the range of x



Review Problem ...

Plotting ...

```
In []: x=linspace(-5*pi, 5*pi, 500)
In []: plot(x, x, 'b')
In []: plot(x, -x, 'b')
In []: plot(x, sin(x), 'g', linewidth=2)
In []: plot(x, x*sin(x), 'r',
            linewidth=3)

:
```

Review Problem ...

Legend & Annotation...

```
In []: legend(['x', '-x', 'sin(x)',  
              'xsin(x)'])
```

```
In []: annotate('origin', xy = (0, 0))
```

Setting Axes limits...

```
In []: xlim(-5*pi, 5*pi)
```

```
In []: ylim(-5*pi, 5*pi)
```

Command History

Use the `%hist` **magic** command of IPython

```
In []: %hist
```

This displays all the commands typed in so far aka Command History.

Careful about errors!

`%hist` will contain the errors as well.

Magic Commands?

Magic commands are commands provided by IPython to make our life easier.

Saving commands into script

Use the **%save magic** command of IPython

```
%save script_name line_numbers
```

Line numbers can be specified individually separated by commas or as a range separated by a dash.

```
%save four_plot.py 16 18-27
```

This saves from the history the commands entered on line numbers **16, 18, 19, 20, ... 27**

Python Scripts...

Now, four_plot.py is called a Python Script.

- run the script in IPython using
`%run four_plot.py`

`NameError: name 'linspace' is not defined`

To avoid this, run using **`%run -i four_plot.py`**

Python Scripts...

Now, four_plot.py is called a Python Script.


- run the script in IPython using

```
%run four_plot.py
```

NameError: name 'linspace' is not defined

To avoid this, run using **%run -i four_plot.py**

Result graph



What did we learn?

- Starting up IPython
- Creating simple plots.
- Adding labels and legends.
- Annotating plots.
- Changing the looks: size, linewidth
- **%hist** - History of commands
- **%save** - Saving commands
- Running a script using **%run -i**