

Previous work

Algorithms:

• Cormode, Muthukrishnan and Yi '11: $\tilde{O}(n^{1-2/p} \cdot \text{poly}(s/\epsilon))$ bits

- Woodruff and Zhang '12: $\tilde{O}(s^{p-1}/\varepsilon^{\Theta(p)} \cdot \text{poly}(\log n))$

- Kannan, Vempala and Woodruff '14: $\tilde{O}(s^p/\varepsilon^2 \cdot \text{poly}(\log n))$

- For general functions $\mathcal{O}(s^2 \cdot c_{f,s} / \varepsilon^2 \cdot \text{poly}(\log n))$

Lower Bounds:

- **Voddruff and Zhang '12: $\Omega(s^{p-1}/\varepsilon^2)$ (s-BTX problem)**

• Kannan, Vempala and Woodruff '14 : $\Omega(c_{f,s}/\varepsilon)$ (s -Player Promise Set-Disjointness)



Distributed functional monitoring

Previous Work

Algorithms:

- Cormode, Muthukrishnan and Yi '11 : $\tilde{O}(n^{1-2/p} \cdot \text{poly}(s/\varepsilon))$ bits
- Woodruff and Zhang '12 : $\tilde{O}(s^{p-1}/\varepsilon^{\Theta(p)} \cdot \text{poly}(\log n))$
- Kannan, Vempala and Woodruff '14 : $\tilde{O}(s^p/\varepsilon^2 \cdot \text{poly}(\log n))$
 - For general functions $O(s^2 \cdot c_{f,s}/\varepsilon^2 \cdot \text{poly}(\log n))$

Lower Bounds:

- Woodruff and Zhang '12 : $\Omega(s^{p-1}/\varepsilon^2)$ (s -BTX problem)
- Kannan, Vempala and Woodruff '14 : $\Omega(c_{f,s}/\varepsilon)$ (s -Player Promise Set-Disjointness)

The Parameter $c_{f,s}$