**Wad practical**

**Prac1**

**A: Design a web page using different text formatting tags.**

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <title>Text Formatting Example</title>
</head>
<body>
   <h1>Welcome to HTML Text Formatting</h1>
   <p><b>Bold text</b></p>
   <p><strong>Important text</strong></p>
   <p><i>Italic text</i></p>
   <p><em>Emphasized text</em></p>
   <p><u>Underlined text</u></p>
   <p><del>Deleted text</del></p>
   <p><mark>Highlighted text</mark></p>
   <p>H<sub>2</sub>O (Subscript)</p>
   <p>10<sup>2</sup> = 100 (Superscript)</p>

   <p><small>This is small text </small></p>
   <p>Normal text and <big>big text</big> (old tag)</p>


      <hr>
      <h2>Example</h2>
      <blockquote>This is a blockquote - used for long
   quotations.</blockquote>
      <p>As Einstein said, <q>Imagination is more important than
   knowledge.</q></p>
   </body>
   </html>
```

**<u>B. Design a web page with links to different pages and allow navigation between web pages.</u>**

```
<!DOCTYPE html>

<html>
```

```
<head>
	<title>Home Page</title>
</head>
<body style="background-color:#87CEEB;">
	<h1>Welcome to Home Page</h1>
	<p>This is Home Page</p>
	<hr>
	<h3>Navigation bar</h3>
	<a href="Prac1b.html">Home</a>
	<a href="b2.html">About Us</a>
	<a href="b3.html">Contact</a>
	<hr>
	<p><a href="b2.html"><button>Go to About Us</button></a></p>
</body>
</html>
```

**b2.html**

```
<!DOCTYPE html>
<html>
<head>
	<title>About US</title>
</head>
<body style="background-color:#FFFFE0">
	<h1>About US</h1>
	<p>We are learning html</p>

	<hr><a href="Prac1b.html">Home</a>
	<a href="b2.html">About Us</a>
	<a href="b3.html">Contact</a>
```

```
        <hr>
        <p><a href="b3.html"><button>Go to Contact</button></a></p>
        </body></html>
```

**b3.html**

```
<!DOCTYPE html>
<html>
<head>
        <title>Contact</title>
</head>
<body style="background-color:#3EB489">
<h1>Contact Us</h1>
<p>Email: student@example.com</p>



<hr><a href="Prac1b.html">Home</a>
        <a href="b2.html">About Us</a>
        <a href="b3.html">Contact</a>
        <hr>
<p><a href="Prac1b.html"><button>Go to Home page</button></a></p>
</body>
</html>
```

**<u>C. Design a web page that automatically redirects the user to another page.</u>**

```
<!DOCTYPE html>
<html>
<head>
   <title>Redirecting...</title>
   <meta http-equiv="refresh" content="5; url=https://www.google.com">
```

```
</head>
<body>
   <h1>You will be redirected in 5 seconds...</h1>
   <p>If not redirected, <a href="https://www.google.com">click here</a></p>
</body>
</html>
```

**D. Design a web page embedding image, audio and video.**

```
<!DOCTYPE html>
<html>
<head>
   <title>Multimedia Page</title>
</head>
<body>
   <h1>HTML5 Multimedia Example</h1>


   <h2>1. Image</h2>
   <!-- Save any image as "sample.jpg" in same folder or use online link -->
   <img src="E:\WAD\sample.jpeg" alt="Sample" width="200">
   <br><br>
   <h2>2. Audio Player</h2>
   <!-- Use any mp3 file or online link -->
   <audio controls>
      <source src="https://www.soundhelix.com/examples/mp3/SoundHelix-Song-1.mp3"
type="audio/mpeg">
      Your browser does not support audio.
   </audio>
   <h2>3. Video Player</h2>
   <!-- Free sample video -->
```

```
<video width="400" controls>
    <source src="https://commondatastorage.googleapis.com/gtv-videos-bucket/sample/BigBuckBunny.mp4" type="video/mp4">
    Your browser does not support video.
</video
<hr>
<p><i>Note: All media above is loaded from the internet so it works without downloading anything!</i></p>
</body>
</html>
```

**Prac3**

**3B.Design a web page with different tables.**

```
<!DOCTYPE html>
<html lang="en">
<head>
        <meta charset="UTF-8">
        <meta name="viewport" content="width=device-width,
initial-scale=1.0">
        <title>Types of table in html</title>


</head>
<body>
<table border="1">
        <caption>1.Basic Tables</caption>
        <tr>
                <th>Name</th>
                <th>Roll no</th>
                <th>Marks</th>
        </tr>
```

```
        <tr>
            <td>Aryan</td>
            <td>48</td>
            <td>98</td>
        </tr>
        <tr>
            <td>Anvi</td>
            <td>62</td>
            <td>99</td>
        </tr>
        <tr>
            <td>Mamta</td>
            <td>85</td>
            <td>93</td>
        </tr>
        <tr>
            <td>Anand</td>
            <td>78</td>
            <td>87</td>
        </tr>
</table>
<table border="1">
        <caption>2.Table with thick border</caption>
        <tr>
            <th>Subject</th>
            <th>Marks</th>
        </tr>
```

```
        <tr>
            <td>Physics</td>
            <td>58</td>
        </tr>

        <tr>
            <td>Chemistry</td>
            <td>67</td>
        </tr>

        <tr>
            <td>Maths</td>
            <td>67</td>
        </tr>

        <tr>
            <td>Biology</td>
            <td>72</td>
        </tr>
</table>

<table border="1">
        <caption>3.Table with colspan and rowspan</caption>
        <tr>
            <th>Student</th>
            <th colspan="2">Semester Result</th>
            <th rowspan="2">Total</th>
        </tr>
```

```
<tr>
        <th>Name</th>
        <th>Theory</th>
        <th>Practical</th>
</tr>

<tr>
        <td>Varsha</td>
        <td>89</td>
        <td>90</td>
</tr>

<tr>
        <td>Adarsh</td>
        <td>87</td>
        <td>93</td>
</tr>

<tr>
        <td>Mamta</td>
        <td>84</td>
        <td>87</td>
</tr>

<tr>
        <td>Anand</td>
        <td>85</td>
```

```
                <td>83</td>
        </tr>
</table>
<table></body></html>
```

3A. Design a web page with a form that uses all types of controls

```
<!DOCTYPE html>
<html lang="en">
<head>
        <meta charset="UTF-8">
        <meta name="viewport" content="width=device-width, initial-scale=1.0">
        <title>Form Registration</title>
</head>
<body>
        <h1>FYIT Registration Form</h1>
                <form id="myForm">
                <label>Name</label>
                <input type="text" name="name" required>
<hr>
                <label>PRN/Roll no.</label>
                <input type="text" required>
<hr>
                <label>Email</label>
                <input type="email" required>
<hr>

                <label>Password</label>
                <input type="password" required>
<hr>
```

```
        <label>Date of Birth</label>
        <input type="date" required>
<hr>
        <label>Mobile no.</label>
        <input type="tel" required>
<hr>
        <label>Course</label>
        <select required>
        <option>FYBSCIT.A</option>
        <option>FYBSCIT.B</option>
        <option>FYCS</option>
        </select>
<hr>
        <label>Gender</label>
        <input type="radio" name="gender" value="Male" required>Male
        <input type="radio" name="gender">Female
        <input type="radio" name="gender">Other
<hr>
        <label>Skill Known</label>
        <input type="checkbox"> HTML/CSS
        <input type="checkbox">Java
        <input type="checkbox">Python
        <input type="checkbox">C programming
<hr>
        <label>Message</label>
        <textarea rows="4"></textarea>
<hr>
         <input type="submit" value="Submit">
```

```
<input type="reset" value="Clear">
</form>
<script>
document.getElementById("myForm").addEventListener("submit",
function(e){
e.preventDefault();
alert("Registration Successful!\nWelcome to FY.IT Family!");
});
</script>
</body>
</html>
```

**Prac4**

**JavaScript Conditional Statements**

**a. Design a webpage to take a number from user and check for an even number.**

```
<!DOCTYPE html>
<html lang = "en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Check even or odd</title>
</head>
<body>
<h1>Check the no. is even or odd</h1>
<div class= "container">
<label>Enter a number</label>
<input type="number" id="number" placeholder="enter a number">
<br><hr>
<button onclick="checkEvenOdd()">Check</button>
```

```
<p id ="result"></p>
</div>
<script>
function checkEvenOdd(){
let num = document.getElementById("number").value;
if(num===""){
document.getElementById("result").innerHTML="Please enter a num";
}
else if(num%2===0){
document.getElementById("result").innerHTML=num+" is an EVEN num";
}
else{
document.getElementById("result").innerHTML=num+" is an ODD num";
}
}</script>
</body>
</html>
```

**b. Design a webpage to check whether the entered year is a leap year or not.**

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Check the leap year</title>
</head>
<body>
<h1>Check the year is leap year or not</h1>
<div class="container">
<label>Enter a year</label>
```

```
<input type="number" id="year" placeholder="e.g. 2024">
<br><hr>
<button onclick="checkLeapYear()">Check leap Year </button>
<p id="result"></p>
</div>
<script>
function checkLeapYear(){
let year=document.getElementById("year").value;
if(year===""){
document.getElementById("result").innerHTML="Please enter a year";
}
else if((year%4===0 && year%100!==0)||(year%400===0)){
document.getElementById("result").innerHTML= year +" is an Leap year";
}
else{
document.getElementById("result").innerHTML=year +" is not an leap year";
}
}
</script>
</body>
</html>
```

c. Design a webpage to check whether the entered character is a vowel or not.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Check the char</title>
</head>
```

```
<body>
<h1>Vowel or consonant checker</h1>
<div class ="box">
<label>Enter a single char</label>
<input type="text" id="char" maxlength="1" placeholder="e.g.a">
<br><hr>
<button onclick="CheckVowel()">Check</button>
<p id ="result"></p>
</div>
<script>
function CheckVowel(){
let ch = document.getElementById("char").value.toLowerCase();

if(ch===""){
document.getElementById("result").innerHTML="please enter a char";
}
else if (ch === 'a' || ch === 'e' || ch === 'i' || ch === 'o' || ch === 'u') {
document.getElementById("result").innerHTML = "'" + ch.toUpperCase() + "' is a VOWEL";
}
else if ((ch >= 'a' && ch <= 'z')) {
document.getElementById("result").innerHTML = "'" + ch.toUpperCase() + "' is a
CONSONANT";
}
 else {
document.getElementById("result").innerHTML = "Invalid input! Enter a letter.";
}
}
</script>
```

```
</body>
</html>
```

***Subquestion d refer from clsroom***

e. Design a webpage to demonstrate switch case.

```
<!DOCTYPE html>
<html lang = "en">
<head>
<meta charset="UTF-8">
<title>Switch-case days of the week</title>
</head>
<body>
<h1>Days of the week</h1>
<div class="box">
<label>Choose a no.(1-7)</label>
<br>
<select id="day">
<option value="1">1-Monday </option>
<option value="2">2-Tuesday </option>
<option value="3">3-Wednesday</option>
<option value="4">4-Thursday</option>
<option value="5">5-Friday</option>
<option value="6">6-Saturday</option>
<option value="7">7-Sunday</option>
</select>
<br>
<button onclick="showDays()"> Show days</button>
<p id="result"></p>
</div>
```

```
<script>
function showDays(){
let num =parseInt(document.getElementById("day").value);
switch(num){
case 1:
document.getElementById("result").innerHTML="Monday";
break;
case 2:
document.getElementById("result").innerHTML="Tuesday";
break;
case 3:
documenet.getElementById("result").innerHTML="Wednesday";
break;
case 4:
documenet.getElementById("result").innerHTML="Thursday";
break;
case 5:
documenet.getElementById("result").innerHTML="Friday";
break;
case 6:
documenet.getElementById("result").innerHTML="Saturday";
break;
case 7:
documenet.getElementById("result").innerHTML="Sunday";
break;
default:
document.getElementById("result").innerHTML="Invalid Input";
}
```

```
}
</script></body><html>
```

**Prac5**

**JavaScript simple 'for' Loop**

**a. Using JavaScript, design a web page to accept a number from the user**

```
<!DOCTYPE html>
<html>
<body>

<h2>Factorial Calculator</h2>
<button onclick="calculateFactorial()">Calculate Factorial</button>
<p id="result"></p>

<script>
function calculateFactorial() {
let num = Number(prompt("Enter a positive number:"));

if (isNaN(num) || num < 0) {
document.getElementById("result").innerHTML = "Please enter a valid positive number.";
return;
}
let factorial = 1;
for (let i = 1; i <= num; i++) {
factorial *= i;
}
document.getElementById("result").innerHTML =
"Factorial of " + num + " is: " + factorial;
```

```
}
</script>
</body>
</html>
```

b. Using JavaScript, a web page that prints Fibonacci series/any given series.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Fibonacci</title>
</head>
<body>
<h1>Fibonacci</h1>
<button onclick="generateFibonacci()">Calculate</button>
<p id="result"></p>
<script>
function generateFibonacci(){
let terms = parseInt(prompt("Enter the number of terms (e.g., 10):"));
if (isNaN(terms) || terms <= 0) {
document.getElementById("result").innerHTML = "Please enter a positive num.";
return;
}
 let a=0,b=1;
let series = "Fibonacci series: " + a;

if (terms > 1) {
series += " ," + b;
```

```
}
for(let i=3;i<=terms;i++){
let c= a+b;
series +=","+c;
a=b;
b=c;
}
document.getElementById("result").innerHTML =
`<strong>${series}</strong>`;
}
</script>
</body>
</html>
```

c. Write a JavaScript program to display all the prime numbers between 1and 100.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Prime nun 1-100</title>
</head>
<body>
<h2>Prime num 1-100</h2>
<button onclick="calculatePrime()">Show Primes()</button>
<p id ="result"></p>
<script>
function calculatePrime(){
let primes=[];
```

```
for(let num =2; num <=100; num++){
let isPrime = true;
for(let i = 2;i<Math.sqrt(num);i++){
if(num%i===0){
isprime=false;
break;
}
}
if (isPrime) primes.push(num);
}
document.getElementById("result").innerHTML =
"Prime numbers: <strong>" + primes.join(", ") + "</strong>"; }
</script>
</body>
</html>
```

d. Write a JavaScript program to accept a number from the user and display the sum of its digits.

```
<!DOCTYPE html>
<html>
<head>
<title>Sum of Digits</title>
</head>
<body>
<h2>Sum of Digits</h2>
<button onclick="calculateSum()">Calculate</button>
<p id="result"></p>
<script>
```

```
function calculateSum() {
let num = prompt("Enter a positive number:");
if (num === null || num === "" || isNaN(num) || num < 0) {
document.getElementById("result").innerHTML = "Please enter a valid number.";
return;
}
let sum = 0;
let originalNum = num;
for (let i = 0; i < num.length; i++) {
sum += Number(num[i]);
}
document.getElementById("result").innerHTML =
"Sum of digits of " + originalNum + " = " + sum;
}
</script>
</body>
</html>
```

**Prac6**

**6a**

```
<!DOCTYPE html>
<html lang ="en">
<head>
<meta charset="UTF-8">
<title>a..for-in loop</title>
</head>
<body>
<h2>for..in loop</h2>
```

```
<p>open console(F12) to see output</p>
<script>
let student ={
name:"Rahul",
age:19,
course:"FYBSC",
city:"Mumbai",
marks:85
};
console.log("****for....in Loop Demo****");
for(let key in student){
console.log(key+":"+student[key]);
}
</script></body></html>
```

**6b**

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>B...for...of Loop</title>
</head>
<body>
<h2>for...of Loop</h2>
<p>open console(f12)to see output</p>
<script>
let fruits=["Apple","Mango","chikoo", "banana"];

console.log("*******for....of loop demo******");
```

```
for(let item of fruits){
console.log("fruits"+item);
}
</script></body></html>
```

**6c**

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>c-While loop</title>
</head>
<body>
<h2>c. While loop</h2>
<p>open console(f12) to see the output</p>
<script>
let count =2;
while (count <= 8) {
console.log("Count is: "+count);
count+=1;
}
</script></body></html>
```

**6d**

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>d- do-while loop</title>
</head>
```

```
<body>
<h2>d- Do-while loop</h2>
<p>Open console (F12) to see the output</p>
<script>
let num = 15;
console.log("**** do-while loop demo ****");
do {
   console.log("Number is: " + num);
   num++;
} while (num <= 10);
console.log("(Notice: it ran once even when condition was false!)");
</script>
</body>
</html>
```

**Prac7**

**JavaScript Objects**

a. Using JavaScript, design a web page demonstrating different native objects of JavaScript.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>JavaScript Native Object Demo</title>
</head>
<body>
<h1>JavaScript Built-in / Native Objects Demo</h1>
```

```
<div class="card">
   <h2>1. String Object</h2>
   <div class="output" id="stringDemo"></div>
</div>

<div class="card">
   <h2>2. Number Object</h2>
   <div class="output" id="numberDemo"></div>
</div>

<div class="card">
   <h2>3. Math Object</h2>
   <div class="output" id="mathDemo"></div>
</div>

<div class="card">
   <h2>4. Date Object</h2>
   <div class="output" id="dateDemo"></div>
</div>

<div class="card">
   <h2>5. Array Object</h2>
   <div class="output" id="arrayDemo"></div>
</div>

<script>
// 1. String object
let text = new String("Hello JavaScript World!");
```

```
document.getElementById("stringDemo").innerHTML =
    "Original: " + text + "<br>" +
    "Length: " + text.length + "<br>" +
    "Uppercase: " + text.toUpperCase() + "<br>" +
    "Includes 'Java': " + text.includes("Java") + "<br>" +
    "Character at position 6: " + text.charAt(6);

// 2. Number object
let num = new Number("54.5678");
document.getElementById("numberDemo").innerHTML =
    "Original: " + num + "<br>" +
    "toFixed(2): " + num.toFixed(2) + "<br>" +
    "toPrecision(4): " + num.toPrecision(4) + "<br>" +
    "isInteger(42): " + Number.isInteger(42);

// 3. Math object
document.getElementById("mathDemo").innerHTML =
    "Math.PI = " + Math.PI.toFixed(4) + "<br>" +
    "Math.abs(-85) = " + Math.abs(-85) + "<br>" +
    "Math.pow(2,5) = " + Math.pow(2,5) + "<br>" +
    "Math.sqrt(144) = " + Math.sqrt(144) + "<br>" +
    "Math.floor(7.89) = " + Math.floor(7.89) + "<br>" +
    "Random (0-1): " + Math.random().toFixed(4);

// 4. Date object
let today = new Date();
document.getElementById("dateDemo").innerHTML =
    "Current date: " + today.toLocaleDateString() + "<br>" +
```

```
    "Current time: " + today.toLocaleTimeString() + "<br>" +
    "Year: " + today.getFullYear() + "<br>" +
    "Month (0-11): " + today.getMonth() + "<br>" +
    "Day of week (0=Sun): " + today.getDay();

// 5. Array object
let fruits = new Array("Mango", "Banana", "Apple", "Chikoo");
fruits.push("Orange");
document.getElementById("arrayDemo").innerHTML =
    "Array: " + fruits.join(" → ") + "<br>" +
    "Length: " + fruits.length + "<br>" +
    "First item: " + fruits[0] + "<br>" +
    "Last item: " + fruits[fruits.length - 1] + "<br>" +
    "Index of Apple: " + fruits.indexOf("Apple");
</script></body></html>
```

b. Write a program in JavaScript to accept a sentence from the user and display the number of words in it. (Do not use split () function).

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>Word Counter (without split())</title>
</head>
<body>
<h2>Word Counter (without using split())</h2>
<textarea id="sentence" placeholder="Type or paste your sentence here..."></textarea>
```

```
<br><br>
<button onclick="countWords()">Count Words</button>
<div id="result"></div>


<script>
function countWords() {
   let text = document.getElementById("sentence").value;
   text = text.trim();
   if (text === "") {
      document.getElementById("result").textContent = "Number of words: 0";
      return;
   }
   let wordCount = 1;
   for (let i = 0; i < text.length - 1; i++) {
      if (text[i] === " " && text[i + 1] !== " ") {
         wordCount++;
      }
   }
   document.getElementById("result").innerHTML =
      "Number of words: " + wordCount;
}
</script></body></html>
```

**Prac8**

**JavaScript Events**

a. Write a JavaScript program to design a simple calculator.

```
<!DOCTYPE html>
<html lang="en">
<head>
```

```
<meta charset="UTF-8">
<title>Simple Calculator</title>
<style>
body {
   font-family: Arial;
   text-align: center;
}
.calculator {
   display: inline-block;
   padding: 10px;
   border: 1px solid black;
}
input {
   width: 200px;
   height: 40px;
   font-size: 20px;
   text-align: right;
   margin-bottom: 10px;
}
button {
   width: 45px;
   height: 45px;
   margin: 2px;
   font-size: 16px;
}
</style></head><body>
<h2>Simple Calculator</h2>
```

```
<div class="calculator">
    <input type="text" id="display" readonly value="0">
    <br>
    <button onclick="clearDisplay()">C</button>
    <button onclick="appendToDisplay('(')">(</button>
    <button onclick="appendToDisplay(')')">)</button>
    <button onclick="appendToDisplay('/')">/</button>
    <br>
    <button onclick="appendToDisplay('7')">7</button>
    <button onclick="appendToDisplay('8')">8</button>
    <button onclick="appendToDisplay('9')">9</button>
    <button onclick="appendToDisplay('*')">*</button>
    <br>
    <button onclick="appendToDisplay('4')">4</button>
    <button onclick="appendToDisplay('5')">5</button>
    <button onclick="appendToDisplay('6')">6</button>
    <button onclick="appendToDisplay('-')">-</button>
    <br>
    <button onclick="appendToDisplay('1')">1</button>
    <button onclick="appendToDisplay('2')">2</button>
    <button onclick="appendToDisplay('3')">3</button>
    <button onclick="appendToDisplay('+')">+</button>
    <br>
    <button onclick="appendToDisplay('0')">0</button>
    <button onclick="appendToDisplay('.')">.</button>
    <button onclick="calculate()">=</button>
    <button onclick="appendToDisplay('^')">^</button>
</div>
```

```
<script>
const display = document.getElementById('display');
function appendToDisplay(value) {
    if (display.value === '0') {
        display.value = value;
    } else {
        display.value += value;
    }
}
function clearDisplay() {
    display.value = '0';
}
function calculate() {
    try {
        let expression = display.value;
        expression = expression.replace(/\^/g, '**');
        display.value = eval(expression);
    } catch {
        display.value = 'Error';
    }
}
</script></body></html>
```

b. Design a form and validate all the controls placed on the form using

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
```

```
<title>Registration Form with Validation</title>
</head><body>
<h2>Student Registration Form</h2>
<form id="registrationForm" onsubmit="return validateForm(event)">
  <div>
    <label for="fullname">Full Name *</label><br>
    <input type="text" id="fullname" name="fullname"><br>
    <div class="error" id="nameError" style="display:none;">
      Name must be 3-30 characters (letters & spaces only)
    </div></div>
  <br>
  <div>
    <label for="email">Email *</label><br>
    <input type="email" id="email" name="email"><br>
    <div class="error" id="emailError" style="display:none;">
      Please enter a valid email address
    </div>
  </div>
  <br>
  <div>
    <label for="mobile">Mobile Number *</label><br>
    <input type="text" id="mobile" name="mobile" maxlength="10"><br>
    <div class="error" id="mobileError" style="display:none;">
      Enter valid 10-digit mobile number
    </div></div>
  <br>
  <div>
    <label for="password">Password *</label><br>
```

```
        <input type="password" id="password" name="password"><br>
        <div class="error" id="passError" style="display:none;">
            Password must be 6-20 characters
        </div></div>
    <br>
    <div>
        <label for="gender">Gender *</label><br>
        <select id="gender" name="gender">
            <option value="">Select Gender</option>
            <option value="male">Male</option>
            <option value="female">Female</option>
            <option value="other">Other</option>
        </select><br>
        <div class="error" id="genderError" style="display:none;">
            Please select your gender
        </div></div>
    <br>
    <button type="submit">Register</button>
    <br><br>
    <div class="success" id="successMsg" style="display:none;">
        Registration Successful!
    </div>
</form>
<script>
function validateForm(event) {
    event.preventDefault();
    let isValid = true;
```

```
// Reset error messages
document.querySelectorAll('.error').forEach(el => el.style.display = 'none');
document.getElementById('successMsg').style.display = 'none';

// 1. Full Name
const name = document.getElementById('fullname').value.trim();
const nameRegex = /^[A-Za-z\s]{3,30}$/;
if (!nameRegex.test(name)) {
    document.getElementById('nameError').style.display = 'block';
    isValid = false;
}
// 2. Email
const email = document.getElementById('email').value.trim();
const emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;
if (!emailRegex.test(email)) {
    document.getElementById('emailError').style.display = 'block';
    isValid = false;
}
// 3. Mobile
const mobile = document.getElementById('mobile').value.trim();
const mobileRegex = /^[6-9]\d{9}$/;
if (!mobileRegex.test(mobile)) {
    document.getElementById('mobileError').style.display = 'block';
    isValid = false;
}
// 4. Password
const password = document.getElementById('password').value;
if (password.length < 6 || password.length > 20) {
```

```
        document.getElementById('passError').style.display = 'block';
        isValid = false;
    }
    // 5. Gender
    const gender = document.getElementById('gender').value;
    if (!gender) {
        document.getElementById('genderError').style.display = 'block';
        isValid = false;
    }
    // Success
    if (isValid) {
        document.getElementById('successMsg').style.display = 'block';
        document.getElementById('registrationForm').reset();
    }
    return false;
}
</script></body></html>
```