

# RELENTLESS POWER RELIABLE PERFORMANCE



**KOHLER**  
IN POWER. SINCE 1920.

## ENGINE SPECIFICATION

**KOHLER.**  
IN POWER. SINCE 1920.



KD440 / KD441

## SERIES KD440 / KD441

### DIESEL KD440 / KD441

#### CERTIFICATION / HOMOLOGATION

• CPCB II • BHARAT (Trom) STAGE III • BIS • CIFT Compatible

#### APPLICATIONS

• Two-wheel tractor • Agricultural mower • Agricultural pump • High pressure cleaner • Generator set • Vibrating plate • Hydraulic power pack

#### STANDARD EQUIPMENT

- Recoil starting and automatic & manual compression release
- Fuel tank
- Fuel filter
- Dry-air cleaner
- Muffler with guard
- Accelerator and stop manual control
- User maintenance-spare parts booklet

#### ACCESSORIES

- Power take-off flywheel side (engines with electrical starting)
- Power take-offs with flanging and special shaft
- Parallel crankshaft internal dynamic balancer
- Oil-bath air-cleaner
- Electric start 12 V / 24 V
- Keyswitch panel
- Emergency stop through electrovalve
- Accelerator and stop remote control
- Keystart panel with shutdown device
- Fuel lift pump
- Oil dipstick on cylinder head
- Oil pressure switch
- Oil temperature switch
- Glow plug on intake manifold
- Recoil with demolding cover
- Grass protection for engine cooling

#### CONSTRUCTION

- 4 -stroke air cooled diesel engine
- Conical & cylindrical power take-off on crankshaft
- Anticlockwise rotation
- Direct injection
- Forced lubrication with oil pump
- Centrifugal mass governor
- Built-in full flow oil filter
- Oil breathing blow-by with safety device
- Automatic extra fuel starting device
- Self bleeding fuel system
- Torque regulator
- Automatic/manual compression release
- Die-cast aluminum crankcase with integral & separable cast iron cylinder liner
- Aluminum alloy cylinder head
- Built-in rigid foot
- Hydraulic & mechanical tappets.

#### TECHNICAL SPECIFICATIONS:

| KD440 / KD441                                                           |                          |                     |
|-------------------------------------------------------------------------|--------------------------|---------------------|
| Cylinders                                                               | N                        | 1                   |
| Displacement                                                            | cm <sup>3</sup>          | 441                 |
| Bore                                                                    | mm                       | 66                  |
| Stroke                                                                  | mm                       | 76                  |
| Compression ratio                                                       |                          | 20.3:1              |
| Rating kW/HP @ 3600 r.p.m.                                              | N (80/1260/CEE) ISO 1585 | 6.0/10.9            |
|                                                                         | NB ISO 3046 IFN          | 7.4/10.1            |
|                                                                         | NA ISO 3046 IQXN         | 6.7/9.1             |
| Max. torque                                                             | Nm                       | 24.5 @ 2200         |
| Min. idling speed                                                       | rpm                      | 1050 - 1150         |
| Fuel tank capacity                                                      | l                        | 5                   |
| Oil consumption                                                         | kg/h                     | 0.0048              |
| Oil sump capacity                                                       | l                        | 1.5                 |
| Min. allowable oil pressure                                             | bar                      | 0.8 - 1.0           |
| Max. allowable inclination for short periods of operation (peak values) | deg                      | 25° (35°)           |
| Vol. of air required for correct combustion @ 3600 r.p.m.               | l/min                    | 635                 |
| Vol. of air required for correct cooling @ 3600 r.p.m.                  | l/min                    | 5500                |
| Dry weight                                                              | kg                       | 45                  |
| Base engine dimensions (LxWxH)                                          | mm                       | 412.8 x 340 x 403.1 |
| Recommended battery                                                     | V/Ah                     | 12/44               |

- Specifications may vary depending on Homologation.
- Kohler reserves the right to change the design or specifications without notice & without any obligation or liability whatsoever.



## DC WELDING GENERATOR

