

ECO-SERIES PORTABLE GENERATOR

PELICAN

The Intelligent Power Back Up Solution

Excellent Value for Money | Long Lasting Life Span



ECO-SERIES PORTABLE
GENERATOR

PELICAN

SPECIFICATION

Models	MLT 1000	MLT 1000i	MLT 3700 L(M)	MLT 3700 L(E)	W 650 APL
Rated Output (VA) (50Hz)	750	800	2800	2800	5000
Max Output (VA) (50Hz)	850	900	3000	3000	5500
Starting System	Manual	Manual	Manual	Electric/Manual	Electric/Manual
Oil Alert System	Yes	yes	Yes	Yes	Yes
Displacement CC	98	56	208	208	389
Dimension (LxWxH) mm	455x360x375	336x327x306	598x458x483	598x458x483	684x515x578
Dry Weight (Kg)	26	13.5	50	50	80

Models	W 800 APL	W 900 APL	7000i	W 12500 i	WG 700 AP
Rated Output (VA) (50Hz)	6000	8000	6000	10000	5000
Max Output (VA) (50Hz)	6500	8200	7000	10500	5500
Starting System	Electric/Manual	Electric/Manual	Electric/Manual	Electric	Electric/Manual
Oil Alert System	Yes	Yes	Yes	yes	Yes
Displacement CC	420	438	420	500	438
Dimension (LxWxH) mm	684x515x578	684x515x578	950x765x773	700x560x585	680x510x540
Dry Weight (Kg)	85	90	130	100	90

For WG 700 AP:

Welding Rod:- Upto 4mm for Welding Set Model WG 700 AP

Dimension of Welding Genset are without wheels

Rated output: 5000 VA AC OUTPUT 160 AMP at 60% duty cycle for WELDING

Max Output: 5500 VA AC OUTPUT 200 AMP at 40% duty cycle for WELDING

*Under Standard Test Conditions

- Automatic Voltage Regulator (AVR)
- Oil Alert System
- Lowest Fuel Consumption

*Specifications and Models subjected to change without prior notice

- Simple, Reliable, Starting
- OHV 4-Stroke Engine
- Rugged Full-Framed
- Economically Priced