

[Pranesh S A 251801234-2025-AIDS](#) ▾**P2****Started on** Monday, 31 August 2026, 10:13 AM**State** Finished**Completed on** Wednesday, 30 September 2026, 11:57 AM**Time taken** 30 days 1 hour**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compareAsc(const void *a, const void *b) {
5      long long int x = *(const long long int *)a;
6      long long int y = *(const long long int *)b;
7      if (x < y) return -1;
8      if (x > y) return 1;
9      return 0;
10 }
11
12 int compareDesc(const void *a, const void *b) {
13     long long int x = *(const long long int *)a;
14     long long int y = *(const long long int *)b;
15     if (x < y) return 1;
16     if (x > y) return -1;
17     return 0;
18 }
19
20 int main() {
21     int n;
22     if (scanf("%d", &n) != 1) return 0;
23
24     long long int a[n], b[n];
25     for (int i = 0; i < n; i++) {
26         scanf("%lld", &a[i]);
27     }
28     for (int i = 0; i < n; i++) {
29         scanf("%lld", &b[i]);
30     }
31
32     qsort(a, n, sizeof(long long int), compareAsc);
33     qsort(b, n, sizeof(long long int), compareDesc);
34
35     long long int minSum = 0;
36     for (int i = 0; i < n; i++) {
37         minSum += a[i] * b[i];
38     }
39
40     printf("%lld\n", minSum);
41
42     return 0;
43 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)