

Local convergence rates computed from adjacent refinement levels. The final row shows fitted rates with uncertainties from the log-log least-squares fit. Reynolds number 7500.

cycle	# cells	# dofs	L2_velocity	rate	L2_pressure	rate	H1_velocity	rate
0	25	278	4.739e-02	–	3.629e-02	–	4.603e-01	–
1	100	1003	9.672e-03	2.29	7.438e-03	2.29	1.873e-01	1.30
2	400	3803	1.278e-03	2.92	1.057e-03	2.82	7.486e-02	1.32
3	1600	14803	1.587e-04	3.01	1.895e-04	2.48	2.219e-02	1.75
4	6400	58403	1.441e-05	3.46	4.157e-05	2.19	4.219e-03	2.39
fitted rate			–	2.93 ± 0.12	–	2.48 ± 0.06	–	1.66 ± 0.13

Table 1: Q2/Q1 elements

cycle	# cells	# dofs	L2_velocity	rate	L2_pressure	rate	H1_velocity	rate
0	25	633	1.984e-03	–	1.504e-03	–	3.755e-02	–
1	100	2363	6.193e-05	5.00	1.212e-04	3.63	3.288e-03	3.51
2	400	9123	2.760e-06	4.49	1.532e-05	2.98	3.239e-04	3.34
3	1600	35843	1.223e-07	4.50	1.944e-06	2.98	3.394e-05	3.25
4	6400	142083	6.411e-09	4.25	2.447e-07	2.99	3.743e-06	3.18
fitted rate			–	4.55 ± 0.08	–	3.11 ± 0.07	–	3.32 ± 0.04

Table 2: Q3/Q2 elements

cycle	# cells	# dofs	L2_velocity	rate	L2_pressure	rate	H1_velocity	rate
0	25	1138	4.737e-05	–	2.499e-05	–	1.868e-03	–
1	100	4323	1.939e-06	4.61	1.407e-06	4.15	1.696e-04	3.46
2	400	16843	5.419e-08	5.16	8.571e-08	4.04	1.132e-05	3.90
3	1600	66483	9.839e-10	5.78	5.341e-09	4.00	4.974e-07	4.51
4	6400	264163	2.013e-11	5.61	3.341e-10	4.00	1.770e-08	4.81
fitted rate			–	5.33 ± 0.14	–	4.042 ± 0.018	–	4.18 ± 0.16

Table 3: Q4/Q3 elements