

VISVESVARAYA TECHNOLOGICAL UNIVERSITY, BELGAUM

"Jnana Sangama", Belgaum-590018



Experiential Learning Report On

"Emergency Response Network Optimization"

Submitted By,
PRANITH C GOWDA – 4NI24IS136

Under the Guidance of

Ms. Prathibha.B.S.,
Assistant Professor
Dept of IS&E
NIE, Mysuru



The National Institute of Engineering
MYSURU-571130



Department of Information and Engineering
MYSURU-571130

2025-2026

ABSTRACT

Rapid urbanization and increasing population density have created major challenges in urban emergency response management. Traditional emergency dispatch methods rely on fixed routing and manual planning, which often result in delayed response times, suboptimal vehicle routing, excessive fuel consumption, and increased operational costs. In many cities, emergency vehicles travel through non-optimized routes, leading to traffic congestion, resource wastage, and avoidable loss of life.

This project presents an intelligent Emergency Response Network Optimization System using Graph Theory and Dijkstra's Shortest Path Algorithm. The system models the city's emergency infrastructure as a weighted undirected graph where hospitals, fire stations, police stations, clinics, trauma centers, dispatch centers, residential zones, commercial zones, industrial zones, and emergency incident sites are represented as nodes, while road connections between them are represented as weighted edges. Edge weights indicate travel distance in kilometres between nodes.

The developed system accepts source and destination inputs from the user through a commandline interface. The application constructs the emergency response network and computes the optimal routing path between any two locations using Dijkstra's algorithm. The generated network visualization highlights the shortest and most efficient emergency route in red, with all edge weights labeled and nodes color-coded by service type.

The project is implemented using Python along with NetworkX and Matplotlib libraries for graph construction, shortest path computation, and network visualization. The system demonstrates how graph-theoretic concepts can be applied to solve real-world emergency response problems efficiently.

The proposed solution helps in reducing emergency response time, minimizing travel distance, improving dispatch coordination, and supporting sustainable smart-city public safety infrastructure. The system can further be extended using IoT sensors, live traffic integration, GPS tracking, and AI-based prediction models for fully automated emergency dispatch operations.

Keywords: Graph Theory, Dijkstra Algorithm, Emergency Response, Network Optimization, Smart City, Shortest Path, Python, Route Optimization.

TABLE OF CONTENTS

SL. No.	Chapter	Page No.
1.	Problem Statement (Real-Time Scenario)	1
2.	Objective of the Work	2
3.	Graph Representation	3 – 4
4.	Applied Graph Theory Concepts	5 – 7
5.	Methodology	8
6.	Analysis & Results	9 – 10
7.	Reflection & Learnings	11
8.	Conclusion & Future Scope	12
9.	References	13 – 14
10.	Screenshots	15 – 16

Chapter 1:

PROBLEM STATEMENT (REAL-TIME SCENARIO)

Urban emergency response management has become one of the most critical challenges faced by modern cities. Rapid urbanization, population growth, industrialization, and increasing road traffic generate enormous quantities of emergency incidents every day. Municipal corporations and public safety departments are under continuous pressure to ensure timely emergency dispatch, minimize response time, and protect human life. However, traditional emergency dispatch systems rely heavily on manual route planning and dispatcher experience, which are inefficient and outdated for modern smart cities.

According to recent urban development studies, more than 55% of the global population currently lives in urban areas, and this percentage is expected to increase significantly in the coming decades. As urban populations grow, emergency incidents increase proportionally. Research in emergency medicine consistently shows that survival rates drop by approximately 10% for every minute of delay in critical emergencies, creating severe pressure on emergency response infrastructure and transportation systems.

The primary problem in conventional emergency dispatch systems is inefficient routing. Emergency vehicles are often dispatched based on dispatcher intuition rather than mathematically optimal paths. Some routes are longer than necessary while faster alternatives exist in the road network. This creates multiple operational problems such as:

- Delayed emergency response times
- Increased risk to human life
- Excess fuel consumption
- Suboptimal vehicle routing
- Traffic congestion caused by emergency vehicles
- Higher operational and maintenance costs

Delayed emergency response creates life-threatening conditions in medical emergencies, fire incidents, and criminal activities. Every minute of additional travel time directly increases the probability of negative outcomes for the people requiring emergency assistance. Nonoptimized routing also increases fuel consumption and vehicle maintenance costs, placing additional financial burden on public safety budgets.

Manual route planning is another major issue. Routes are generally assigned based on dispatcher experience rather than systematic optimization techniques. As cities expand and

road conditions change, previously known routes become inefficient. Emergency vehicles often encounter traffic congestion, suboptimal turn sequences, and unnecessarily long paths, further increasing response time and reducing dispatch efficiency.

The emergency response process also requires coordination between multiple service types — hospitals, fire stations, police departments, trauma centers, and dispatch centers must all operate in a coordinated manner. Without a unified graph model of the network, each service optimizes independently, potentially causing conflicts, route overlaps, and coordination failures at incident sites.

To address these challenges, there is a need for an intelligent and optimized emergency response system capable of dynamically computing the shortest and most efficient routes. Graph Theory provides a strong mathematical foundation for representing urban transportation networks and applying shortest-path algorithms for route optimization.

This project proposes an Emergency Response Network Optimization System using Graph Theory and Dijkstra's Algorithm. The system models the emergency response infrastructure as a weighted undirected graph where all service locations and zones are represented as nodes, while roads between them are represented as weighted edges. The shortest path between any source location and the emergency site is computed using Dijkstra's shortest-path algorithm to minimize travel distance and improve dispatch efficiency.

Chapter 2:

OBJECTIVE OF THE WORK

The primary objective of this project is to design and implement an intelligent emergency response optimization system using graph-theoretic concepts and shortest-path algorithms. The system aims to improve emergency dispatch efficiency, reduce travel distance, and support sustainable smart-city public safety infrastructure.

The detailed objectives of the project are as follows:

Objective 1: Optimize Emergency Routes

The project aims to develop a graph model of the city's emergency response network and apply Dijkstra's shortest-path algorithm to compute minimum-cost routes between any service location and the emergency incident site. The system must correctly handle all 10 nodes, 20 weighted edges, and all 45 possible source-destination combinations.

Objective 2: Reduce Response Time and Operational Cost

The project focuses on minimizing total emergency vehicle travel distance by eliminating suboptimal routing and ensuring the globally shortest path is always identified. Optimized routing directly reduces fuel consumption, maintenance expenses, and operational overhead.

Objective 3: Enable Robust Input Handling

The system is designed to support case-insensitive, validated input handling with a retry loop. The input module normalizes user entries and validates them against the node list, ensuring the system never crashes on invalid input and always guides the user to a valid selection.

Objective 4: Provide Clear Network Visualization

The project aims to render the complete emergency network using Matplotlib with color-coded nodes by service type, labeled edge weights on all 20 roads, and the shortest path highlighted in red. Fixed node positions ensure consistent, reproducible layouts across all program executions.

Objective 5: Demonstrate Practical Application of Graph Theory

The project demonstrates how graph-theoretic algorithms can solve real-world public safety problems. It bridges the gap between academic concepts and practical smart-city emergency management implementations.

Chapter 3:**GRAPH REPRESENTATION**

Graph Theory provides a mathematical framework for representing complex transportation networks. In this project, the city's emergency response infrastructure is modeled as a weighted undirected graph.

The graph representation is defined as:

$$G = (V, E, w)$$

Where:

- V represents the set of vertices or nodes.
- E represents the set of edges connecting nodes.
- w represents the weight function associated with edges.

The graph is modeled as a weighted undirected graph because each road connection contains a distance value in kilometres, and emergency vehicles can travel in both directions on any road.

Vertex Representation

Vertices represent the 10 locations in the emergency response network:

- Medical Facilities: Hospital, Clinic, TraumaCenter
- Emergency Services: FireStation, PoliceStation, DispatchCenter
- Urban Zones: ResidentialZone, CommercialZone, IndustrialZone
- Incident Site: Emergency

Edge Representation

Edges represent road connections between nodes. Each edge contains a positive integer weight value representing:

- Travel distance in kilometres

- Transportation cost
- Estimated travel time

The graph contains 20 edges connecting the 10 nodes. The maximum possible edges for 10 nodes would be $10 \times 9 / 2 = 45$. Our 20 edges represent only the realistic road connections between nearby and logically connected locations, making the graph sparse — exactly as real urban road networks behave.

Node Classification

Medical Facilities

Hospital, Clinic, and TraumaCenter represent locations providing medical emergency services to incident victims.

Emergency Service Stations

FireStation, PoliceStation, and DispatchCenter represent operational stations for fire suppression, law enforcement, and emergency coordination.

Zone Nodes

ResidentialZone, CommercialZone, and IndustrialZone represent geographic area nodes through which emergency vehicles may pass en route to the incident site.

Emergency Incident Site

The Emergency node represents the destination — the active incident location to which emergency vehicles must be dispatched via the shortest possible route.

Weight Function Design

The project uses a weighted cost function for route optimization:

$$w(e) = \alpha \times \text{distance}(e) + \beta \times \text{time}(e) + \gamma \times \text{traffic_penalty}(e)$$

Where:

- $\text{distance}(e)$ represents travel distance in kilometres
- $\text{time}(e)$ represents estimated travel time
- $\text{traffic_penalty}(e)$ represents congestion factor
- α, β, γ are tunable parameters

In the current implementation $\alpha = 1, \beta = 0, \gamma = 0$, producing a pure distance minimizer. All edge weights are validated as strictly positive before the graph is used, satisfying Dijkstra's non-negative weight requirement.

Chapter 4 :

APPLIED GRAPH THEORY CONCEPTS

The project applies several graph theory concepts for transportation optimization and shortestpath analysis.

Weighted Graph

A weighted graph is a graph where every edge contains a numerical value called weight. In this project, edge weights represent road distance in kilometres between emergency service locations.

Undirected Graph

The emergency response network is represented as an undirected graph because emergency vehicles can travel in both directions on any road. This means edge (u, v) and edge (v, u) represent the same road and have the same cost.

Shortest Path Problem

The shortest path problem involves finding the minimum-cost route between two nodes in a graph. The project computes the shortest path between any emergency service source node and the Emergency incident site node.

Dijkstra's Shortest Path Algorithm

The project uses Dijkstra's Algorithm for shortest-path computation because:

- It works efficiently with non-negative edge weights.
- It guarantees globally optimal shortest paths.
- It has good computational efficiency for urban transportation networks.
- It is directly supported by the NetworkX Python library via `nx.shortest_path()`.

The shortest-path relaxation condition is: **dist[v]**

$$= \min(\text{dist}[v], \text{dist}[u] + w(u, v))$$

Algorithm Workflow

Phase 1: Initialization

- Source node distance is set to zero.
- All other nodes are initialized to infinity.
- Priority queue is initialized with all nodes.

Phase 2: Neighbour Exploration

- The node with minimum distance is extracted from priority queue.
- All neighboring nodes are explored via their connecting edges. Phase 3:

Distance Relaxation

- Distances are updated if shorter paths are found through current node.
- Predecessor array is updated to enable path reconstruction.

Phase 4: Path Reconstruction

- The final shortest path is reconstructed using the predecessor array.
- The path is traced backwards from destination to source, then reversed.

Time Complexity

The time complexity of Dijkstra's Algorithm is:

$$O((V + E) \log V)$$

Where:

- V = Number of vertices (10 in our network)
- E = Number of edges (20 in our network)

Python Implementation

```
def find_shortest_path(graph, source, destination):  
    """  
        Uses Dijkstra's Algorithm via NetworkX to find the shortest weighted  
        path between source and destination.  
        """  
    path = nx.shortest_path(  
graph, source=source,  
target=destination,  
weight='weight',
```

```
method='dijkstra'      )      distance =  
nx.shortest_path_length(      graph,  
source=source,          target=destination,  
weight='weight'      )  
    return path, distance
```

Chapter 5 :

METHODOLOGY

The project follows a systematic methodology for generating optimized emergency response routes.

Step 1: Graph Construction

The system constructs the weighted undirected graph $G = (V, E, w)$ using NetworkX. Ten location nodes are added representing all emergency service types and urban zones. Twenty road connections are added as weighted edges with positive integer distance values in kilometres. All edge weights are validated as positive before the graph is used.

Step 2: Input Validation

The user enters source and destination location names through the command-line interface. Input is normalized to title case and validated against the node list using case-insensitive dictionary lookup. If an unrecognized name is entered, the system displays all valid location names and prompts again until valid input is provided.

Step 3: Run Dijkstra's Algorithm

The shortest-path algorithm computes the optimal emergency route between the validated source and destination nodes. NetworkX's `nx.shortest_path()` function is called with `method='dijkstra'` and `weight='weight'` to guarantee globally optimal results.

Step 4: Route Output

The system prints the complete optimal path with arrow notation, total distance in kilometres, and a step-by-step breakdown showing each road segment traversed. This gives dispatchers a clear, auditable record of the computed emergency route.

Step 5: Network Visualization

The complete emergency network is visualized using Matplotlib. Nodes are color-coded by service type, edge weights are labeled on all 20 roads, and the shortest path is highlighted in red with directional arrows. Fixed node positions ensure a consistent, reproducible layout every run.

Chapter 6 :**ANALYSIS & RESULTS**

The developed Emergency Response Network Optimization System successfully demonstrates shortest-path-based route optimization using graph theory concepts.

The command-line interface allows users to:

- Enter source and destination location names
- Receive case-insensitive validated input handling
- View the complete optimal route with step-by-step breakdown
- View the network visualization with highlighted shortest path

The generated graph visualization displays:

- Hospital in blue
- FireStation in red
- PoliceStation in green • Clinic in purple
- TraumaCenter in pink
- DispatchCenter in cyan
- Emergency site in orange
- Zone nodes in grey
- Shortest path highlighted in red with directional arrows

The project successfully computes minimum-cost emergency routes using Dijkstra's Algorithm across all 45 possible source-destination combinations.

Quantitative Benefits

The optimized routing system provides several measurable benefits:

- Reduced emergency response distance
- Reduced fuel consumption
- Lower operational cost
- Reduced vehicle travel time
- Improved emergency dispatch efficiency

Projected improvements include:

- 25-35% reduction in route distance

12

- 30-40% reduction in fuel consumption
- 20-30% reduction in vehicle-hours
- Near-zero routing errors (algorithm guarantees globally optimal path)

Qualitative Benefits

Guaranteed Route Optimality

Dijkstra's algorithm provides a mathematical guarantee that the returned route is the globally shortest path, eliminating routing errors that human dispatchers might make under stress.

Reduced Response Time

Optimized routes ensure emergency vehicles always take the shortest available path, directly improving survival outcomes in time-critical emergencies.

Better Transparency

The system provides a detailed step-by-step route breakdown and visualization logs for monitoring and auditing dispatch decisions.

Sustainable Urban Infrastructure

The project supports smart-city emergency management initiatives and demonstrates how graph theory directly improves public safety outcomes.

Chapter 7:

REFLECTION & LEARNINGS

This project provided practical understanding of graph theory and shortest-path algorithms. It demonstrated how theoretical concepts can solve real-world municipal emergency response problems efficiently.

The project improved knowledge in:

- Graph Theory — modeling real-world networks as $G = (V, E, w)$
- Dijkstra's Algorithm — understanding greedy shortest-path computation
- Python Programming — implementing graph algorithms using NetworkX
- Network Visualization — rendering weighted graphs using Matplotlib
- Route Optimization — applying algorithms to reduce travel distance
- Input Validation — building robust case-insensitive input systems
- Smart-City Infrastructure — understanding emergency response systems

One of the major learnings from the project was understanding how graph-based route optimization can significantly reduce emergency response time and directly improve public safety outcomes. The project demonstrated that the difference between naive routing and Dijkstra-optimized routing can be several kilometres — a difference that in real emergencies can mean the difference between life and death.

The project also highlighted the importance of weight validation before algorithm execution. Dijkstra's algorithm requires non-negative edge weights to guarantee correctness — a mathematical constraint that has direct practical consequences. Building the validation check into the graph construction phase demonstrated the principle of fail-fast design in software engineering. Working on this project improved problem-solving ability, algorithmic thinking, graphtheoretic modelling skills, and practical software development capabilities.

Chapter 8:

CONCLUSION & FUTURE SCOPE

The Emergency Response Network Optimization System successfully demonstrates the application of graph theory concepts in urban emergency dispatch management.

The project models the city's emergency response network as a weighted undirected graph and applies Dijkstra's shortest-path algorithm to compute optimized routes between any service location and the emergency incident site.

The developed system reduces emergency response distance, minimizes fuel consumption, improves dispatch efficiency, and supports sustainable public safety management practices. The system was validated across all 45 possible source-destination node pairs and returned the globally optimal path in every case.

The project establishes a strong foundation for future smart-city emergency response infrastructure systems.

Future Scope

The system can be further enhanced using:

- IoT Sensors for real-time traffic and road condition monitoring
- GPS Vehicle Tracking for dynamic re-routing of active emergency units
- Real-Time Traffic Integration via Google Maps API or HERE Traffic
- AI-Based Incident Prediction using historical data and ML models
- Multi-Vehicle Optimization extending to full Vehicle Routing Problem
- Mobile Applications for field emergency crew navigation

- Smart-City Infrastructure integration with city management platforms

Chapter 9:


REFERENCES

1. Graph Theory with Applications to Engineering and Computer Science, Dover Publications, 2016.
2. Graph Theory with Applications, Springer, 1st Edition, 2008.
3. Discrete and Combinatorial Mathematics, PHI, 5th Edition, 2006.
4. Handbook of Discrete and Combinatorial Mathematics, 2000.
5. Discrete Mathematics, McGraw Hill Education, 3rd Edition, 2017.
6. E. W. Dijkstra — A Note on Two Problems in Connexion with Graphs, Numerische Mathematik, Vol. 1, 1959.
7. NetworkX Documentation — NetworkX: Network Analysis in Python, networkx.org, 2024.
8. Prescribed TextBook – Narsingh Deo – Graph Theory With Applications to Engineering and Computer Science.

Chapter 10:

SCREENSHOTS

Screenshot 1: Network Visualization



[Screenshot of the Matplotlib graph showing the 10-node emergency network with color-coded nodes, labeled edge weights on all 20 roads, and the shortest path highlighted in red]

- Displays the complete 10-node emergency response network.
- Shortest path highlighted in red with directional arrows.
- All edge weights labeled in kilometres.
- **Screenshot 2: Python Code Implementation**

```
#
# 3. FIND SHORTEST PATH (DIJKSTRA)
# -----

def find_shortest_path(graph, source, destination):
    """
    Uses Dijkstra's Algorithm (via NetworkX) to find the
    shortest weighted path between source and destination.

    Returns:
        path      (list) : ordered list of nodes
        distance  (float): total distance in km
    Raises:
        nx.NetworkXNoPath if no route exists.
    """
    path = nx.shortest_path(
        graph,
        source=source,
        target=destination,
        weight='weight',
        method='dijkstra'      # explicit - no ambiguity
    )
    distance = nx.shortest_path_length(
        graph,
        source=source,
        target=destination,
        weight='weight'
    )
    return path, distance
```

- Dijkstra's shortest-path implementation using NetworkX library.
- Returns the optimal path list and total distance in kilometres.