

Plumber (Service and Operation)

Level - 4

NOS PSC/N 0101 Installation of basic sanitary fixtures, fittings, related piping and accessories

NOS1: PSC/N 0101 Installation of	f basic sanitary	fixtures, fittings,	related piping an	d accessories
----------------------------------	------------------	---------------------	-------------------	---------------

1.	Mark	kings of sanitary fixtures and pipe lines can be done by using
		Water level
		Spirit level
		Measurment tape
		Measurment scale
	٥.	- Nousannent source
2.	Maxi	mum height of normal EWC should be
		450mm to 500 mm
	В.	1000mm to 1200 mm
	C.	900mm to 1000 mm
	D.	100mm to 200 mm
2	If fivt	ture point is lower than finishing wall level, fitting should be used to fix any tap
٦.		Pipe bend
		Hex nipple
		Extension nipple
		Pipe nipple
	٥.	Tipe implies
4.	For fi	ixtures like pillar cock, sink cock with outside threads, fittings is suitable.
		Female threaded adapter
		Male threaded adapter
		Plain elbow
	D.	Pipe bushing reducer (plain)
5.		is used for dye test of flush line
	A.	Brine solution
		Filter water
	C.	Potassium permanganate
	D.	Acid
6	Dillar	cock is used for
υ.		Sink
		Wash basin EWC
		All the above
	υ.	All the above
7.	Angle	e valve is used near
•	_	Supply points
		Delivery points
		Waste line
		Flush line



8. Cock	roach trap is used in
A.	<mark>Floor</mark>
	Terrace
C.	Ceiling
D.	All the above
9. Hold	Itite is used for fittings.
	Threaded fittings
В.	Push type fittings
C.	Plain fittings
D.	Rubber fittings
10. Ma	ximum height of wash basin is
	1 to 2 metre
В.	2 to 3 metre
C.	4 to 6 metre
D.	0.8 to 0.9 metre
11. Thr	read ball is used for fittings.
	Threaded fittings
В.	Push type fittings
	Plain fittings
D.	Rubber fittings
12. Ho	w to connect bath tub tap with angle valve
A.	Flexible hose pipe
В.	PVC pipe
C.	UPVC pipe
D.	CPVC pipe
13. Ho	w many angle valves are needed for one pillar cock?
A.	<mark>One</mark>
В.	Two
C.	Three
D.	Four
14. Gei	nerally, maximum height of bath tub is
A.	1.4 to 2 metre
В.	2.5 to 3 metre
C.	3- 4 metre
D.	0.4-0.55 metre
15. Aqı	ua guard water purifier is fixed in
A.	Toilet
В.	Balcony
C.	Bedroom
D.	<mark>Kitchen</mark>



16.		se union bib tap is generally used in
		Gardens Rate of the second sec
		Balcony
		Toilet
	υ.	Kitchen
NO	S2:	PSC/ N 0102 (Repair of basic plumbing systems)
17.	Nor	return valve direction should be in the
		Direction of flow of water
		Opposite to water flow
		Parallel to water flow
		Perpendicular to water flow
18.		nerally, you need fitting to fix flanged gate valves.
		Male threaded adapter
		Female threaded adapter
		Vanstone flange
	D.	All the above
19.	Cut	ting of pipes should be to pipe axis.
	A.	Parallel
	В.	Perpendicular Pe
		Same direction
	D.	None of the above
20	W/h	ile emptying tank/sump, it must be
20.		Opened
		Closed
		Damaged
	υ.	All the above
21.	То	connect these two pipes, the fittings needed are
	A.	Pipe wye, pipe bend
	В.	Pipe adapter
	C.	Pipe double wye
		Pipe bend, pipe adapter
22. PRV full form is		
	Α.	Pressure relief valve
		Pressure refusing valve
		Pressure reading valve
	D.	Pressure reducing valve



23. While assembling pipes should be prepared.	
A. <mark>Pipe edge</mark>	
B. Pipe inside	
C. Pipe outside	
D. None of the above	
24. Why is P-trap used for waste line?	
A. To reduce the bad smell	
B. To increase the bad smell	
C. To reduce the cost	
D. To increase the cost	
25. 65 mm upvc astm pipe is thick	
A. 1 "	
B. 2"	
C. 1 ¼"	
D. <mark>2 ½"</mark>	
26. Which of the following is suitable to connect 160 mm pipe and 110	mm pipe?
A. 160 mm elbow	
B. 100 mm wye	
C. 110 x 160 mm reducer coupler	
D. All the above	
27. Consently, which give is used for self-weeks giving 2	
27. Generally, which pipe is used for soil waste piping?A. Mild steel	
B. Stainless steel	
C. PVC	
D. CPVC	
D. CIVC	
28. 10 centimetre = m	
A. <mark>0.1</mark>	
B. 100	
C. 1000	
D. 10	
29. In plumbing, male threaded means	
A. Inside threaded	
B. Outside threaded	
C. Full threaded	
D. Half threaded	
30. In general practice, levelling of water pipes will be done by using	·
A. Spirit level	
B. Water level	
C. Pipe level	
D. Mercury meter	



NOS 3: PSC/ N 0106 (Service and operation of plumbing systems)

31. N	Nun	nber of fittings in the system should be
A	٩.	More
E	В.	Less
(C.	Equal to the length of pipe
		None of the above
32. If	f nı	umbers of joints are more, then there are chances of leakage.
	۹.	More Service S
E	В.	Less
		No
		Option B & C
•	٠.	option b a c
33 A	۱fte	er completion of plumbing system, checking the lines with water is called
		Mock run
		Model run
		All the above
	υ.	All the above
34 A	۱۱ ۱	he joints should be checked
		Yearly
		Monthly
		Daily
		When you have time
ı	υ.	vitien you have time
35 9	inn	ut is used in
	•	Higher levels
		Soil line
		Waste line
		Sunken Sunken
	υ.	Suiken
NOS	: 4.	PSC/ N 0108 (Coordinate with working team)
1403	, 7.	1 3C/ W 0100 (Coordinate with working team)
36. N	Mat	terial should be received as per the requirement of
		Plumber
		Mason
	С. С.	Electrician
		All the above
	٥.	All the above
37 A	۱fte	er completion of work, plumber assistant needs to
	νιτο 4.	Collect and dispose of all the waste material
	ъ. В.	Check the joints
		Conduct hydro test
		Carry out levelling of pipes
L	υ.	carry out revening or pipes
38	Δn	lumber has to always carry
	Αρ 4.	Basic tools
		Pipes
		Fittings
		Solvent cement
L	┙ .	Joivent centent



	А. В.	aying down power cables of machines, plumber has to coordinate with Mechanical Electrical	Department
		Power tools dept. Civil	
	A. B. C.	nich department does issue the materials? Purchase Estimation Stores Civil execution	
NO	S5.	PSC/ N 0109 (maintain a healthy, safe and secure working environment	
	A. B. C.	Power chord Hand tools Hand gloves Dust mask	
	A. B. C.	nat safety measure is needed while working at height? Dust mask Ear plugs Hand glove Safety belt	
	A. B. C.	avoid the effect of sound pollution is useful. Dust mask Ear plugs Hand glove Safety belt	
	A. B. C.	avoid head injuries is needed. Helmet Safety belt Shoe Apron	
	Wh A. B. C. D.	cat is the first safety measure to be taken while doing underground works? Caution board near working area Dust mask Hand glove Safety belt	