



edureka!
a Veranda Enterprise



Full Stack Web Development Program



edureka!
a Veranda Enterprise



Day 18 - Data Types and Operators in JavaScript

Activate Windows
Go to Settings to activate Windows.

Titles - I

- String
- Number
- Boolean
- Undefined
- Null
- BigInt
- Symbol
- Arrays
- Objects
- Function
- Operators



Activate Windows
Go to Settings to activate Windows.

Titles - II

- Arithmetic Operators
- Assignment Operators
- Comparison Operators
- Logical Operators
- Conditional Statements
- If Statement
- If-else Statement
- else if Statement
- Switch Statement
- Looping Statements
- for Loop



Activate Windows
Go to Settings to activate Windows.

Titles - III

- while Loop
- do..while Loop
- for..in loop
- for..of Loop



Activate Windows
Go to Settings to activate Windows.

Learning Objectives

By the end of this module, you will be able to:

- Elaborate Primitive and Reference data types
- Make use of Arithmetic, Assignment, Logical and Comparison operators
- Recall the syntax and usage of the Conditional and Looping statements



Activate Windows
Go to Settings to activate Windows.



Data Types and Operators in JavaScript

Activate Windows
Go to Settings to activate Windows.

String

- JavaScript's String is a type that is used to represent a sequence of characters.
- It is useful for holding data represented in text form.
- String data must be enclosed either in single(') or double quotation(") marks.

Syntax:

```
keyword variablename = "value/text";  
                        (OR)  
keyword variablename = new String("text")
```

General way for
creating string

Creation of string
using **new** operator

Example:

```
var str = " Edureka ";  
OR  
var str = new  
String("Edureka " );
```

Activate Windows
Go to Settings to activate Windows.

Number

- The number is a type that is used to represent and manipulate numbers like 37 or -9.25.
- The number can be written with or without decimals.
- In JavaScript, we only have numbers; it does not categorize numbers into further categories like int, short int, long, float, long int, etc.

Syntax:

```
keyword variablename = value;  
                        (OR)  
keyword variablename = new Number(value);
```

General way for creating
variable of type number

Creation of number using
new operator

Example:

```
var number = 90;  
OR  
var str = new  
Number(90);
```

Activate Windows
Go to Settings to activate Windows.

Boolean

- Boolean is a type that is used to represent true and false values.
- This data type is mainly used in a conditional expression with true or false values.

Syntax:

```
keyword variablename = true/false;  
OR  
keyword variablename = new Boolean(true/false);
```

The general way for
creating a variable of
type boolean

Creation of boolean using
new operator using
Constructor

Example:

```
var boolean=true;  
OR  
var str = new  
Boolean(false);
```

Undefined

- It is a primitive data type in JavaScript.
- The undefined property indicates that a variable has not been assigned a value or not declared at all.
- It indicates there is no value in the variable, or you can assume a variable has nothing inside it.



Variable with value – (Defined)



Variable without value – (Undefined)

Null

- JavaScript null is a primitive data type that contains a special value **null**.
- JavaScript uses the null value to represent the intentional absence of any object value.
- If you find a variable or a function that returns null, it means that the expected object could not be created.

Syntax:

```
variablename = null;
```

General way for creating
variable of type null

Example:

```
var a=null;
```

BigInt

- BigInt is a numeric primitive data type in JavaScript.
- The name of the data type itself tells that it can store large numbers. It stores a large number which is not possible for the Number data type to store.
- We must add **n** at the end of the number while assigning value to a BigInt variable.

Syntax:

```
keyword variablename = value;  
OR  
keyword variablename = new BigInt(value);
```

The general way for creating a variable of type BigInt

Creation of BigInt using **new** operator using Constructor

Example:

```
var a=39898998n;  
OR  
var  
a=BigInt(59898)
```

Activate Windows
Go to Settings to activate Windows.

Symbol

- A Symbol is an immutable primitive data type.
- It can be used to store the symbol values.
- It can be used as the key to an object

Syntax:

```
keyword variablename = new Symbol(value);
```

Creation of Symbol using
new operator using
Constructor

Example:

```
var a= Symbol(87)
```

Activate Windows
Go to Settings to activate Windows.


Arrays

- Array is defined as a collection of heterogeneous elements.
- It helps to store multiple values of the different or same data type in a single variable.



Example

```
var arr = [ "Apple", "Mango", 123, "Avocado", 153.1 ]
```



Activate Windows
Go to Settings to activate Windows.

Objects

- JavaScript object is a non-primitive data type that allows you to store multiple collections of data.
- An object can be created with figure brackets {...} with an optional list of properties.
- A property is a **key: value** pair, where the **key** is a string (also called a property name), and the **value** can be anything.

Syntax:

```
let objectname = {           //  
    an object  
  
    "key1": "value1",  
    "key2": "value2"  
    ...  
    ...  
};
```

Example:

```
let studentObject = { // an object  
  
    rno: 101, // key "rno" stores value 101  
    name: "Alexa" // key "name" stores value  
};
```

Function

- JavaScript functions provide encapsulated environments, isolating their variables and logic from the global scope.
- Functions in JavaScript are versatile objects, usable as variables, arguments, and with properties, supporting advanced programming patterns.
- JavaScript functions can be used as callbacks, enabling asynchronous programming and handling events or data after an operation completes.

Syntax:

```
functionName = function() {  
    .....  
    .....  
    return value;  
}
```

Block of code

Activate Windows
Go to Settings to activate Windows.

Function - Example

```
<script>
```

```
myFunc = function () {  
  var a = 10;  
  var b = 20;  
  return (a + b);  
}
```

Function
Declaration

```
console.log(myFunc())
```

Function
Call

```
</script>
```

Output:

30