

Practical 3

- **Create a Sign-Up Form in React JS. The Sign-up form should ask for Name, Mobile, Email, Address, Date of Birth, Gender, Username, Password and Confirm Password. The Form should have two buttons, one for reset and one for submitting. The Submit Button should be enabled only when all the input values are validated.**

src/App.js

```
import './App.css';

import SignUpForm from '../components/SignUpForm';

function App() {
  return (
    <>
    <SignUpForm/>
    </>
  );
}

export default App;
```

src/components/SignUpForm.js

```
import React, { useState, useEffect } from 'react';

import './SignUpForm.css'

const SignUpForm = () => {
  // State for form fields

  const [name, setName] = useState("");
  const [mobile, setMobile] = useState("");
  const [email, setEmail] = useState("");
  const [address, setAddress] = useState("");
  const [dob, setDob] = useState("");
```

xyz

xyz

```

    const [gender, setGender] = useState("");
    const [username, setUsername] = useState("");
    const [password, setPassword] = useState("");
    const [confirmPassword, setConfirmPassword] = useState("");

    // State for form validation
    const [isFormValid, setIsFormValid] = useState(false);

    // Basic validation checks
    useEffect(() => {
        const isValid = name && mobile.match(/^d{10}$/) &&
        // Mobile should be 10 digits
        email.match(/^[a-zA-Z0-9_+-.]+@[a-zA-Z0-9-]+\.[a-zA-Z0-9-]+$/ ) &&
        // Valid email format address && dob && gender && username && pass.length >=6
        // Password should be at least 6 characters password ===confirmPassword;
        // Password and Confirm Password match

        setIsFormValid(isValid);
    }, [name, mobile, email, address, dob, gender, username,
        password, confirmPassword]);

    // Handle form submission
    const handleSubmit = (e) => {
        e.preventDefault();
        if (isFormValid) {
            alert('Form submitted successfully');
            // Submit logic goes here, like sending data to the server }; }
        } else {
            alert('Please fill in all fields correctly'); }
    }

    // Handle form reset
    const handleReset = () => {
        setName(' ');
        setMobile("");
    }

```

```
    setEmail("");
    setAddress("");
    setDob("");
    setGender("");
    setUsername("");
    setPassword("");
    setConfirmPassword("");
  };
  return (
    <div className='main'>
      <h1>Sign Up</h1>
      <form onSubmit={handleSubmit}>
        <div>
          <label>Name:</label>
          <input type="text" value={name} onChange = { (e) =>
            setName (e.target.value)} required/>
        </div>

        <div>
          <label>Mobile:</label>
          <input type="text" vaue={mobile} onChange ={ (e) =>
            setMobile(e.target.value)} maxLength={10} required/>
        </div>

        <div>
          <label>Email:</label>
          <input type="email" value={email} onChange = { (e) =>
            setEmail (e.target.value)} required/>
        </div>
      </form>
    </div>
  );
}
```

```
<div>
<label>Address:</label>
<textarea value={address} onChange = { (e) =>
setAddress (e.target.value)} required/>
</div>
```

```
<div>
<label>Date of Birth:</label>
<input type="date" value={dob} onChange = { (e) =>
setDob (e.target.value)} required/>
</div>
```

```
<div>
<label>Gender:</label>
<select value={gender} onChange = { (e) =>
setGender (e.target.value)} required>
<option value="">Select</option>
<option value="male">Male</option>
<option value="female">Female</option>
<option value="other">Other</option>
</select>
</div>
```

```
<div>
<label>Username:</label>
<input type="text" value={username} onChange={{e)=>
setUsername (e.target.value)} required/>
</div>
```

```
<div>
  <label>Password:</label>
  <input type="password" value={password}
    onChange = { (e) => setPassword (e.target.value)}
    required/>
</div>
```

```
<div>
  <label>Confirm Password:</label>
  <input type="password" value={confirmPassword}
    onChange = { (e) =>
      setConfirmPassword (e.target.value)} required/>
</div>
```

```
<div>
  <button type="reset" onClick={handleReset}>Reset</button>
  <button type="submit" disabled={!isFormValid}>Submit</button>
</div>
</form>
</div>
```

```
);
```

```
};
```

```
export default SignUpForm;
```