

# CS315: Principles of Database Systems

## Entity-Relationship Diagram

Arnab Bhattacharya  
`arnabb@cse.iitk.ac.in`

Computer Science and Engineering,  
Indian Institute of Technology, Kanpur  
<http://web.cse.iitk.ac.in/~cs315/>

2<sup>nd</sup> semester, 2013-14  
Tue, Fri 1530-1700 at CS101

# Model

- A database is a collection of *entities* and the *relationships* among them

- A database is a collection of *entities* and the *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons

- A database is a collection of *entities* and the *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons
- A **relationship** is an association among the entities
- A **relationship set** is a relation among two or more entities, each taken from an entity set, e.g., person is a depositor for an account

- A database is a collection of *entities* and the *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons
- A **relationship** is an association among the entities
- A **relationship set** is a relation among two or more entities, each taken from an entity set, e.g., person is a depositor for an account
- Relationship sets can also have attributes, e.g., access date for depositor
- Primary keys of entity sets form a superkey of the relationship set

## Model (contd.)

- Relationships between two entity sets are *binary*
  - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many

# Model (contd.)

- Relationships between two entity sets are *binary*
  - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
  - Simple or composite
  - Single-valued or multi-valued (e.g., phone number)
  - Derived (e.g., age)

# Model (contd.)

- Relationships between two entity sets are *binary*
  - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
  - Simple or composite
  - Single-valued or multi-valued (e.g., phone number)
  - Derived (e.g., age)
- Participation can be total (every entity participates in the relationship) or partial (not all participate)



# Model (contd.)

- Relationships between two entity sets are *binary*
  - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
  - Simple or composite
  - Single-valued or multi-valued (e.g., phone number)
  - Derived (e.g., age)
- Participation can be total (every entity participates in the relationship) or partial (not all participate)
- Specialization, generalization, aggregation are features of extended ER model


# Weak entity sets

- An entity set that does *not* have a primary key is called a **weak entity set**
- Its existence depends on the existence of another entity set called the **identifying entity set** or **owner entity set**
- The **identifying relationship set** that exists between the two must be *total* and *many-to-one* from the weak entity set
- A weak entity set has a *discriminator* or **partial key** instead of a primary key
- The discriminator distinguishes weak entities that are related to the same entity of the identifying entity set
- The *primary key* is formed by the primary key of the identifying set and the discriminator


# ER diagram

- Entity sets: rectangles
- Relationship sets: diamonds
- Attributes: ellipses
  - Multivalued attributes: double ellipses
  - Derived attributes: dashed ellipses
- Primary keys: underlines
- Roles: on links
- Cardinality constraints
  - One: directed
  - Many: undirected
  - One-to-many: directed-diamond-undirected
- Participation
  - Total: double line
  - Partial: single line
- Cardinality limits: on lines
- Weak entity sets: double rectangle
- Weak relationship set: double ellipse
- Discriminator of a weak entity sets: underline with dashed lines

# Summary of ER diagram



# Example: banking schema



# Reduction to relational model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
  - A foreign key relationship is set up
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
  - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships,

# Reduction to relational model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
  - A foreign key relationship is set up
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
  - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial,

# Reduction to relational model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
  - A foreign key relationship is set up
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
  - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships



# Reduction to relational model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
  - A foreign key relationship is set up
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
  - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships must be reduced to relations
- Each component of a composite attribute is modeled separately
- Multivalued attributes

# Reduction to relational model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
  - A foreign key relationship is set up
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
  - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships must be reduced to relations
- Each component of a composite attribute is modeled separately
- Multivalued attributes are reduced to relations that include the primary key of the entity set