

# TU-Delft Deep Learning course 2018-2019

03.backprop

20 Feb 2019



Delft University of Technology

Lecturer: Jan van Gemert  
Several slides credit to Roger Grosse

# Learning goals

After this lecture you can:

- Understand what the goal of backpropagation is
- Explain the forward/backward pass
- Apply the calculus chain rule to compute derivatives
- Apply the backpropagation algorithm to efficiently compute derivatives
- Understand the modularity of network nodes

Book chapters: 4.3, 6.5

# Training a network


## Chapter 4.3

Training set:

| Data |   | Label |
|------|---|-------|
| 0    | 1 | 1     |
| 1    | 1 | 0     |
| 0    | 0 | 0     |
| 1    | 0 | 1     |

While not converged:

1. Present a training sample
2. Compare the results
3. Update the weights



# Training a network


## Chapter 4.3

Training set:

| Data |   | Label |
|------|---|-------|
| 0    | 1 | 1     |
| 1    | 1 | 0     |
| 0    | 0 | 0     |
| 1    | 0 | 1     |

While not converged:

1. Present a training sample → Forward pass
2. Compare the results
3. Update the weights



# Training a network


## Chapter 4.3

Training set:

| Data |   | Label |
|------|---|-------|
| 0    | 1 | 1     |
| 1    | 1 | 0     |
| 0    | 0 | 0     |
| 1    | 0 | 1     |

While not converged:

1. Present a training sample → **Forward pass**
2. Compare the results → **Loss**
3. Update the weights



# Training a network


## Chapter 4.3

Training set:

| Data |   | Label |
|------|---|-------|
| 0    | 1 | 1     |
| 1    | 1 | 0     |
| 0    | 0 | 0     |
| 1    | 0 | 1     |

While not converged:


1. Present a training sample → **Forward pass**
2. Compare the results → **Loss**
3. Update the weights → **Backward pass**



# Backward pass: Backpropagation

- Backpropagation: Efficient algorithm to compute gradients
- Used to train a huge majority of deep nets
- Engine that powers “End-to-End” optimization and representation learning
- Its “just” a clever application of the chain rule of calculus


# Updating the weights: Gradient descent



1-d gradient descent




# Updating the weights: Gradient descent



1-d gradient descent

- Q: How does “1-d” change for a multi-layer network?


# Updating the weights: Gradient descent



1-d gradient descent

- Q: How does “1-d” change for a multi-layer network?
- A: One coordinate for each weight/bias in *all* the layers


# Updating the weights: Gradient descent



1-d gradient descent

- Q: How does “1-d” change for a multi-layer network?
- A: One coordinate for each weight/bias in *all* the layers
- Compute cost gradient  $\frac{d\mathcal{E}}{d\mathbf{w}}$ : vector of partial derivatives
- Q: How to get cost gradient from training samples?

# Updating the weights: Gradient descent



1-d gradient descent

- Q: How does “1-d” change for a multi-layer network?
- A: One coordinate for each weight/bias in *all* the layers
- Compute cost gradient  $\frac{d\mathcal{E}}{d\mathbf{w}}$ : vector of partial derivatives
- Q: How to get cost gradient from training samples?
- A: Average  $\frac{d\mathcal{L}}{d\mathbf{w}}$  for loss  $\mathcal{L}$  over all training samples

# Chain rule to compute derivatives

- Deep net is a function chain  $f(x) = f^{(3)}(f^{(2)}(f^{(1)}(x)))$

Q: How to compute  $f(g(x))'$  ?

# Chain rule to compute derivatives

- Deep net is a function chain  $f(x) = f^{(3)}(f^{(2)}(f^{(1)}(x)))$

Q: How to compute  $f(g(x))'$  ?

A:  $f(g(x))' = f'(g(x))g'(x)$

# Chain rule to compute derivatives

- Deep net is a function chain  $f(x) = f^{(3)}(f^{(2)}(f^{(1)}(x)))$

Q: How to compute  $f(g(x))'$  ?

A:  $f(g(x))' = f'(g(x))g'(x)$

- Let:  $y = g(x)$ , and  $z = f(g(x)) = f(y)$ .
- Other notation:

$$\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$$

- Multi-variate chain rule, let  $f = (x(t), y(t))$ , then

# Chain rule to compute derivatives

- Deep net is a function chain  $f(x) = f^{(3)}(f^{(2)}(f^{(1)}(x)))$

Q: How to compute  $f(g(x))'$  ?

A:  $f(g(x))' = f'(g(x))g'(x)$

- Let:  $y = g(x)$ , and  $z = f(g(x)) = f(y)$ .
- Other notation:

$$\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$$

- Multi-variate chain rule, let  $f = (x(t), y(t))$ , then

$$\frac{d}{dt} f(x(t), y(t)) = \frac{\partial f}{\partial x} \frac{dx}{dt} + \frac{\partial f}{\partial y} \frac{dy}{dt}$$



# Chain rule to compute derivatives

- Deep net is a function chain  $f(x) = f^{(3)}(f^{(2)}(f^{(1)}(x)))$

Q: How to compute  $f(g(x))'$  ?

A:  $f(g(x))' = f'(g(x))g'(x)$

- Let:  $y = g(x)$ , and  $z = f(g(x)) = f(y)$ .
- Other notation:

$$\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$$

- Multi-variate chain rule, let  $f = (x(t), y(t))$ , then

$$\frac{d}{dt} f(x(t), y(t)) = \frac{\partial f}{\partial x} \frac{dx}{dt} + \frac{\partial f}{\partial y} \frac{dy}{dt}$$

- Interpretation: How much does output change if the input slightly changes

## Assignment: Compute loss $\mathcal{L}$ derivatives

Model:  $\mathcal{L} = \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x} + \mathbf{b}) - t)^2$ , where  $t = \text{true label}$

Q: What to compute?

# Assignment: Compute loss $\mathcal{L}$ derivatives

Model:  $\mathcal{L} = \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2$ , where  $t = \text{true label}$

Q: What to compute?

A: Derivative to  $w$

$$\frac{\partial}{\partial w} \mathcal{L} = \frac{\partial}{\partial w} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right]$$

A: Derivative to  $b$

$$\frac{\partial}{\partial b} \mathcal{L} = \frac{\partial}{\partial b} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right] =$$

# Assignment: Compute loss $\mathcal{L}$ derivatives

Model:  $\mathcal{L} = \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2$ , where  $\mathbf{t}$  = true label

Q: What to compute?

A: Derivative to  $w$

$$\begin{aligned}\frac{\partial}{\partial w}\mathcal{L} &= \frac{\partial}{\partial w} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right] \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \frac{\partial}{\partial w} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \frac{\partial}{\partial w} (\mathbf{w}\mathbf{x}+\mathbf{b}) \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \mathbf{x}\end{aligned}$$

A: Derivative to  $b$

$$\begin{aligned}\frac{\partial}{\partial b}\mathcal{L} &= \frac{\partial}{\partial b} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right] = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \frac{\partial}{\partial b} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \frac{\partial}{\partial b} (\mathbf{w}\mathbf{x}+\mathbf{b}) = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b})\end{aligned}$$

# Assignment: Compute loss $\mathcal{L}$ derivatives

Model:  $\mathcal{L} = \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2$ , where  $\mathbf{t}$  = true label

Q: What to compute?

A: Derivative to  $w$

$$\begin{aligned}\frac{\partial}{\partial w} \mathcal{L} &= \frac{\partial}{\partial w} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right] \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \frac{\partial}{\partial w} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \frac{\partial}{\partial w} (\mathbf{w}\mathbf{x}+\mathbf{b}) \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \mathbf{x}\end{aligned}$$

A: Derivative to  $b$

$$\begin{aligned}\frac{\partial}{\partial b} \mathcal{L} &= \frac{\partial}{\partial b} \left[ \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t})^2 \right] = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \frac{\partial}{\partial b} (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b}) \frac{\partial}{\partial b} (\mathbf{w}\mathbf{x}+\mathbf{b}) = \\ &= (\sigma(\mathbf{w}\mathbf{x}+\mathbf{b})-\mathbf{t}) \sigma'(\mathbf{w}\mathbf{x}+\mathbf{b})\end{aligned}$$

Q: What are the disadvantages of this approach?

## More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(\mathbf{w}\mathbf{x} + \mathbf{b}) - t)^2$$

$$\text{Decompose in: } z = \mathbf{w}\mathbf{x} + \mathbf{b}, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives?



# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives? A: 4 (efficient re-use)

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2}(y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives? A: 4 (efficient re-use)

$$(1) : \frac{d\mathcal{L}}{dy} =$$

$$(2) : \frac{d\mathcal{L}}{dz} =$$

$$(3) : \frac{d\mathcal{L}}{dw} =$$

$$(4) : \frac{d\mathcal{L}}{db} =$$

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives? A: 4 (efficient re-use)

$$(1) : \frac{d\mathcal{L}}{dy} = y - t, \quad (2) : \frac{d\mathcal{L}}{dz} = \frac{d\mathcal{L}}{dy} \sigma'(z), \quad (3) : \frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dz} x, \quad (4) : \frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dz}.$$

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2} (y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives? A: 4 (efficient re-use)

$$(1) : \frac{d\mathcal{L}}{dy} = y - t, \quad (2) : \frac{d\mathcal{L}}{dz} = \frac{d\mathcal{L}}{dy} \sigma'(z), \quad (3) : \frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dz} x, \quad (4) : \frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dz}.$$

Q: Dependency order of computation?

# More efficient computation of loss $\mathcal{L}$ derivatives

$$\text{Model: } \mathcal{L} = \frac{1}{2} (\sigma(wx+b)-t)^2$$

$$\text{Decompose in: } z = wx + b, \quad y = \sigma(z), \quad \mathcal{L} = \frac{1}{2}(y - t)^2$$

Q: Rewrite using chain rule in terms of  $\frac{dz}{dx} = \frac{dy}{dx}$ ?

A: Derivative to  $w$

$$\frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{dw}$$

A: Derivative to  $b$

$$\frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dy} \frac{dy}{dz} \frac{dz}{db}$$

Q: Nr unique terms to compute both derivatives? A: 4 (efficient re-use)

$$(1) : \frac{d\mathcal{L}}{dy} = y - t, \quad (2) : \frac{d\mathcal{L}}{dz} = \frac{d\mathcal{L}}{dy} \sigma'(z), \quad (3) : \frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dz} x, \quad (4) : \frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dz}.$$

Q: Dependency order of computation? A: Starts backwards.

# Re-using pre-computed values

Expressions to evaluate

$$\frac{df}{dt} = \left( \frac{\partial f}{\partial x} \frac{dx}{dt} \right) + \left( \frac{\partial f}{\partial y} \frac{dy}{dt} \right)$$


Values already computed

The diagram illustrates the reuse of pre-computed values in a chain rule expression. The equation  $\frac{df}{dt} = \left( \frac{\partial f}{\partial x} \frac{dx}{dt} \right) + \left( \frac{\partial f}{\partial y} \frac{dy}{dt} \right)$  is shown. The terms  $\frac{\partial f}{\partial x}$  and  $\frac{\partial f}{\partial y}$  are circled and labeled 'Values already computed' with arrows pointing to them from below. The terms  $\frac{dx}{dt}$  and  $\frac{dy}{dt}$  are also circled and labeled 'Expressions to evaluate' with arrows pointing to them from above.

---

<sup>1</sup>Bar notation credits to Roger Grosse

# Re-using pre-computed values




Bar notation:

- Backprop is an algorithm to compute values
- Bar notation<sup>1</sup> for computed values:  $\bar{y} = \frac{d\mathcal{E}}{dy}$
- Less cluttered and emphasizes value re-use

---

<sup>1</sup>Bar notation credits to Roger Grosse

# Re-using pre-computed values



Bar notation:

- Backprop is an algorithm to compute values
- Bar notation<sup>1</sup> for computed values:  $\bar{y} = \frac{d\mathcal{E}}{dy}$
- Less cluttered and emphasizes value re-use


Example:  $z = wx + b$ ,  $y = \sigma(z)$ ,  $\mathcal{L} = \frac{1}{2}(y - t)^2$

---

<sup>1</sup>Bar notation credits to Roger Grosse



# Re-using pre-computed values



Bar notation:

- Backprop is an algorithm to compute values
- Bar notation<sup>1</sup> for computed values:  $\bar{y} = \frac{d\mathcal{E}}{dy}$
- Less cluttered and emphasizes value re-use


Example:  $z = wx + b$ ,  $y = \sigma(z)$ ,  $\mathcal{L} = \frac{1}{2}(y - t)^2$

Instead of:

$$(1) : \frac{d\mathcal{L}}{dy} = y - t, \quad (2) : \frac{d\mathcal{L}}{dz} = \frac{d\mathcal{L}}{dy} \sigma'(z), \quad (3) : \frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dz} x, \quad (4) : \frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dz}.$$

<sup>1</sup>Bar notation credits to Roger Grosse

# Re-using pre-computed values



Bar notation:

- Backprop is an algorithm to compute values
- Bar notation<sup>1</sup> for computed values:  $\bar{y} = \frac{d\mathcal{L}}{dy}$
- Less cluttered and emphasizes value re-use

Example:  $z = wx + b$ ,  $y = \sigma(z)$ ,  $\mathcal{L} = \frac{1}{2}(y - t)^2$

Instead of:

$$(1) : \frac{d\mathcal{L}}{dy} = y - t, \quad (2) : \frac{d\mathcal{L}}{dz} = \frac{d\mathcal{L}}{dy} \sigma'(z), \quad (3) : \frac{d\mathcal{L}}{dw} = \frac{d\mathcal{L}}{dz} x, \quad (4) : \frac{d\mathcal{L}}{db} = \frac{d\mathcal{L}}{dz}.$$


Write:

$$(1) : \bar{y} = y - t, \quad (2) : \bar{z} = \bar{y} \sigma'(z), \quad (3) : \bar{w} = \bar{z} x, \quad (4) : \bar{b} = \bar{z}.$$

<sup>1</sup>Bar notation credits to Roger Grosse


# Computational graph

Book: Section 6.5.1



# Computational graph


Book: Section 6.5.1



- A node is a variable: scalar, vector, matrix, tensor, other node, etc.
- An operation: simple function of 2 variables (often omitted)
- Operation have single output (possibly multiple entries)
- $x \rightarrow y$ :  $y$  is computed by applying operation to  $x$ .

# Backpropagation algorithm

Book: Algorithms 6.1 and 6.2




Topological ordering:

Linear ordering of vertices so for every directed edge  $uv$ , vertex  $u$  comes before  $v$  in the ordering.

# Backpropagation algorithm

Book: Algorithms 6.1 and 6.2




Topological ordering:

Linear ordering of vertices so for every directed edge  $uv$ , vertex  $u$  comes before  $v$  in the ordering.

Q: Topological ordering of graph?

# Backpropagation algorithm

Book: Algorithms 6.1 and 6.2



Topological ordering:


Linear ordering of vertices so for every directed edge  $uv$ , vertex  $u$  comes before  $v$  in the ordering.

Q: Topological ordering of graph?

A:  $(w, b, x, z, y, t, \mathcal{L}, \mathcal{R}, \mathcal{L}_{reg})$

# Backpropagation algorithm

Book: Algorithms 6.1 and 6.2



Topological ordering:

Linear ordering of vertices so for every directed edge  $uv$ , vertex  $u$  comes before  $v$  in the ordering.

Q: Topological ordering of graph?

A:  $(w, b, x, z, y, t, L, R, L_{\text{reg}})$

Backpropagation algorithm to compute gradients of node  $n_N$ :

1. Create topological ordering of graph

2. For  $i = 1, 2, \dots, N$  :

Evaluate  $n_i$  using its function  $f^{(i)}(n_i)$

3.  $\overline{n}_N = 1$  (gradient of a node wrt itself is 1;  $\frac{df}{df} = 1$ )


4. For  $i = N - 1, \dots, 1$  :

$$\overline{n}_i = \sum_{n_j \in \text{Children}(n_i)} \overline{n}_j \frac{\partial n_j}{\partial n_i}$$

Note on step 4: node only gets gradients wrt children nodes




# Backprop as message passing




- Each node aggregates the error signal from its children
- Each node passes messages to its parents
- Q: Benefit from this node-centered point of view?

# Backprop as message passing



- Each node aggregates the error signal from its children
- Each node passes messages to its parents
- Q: Benefit from this node-centered point of view?
- A: Modularity: Only needs to compute derivatives wrt its arguments.

# Example: Univariate logistic least squares regression



Q: Do the backward pass:

Forward pass:

$$z = wx + b$$


$$y = \sigma(z)$$

$$\mathcal{L} = \frac{1}{2}(y - t)^2$$

$$\mathcal{R} = \frac{1}{2}w^2$$

$$\mathcal{L}_{reg} = \mathcal{L} + \lambda\mathcal{R}$$

# Example: Univariate logistic least squares regression



Q: Do the backward pass:

Forward pass:

$$z = wx + b$$

$$y = \sigma(z)$$

$$\mathcal{L} = \frac{1}{2}(y - t)^2$$

$$\mathcal{R} = \frac{1}{2}w^2$$

$$\mathcal{L}_{reg} = \mathcal{L} + \lambda \mathcal{R}$$

$$\overline{\mathcal{L}_{reg}} =$$

$$\overline{\mathcal{R}} =$$

$$\overline{\mathcal{L}} =$$


$$\overline{y} =$$

$$\overline{z} =$$

$$\overline{w} =$$

$$\overline{b} =$$

# Example: Univariate logistic least squares regression



Q: Do the backward pass:

Forward pass:

$$z = wx + b$$

$$y = \sigma(z)$$

$$\mathcal{L} = \frac{1}{2}(y - t)^2$$

$$\mathcal{R} = \frac{1}{2}w^2$$

$$\mathcal{L}_{reg} = \mathcal{L} + \lambda \mathcal{R}$$

$$\overline{\mathcal{L}_{reg}} = 1$$

$$\overline{\mathcal{R}} = \overline{\mathcal{L}_{reg}} \frac{d\mathcal{L}_{reg}}{d\mathcal{R}} = \overline{\mathcal{L}_{reg}} \lambda$$

$$\overline{\mathcal{L}} = \overline{\mathcal{L}_{reg}} \frac{d\mathcal{L}_{reg}}{d\mathcal{L}} = \overline{\mathcal{L}_{reg}}$$

$$\overline{y} = \overline{\mathcal{L}} \frac{d\mathcal{L}}{dy} = \overline{\mathcal{L}}(y - t)$$

$$\overline{z} = \overline{y} \frac{dy}{dz} = \overline{y} \sigma'(z)$$

$$\overline{w} = \overline{z} \frac{\partial z}{\partial w} + \overline{\mathcal{R}} \frac{\partial \mathcal{R}}{\partial w} = \overline{z} x \overline{\mathcal{R}} w$$

$$\overline{b} = \overline{z} \frac{\partial z}{\partial b} = \overline{z}$$

# Learning goals

- Understand how backpropagation powers deep learning
- Explain about the forward/backward pass
- Apply the calculus chain rule to compute derivatives
- Apply the backpropagation algorithm to efficiently compute derivatives
- Understand the modularity of network nodes