

Multilingual NLP

PolyFact: Comparing Consistency-Driven Post-training Methods for Cross-Lingual Factual Recall [\[arxiv\]](#)

Jonathan von Rad, Louis Arts, George Burgess, Eleftheria Kolokytha, Harry O'Donnell, Ektor Oikonomidis Doumpas, Eduardo Sanchez, Yao Lu, Pontus Stenetorp

Multilingual factual recall is as much about cross-language agreement as accuracy; post-training methods trade off QA accuracy, consistency, and real generation transfer.

Releases PolyFact: 60K Wikidata-grounded facts asked in parallel across 12 diverse languages, enabling direct measurement of cross-lingual inconsistency; benchmarks SFT, DCO, CM-Align, and a consistency-rewarded GRPO variant to show they optimize different objectives. Consistency-driven GRPO with reward pooled over parallel prompts for the same fact, incentivizing identical answers across languages; compared against SFT/DCO/CM-Align and with/without light continual pretraining on parallel data; evaluated on controlled QA plus free-form factual recall and unseen languages. SFT best boosts in-distribution QA but doesn't reliably fix inconsistency; DCO yields the largest QA consistency gains but transfers poorly to free-form recall; pooled-reward GRPO transfers best to free-form factual recall and unseen languages (especially from multilingual bases). Light parallel continual pretraining can help monolingual models but may hurt multilingual ones; analysis links GRPO gains to reduced language specialization (more shared representations).

Measuring the Cross-Lingual Comprehension Gap: How the language of the evidence shapes what language models understand [\[arxiv\]](#)

Rafael da Silva, Jeff Eicher

Holding content fixed, LLM comprehension drops when evidence is non-English; CLCG quantifies this “evidence-language” penalty cleanly.

Defines Cross-Lingual Comprehension Gap (CLCG): performance loss when only the evidence passage language changes, avoiding confounds in typical multilingual benchmarks via a within-item parallel design. Uses ParallelQA-18 (English + 17 human-translated languages): same question/answer, evidence swapped by language; scores open-ended answers with Token-F1; CLCG = English minus target score; uncertainty via article-cluster bootstrap; reports pooled and macro averages and correlates gaps with language resource class. Finds a robust pooled CLCG 0.078 Token-F1 (~17% relative drop) with similar macro magnitude; beyond a high-resource baseline (Portuguese), remaining macro gap 0.016 but still tight. Gaps grow for lower-resource languages ($\rho = 0.59$). Paired human judgments align directionally (higher-resource outputs preferred ~0.655 among decisive cases).

Multi-Legal-Bench: Evaluating LLMs on Legal Reasoning Across Jurisdictions, Languages, and Legal Traditions

[\[arxiv\]](#)

Volodymyr Ovcharov

A cross-jurisdiction, multilingual legal benchmark shows transfer depends more on label/jurisdiction alignment than language similarity.

Builds Multi-Legal-Bench: comparable legal prediction tasks anchored in court-registry metadata across six countries and multiple languages/traditions, exposing jurisdiction- and task-specific failure modes hidden by single-country benchmarks. Instantiates five tasks (court type, judgment form, outcome, norm extraction, cause category) via registry-field mappings, yielding a sparse but well-defined 50E6 matrix (20 valid cells). Evaluates frontier and 3–12B models with zero-shot and 3-shot prompting; analyzes predictors of transfer (language family, label-set alignment, tokenizer fertility). Performance varies sharply by task and jurisdiction; no stable “best model per language.” Few-shot often helps unevenly and can hurt (e.g., judgment-form: 8/28 pairs degrade). Cross-lingual few-shot transfer does not track linguistic proximity (e.g., UkrainianFrench can beat UkrainianPolish); label-set alignment better predicts transfer. Tokenizer fertility varies but doesn't significantly predict accuracy.

Dependency Parsing Across the Resource Spectrum: Evaluating Architectures on High and Low-Resource Languages

[\[arxiv\]](#)

Kevin Guan, Happy Buzaaba, Christiane Fellbaum

For truly low-resource dependency parsing, tuned biaffine LSTMs often beat pretrained transformers until labeled data is large enough.

Controlled comparison across 12 languages (including low-resource African treebanks) maps where architecture rankings flip with data size; argues “transformers always win” is mainly high-resource and morphology-sensitive. Compare biaffine LSTM and stack-pointer parsers vs transformer encoders (AfroXLMR-large, RemBERT) for parsing; evaluate across increasing training sizes (“resource spectrum”); analyze drivers using corpus size plus morphological complexity proxy (MATTR). In low-resource regimes, biaffine LSTM consistently outperforms transformer-based parsers; transformers overtake only with more annotation, with crossover near typical under-resourced treebank sizes. MATTR predicts additional transformer disadvantage beyond dataset size, suggesting rich morphology amplifies low-resource shortfalls.

Multilingual Speech Processing

MetaSICL: Globalizing Auditory LLMs for Underserved Speakers and Languages via Meta Speech In-Context Learning [\[arxiv\]](#)

Haolong Zheng, Siyin Wang, Zengrui Jin, Mark Hasegawa-Johnson

You can train auditory LLMs (using only high-resource data) to reliably adapt at test time from a few spoken demos, and that skill transfers to underserved languages/speakers.

Introduces MetaSICL, a post-training recipe that explicitly teaches speech in-context learning as the adaptation mechanism, avoiding brittle low-resource fine-tuning; also serves as a strong warm start for later in-domain RL when small target data exists. Meta-learning-style post-training: model repeatedly conditions on small support sets (speech-task demonstrations) to solve a query, matching inference-time prompting for ASR, speech translation, and audio understanding; optionally followed by in-domain reinforcement learning to further optimize task rewards while preserving ICL behavior. Improves ICL where fine-tuning is fragile (children’s ASR, audio reasoning, unseen-language/direction ASR/ST) despite never training on those domains; with limited target data, MetaSICL + in-domain RL yields the best low-resource ASR across five diverse languages, outperforming standard fine-tuning baselines.

A Practical Evaluation Method for Long-Form Simultaneous Speech-to-Speech Translation [\[arxiv\]](#)

Yulin Xue, Siqi Ouyang, Lei Li

Provides a reproducible way to evaluate long-form simultaneous speech-to-speech translation for both quality and true end-to-end latency.

End-to-end evaluation pipeline that works without model-internal timestamps or perfect segmentation: recovers when the system spoke each target token and aligns it back to source sentences to compute sentence-level latency/quality over long streams. Run ASR + forced alignment on generated target audio to obtain token timestamps; use sentence-embedding alignment to map target chunks to source transcript sentences; compute per-sentence latency (e.g., YAAL) and quality (e.g., xCOMET) and aggregate across the full long-form session. Applied to SimulS2ST systems, the method reveals latency accumulation over long speech—systems that look fine on short clips can steadily fall behind—making drift/backlog measurable and comparable in a way short-form tests miss.

Foundation Model Theory

Transformers Struggle to Use Their Emergent World Models: Revisiting the Tower of Hanoi, and the Illusion of Thinking [\[arxiv\]](#)

Devin Pereira, Willem Zuidema

Reasoning Transformers can encode an accurate Tower-of-Hanoi world model, but often fail because that representation drifts during long plan generation.

Disentangles “no world model” from “can’t maintain it”: shows a linearly decodable, geometrically correct (Sierpinski-like) state representation that is causally linked to success, yet degrades over chain-of-thought in frontier LRMs. Train small Transformers on Hanoi traces for mechanistic study; probe hidden states for state encoding and Sierpinski geometry; test causality via representation

interventions (injecting good states). Replicate probing/interventions on Qwen3.6-27B and DeepSeek-R1-Distill-Qwen-32B, tracking representation quality from prompt end through generation. Frontier LRMs encode near-perfect state immediately after the prompt even where task accuracy collapses (harder variants >3 rings). The decodable world model degrades during generation and predicts failure; reinjecting the prompt-time representation improves performance, implicating representational drift—not missing understanding—as a key planning failure mode.

Field Overview

Today's batch is dominated by LLM agents and their infrastructure: at least ~20 papers on long-horizon agents (planning/execution gaps, memory compression & revocation, skill libraries, trajectory attribution, agent auditing, coding/web agents, and multi-agent coordination/negotiation). A second major theme is efficiency for deployment—roughly ~15 papers on routing/MoE and serving/compute reduction (MoE supervision & entropy routing, LLM routers, KV-cache compression/reuse, sparse/linear attention, token/visual-token pruning, quantization/PTQ, latency/energy modeling). Safety, evaluation, and reliability form another dense cluster (~15): LLM-as-a-judge failure modes and calibration, benchmark contamination, prompt-injection/agent harness safety, backdoors/watermarking/privacy, and misinformation/fact-checking. A notable emerging direction is diffusion language models and flow/rectified-flow methods showing up across both modeling and safety/efficiency (6–8 papers), alongside a smaller but visible audio/music surge (10) spanning audio LLM audits/jailbreaks, speech codecs/editing, and AI-music detection/benchmarks.