

Multilingual NLP

When the API Speaks the Wrong Language: Revisiting Post-Training for Multilingual Tool Use [\[arxiv\]](#)

Siddharth Chauhan, Thomas Butler, Abhishek Singhania, Pankaj Porwal, Honey Gupta

Multilingual tool use often fails via Argument Language Mismatch (right API, wrong-language arguments); supervised fine-tuning fixes most of it, with RL mainly refining trade-offs/generalization.

Identifies ALM as a production-relevant failure mode missed by typical function-calling metrics, and shows that measuring operational validity reveals SFT—not RL—as the primary driver of language-consistent, valid tool calls. Evaluate multilingual function calling with metrics that penalize ALM and invalid calls; compare SFT vs RL variants (e.g., GRPO) using structured, argument-aware rewards; isolate formatting/argument errors by controlling for tool-selection correctness. SFT sharply reduces ALM and boosts end-to-end call accuracy; when tool choice is already correct, SFT matches or can beat RL. RL with structured rewards yields smaller, incremental gains, mainly for multi-objective trade-offs (strict language consistency vs broader reasoning) and generalization.

Reference-Free Post-Training of Open Large Language Models for Multilingual Machine Translation [\[arxiv\]](#)

Chris Han, Pengzhi Gao, Pei Fu, Jian Luan

Reference-free RL can improve an open multilingual MT model across 46 languages; blending RL and SFT checkpoints preserves gains without destabilizing behavior.

Post-trains a supervised multilingual MT LLM without parallel references by rewarding outputs using two reference-free quality estimators; mitigates RL over-optimization by linear parameter interpolation with the original SFT model, producing MiLMMT-46-v1.0. Use GRPO with rewards averaged from two QE models plus a language-ID gate to prevent target-language cheating; after RL, linearly interpolate RL and SFT checkpoints to recover stability/coverage while keeping quality gains. Interpolated RL models consistently outperform the SFT baseline across all 46 languages; they beat several strong open MT baselines (Seed-X, HY-MT2, TranslateGemma) and reach leading reference-free scores even versus evaluated proprietary systems. OPD can match but not exceed the RL-interpolation quality frontier.

Language-Conditional Dequantization: Recovering What Quantization Steals from Non-English Languages [\[arxiv\]](#)

Nirmal Thomas

Low-bit quantization disproportionately hurts non-English; tiny per-language rank-2 LoRA “dequantization” patches recover most lost multilingual performance at negligible cost.

Quantifies that INT3 GPTQ can degrade non-English perplexity 2–4 $\times$ more than English, and proposes Language-Conditional Dequantization (LCD): language-specific micro-adapters that correct language-dependent quantization error better than a single global patch. Start from an INT3-quantized model (e.g., Qwen2.5-3B, Llama-3.2-3B) and add per-language rank-2 LoRA modules to linear layers; train each language adapter briefly (<20 min, single GPU). At inference, select the adapter by language; overhead ~0.12% params per language. LCD recovers ~70–83% of the INT3-induced perplexity gap for non-Latin scripts and ~17–28% of the GlobalMMLU accuracy gap; language-conditional adapters beat equally small language-agnostic fixes. Layer-restricted tests support a depth-of-damage story: early-layer quantization errors (observed in Llama) are harder to repair than later-layer damage (Qwen).

From Reasoning Depth to Reasoning Breadth: Evaluating Multi-Point Associative Reasoning in Large Language Models [\[arxiv\]](#)

Si'an Xie, Jiaxun Liu, Biao Yang, Wei Yuan, Fan Yang, Tingting Gao, Ming Wu

LLM “reasoning” benchmarks over-measure depth; a distinct skill—reasoning breadth (integrating diverse weak clues)—is brittle and not reliably improved by longer thinking.

Defines reasoning breadth and introduces MPAR-Bench (English/Chinese), a Just-One-style hidden-word task requiring multi-clue evidence integration; adds robustness perturbations and multiple similarity/trace-alignment metrics to test stability, not just accuracy. Create items with multi-agent clue generation plus embedding-based diversity filtering; human-verify recoverability. Evaluate with

exact match, ANLS/embedding similarity, and reasoning-trace verification; stress-test via clue removal, shuffling, distractors, and multi-step hint variants. Strong “deep reasoning” models remain fragile on breadth: perturbations drop performance ~9–18 points (English) and ~5–12 (Chinese). “Thinking mode” often boosts baseline accuracy but doesn’t consistently improve robustness and can even talk models out of correct guesses, showing depth and breadth are separable and breadth is under-evaluated.

Multilingual Speech Processing

Confucius4-TTS: Transcript-Free Cross-Lingual Zero-Shot TTS with a Learnable Speaker Encoder [\[arxiv\]](#)

Huaxuan Wang, Huimin Wang, Ruiyu Zhang, Yingjie Li, Yitao Duan

Transcript-free cross-lingual zero-shot voice cloning from a raw audio prompt by learning a speaker embedding from self-supervised speech features and conditioning a two-stage TTS pipeline.

Removes the common “reference transcript required” bottleneck for zero-shot TTS by learning a speaker encoder that extracts timbre identity from audio alone, enabling practical in-the-wild and cross-lingual cloning (plus optional transcript-based continuation when available) across 14 languages. Two-stage TTS: (1) LLM-based text-to-semantic token predictor conditioned on a learnable speaker encoder fed with self-supervised speech representations from the prompt audio; (2) semantic-to-acoustic mel generation via conditional flow matching, conditioned on tokens + speaker embedding. On CV3-Eval cross-lingual directions, achieves 3.73% average WER (high intelligibility) and is top-ranked by human overall preference in internal cross-lingual tests versus open-source/commercial baselines, showing transcript-free prompting can preserve speaker similarity without major quality loss.

DonorRank: Donor Language Selection for Low-Resource Cross-Lingual Speech Recognition [\[arxiv\]](#)

Akriti Dhasmana, Aarohi Srivastava, David Chiang

Donor-language choice for low-resource cross-lingual ASR can be predicted: learn a ranking over donors instead of relying on “relatedness” or “more data” heuristics.

Introduces DonorRank, casting donor selection as learning-to-rank from observed transfer outcomes, showing donor usefulness depends on contextual mixes of linguistic/resource cues rather than a single similarity metric. Train a ranking model on many target–donor transfer experiments; use features capturing linguistic similarity and resource signals to score donors so higher scores match better observed zero-shot transfer; analyze which cues matter under different donor-pool compositions. On Indic and African multilingual corpora, DonorRank improves practical donor selection over baselines like “closest language” or “highest-resource,” and shows cue importance is donor-pool dependent (donor selection is inherently contextual), yielding actionable patterns on when to favor similarity vs strong but less-related donors.

Foundation Model Theory

Geometric and Behavioral Stratification in Transformer Residual Streams [\[arxiv\]](#)

Nelson Guda

Residual streams stratify around the current predicted token’s unembedding direction, yielding a scale-invariant “prediction interface” geometry that predicts and causally affects behavior.

Anchors residual-stream analysis to a content-dependent “prediction direction” (unembedding of the argmax token), revealing a thin prediction-proximal subspace that carries readout-relevant structure and a large prediction-distal complement; shown across 18 models (dense/MoE, base/instruct, 7B–120B). At each position, use the predicted token’s unembedding as an anchor; analyze clustering/discriminability as a function of alignment to this direction; run causal ablations/disruptions of residual directions ranked by prediction-alignment and compare to more distal directions, tracking divergence and task-frame shifts. Prediction-aligned structure concentrates in a narrow interface while the orthogonal space grows with scale and can look flat/anti-discriminative; the prediction direction is near-orthogonal to PCA variance axes, so variance-only analyses miss key organization. Ablating the most prediction-aligned variance directions causes immediate divergence and frequent task-frame shifts; slightly more distal disruptions delay divergence and preserve framing longer.

LLM Evaluation

The Wording Effect: Quantifying Two-Way Drift in LLM Benchmark Performance [\[arxiv\]](#)

Shailja Thakur, Sungeun An, Chad DeLuca, Hima Patel

Meaning-preserving rewordings can flip benchmark answers both ways, and stronger models can be harmed more than helped—so scores depend heavily on the benchmark’s exact phrasing.

Defines and measures two-way “drift” (successfailure and failuresuccess) under semantics-preserving rephrases, introducing BenchDrift to show benchmark performance is a property of wording choices, not just task competence. Generate controlled rephrasings along four axes—linguistic, referential, pragmatic, structural—evaluate originals vs variants, and compute flip rates in both directions; analyze which rephrases/axes drive drift and whether patterns are model- or phrasing-driven. Across GSM8K, MMLU, and MATH-Hard, drift is large and genuinely two-way; net effect flips with model strength (weaker models benefit more, stronger models are harmed more). Models largely agree on which rephrasings are most damaging; failures aren’t explained by prompt length and can break high-confidence answers.

Field Overview

Today’s list is dominated by LLM agents + evaluation/benchmarks: at least ~25–35 papers introduce new benches or auditing frameworks (e.g., TRACE Bench, InfraBench, EnterpriseRAG, CTBench, VAKRA, Backtrader-Bench, FrontierFinance, OEIS Open, Diagram-MMU, TRACES), reflecting a shift from raw capability to measuring instruction adherence, epistemic reliability, and real-world task completion. A second major cluster is agent infrastructure for long-horizon operation—memory, context compaction, harnesses, and runtime contracts—with ~15–20 papers on memory systems/caching/compaction and “harness” design (e.g., Total Recall cost, LinearKV/QV-PIC, MaSRead, EvoGraph-Mem, memorywire, The Sleeping Agent, Lost in Compaction, Agent Safety Should Be a Runtime Contract). Diffusion is unusually prominent beyond vision: ~10–15 papers touch diffusion language models/decoding/compression or diffusion planning (Ripple-Pivot Search, CORA-Diff, DARTree, Diffuse to Compress, cache reuse for diffusion, LoSA), suggesting diffusion-style inference is becoming a serious alternative for text and agent pipelines. Finally, there’s a noticeable safety/robustness/governance thread (~15+ papers) spanning unlearning, sycophancy/persuasion/political alignment, prompt injection/tool hazards, and regulatory/enterprise risk reporting—indicating growing attention to deployment failure modes rather than just benchmark scores.