

Multilingual NLP

Universal Byte-Level Encoding: UTF-8/UTF-16 Routing to Reduce Cross-Script Token-Budget Disparities [\[arxiv\]](#)

Hyunsik Kim, Youngmoon Jung

A reversible byte-representation tweak before BBPE sharply reduces the “token tax” on many nonLatin scripts without hurting English or model quality.

Shows cross-script tokenization unfairness largely comes from the UTF8 “encoding floor” (raw-byte fallback) rather than BPE merges, and proposes Universal Byte-Level Encoding (UBE) as a drop-in replacement at the bytes-to-BPE interface with exact round-trip decoding. Route each Unicode character to UTF8 or UTF16 bytes before standard byte-level BPE: keep 1–2 byte UTF8 chars on UTF8; send 3–4 byte UTF8 chars (often BMP scripts) through UTF16 so fallback is typically 2 bytes. Keep BPE unchanged; audit round-trip correctness across Unicode/emoji/normalization tests. UBE narrows token-count disparities vs English, with largest reductions for scripts dominated by 3-byte UTF8 BMP characters; English is not worse (sometimes slightly better in mixed text). LM quality matches UTF8 BBPE, yielding more usable context and faster processing under fixed token budgets.

Index-Translate: A Multilingual Translation Model Family – Text, Speech, Controlled Dubbing, and Long-Document Translation [\[arxiv\]](#)

Tianjiao Li, Mengran Yu, Chenyu Shi, Lusheng Zhang, Qisi Chen, Yanshan Zhou, Ji Qi, Jingying Liu, Yuang Feng, Ziang Cui, Tianxing Yan

Index-Translate shows one shared 150-language translation backbone can be specialized into strong text, speech, dubbing, and long-document translators instead of training separate giant models.

Presents a “translation family” design: a common multilingual foundation (multiple sizes) plus targeted descendants for instruction-following translation, end-to-end speech translation, controlled dubbing, and native long-document translation. Train a shared multilingual MT model (2B/9B/35B-A3B) then specialize: instruction-tuned translation; Index-Echo for end-to-end speech-to-text and speech-to-speech; Index-Homura with syllable/timing controls for dubbing; Index-NativeLong with a long-input formulation and a dedicated long-doc consistency benchmark. Across regimes, specialized variants are competitive with much larger systems: strong general + instruction translation (near ~100B-scale MT), improved end-to-end speech translation approaching frontier omni-models, and evaluated gains for controlled dubbing and long-document consistency via explicit mechanisms (syllable control, native long-doc setup).

Where’s Waldo? Query-language Preference under Cross-lingual Knowledge Disparities [\[arxiv\]](#)

Dayeon Ki, Ruochen Zhang, Silviu Cucerzan, Ryan W. White, Ning Gao

When languages disagree, multilingual LLMs often follow the query language, so the same question in different languages can yield different “facts”; Waldo measures this and targeted fixes reduce it.

Separates cross-lingual knowledge gaps from true conflicts and shows query-language preference is mainly harmful under conflicts; introduces Waldo, a Wikipedia-based multilingual QA benchmark labeled for gap vs conflict cases. Build 12K QA instances across five languages with multilingual evidence; evaluate eight LLMs by asking equivalent questions in different languages and measuring alignment to query-language vs other-language evidence; mitigate via (1) attention-head ablation linked to preference and (2) LoRA fine-tuning to reduce preference under conflict. Models readily use other-language evidence to fill gaps, but under conflicts they disproportionately choose the query-language version, producing language-dependent answers. Both interventions reduce the preference gap; LoRA cuts it by up to 61.5%.

Assessing the Impact of Language Disparity on Multilingual Linguistic Ability in Large Language Models [\[arxiv\]](#)

Zhanyu Chen, Jaap Jumelet

Multilingual “grammar ability” depends heavily on evaluation style: post-training can hide or degrade syntactic competence, and common setups systematically understate low-resource performance.

A controlled, multi-paradigm study (six model families; base vs post-trained) showing that conclusions about multilingual syntax shift with scoring method, especially for instruction-tuned models and low-resource languages. Use MultiBLiMP (101 languages) minimal

pairs and evaluate the same models with four paradigms (implicit probability preference vs prompted judgments/explanations, including prompt-language choices). Analyze effects of post-training, scale, and language resource level; highlight near-chance baselines in low-resource settings. Post-training generally worsens implicit syntactic preference, with larger models degrading less and low-resource languages degrading most. Some competence becomes “hidden” (present in probabilities but not elicited by direct prompts), mainly in high-resource languages; for low-resource languages, near-chance baselines limit recoverable signal. Prompting in the target language can recover low-resource performance, implying many evaluations underestimate it.

Cross-Lingual Alignment for Decoder-Only Models using MoE Routers [\[arxiv\]](#)

Lucas Bandarkar, Clark Peng, Ahmed Haj Ahmed, Aditi Khandelwal, Nanyun Peng

For decoder-only multilingual MoE LLMs, aligning expert-router decisions across translation pairs yields robust cross-lingual alignment and better transfer without token-level matching.

Replaces brittle token-level contrastive alignment (broken by differing tokenizations) with router-output alignment: MoE routing distributions provide a comparable, sequence-level signal that can drive cross-lingual consistency. During continual pretraining on parallel data, pool router outputs over each sequence to form a routing signature; apply a contrastive objective to bring signatures of translation pairs together and push non-pairs apart. This supervision backpropagates through the network, indirectly aligning hidden states. Router alignment makes routing behavior more language-invariant for the same meaning and also improves hidden-state cross-lingual alignment without direct token matching, translating into better multilingual/cross-lingual transfer on a broad evaluation suite.

Multilingual Speech Processing

MultiTalk: Scaling Full-Duplex Speech Models to Long, Multi-Party, Bilingual Conversation [\[arxiv\]](#)

Ke Wang, Houxing Ren, Zimu Lu, Yunqiao Yang, Zhuofan Zong, Mingjie Zhan, Hongsheng Li

MultiTalk brings fullduplex speech agents closer to meeting-like reality via massive structured synthetic data, a long multi-party bilingual benchmark, and a strong Moshi-style model.

Addresses the long-context, multi-speaker gap in open fullduplex systems by releasing (1) large bilingual multi-party synthetic training data and (2) MultiTalkBench, a real long-form multi-party English–Chinese evaluation with targeted conversational probes. Generate 57.6k hours of synthetic codec-frame training with controllable participants, turn-taking, overlap, interruptions, addressee shifts, and long-range dependencies; build a real-recorded benchmark with probes for entity tracking, topic coherence, and addressee selection; train a bilingual Moshi-style fullduplex model and compare to open baselines. On MultiTalkBench, the trained bilingual model sustains coherent long multi-party EN–ZH interaction and outperforms Moshi, MiniCPM-o-4.5, and Qwen3-Omni-30B-A3B-Instruct, with gains visible on concrete skills (entity tracking, topic coherence, correct addressee).

MGhana-ST: A Low-Resource Speech Translation Dataset for Ghanaian Languages and an Analysis of Multilingual Training Trade-offs [\[arxiv\]](#)

Frank Lawrence Nii Adoquaye Acquaye, Eric George Parakal, Jesse Johnson, Kishankumar Bhimani, Jochebed Afua Basil

MGhana-ST releases scarce Ghanaian speechEnglish translation data and shows multilingual training can fail—or hurt—once you replicate across seeds in extreme low-resource settings.

Introduces MGhana-ST (Ga, Twi, Ewe, Fante; ~16 hours paired audio–English in current subset) and demonstrates that apparent multilingual gains can be seed artifacts; emphasizes replicated evaluation for tiny ST datasets. Curate audio from two Ghanaian speech resources; collect new English translations directly from audio via 37 native-speaker annotators (including verbal/non-verbal events). Fine-tune Whisper-small with monolingual-per-variety vs one flat multilingual model; report 3-seed averages; analyze variance and relate transfer to URIEL similarity and empirical transfer signals. With replication, flat multilingual training helps none and harms two varieties: Ga/Twi ~unchanged; Ewe ~7 BLEU; Fante ~5 BLEU. Monolingual runs show large seed-to-seed swings, explaining fragile “multilingual helps” claims. Empirical transfer patterns track interactions better than URIEL, but neither reliably predicts benefit—replication is essential.

Foundation Model Theory

The Geometry of Contextual Relations: Language Models Address Facts by Order of Mention [\[arxiv\]](#)

Yufa Zhou

LLMs often retrieve prompt facts by order-of-mention: internally, “which fact” is encoded as an ordinal address more than by the entity name in the question.

Identifies ordinal addressing: stable representation-space directions that shift the model from fact k to fact $k+1$ across prompts and model families, implying a general positional indexing mechanism for contextual facts. Create prompts with multiple simple facts; compute activation differences when questions target different facts; average across random lists to extract “ordinal vectors.” Test causality by steering: add the $+1$ vector to a question’s hidden state and see if answers switch to the next-mentioned fact. Query representations organize primarily by mention order, even when entity names suggest otherwise. Ordinal vectors causally steer answers to adjacent facts, lie in a low-rank subspace, favor early-mentioned facts, and appear across Qwen/Gemma/Llama (1.5B–32B), emerging in late-middle layers and early in pretraining.

Field Overview

Today’s batch is dominated by agentic LLM systems and how to evaluate/control them: at least ~30 papers on long-horizon agents, harnesses, tool use, memory/compaction, and workflow optimization (e.g., DAYJOB, Argo-Bench, WebArena audits, Mem++/MemCodex/LatentHarvest, Sapient/PACE, over-authorization and empty-commitment failures). A second major cluster is post-training and inference-time scaling for LLMs—roughly ~25 papers on RLVR/RLHF variants, on-policy distillation, preference optimization, verifiers/judges, and test-time sampling/verification (CARM/GAW-PO/Range-GRPO, “Cheap to Draw, Expensive to Trust,” cross-model review, judge reliability). The most striking surprise is the sheer volume of audio/speech work—well over 150 titles—spanning full-duplex spoken agents, speech LLMs, TTS/voice conversion, deepfake detection/watermarking, diarization, and audio benchmarks (HEAR, VoxMem, Speech-ConversationBench, many ADD/SDD papers), suggesting speech is having a “benchmark + safety + deployment” moment similar to text agents. Across modalities, efficiency/compute constraints (quantization/pruning/speculative decoding/token compression) and safety/fairness/unlearning (bias audits, safety routing fragility, multilingual unlearning loopholes, multimodal unlearning) form a consistent cross-cutting trend (~30+ papers).