

## Multilingual NLP

---

### Tokenisation via Convex Relaxations [\[arxiv\]](#)

Jan Tempus, Philip Whittington, Craig W. Schmidt, Dennis Komm, Tiago Pimentel

*Tokenizers can be learned via a single convex program (not greedy merges), yielding better tokenization and a near-optimality certificate.*

Formulates tokenizer/vocabulary design as a global linear program and introduces ConvexTok, a practical convex-optimization approach that also provides a lower bound to quantify suboptimality at a given vocab size. Encode vocabulary choice + segmentation behavior in an LP; solve with convex optimization to obtain the tokenizer. Use the LP's lower bound as an optimality certificate to compare any candidate tokenizer. Improves intrinsic tokenization metrics and LM bits-per-byte; downstream gains are less consistent. Empirically certifies solutions within ~1% of optimal (per their objective) at common vocab sizes.

### Moral Semantics Survive Machine Translation: Cross-Lingual Evidence from Moral Foundations Corpora [\[arxiv\]](#)

Maciej Skorski

**! Summary may contain inaccuracies:** The summary says the posts are translated “into Polish.” The abstract indicates Polish is the test case for bridging the gap, but does not explicitly state the direction of translation (it could be EnglishPolish or PolishEnglish); asserting the direction as into Polish is not supported by the abstract.

*LLM translation can preserve moral-foundations signal well enough to build reliable Polish moral NLP from English-labeled data.*

Systematic validation that machine-translating a large English moral foundations corpus into Polish largely retains moral semantics, enabling cross-lingual classifier training/evaluation rather than requiring new native annotations. Translate ~50k labeled posts to Polish; assess preservation via LaBSE similarity, CKA representation alignment, LLM-as-judge checks, and classifier-parity tests comparing performance on original vs translated data. High semantic similarity (mean cosine ~0.86) and small AUC gaps (~0.01–0.02) across foundations; remaining issues concentrate in slang/vulgar/culture-loaded text, and fine-tuning further narrows gaps.

### Fine-grained Claim-level RAG Benchmark for Law [\[arxiv\]](#)

Souvik Das, Sallam Abualhaija, Domenico Bianculli

*A new bilingual, claim-level legal RAG benchmark enables finer diagnosis of retrieval vs generation failures beyond coarse QA scores.*

Introduces ClaimRAG-LAW (English/French) with expert and non-expert questions and diverse legal query types, aimed at claim-level, fine-grained evaluation to better localize hallucinations and pipeline weaknesses. Build the dataset and apply a fine-grained evaluation framework to SOTA legal RAG systems to separate retrieval and generation behavior (abstract emphasizes diagnostic granularity over a single end-to-end metric). Even with RAG, substantial limitations persist: retrieval and generation both fail in ways coarse metrics miss, and existing claim-level analyses are still insufficient—motivating more granular evaluation using ClaimRAG-LAW.

### DocAtlas: Multilingual Document Understanding Across 80+ Languages [\[arxiv\]](#)

Ahmed Heakl, Youssef Mohamed, Abdullah Sohail, Rania Elbadry, Ahmed Nassar, Peter W. J. Staar, Fahad Shahbaz Khan, Imran Razzak, Salman Khan

*DocAtlas builds trustworthy multilingual document labels from rendering (not model annotation) and shows DPO adapts doc models across 80+ languages without OOD collapse.*

DocAtlas: 82-language, 9-task document benchmark with high-fidelity ground truth derived from controlled rendering (DOCX differential rendering + LaTeX for RTL), unified as DocTag; demonstrates preference-style adaptation is safer than SFT. Generate exact text/layout/component labels via rendering-based pipelines; benchmark 16 models; adapt using DPO treating rendering-derived outputs as preferences, comparing against supervised fine-tuning. Large drops remain on low-resource scripts. DPO improves in-domain (~+1.9%) and out-of-domain (~+1.8%) without hurting base performance, while SFT can cause up to 21% OOD degradation; best adapted model is ~+1.7% over strongest baseline.

# Multilingual Speech Processing

---

## Benchmarking Commercial ASR Systems on Code-Switching Speech: Arabic, Persian, and German [\[arxiv\]](#)

Sajjad Abdoli, Ghassan Al-Sumaidae, Clayton W. Taylor, Ahmad ElShiekh, Ahmed Rashad

*Commercial ASR can look fine on aggregate WER yet fail on real code-switching; a new benchmark plus meaning-aware metrics exposes this.*

Releases a code-switching ASR benchmark (English mixed with Egyptian Arabic, Saudi Arabic, Persian, or German) and argues for WER+semantic metrics (BERTScore) to handle script/transliteration variance and reveal hidden failures. Create 4000-utterance datasets via heuristic prefiltering + GPT-4o/Gemini scoring (91% LLM-cost reduction vs scoring all). Benchmark five commercial ASR systems; report WER and BERTScore with stratified difficulty analyses. Rankings shift notably between WER and BERTScore, especially for Arabic/Persian code-switching under transliteration variation. ElevenLabs Scribe v2 is best overall (WER 13.2%, BERTScore 0.936), and stratification shows some systems degrade sharply on harder mixed utterances.

## RobustSpeechFlow: Learning Robust Text-to-Speech Trajectories via Augmentation-based Contrastive Flow Matching [\[arxiv\]](#)

Jinhyeok Yang, Hyeonju Kim, Yechan Yu, Joon Byun, Frederik Bous, Juheon Lee

*Flow-matching TTS becomes more robust to skips/repeats by training against synthetic latent misalignment corruptions—no aligners or preference labels needed.*

RobustSpeechFlow: an augmentation-based contrastive flow-matching recipe that targets alignment-driven content errors by simulating skip/repeat-like, length-preserving latent distortions during training. Use contrastive flow matching with “negative” targets created by local repeat/skip latent augmentations that preserve length; penalize similarity between clean and corrupted trajectories to stabilize dynamics against misalignment at inference. Improves intelligibility/content fidelity: Seed-TTS-eval WER drops 1.441.38 (0.06B model). On ZERO500, English CER 0.48%0.35% and Korean CER 0.81%0.57% (NFE=24), with gains across speakers/prosody.

# Foundation Model Theory

---

## Represented Is Not Computed: A Causal Test of Candidate Algorithmic Intermediates in a Transformer [\[arxiv\]](#)

Ishita Darade, Sushrut Thorat

*Transformers can encode textbook-like intermediates that probes decode, yet those intermediates may be non-causal for the model’s actual computation.*

In a closed-form arithmetic task (extract base-B digit at position D), shows a sharp “decodable used” gap: linear probes recover plausible intermediates, but causal interventions/circuit analysis indicate the model relies on different pathways. Train a Transformer to output  $N/B^D \bmod B$ ; fit linear probes for expected intermediates; run causal tests on information flow (esp. Doutput) and perform sparse circuit search to identify minimal causal components/routes. Despite 99.83% accuracy, the key Doutput route is largely independent of N and B, contradicting the probed staged algorithm; sparse circuits suggest mostly separate N/B/D routes that combine late, warning against probe-only mechanistic claims.

# LLM Evaluation

---

## Provable Joint Decontamination for Benchmarking Multiple Large Language Models [\[arxiv\]](#)

Zhenlong Liu, Hao Zeng, Hongxin Wei

! Summary may contain inaccuracies: The summary repeatedly describes JECS as producing a “final retained benchmark” / “single decontaminated benchmark” by “select[ing] which items to flag as contaminated.” The abstract instead says JECS “select[s] a benchmark” (i.e., selects items to keep). This is a directional mismatch about what the selection output represents (kept vs flagged items).; The summary claims the max-p aggregation is conservative because “a single large p-value can mask

small p-values from other models.” The abstract does not state this rationale; it only says JECS aggregates by per-item maximum and compares to a max-p baseline. This masking explanation materially changes the interpretation of why max-p is conservative.

*A joint, provable way to decontaminate one shared benchmark across many LLMs while controlling a global false-flagging/contamination rate.*

JECS reframes multi-model decontamination as one conformal-selection problem with a global contamination rate (GCR) guarantee, correcting the conservativeness of per-item max-p aggregation so power isn’t lost. Compute per-model conformal p-values per item; aggregate by per-item max p-value; estimate an “envelope” null for max-p from the right tail above a data-driven threshold; rescale and apply adaptive BH to flag contaminated items, producing one filtered benchmark. Across model families/benchmarks, JECS meets the target GCR while removing more truly contaminated items than running BH directly on raw max-p, yielding a larger, cleaner shared eval set than naive per-model filtering.

## Field Overview

---

Today’s batch is dominated by LLM post-training + agent reliability work: at least ~25–35 papers on RLVR/GRPO-style credit assignment, self-distillation, planning/test-time search, and “harness”/workflow engineering (e.g., token-level credit assignment, state-distribution views of post-training, tree/KV-cache management, agent benchmarks like TerminalWorld/WorkstreamBench). A second large cluster is safety/security/evaluation for LLMs and agents (at least ~15–25): data contamination and decontamination, jail-break/refusal evasion (including latent-space attacks), prompt-injection/RAG corruption defenses, membership inference, distillation theft/watermarking, and DP auditing/robustness. There’s also a noticeable efficiency-systems thread (10) around KV-cache compression/decoding, hybrid Mamba/Transformer inference, pruning, and serving infrastructure, alongside a steady stream of uncertainty/OOD/calibration papers (10) spanning covariate shift, epistemic/aleatoric decomposition, and test-time adaptation guarantees. A somewhat surprising emerging direction is “self-evolving” agents and autonomous research pipelines (8–12) that emphasize continual skill/library growth, event-sourced/auditable agent logs, and automated evaluation/CI gates rather than just better base models.