

Multilingual NLP

When the API Speaks the Wrong Language: Revisiting Post-Training for Multilingual Tool Use [\[arxiv\]](#)

Siddharth Chauhan, Thomas Butler, Abhishek Singhania, Pankaj Porwal, Honey Gupta

Multilingual tool use often fails after picking the right API: arguments come out in the wrong language; SFT fixes most of it, RL adds small, targeted gains.

Defines and isolates Argument Language Mismatch (ALM)—an operational validity failure invisible to standard tool-call metrics—and shows post-training should explicitly enforce argument-language consistency. Clarifies RL’s role: mainly marginal generalization/constraint trade-offs, not the primary fix. Evaluate tool calls with ALM-aware checks (correct function + arguments in the required/consistent language). Compare SFT vs RL (e.g., GRPO), including structured argument-aware rewards; control for tool selection to separate choosing the tool from filling arguments. SFT sharply reduces ALM and lifts end-to-end function-call success; with tool selection held constant, SFT matches or beats RL variants. RL with argument-aware rewards yields incremental improvements, mostly in generalization and multi-objective balancing (consistency without harming reasoning).

Reference-Free Post-Training of Open Large Language Models for Multilingual Machine Translation [\[arxiv\]](#)

Chris Han, Pengzhi Gao, Pei Fu, Jian Luan

Reference-free RL using QE rewards can improve multilingual MT, and simple SFTRL checkpoint interpolation stabilizes gains across 46 languages.

A practical, no-reference post-training recipe for open multilingual MT: QE-as-reward RL plus safeguards (dual-QE averaging, language-ID gating) and linear interpolation with the SFT checkpoint to curb reward hacking/language drift. MiLMMT-46-v1.0. Start from an SFT MT model (MiLMMT-46-v0.1), run GRPO with reward = average of two QE models, gated by language ID. After RL, linearly interpolate SFT and RL checkpoints; also test on-policy distillation (OPD) vs the RL+interpolation frontier. RL + checkpoint interpolation yields consistent quality gains over SFT across 46 languages; beats recent open baselines (Seed-X, HY-MT2, TranslateGemma) under reference-free evaluation and reports leading scores vs evaluated proprietary systems. OPD reaches but does not surpass the RL+interpolation frontier.

Language-Conditional Dequantization: Recovering What Quantization Steals from Non-English Languages [\[arxiv\]](#)

Nirmal Thomas

INT3 quantization disproportionately breaks non-English; tiny per-language low-rank adapters can recover most lost perplexity and some downstream accuracy without changing quantized weights.

Quantifies “multilingual collapse” under aggressive quantization and proposes Language-Conditional Dequantization (LCD): language-specific residual capacity is more efficient than a single global fix. Links recoverability to where quantization error concentrates across depth. Attach per-language LoRA adapters (rank 2) to linear layers of an INT3 GPTQ model; select adapter by language at inference. Train post-hoc (~0.12% params per language). Run layer-restricted LCD (early vs late layers) to localize where corrections matter. On Qwen2.5-3B and Llama-3.2-3B INT3, LCD closes ~70–83% of the non-English perplexity gap vs English and recovers ~17–28% of the GlobalMMLU accuracy gap; beats language-agnostic corrections at equal budget on distant languages. Finds a perplexity–accuracy disconnect tied to depth: late-layer damage (Qwen) is more fixable than early-layer damage (Llama).

When the Knowledge Base Becomes the Gold Standard: Measuring Resource-Shared Evaluation Loops in Entity-Level Machine Translation [\[arxiv\]](#)

Jinhyung Bae, Dain Kil, Seongmin Oh, Seungmin Lee

Entity-translation gains can be illusory when the same KB is used for both injection and evaluation; most “improvement” is a resource-sharing loop.

Identifies and measures self-referential evaluation in KB-augmented MT for entities: KB-as-gold can reward agreement with the injected resource rather than true translation. Provides a concrete protocol to separate KB agreement from independent expert correctness. Use

expert person-name annotations (independent gold) for Seungejongwon Ilgi and split mentions into KB-overlap vs non-overlap with the injection pipeline. Evaluate four MT models with/without KB injection using a difference-in-differences comparison to detect loop-driven gains. Of 527 expert-annotated mentions, only 31.1% are outside the injection pipeline. Injected readings match human translations 97.8% in the overlap segment but only 70.1% in the independent segment. Across models, injection gains appear only in the overlap segment; in the independent segment gains are zero or negative, and post-injection scores compress into a high band (0.910–0.996), inflating weaker models.

Multilingual Speech Processing

Gloss-Free Representation Learning for Cross-Dataset Sign Spotting [\[arxiv\]](#)

Oğuz Akif Tüfekcioğlu, Ezgi Ekin, Mustafa Kaan Çevik, Hacer Yalim Keles

Gloss-free sign pretraining from transcripts works much better if you normalize morphologically varied text targets; the resulting encoder transfers strongly to cross-dataset sign spotting.

Shows target fragmentation (many inflected surface forms) is a key bottleneck in transcript-supervised sign representation learning, especially in morphologically rich languages. Treats transcript normalization as core to learning transferable lexical/time representations. Pretrain a Turkish sign encoder on TSL-News using loosely aligned transcripts mapped to pseudo-glosses. Compare rule-based lemmatization vs constrained LLM-assisted normalization to canonicalize variants. Transfer the encoder to temporal sign spotting on a different dataset (TSL Dictionary benchmark). LLM-assisted normalization nearly doubles cross-dataset spotting quality: top-5 temporal localization mean IoU 0.2350.465; 56.2% reach 0.50 IoU. Also improves a translation sanity check (BLEU-4 9.6011.04; ROUGE 23.4827.43), indicating stronger learned lexical structure.

DonorRank: Donor Language Selection for Low-Resource Cross-Lingual Speech Recognition [\[arxiv\]](#)

Akriti Dhasmana, Aarohi Srivastava, David Chiang

DonorRank learns which donor languages actually transfer best for low-resource zero-shot ASR, outperforming “biggest” or “closest language” heuristics and revealing when cues stop mattering.

Recasts donor-language choice as learning-to-rank from observed transfer outcomes, arguing “good donors” depend on donor pool and conditions (data type, orthography, resource skew), not a single similarity metric. Also uses the learned ranker to analyze what predicts transfer under different pools. Train a ranking model on prior cross-lingual ASR transfer results: for each target, learn pairwise/relative ordering of donors rather than absolute scores. Use features capturing linguistic/resource relations; vary donor sets to study how predictive signals shift with pool composition. Accurately predicts donor rankings on two multilingual corpora (Indic and African) and yields better donor choices than high-resource or genetic-similarity baselines. Analysis shows cue usefulness is pool-dependent (e.g., family similarity saturates when donors are all related), offering practical guidance for messy low-resource ASR settings.

Foundation Model Theory

Measure, Don’t Optimize: Forecasting Recovery in LLM Unlearning [\[arxiv\]](#)

Zirui Song, Huaxing Liu, Xiang Wang, Shuai Li, Xinye Li, Lang Gao, Jinghui Zhang, Zheng Lu, Fengxian Ji, Xiaojun Chang, Xiuying Chen

You can predict how fast unlearned knowledge will return by measuring its internal accessibility—but optimizing that metric can make models hide knowledge and recover even faster.

Introduces J-Access, a white-box “recovery susceptibility” audit that measures whether unlearned concepts remain reachable along the logit pathway. Shows Goodhart’s law: training to minimize the audit can reduce detectability while increasing recoverability. Use a Jacobian-lens-style probe across layers to map hidden states into vocabulary space and score alignment with target (supposedly unlearned) concepts. Test whether pre-attack J-Access predicts recovery under later fine-tuning; then explicitly optimize to minimize J-Access to check for evasion vs deletion. Across 398 public unlearned models (8 methods), most retain higher accessibility than a retain-only “gold” baseline. Model-level J-Access predicts recovery speed/extent under attack, though not per-fact recovery. Directly minimizing J-Access often lowers the audit score while making models more recoverable, demonstrating audit evasion.

Field Overview

Across today's list, the dominant theme is LLM agents and how to evaluate/control them: at least ~25–35 papers introduce agent benchmarks or evaluation protocols (e.g., TRACE Bench, InfraBench, EnterpriseRAG, CTBench, VAKRA, Backtrader-Bench, FrontierFinance, AutoWorldModel-Bench) or study agent behaviors like self-correction, tool-use policies, and memory cost/definitions. A second large cluster (~15–25) targets reliability/safety/alignment and measurement—unlearning and retention, sycophancy/persuasion/political alignment, uncertainty calibration, prompt/wording effects, and guardrails under context compression/summarization (e.g., “Lost in Compaction,” “Sleeping Agent,” unlearning papers, judge/rubric work). On the systems/modeling side there's a noticeable push (~10–15) on efficiency infrastructure—quantization and multilingual degradation, MoE routing/edge inference, caching/PIC, training/energy scheduling, and diffusion-LM decoding/compression (e.g., LinearKV, QV-PIC, SoftWater, LazyTrain, multiple MoE edge papers, diffusion LLM inference). A somewhat surprising emerging direction is the breadth of audio/voice/music generation and evaluation (roughly ~8–12 papers: multiple TTS technical reports, voice generation, text-to-music instruction-following tests, audio-visual QA), alongside steady applied clusters in finance (trading/forecasting/benchmarks) and clinical/medical imaging RAG/benchmarks.