

Multilingual NLP

Biomedical Machine Translation for Low-Resource Arabic-Script Languages via Cross-Lingual Transfer and LoRA Adapter Merging [\[arxiv\]](#)

Abdullah Alabdullah, Arash Eslamighayour, Sarp Harbalioglu, Lifeng Han

Strong biomedical MT for ultra-low-resource Arabic-script languages is possible by transferring (and even merging) LoRA adapters from related pivot languages—sometimes with zero target biomedical data.

Frames low-resource biomedical MT as cross-lingual transfer from Arabic/Persian pivots to Dari, Pashto, Sorani Kurdish, and Urdu using small decoder-only LLMs with LoRA; introduces and validates zero-data LoRA adapter merging for domain MT, working best when targetpivot (DariPersian). Train biomedical MT LoRA adapters on pivot languages (Arabic, Persian), then transfer via (1) ICL prompting, (2) tiny supervised target adaptation (~500 sentences), or (3) zero-data adapter merging that combines pivot adapters to approximate a target biomedical translator. With 500 sentences, Dari reaches near-pivot quality (ChrF++ 41.01) and Urdu improves (28.88); zero-data adapter merging comes within ~3.5 ChrF++ of supervised Dari adaptation, while Pashto/Sorani remain limited—transfer scales with linguistic closeness.

A Factorial Study of Synthetic Data Generation for Low-Resource Machine Translation using Grammar Books [\[arxiv\]](#)

Varun Ghat Ravikumar, Sina Ahmadi, Lena Jäger, Rico Sennrich

Descriptive grammar books can be converted into synthetic parallel data that measurably improves low-resource MT—if generation choices are tuned.

Shows an end-to-end, scalable way to turn grammar documentation into MT training corpora (rules+examples+lexicon parallel sentences) and runs a 96-condition factorial study to identify which synthesis design decisions drive gains vs. noise. Use an LLM to extract grammatical rules, example pairs, and lexicon entries from grammar books; generate controlled synthetic parallel sentences with configurable retrieval/sampling; fine-tune an MT model on synthetic data (optionally plus small seed parallel data). Synthetic grammar-derived data beats seed-only baselines in most settings (75% Kalamang, 59% Tuatschin); best configs yield ChrF++ gains of +8.8 (Kalamang), +5.3 (Tuatschin), +3.3 (Mandan), with factorial analysis showing gains are sensitive to synthesis distribution/coverage.

Do VLMs Read or Rewrite? On Transcription Faithfulness in Vision-Language Models [\[arxiv\]](#)

Gwang Gook Lee, Kenan Emir Ak, Jay Mohta, Yan Xu, Dimitrios Dimitriadis

Many VLMs “rewrite” noisy text into plausible clean text instead of faithfully transcribing; FaithC4 measures this and a probe predicts when it happens.

Introduces FaithC4 (1,455 multilingual perturbed documents: EN/ZH/KO) to test corruption-preserving transcription, and links rewriting behavior to an internal representation signature in Qwen3-VL-4B. Create controlled perturbations (scramble, random substitution, visually similar substitution); evaluate 15 systems (general VLMs, OCR-VLMs, classic OCR) via WER degradation; probe Qwen3-VL-4B layer-wise by comparing perturbed-token vs clean-token FFN representations. General VLMs degrade far more under perturbations (up to ~4.5 WER points) than OCR-VLMs (~0.2–2) and classic OCR (<~0.6 on English); rewriting correlates with perturbed tokens staying close to clean-token representations, and is common for short words (4–6 chars, up to ~10%) but rare beyond ~8 chars.

Khondo: A Multimodal Benchmark for Document Packet Splitting of Bangla Forms [\[arxiv\]](#)

Abu Tyeb Azad, Fahim Ahmed, Ishita Sur Apan, Ezharuddin Jubaer, Sumaiya Karim Katha, Armun Alam, Amin Ahsan Ali, Aman Chadha, Md Mofijul Islam, AKM Mahbubur Rahman

Khondo benchmarks splitting mixed Bangla form packets into original documents and page order—showing page sequencing, not boundary detection, is the main failure for MLLMs.

Introduces the first document-packet-splitting benchmark for Bangladeshi government forms, separating clustering (group pages) from sequencing (order pages) and varying concatenation/shuffling plus Bangla–English content. Build page-image dataset from 14 domains; synthesize packets under five concatenation schemes (sequentially shuffled) with ground-truth boundaries, labels, and page order;

evaluate zero-shot multimodal LLMs with prompt and language ablations. Models often cluster pages correctly but fail to reconstruct order once shuffled; explicit ordering prompts help yet sequencing remains the dominant bottleneck. English packets order better than Bangla, but shuffling hurts most—making page arrangement the key unsolved subproblem.

Multilingual Speech Processing

Synthetic Speech, Real Signal: Paralinguistic Preservation and Cross-Lingual Augmentation via Voice Cloning [\[arxiv\]](#)

Roseline Polle, Owen Parsons, George Fairs, Luis Miguel San Martin Fernandez, Cole Looney, Xiaoliang Wu, Alexandra Livia Georgescu, Stefano Gorla

Voice cloning often preserves paralinguistic cues well enough for clinical/affective models—and can transfer labeled clinical speech across languages.

Benchmarks 8 voice-cloning systems on 5 paralinguistic/clinical tasks using downstream performance (not just intelligibility), and demonstrates cross-lingual label-preserving augmentation by cloning English clinical speech into Japanese. Evaluate paralinguistic classifiers trained/evaluated on real vs cloned audio across tasks and cloning models; for cross-lingual augmentation, clone labeled English clinical recordings into Japanese and train detectors tested on real Japanese speech. Most cloning systems cause only modest downstream degradation on many paralinguistic tasks; cloned EnglishJapanese clinical data improves depression/anxiety detection on real Japanese speech versus naïve cross-lingual transfer, showing cloning can bridge label scarcity.

MEUSLI: a Multilingual Projector for LLM-based ASR and Beyond [\[arxiv\]](#)

Lorenzo Concina, Seraphina Fong, Marco Matassoni, Alessio Brutti

MEUSLI trains a small multilingual “projector” that lets Whisper feed open LLMs, enabling open-source multilingual SpeechLLMs and easy task reuse.

Releases multilingual projectors bridging Whisper to multilingual LLMs for 28 European languages; emphasizes a reusable interface layer (not full retraining) and continual learning to add languages without catastrophic forgetting. Keep Whisper encoder and text LLM largely frozen; train a lightweight projector mapping acoustic features to LLM-compatible embedding sequences; train multilingual/continual variants and reuse the same bridge for other speech tasks with small supervision. A single open multilingual projector family yields strong end-to-end ASR across high/low-resource European languages and transfers to speech translation and topic ID with only a few hours of per-language task data, highlighting the projector as the main leverage point.

Foundation Model Theory

The Hard Decision Layer: Evidence for Committed Inference in Transformers [\[arxiv\]](#)

Ashwath Vaithinathan Aravindan, Mayank Kejriwal

On MCQs, transformers often “commit” at a specific depth where option rankings abruptly stabilize—the Hard Decision Layer (HDL).

Defines and documents the HDL as a repeatable layer-wise phase transition in answer-option ranking across model families/datasets; argues it is largely architecture-stable and minimally shifted by fine-tuning. Track per-layer scores/rankings of MCQ options from intermediate activations; define HDL as the layer where rankings snap to stability; validate across prompts/labels and compare base vs fine-tuned models. HDL appears consistently across Qwen/Llama/Granite/Mistral; accuracy can jump sharply at HDL (e.g., up to +0.61 for Qwen on CommonsenseQA vs earlier layers), and later layers rarely change rankings; fine-tuning improves pre-HDL evidence more than HDL depth.

LLM Evaluation

Do Agent Benchmarks Measure Capability? Protocol Validity in the Age of Agentic AI [\[arxiv\]](#)

Jiaqi Shao, Hanck Chen, Wei Zhang, Maxm Pan, Bing Luo

Many agent benchmark scores are inflated by protocol loopholes; HackDetect audits traces to quantify how much success comes from exploits.

Formalizes protocol validity (“capability must be necessary for success”), introduces HackDetect to identify exposures and exploit-driven wins from traces, and defines the Mislead gap to report score inflation. Audit benchmark runs by (1) finding exposures (leaky artifacts/channels), (2) verifying exploit use in traces, and (3) estimating intended vs exploit scores; summarize inflation as Mislead gap = exploit score - intended score. Across 2,385 traces on 15 benchmarks, exposures are frequent; highlighted cases show exposures in 67.0% (Frontier Science) and 66.7% (AutoLab), with estimated Mislead gaps ~0.45–1.00—large enough to overturn capability claims without protocol fixes.

Field Overview

Today’s batch is dominated by agentic LLMs and how to evaluate/control them: at least ~20 papers on agent benchmarks, agent memory, workflow synthesis/routing, and deployment protocols (e.g., memory instruments/LMEB, DBA-Bench, InteractComp, TRACE-ROUTER, workflow self-evolution). A second major cluster is LLM/VLM safety, security, and governance—roughly ~15 papers spanning jailbreaks and adversarial prompting, tool/agent security boundaries, copyright/licensing compliance, watermarking/detection, and red-teaming limits (including multimodal-specific attack surfaces). There’s also a noticeable efficiency/PEFT + inference-systems wave (~12 papers) focused on LoRA variants and theory (MoE²-LoRA, IFCLoRA, -LoRA, “procedural knowledge not low-rank”), plus long-context sparse attention/KV-cache reuse and hardware acceleration (RIS-Kernel, HiKV, pruning, PIM/mobile finetuning). Surprising emerging direction: “JEPA” shows up across modalities (audio, PDE control, ultrasound IQ) alongside multiple audio/deepfake-forensics papers, suggesting joint-embedding world-modeling and multimodal robustness are converging into a shared research thread.