

Multilingual NLP

Where’s Waldo? Query-language Preference under Cross-lingual Knowledge Disparities [\[arxiv\]](#)

Dayeon Ki, Ruochen Zhang, Silviu Cucerzan, Ryan W. White, Ning Gao

When languages disagree, multilingual LLMs often follow the query language—so the same question asked in different languages can yield different “facts.”

Creates Waldo, a Wikipedia-derived benchmark that separates cross-lingual missingness from true cross-lingual conflict, exposing query-language preference as a reliability issue specifically under disagreement. Mine 12K QA pairs across five languages with retrieval evidence labeled as gap vs conflict; test eight LLMs with equivalent multilingual queries; mitigate via (i) ablating attention heads linked to language preference and (ii) LoRA fine-tuning to reduce same-language bias under contradiction. Models usually cross languages in gap cases, but in conflict cases they strongly snap to the query language, producing inconsistent answers across languages; LoRA reduces the preference gap by up to 61.5%, showing the bias is measurable and correctable.

Universal Byte-Level Encoding: UTF-8/UTF-16 Routing to Reduce Cross-Script Token-Budget Disparities [\[arxiv\]](#)

Hyunsik Kim, Youngmoon Jung

Routing Unicode through UTF-8 or UTF-16 before byte-level BPE makes token counts fairer across scripts without hurting quality or reversibility.

Identifies the “encoding floor” as a root cause of token unfairness under UTF-8 BBPE and proposes Universal Byte-Level Encoding (UBE), a reversible dual-path byte view that lowers worst-case symbol counts for many non-Latin scripts. Keep UTF-8 for characters that are 1–2 bytes in UTF-8; represent 3–4 byte UTF-8 characters via UTF-16 code units instead, reducing fallback length (often 32 bytes for BMP-heavy scripts) while leaving BPE unchanged and ensuring exact round-trip decoding (validated via Unicode audits/tests). UBE reduces cross-language token-premium dispersion (largest gains for scripts dominated by 3-byte UTF-8 chars) without degrading multilingual LM quality vs standard UTF-8 BBPE; yields more usable context and faster prompt processing under fixed token budgets.

Assessing the Impact of Language Disparity on Multilingual Linguistic Ability in Large Language Models [\[arxiv\]](#)

Zhanyu Chen, Jaap Jumelet

Multilingual “grammar ability” depends strongly on the probing method, and post-training often degrades syntactic judgments—especially in low-resource languages—unless evaluated with language-aware prompting.

Systematic comparison across six model families (base vs post-trained) and 101 languages on MultiBLiMP, showing evaluation paradigm and prompting can flip conclusions about syntactic competence and disproportionately mis-measure low-resource languages. Use Multi-BLiMP minimal pairs and test four paradigms (from raw probability preference to explicit grammaticality prompting); compare base vs instruction-tuned/aligned variants and stratify by language resource level to disentangle knowledge vs expressibility under a probe. Post-training generally worsens minimal-pair syntactic accuracy, with larger drops in low-resource languages; some grammatical knowledge becomes “hidden” under certain prompts (mostly detectable in high-resource languages), and native-language prompting can recover competence that looks absent under English/generic prompts—implying multi-paradigm, language-aware evaluation is necessary.

Cross-Lingual Alignment for Decoder-Only Models using MoE Routers [\[arxiv\]](#)

Lucas Bandarkar, Clark Peng, Ahmed Haj Ahmed, Aditi Khandelwal, Nanyun Peng

For decoder-only MoE LLMs, aligning languages via MoE router decisions (not token states) improves cross-lingual transfer without tokenization-alignment headaches.

Proposes router-space contrastive alignment as a robust cross-lingual objective: router distributions live in a shared expert-choice space, avoiding brittle token-level matching while still pulling representations together. During continual pretraining, add an auxiliary contrastive loss on pooled router outputs for translation-equivalent sentence pairs (close) vs non-pairs (far); pooling stabilizes the signal and makes it comparable across languages despite different tokenizations. Across four open-source MoE models, router-alignment increases cross-lingual alignment in internal representations and improves performance on a broad multilingual evaluation suite, showing MoE

routing is an effective alignment surface for decoder-only LLMs.

Multilingual Speech Processing

AURAL: Adaptive Latent Reasoning with Joint Chunk for Speech Language Models [\[arxiv\]](#)

Yuxiang Wang, Kunyu Feng, Yuancheng Wang, Zihang Liu, Shengbo Cai, Qinke Ni, Wan Lin, Tao Feng, Yingda Shen, Ming-Hao Hsu, Zhixian Zhao, Liqiang Zhang, Teddy Sun, Steve Yves, Zhizheng Wu

Speech LMs can keep CoT-like reasoning quality while slashing latency by doing multi-step “thinking” in latent space and emitting only the final answer.

Replaces verbose textual CoT with adaptive latent reasoning to cut time-to-first-audio/token, and releases AuralReason-683K (bilingual) to supervise speech reasoning in this setting. Learn latent reasoning trajectories (distribution over continuations) and predict them with a joint-chunk scheme to reduce sequential steps; train with supervised learning on AuralReason-683K then RL (AURAL-RL) rewarding correctness/quality while encouraging concise, difficulty-adaptive latent compute. AURAL-RL matches CoT-RL performance across two backbones and improves over supervised-only models; it uses more latent steps on harder inputs and cuts time-to-first-token on Qwen2.5-Omni by 11.8% vs CoT (1.22s/0.10s), near direct answering (0.05s).

SHAMS: An Audio-Grounded Pronunciation Benchmark for Levantine Arabic [\[arxiv\]](#)

Ben Sapirstein, Roy Mattar, Guy Mor-Lan, Ahlam Mohamed, Letizia Cerqueglini, Morris Alper

SHAMS provides a shared, audio-grounded benchmark to evaluate Levantine Arabic pronunciation and related speech-language tasks across dialect varieties.

Introduces a 1,300-utterance dataset balanced across five Levantine varieties, with aligned audio plus multiple text/phonetic representations to enable consistent, dialect-stratified evaluation despite nonstandard orthography. Curate and balance utterances (Urban/Rural Palestinian, Urban Jordanian, Lebanese, Syrian) and annotate four aligned tiers per item: audio, unvocalized text, diacritized text, and phonetic transcription—supporting ASR, diacritization, G2P, and audio-to-phoneme evaluation. Benchmarks with open and proprietary models show SHAMS is practical as a multi-task evaluation suite across the five varieties; the resource is released publicly to standardize future comparisons.

Foundation Model Theory

Capturing In-Context Learning Dynamics with Task Operators [\[arxiv\]](#)

Guangzhi Xiong, Zhenghao He, Bohan Liu, Sanchit Sinha, Wenqian Ye, Aidong Zhang

ICL can be “compiled” into a small set of per-attention-head affine tweaks that can be replayed at inference, recovering much of demo-based adaptation without long prompts.

Gives a mechanistic account of ICL at the attention-head level and turns it into a compression scheme: for a fixed task, each head’s demo-induced change is well-approximated by a stable affine map, concentrated in a sparse set of heads/positions. Run two passes (full ICL vs. demo-masked), fit per-head scale/shift mapping masked head outputs to ICL head outputs, then convert these maps into a Task Operator applied via attention output projections at inference; identify salient heads/positions and average operators from different demo batches to mimic many-shot. Task Operators recover a large fraction of full-ICL gains across lexical/algorithmic/reasoning tasks and beat prior single-vector compression; task info is sparse and task-specific, and averaging operators approximates many-shot improvements without extra context.

Field Overview

Today’s batch is dominated by LLM agents and how to make them reliable, auditable, and cost-effective: at least ~60 papers cluster around agent harnesses/workflows, long-horizon evaluation (e.g., DAYJOB, Argo-Bench, Incident-Arena, ReLiveGym), memory/belief-

state design (Mem++, MemFit, Madeleine, Causal Memory Policy), and verification/auditing of tool use and outcomes (Actions with Receipts, Praxa, VeriHarness, WebArena-Lite audits). A second major theme is evaluation/measurement pathology—especially LLM-as-a-judge instability, bias, and metric confounds—with ~25+ papers on judge reliability, preference/rubric design, and benchmark leakage/contamination (e.g., “First Token Is Not the Verdict,” “Pinned and Still Unstable,” “Old Ideas, Novel Problems,” multiple auditing frameworks). Efficiency and deployment constraints are also heavily represented (~30+), spanning quantization/pruning/speculative decoding/KV-cache and on-device systems (FP4/FP4 pretraining, QK-Wanda, EchoPress/CommunityKV, CAST/AgSpec, on-device NER/intent retrieval). A notable emerging direction is diffusion/flow language modeling and its post-training/serving economics (roughly ~15–20 papers on diffusion LMs, one-step/flow-map distillation, and inference-time scaling/cost modeling), alongside a surprisingly large audio/speech cluster (~25+ on full-duplex speech agents, TTS/VC robustness, deepfake detection, and audio benchmarks).