

Multilingual NLP

Translation with Thought: Difficulty-Adaptive Reasoning via Reinforcement Learning for Multi-Domain Machine Translation [\[arxiv\]](#)

Yongshi Ye, Biao Fu, Chongxuan Huang, Yidong Chen, Xiaodong Shi

TwT trains MT models to spend extra reasoning tokens only on hard sentences, improving multi-domain quality while cutting inference tokens.

Introduces Translation with Thought (TwT), a resource-rational MT framework that learns difficulty-adaptive “intuitive vs deliberate” translation behavior across domains, improving efficiency without sacrificing generalization. Two-stage training: (1) SFT on difficulty-aware, economical long-CoT traces distilled from DeepSeek-R1 and rewritten by GPT-4o; (2) RL with a hybrid reward trading off translation quality against reasoning-token cost, directly optimizing “minimal sufficient thought.” On 15 benchmarks (in/out-of-domain), across 3 seen + 59 unseen languages, TwT-7B/14B beat larger reasoning MT baselines while using 32–60% fewer tokens; ablations across three backbones attribute gains to the TwT recipe.

The Morphological Core of Dungan: A Two-Dialect Finite-State Model and a Multi-Genre Evaluation [\[arxiv\]](#)

Anton M. Alekseev, Sergey I. Nikolenko

A two-dialect finite-state analyzer shows Dungan NLP is limited more by lexicon coverage than by missing morphological rules.

Builds the first fairly complete HFST finite-state morphology for Cyrillic Dungan (Gansu + Shaanxi dialects) and uses it as a measurement tool to separate grammar adequacy from vocabulary gaps across genres. Hand-encode published grammatical categories/alternations in HFST; evaluate on multi-genre corpora, tracking overt inflection frequency, ambiguity hotspots, and failure causes (OOV vs unmodeled phenomena). Overt inflection is sparse (~9% marked tokens in encyclopedic text); ambiguity is mostly concentrated in clitics -di/-ni; analyzer failures are 78–95% OOV by genre. Held-out coverage ~80–85%; a stem list already ~67%, implying lexicon expansion is the main frontier. /scripts released.

HalluTruthQA: A Fine-Grained Benchmark for Hallucination Detection, Localization, and Explanation in Arabic Question Answering [\[arxiv\]](#)

Abdessalam Boucekif, Mohammed-En-Nadhir Zighem, Salah Eddine Bekhouche, Hichem Telli, Somaya Eltanbouly, Shahd Gaben, Heba Sbahi, Samer Rashwani, Mutaz Al-Khatib, Emad Mohamed, Mohammed Ghaly, Abdenour Hadid

HalluTruthQA makes Arabic hallucination evaluation actionable by testing detection, localization, verification, and explanation—not just answer correctness.

Releases a 2,400-item Arabic QA benchmark with verified references plus fine-grained hallucination annotations: binary labels, character-level error spans, human explanations, and macro/micro error types, plus MC verification candidates. Each item pairs a question with a (possibly hallucinated) model answer; experts verify the reference, mark erroneous spans at character level when needed, write explanations, assign taxonomy labels, and provide six candidate answers for verification. Zero-shot eval on ALLaM-7B, Falcon-H1R-7B, Qwen3-32B, SILMA shows tasks decouple: best detection Macro-F1 ~0.880 vs best span F1 ~0.516; verification can be high (best LO-Score ~0.852) while explanations lag (best ~0.644), confirming response-level labels miss key failure modes.

DenseOn with the LateOn: Fully Open Dense and Late-Interaction Models for Multilingual, Long-Context, and Code Search [\[arxiv\]](#)

Raphaël Sourty, Antoine Chaffin, Paulo Roberto Moura Junior, Amélie Chatelain

With a fully open pipeline, late-interaction retrieval transfers translate-train supervision to unseen languages/scripts better than dense embeddings.

Releases end-to-end open data/training for strong retrieval and provides a controlled dense vs late-interaction comparison under identical translate-train conditions, isolating interaction mechanism as the driver of multilingual transfer. Curate 665M contrastive pairs

(from 1.4B across 34 sources) + 1.88M supervised pairs with hard negatives; train DenseOn (bi-encoder) and LateOn (ColBERT-style). Translate validated English data into 8 languages + cross-lingual samples (2.8B pairs) and train mDenseOn/mLateOn on the same mmBERT-base backbone/objectives. On BEIR, 149M DenseOn/LateOn reach 56.20/57.22 avg nDCG@10 (SOTA for size). In multi-lingual eval, mLateOn degrades less than mDenseOn on languages/scripts outside translate-train, indicating token-level late interaction improves zero-shot cross-script generalization.

Multilingual Speech Processing

Tokenizer Transplantation: Mitigating Autoregressive Collapse in Edge-Efficient Bengali ASR [\[arxiv\]](#)

Sanjid Hasan, Md. Abdur Rahman

Bengali ASR collapse in tiny autoregressive models is largely a tokenizer problem; swapping to a Bengali WordPiece vocab stabilizes decoding with minimal changes.

Causally links Moonshine’s Bengali failures to English-centric byte tokenization that inflates target length and triggers autoregressive instability, and proposes “tokenizer transplantation” as a lightweight fix. Replace the decoder’s byte-level vocabulary with BanglaBERT WordPiece tokens, resize the embedding matrix, keep the rest of the model unchanged; shorter sequences reduce exposure-bias-driven error accumulation. Token fertility drops 9.161.30 tokens/word (85.8% length). On 882h Lipi-Ghor, the transplanted model reaches 21.54% WER at RTF 0.0053, supporting that the collapse was tokenizer-induced.

M3-DuplexBench: A Multi-Turn, Multilingual, Multidomain Benchmark for Full-Duplex Spoken Dialogue Models

[\[arxiv\]](#)

Ryo Fukuda, Atsushi Ando, Hiroki Kanagawa, Takatomo Kano, Marc Delcroix, Naohiro Tawara, Yuya Chiba

M3-DuplexBench enables controlled, multi-turn evaluation of full-duplex spoken dialogue across languages and domains, exposing turn-taking gaps hidden by standard benchmarks.

Introduces a multilingual (EN/JA), multidomain (chat, multi-turn QA) benchmark tailored to full-duplex interaction (simultaneous listen/speak), where timing, interruptions, and history matter. Evaluate models under controlled context conditions—single-turn, user-history, and teacher-forced full-context—to disentangle turn-taking policy from dialogue-state tracking and reduce confounds from compounding errors. Recent duplex models exhibit distinct, model-specific turn-taking styles and uneven performance across language/domain; adding more history helps inconsistently and can shift behavior unpredictably, showing duplex robustness is not solved.

Foundation Model Theory

Do Music Foundation Models Embed Pitch in Helical Structure? [\[arxiv\]](#)

Hayato Yagi, Shinnosuke Takamichi, Rin Sato, Keitaro Tanaka, Shigeo Morishima

Several music foundation models encode pitch on a helical manifold, naturally capturing octave equivalence plus pitch height.

Turns “do models understand pitch?” into a geometry probe: isolated-note embeddings often form a helix, matching the expected structure for periodic pitch class wrapped around monotonic pitch height. Feed controlled single-note inputs sweeping pitch; extract intermediate-layer embeddings; apply PCA to visualize/quantify low-D structure; vary acoustic/timbre conditions to test robustness of the manifold. Intermediate representations show a clear pitch helix aligned with octave periodicity; helix clarity varies by model and input acoustics, implying pitch coding is learned, structured, but architecture/training- and timbre-dependent.

LLM Evaluation

CalibratedRubric: Task-Adaptive Rubric Banks for Open-Ended LLM Evaluation [\[arxiv\]](#)

Mengting Chen, Yanshu Sun, Wanting Liang, Beidi Luan, Rui Sun, Dezhi Chen, Jing Li, Zuo Bai

CalibratedRubric builds small, task-adaptive rubric banks that judges can apply consistently and that better preserve system rankings at lower cost.

Separates rubric “measurability” (judgeable with agreement) from “informativeness” (discriminates model quality) and selects compact rubric sets via uncertainty-aware filtering plus IRT-based coverage, improving reliability and efficiency. Pipeline: type-specific rubric scoring; estimate measurability with a Beta–Bernoulli posterior over judge agreement; model rubrics with IRT (difficulty/discrimination) and greedily select a submodular, information-maximizing rubric bank over the capability range. Measurability filtering boosts agreement on JudgmentBench (Cohen’s 0.6040.743). IRT-based selection improves rank fidelity vs random across response blocks; on FinResearchBench, 49 rubrics match the target correlation of 131, cutting evaluation cost substantially (with gains depending on sufficient judge redundancy).

Field Overview

Today’s batch is dominated by LLM/agent evaluation, reliability, and governance: at least ~25–35 papers on LLM-as-a-judge auditing and rubric/benchmark design (e.g., bias-robust judges, agreement metrics, sample-level auditing, calibrated rubrics, agent-safety benchmark validity, medical evaluator limits), plus another ~20–30 on agentic systems themselves—especially long-horizon memory/context management and test-time compute control (Zero-Mem/TransMem/MemForest/ViSAGE, aborting futile reasoning, adaptive exits, conformal cascades, OPD/TTRL-style self-improvement). A second major cluster is efficiency + systems for deployment (roughly ~15–25): KV-cache compression/translation, tokenization/serving optimizations, disaggregated GPU inference, quantization trade-offs, and federated pre-training/fine-tuning with privacy defenses. Notable emerging directions include “enterprise/regulated” agent validation and risk gating (regulated-firm shipping checks, tool-call authorization and conformal risk control, evidence traceability), and a surprisingly strong multimodal/audio thread (~10–15) spanning full-duplex spoken dialogue benchmarks, LLM-based ASR, audio/music foundation model analysis, and deepfake voice/media detection.