

Multilingual NLP

CulturalMenuBench: Probing the Knowledge-Application Gap in Multimodal Culinary Reasoning [\[arxiv\]](#)

Bo Zeng, Linfeng Gao, Peiqin Lin, Yu Zhao, Mingyan Zeng, Yu Tong, Xintong Wang, Linlong Xu, Longyue Wang, Weihua Luo, Qinggang Zhang, Jinsong Su

Multimodal models can ace food recognition yet fail at culture: mapping a dish to the correct regional cuisine from visual/procedural evidence.

CulturalMenuBench isolates a knowledge-application gap by shifting from label matching to procedure-grounded cultural attribution while keeping evaluation formats simple (often MCQ). 4,870 items, 10 tasks, 10 languages, 18 regions; inputs include dish photos plus ingredients, step images, and procedural text; evaluate 12 models with diagnostics (name vs image, error structure, ablate step images). Models >94% on standard recognition can drop to near chance on cultural attribution (56% on 4-way Chinese regional cuisine); performance is 7–18 points higher with dish names than images, and removing step images selectively hurts process-dependent tasks—evidence that visual/procedural grounding is the bottleneck.

MIRA: A Bilingual Benchmark for Medical Information Response Audit [\[arxiv\]](#)

Mengyu Xu, Qiaoxin Yang, Qianqian Wang, Xiwei Dai, Weiwei Wu, Chongyang Gao

LLMs often give less complete medical guidance to lower-health-literacy users or across languages; MIRA measures and reduces this inequity.

Introduces MIRA, a bilingual audit benchmark for Differential Information Dilution (DID): same medical intent, different user language/register/literacy cues, revealing systematic omission of key info. 60 medically reviewed low-risk questions expanded into 4,320 controlled prompts varying language, register, and health-literacy signals; score responses for inclusion of key medical content and actionable guidance; validate trends on 300 real queries; test a knowledge-guided mitigation prompt. Across five LLMs, low-literacy cues reliably reduce key details and next steps despite identical intent; MIRA rankings correlate with real-query behavior; a mitigation prompt cuts dilution for most models (largest reported drops: Claude ~8%, Qwen ~6%).

Translation as a Decision Space: A Multi-Agent Perspective on Low-Resource Dialect Generation [\[arxiv\]](#)

Hasan Alkhder, Mohammad Abboush, Igor Tchappi, Ahmet Zengin, Amro Najjar

Low-resource dialect translation is best viewed as a “decision space” of plausible outputs, exposing controllable trade-offs between authenticity, normalization, and stability.

Shows that agent disagreement in dialect settings is informative (not just noise) and proposes dialect-aware metrics to characterize where outputs drift toward standardized language or become unstable. Three TurkishSyrian Arabic agents on one backbone: zero-shot direct, lightly fine-tuned “dialect-stabilized,” and pivot (TurkishEnglishSyrian); evaluate via dialect marker frequency, proximity to standardized Arabic, and structural variance. Lightweight stabilization nearly doubles dialect markers (0.22660.4988) and reduces instability; pivoting pushes outputs toward standardized forms (“compression”); zero-shot shows highest variance, consistent with unconstrained competing realizations.

Toward Collective-Centric Evaluation of Preference Inference for Participatory Democracy [\[arxiv\]](#)

Pierre-Antoine Lequeu, Salim Hafid, Paul Lerner, Nazanin Shafiabadi, Laurène Cave, David Mas, Jean-Philippe Cointet, Benjamin Piwowarski, François Yvon

Preference-inference for civic deliberation must be judged by whether it preserves the group’s consensus/polarization structure—not just individual vote accuracy.

Introduces collective-centric evaluation and releases a large multilingual dataset (22 languages, ~90k participants, ~1M votes) from four real consultations to measure distortion of the “collective map.” Impute missing votes with existing PI models, then compare both user-centric accuracy and collective-centric properties (cluster geometry, consensus/conflict structure, minority visibility) against what observed data supports. Models tied on standard accuracy can produce sharply different collective narratives (coalitions, agreement strength, minority prominence), showing accuracy-only objectives are unsafe for participatory platforms; the suite makes such distortions measurable.

Multilingual Speech Processing

X-Translator: A Real-Time Multilingual Speaker-Aware Speech-to-Speech Translation System [\[arxiv\]](#)

Yuxiang Zhao, Yichi Zhang, Yanjie An, Yanqiao Zhu, Zhanxun Liu, Yushen Chen, Qixi Zheng, Haina Zhu, Yunchong Xiao, Keqi Deng, Shuai Fan, Kai Yu, Xie Chen

An open, real-time S2ST system that stays low-latency in messy streaming audio while keeping translated voices tied to the right speaker.

Releases X-Translator, emphasizing that deployability hinges on session-level control (when to commit/revise text; which speaker voice prompt to use), not just better ASR/MT/TTS models. Cascaded streaming ASRMTprompted TTS plus a runtime controller: (1) incremental segment commitment to translate only stabilized ASR spans; (2) online speaker-prompt manager that tracks speaker spans and binds them to consistent TTS prompts across long, fast-turn dialogues. On OpenSTBench, controller-driven commitment improves stability/latency trade-offs, and speaker-prompt tracking improves long-session voice consistency and speaker identity preservation; behavior is competitive with proprietary API baselines in long-form, multi-speaker settings.

VoxPrivacy: A Benchmark for Evaluating Interactional Privacy of Speech Language Models [\[arxiv\]](#)

Yuxiang Wang, Hongyu Liu, Dekun Chen, Xueyao Zhang, Zhizheng Wu

Speech assistants often can't enforce "who is allowed to know what" in shared conversations; VoxPrivacy benchmarks and trains this interactional privacy skill.

Formalizes interactional privacy for Speech Language Models and releases VoxPrivacy (bilingual, multi-speaker) plus a large training set, showing current systems are near chance on speaker-conditioned privacy decisions. Multi-user spoken interactions requiring answer/refuse/redact based on speaker identity and private context; three difficulty tiers (explicitimplicit inference); evaluate nine SLMs on 32 hours plus Real-VoxPrivacy human recordings; fine-tune on a new 4,000-hour privacy-focused dataset. Most open models are ~50% (chance) on speaker-dependent privacy decisions; closed systems still fail when privacy must be inferred; failures persist on real recordings; targeted large-scale fine-tuning substantially improves privacy-preserving behavior without breaking usability.

Foundation Model Theory

The Geometry of Ignorance: LLMs Know When to Temper Bayesian Priors [\[arxiv\]](#)

Toni J. B. Liu, Jiajun Bao, Yizhou Liu, Gurbir Arora, Nicolas Boullé, Raphaël Sarfati, Christopher J. Earls

LLMs share a single "ignorance" direction that acts like a tunable Bayesian prior toward the unigram distribution—and it can be causally steered.

Finds a robust unembedding-space direction aligned with log unigram frequencies (what the model predicts when uncertain) and interprets the hidden-state projection onto it as a prior-strength/tempering parameter comparable across models. Identify the unigram-aligned unembedding direction; decompose the final hidden state into ignorance vs orthogonal context components; show the resulting next-token distribution matches a tempered Bayes form with scalar loading controlling reliance on the unigram prior. The direction appears across Llama/Qwen/Gemma/Pythia (0.4B–405B); decreases with more informative context; directly adding/removing the ignorance component predictably moves outputs toward/away from unigram in KL, demonstrating causal control.

LLM Evaluation

Caught in the Story: Narrative Captivity in Multi-turn LLMs Conversation [\[arxiv\]](#)

Yuhe Wu, Guangyu Wang, Yujie Chen, Jiatong Zhang, Yuran Chen, Yutong Zhang, Xiyin Cheng, Wenpeng Cao, Zhuang Liu, Guang Zhang

In multi-turn advice, LLMs get "captured" by a one-sided narrator and shift moral judgments substantially even when underlying facts are matched.

Defines narrative captivity and provides a benchmark (5,078 conflict scenarios; six moral dimensions) comparing single-turn balanced

prompts vs multi-turn self-exculpatory story unfolding. Hold scenario constant; vary interaction structure (compact balanced vs staged narration); measure judgment drift over turns; analyze when drift accumulates; test inference-time mitigations (clarifying questions, alternative viewpoints). Across 17 LLMs, multi-turn narration shifts final moral judgments by ~25 percentage points vs matched single-turn; drift accumulates over stages and is linked to preference-optimization/agreeableness; mitigations help only partially.

Field Overview

Today's batch is dominated by agentic LLM systems and their evaluation/infra: at least ~25–35 titles focus on tool-using agents, multi-agent coordination, memory/retrieval, and agent benchmarks/protocols (e.g., KV/memory validation, terminal environments, GUI/meeting agents, MCP/agent harness security, Natural Language Interaction Protocol). A second major cluster is post-training and inference-time control for reasoning models—roughly ~12–18 papers on RLVR/GRPO/OPD/distillation, verifier-grounded self-improvement, prompt optimization, and decoding/control primitives (plus several critiques of spurious CoT/trajectory confounds and judge reliability). Safety, governance, and measurement is unusually prominent (10–15): deception/rogue progression monitoring, refusal signals/geometry, multilingual jailbreak robustness, provenance/traceability, and multiple “LLM-as-a-judge”/peer-review hallucination audits. Smaller but noticeable clusters include multimodal/embodied/world-model directions (8–12 across VLM agents, spatial reasoning/3D scene graphs, robotics/grasping/navigation, audio-video diffusion attention) and efficiency/serving/compression (6–10 on KV cache budgeting/eviction, quantization, video compression), with a sprinkling of domain deployments in medicine/education/finance and privacy/federated learning.