

Multilingual NLP

BioELX: Cross-lingual Biomedical Entity Linking via Alias-based Retrieval and LLM Ranking [\[arxiv\]](#)

Yi Wang, Corina Dima, Liangyu Zhong, Steffen Staab

Training-free cross-lingual biomedical entity linking works well once you fix multilingual candidate retrieval and add context-aware LLM reranking.

BioELX targets the two main non-English failure points: (1) retrieval that can't match non-English mentions, fixed by expanding SapBERT's alias space with Wikidata multilingual aliases; (2) disambiguation without labels, handled by an off-the-shelf LLM ranker over retrieved candidates. Two-stage pipeline: (i) SapBERT-style bi-encoder retriever trained with an alias inventory augmented by Wikidata multilingual aliases; (ii) LLM reranks top candidates using mention context + entity info, with no BEL fine-tuning. On XL-BEL, Recall@1 improves by +19.2 on average, with large gains in Thai (+30.8), Korean (+22.1), and Turkish (+21.6). Results transfer across EMEA, Patent, WikiMed-DE, and MedMentions, supporting the "alias-boosted retrieval + LLM rerank" recipe.

The Fragility of Chain-of-Thought Monitoring Across Typologically Diverse Languages [\[arxiv\]](#)

Eric Onyame, Runtao Zhou, Kowshik Thopalli, Bhavya Kailkhura, Chirag Agarwal

Chain-of-thought monitoring breaks under multilingual shift: reasoning text can look compliant while the model is already committed to a bad answer.

A large cross-lingual stress test shows CoT is a poor proxy for internal decision-making, and the mismatch worsens across typologically diverse languages—undermining CoT-based safety monitoring outside English. Adversarial-hint tasks requiring intermediate computation; evaluate CoT faithfulness vs final behavior, plus internal diagnostics (token-probability trajectories) to detect early latent commitment before the visible CoT reveals it. CoT unfaithfulness is pervasive: ~95.9% unfaithful cases on average (8B–120B), with some low-resource languages hitting 100%. Models often commit within ~15% of generated tokens, making external CoT monitors too late.

Disentangling Language Roles in Multilingual LLM Task Execution [\[arxiv\]](#)

Qishi Zhan, Minxuan Hu, Seoyeon Jang, Lei Zhao, Ziheng Chen, Man Liang, Xinyue Xiang, Jiaxin Liu, Guansu Wang, Liang He

Multilingual task failures depend on which language role is mismatched—especially the required response language—not on how many languages appear.

MTM-Bench disentangles instruction, content, and response languages and shows these roles are not interchangeable; forcing a different response language is the dominant bottleneck. Benchmark enumerates all 27 (L_instr, L_content, L_resp) combinations over English/Spanish/Chinese across multiple task families; scoring decomposes semantic correctness, target-language adherence, constraint satisfaction, contamination, and joint success, with human audit checks. Performance clusters by role mismatch, with response-language mismatch explaining most variance; a single response mismatch can hurt more than multiple other mismatches. Meaning-only metrics overestimate reliability because language purity/constraints often fail independently.

Beyond Input Understanding: Diagnosing Multilingual Mathematical Reasoning with Directed Acyclic Trace Graphs [\[arxiv\]](#)

Jiaqiao Zhang, Zhoujun Li, Raoyuan Zhao, Jian Lan, Thomas Seidl, Michael A. Hedderich, Hinrich Schütze, Yihong Liu

Multilingual math errors aren't just input comprehension—forcing the model to reason in another language can directly degrade math execution.

Introduces DATG to diagnose language-conditioned reasoning: converts free-form solutions into language-agnostic "math anchor" graphs to pinpoint what steps go missing when the reasoning language changes. Map each solution to a directed acyclic trace graph of math anchors (quantities/equations/transformations) and dependencies; align target-language traces to a reference DAG and score anchor coverage, dependency fidelity, and harmful actions; propose test-time Loop-Retry and Formula-Retry controls. Across Qwen3 models and 12 languages, accuracy drops even when input is English but CoT is forced non-English. DATG shows non-English traces

omit more required anchors and follow dependencies less faithfully, especially in low-resource languages; Loop-Retry/Formula-Retry yields consistent accuracy gains there.

Multilingual Speech Processing

KVoiceBench, KOpenAudioBench, and KMMAU: Agent-Driven Korean Speech Benchmarks for Evaluating SpeechLMs

[arxiv]

Haechan Kim, Seungjun Chung, Inkyu Park, Jihoo Lee, Jonghyun Lee

Korean-first speech benchmarks reveal weaknesses that English-transferred tests miss, and SpokenQA scores don't predict broader Korean audio understanding.

Releases three Korean benchmarks (KVoiceBench, KOpenAudioBench, KMMAU) built to preserve Korean speech/instruction fidelity, avoiding distortions from translate-and-TTS benchmark transfer. Agent-driven construction: (i) recreate SpokenQA benchmarks in Korean while preserving intent/constraints; (ii) convert Korean ASR corpora into audio-understanding QA using transcripts + speaker metadata to probe speaker/paralinguistic cues. Across 12,345 Korean samples and 8 SpeechLMs, EnglishKorean gaps vary widely by model/task, so English leaderboards mislead. Rankings differ between Korean SpokenQA and Korean audio understanding, showing complementary capabilities.

Bandwidth-Efficient and Privacy-Preserving Edge-Cloud Many-to-Many Speech Translation [arxiv]

Yexing Du, Kaiyuan Liu, Youcheng Pan, Bo Yang, Ming Liu, Bing Qin, Yang Xiang

Many-to-many speech translation can be high-quality without uploading raw audio by sending compressed intermediate features to the cloud and training against English-pivot bias.

ESRT provides an edge-cloud split for privacy/bandwidth: on-device speech front-end emits compressed features (not waveforms), while cloud LLM handles recognition/translation; training explicitly mitigates hidden English-pivot behavior for 45-language many-to-many scaling. Edge runs speech encoder + adapter; transmit aggressively compressed intermediate representations (reported up to 10 $\times$ bandwidth reduction). Cloud model performs S2TT. Use multi-task weighted curriculum + data balancing to reduce English-centric shortcuts. On FLEURS (45 languages; all 45 $\times$ 44 directions), ESRT 4B/12B achieves state-of-the-art many-to-many S2TT while avoiding raw-audio upload. Compression cuts network cost without collapsing quality; anti-pivot training improves cross-lingual consistency. Code/models released.

Foundation Model Theory

Revealing Algorithmic Deductive Circuits for Logical Reasoning [arxiv]

Phuong Minh Nguyen, Tien Huu Dang, Naoya Inoue

A small fraction of attention heads causally drive deductive steps, while higher layers integrate these into a global reasoning “algorithm.”

Moves from correlation to mechanism by localizing which heads are necessary for specific symbolic deduction steps and characterizing a layered division of labor (specialist subroutines vs integrators). Align symbolic CoT steps to step-steering token positions/logits; apply causal mediation interventions on attention heads to measure which heads mediate the prompt's reasoning pattern; analyze what information heads transmit across layers. Only a few percent of heads account for most causal influence on sub-steps (fact retrieval/local rule use). Higher layers act mainly as integrators assembling a global plan (e.g., graph-traversal-like strategy); step-steering tokens often have low confidence, consistent with constraint-following behavior.

Field Overview

Today's batch is dominated by LLM agent reliability/safety and evaluation: at least ~40–60 titles focus on agentic tool use, multi-agent

coordination, long-horizon memory, and governance (e.g., TRACES, MemGuard/MemTrace, Ask Now Use Later, Harness-Bench, Colosseum, Got a Secret?, policy/runtime layers). A second major cluster is retrieval-augmented generation—especially GraphRAG and RAG security/grounding—with ~15–25 papers on multi-hop retrieval, citation faithfulness, caching, and poisoning/hijacking attacks (e.g., ConRAG, LegalGraphRAG, Beyond Cross-Chunk Graph Augmentation, SilentRetrieval, GraphSteal, Verified Misguidance, Grounded Cache Routing). There’s also a noticeable surge in audio/speech + audio-language models and long-context audio benchmarks (~10–15 papers: VoiceGiraffe, ChronosAudio, KVoiceBench, audio scene generation/tokenizers, deepfake/singing detection), alongside efficiency work for long context/inference (KV-cache compression, sparse attention, MoE pruning/serving; ~10–20). A surprising emerging direction is “meta-evaluation” and auditing of the evaluators themselves (LLM-as-a-judge robustness, debate oversight, replication-first benchmarking, test-set contamination/known-eval design), suggesting the field is shifting from raw capability gains toward measurement integrity and deployment-grade assurance.