

Multilingual NLP

Copy First, Translate Later: Interpreting Translation Dynamics in Multilingual Pretraining [\[arxiv\]](#)

Felicia Körner, Maria Matveev, Florian Eichin, Gitta Kutyniok, Barbara Plank, Michael A. Hedderich

Multilingual pretraining yields “translation” in stages: early behavior is mostly copying/surface overlap, with genuine cross-lingual mapping emerging later.

Provides a time-resolved, mechanistic account of how translation ability forms, separating copy-driven pseudo-translation from later abstract translation via targeted probes and causal ablations. Pretrain a 1.7B, 9-language model with many close checkpoints; evaluate on a word-level translation testbed designed to disentangle copying (cognates/script/subword overlap) from true mapping; link phases to specific components via analyses and parameter ablations. Translation follows a clear two-phase trajectory: early checkpoints look good mainly by copying/orthographic cues and generalize poorly; later checkpoints shift to a more overlap-robust translation mechanism while copying becomes more selective—implying early cross-lingual gains can be misleading without copy controls.

ToxiREX: A Dataset on Toxic REasoning in ConteXt [\[arxiv\]](#)

Stefan F. Schouten, Ilia Markov, Piek Vossen

ToxiREX turns toxicity detection into multilingual, context-dependent reasoning with structured explanations, not keyword spotting.

Introduces a schema-labeled dataset for implicit, thread-dependent toxicity across six languages, enabling evaluation of *why/whom/how* toxicity is implied rather than just toxic/not. Collect Reddit threads tied to major events in EN/AR/TR/ES/DE/NL; annotate each target comment with a hierarchical “toxic reasoning” structure; scale with ~125k LLM-labeled training items and a ~3k native-speaker test set; use structured/partial-credit evaluation; report prompting and fine-tuning baselines. Current models achieve measurable but clearly insufficient structured reasoning accuracy, especially when toxicity depends on thread context; annotator disagreement often reflects genuinely ambiguous implicatures, highlighting a large gap between model behavior and realistic moderation-grade interpretation.

MultiHashFormer: Hash-based Generative Language Models [\[arxiv\]](#)

Huiyin Xue, Atsuki Yamaguchi, Nikolaos Aletras

MultiHashFormer removes vocabulary-sized embeddings/softmax by generating hash signatures, enabling constant-parameter vocabulary growth (e.g., new languages).

Replaces token IDs with multi-part hash codes so autoregressive LMs can add tokens without expanding embedding/output matrices, while keeping generation unambiguous. Map each token to a unique signature from multiple hash functions; Hash Encoder converts the signature to an input vector; Hash Decoder predicts the next-token signature (multiple small categorical predictions) instead of a vocab softmax; decode signature back to token. At 100M/1B/3B scales, the hash-signature LM matches or outperforms standard Transformers on benchmarks, and supports vocabulary expansion with no growth in embedding/softmax parameters—showing vocab-sized layers aren’t essential for high-quality generation.

Ko-WideSearch: A Korean Breadth-Search Benchmark for Exhaustive Set Enumeration by Web Agents [\[arxiv\]](#)

Minbyul Jeong

Ko-WideSearch exposes a key web-agent weakness: agents can find the right items but fail to correctly populate per-item tables in Korean breadth tasks.

Creates a Korean “breadth search” benchmark for exhaustive set enumeration with table filling, plus metrics (Item/Column/Row-F1) that isolate the hard alignment problem depth-style QA misses. Tasks specify a set-parent entity (e.g., season/region/election) and require complete membership plus attributes; difficulty varies by table width and composite (2-D) keys; normalization-aware matching; gold tables built via synthesize-and-verify to ensure completeness; evaluate 20 agents. Across agents, Item-F1 can be high while Row-F1 collapses (e.g., 92.8 vs 53.7), showing a consistent “list found, rows wrong” gap; performance degrades with wider tables/composite keys, and extra steps/compute don’t fix it—errors mainly come from extracting the right values, not formatting.

Multilingual Speech Processing

Measuring the Redundancy of Decoder Layers in SpeechLLMs [\[arxiv\]](#)

Adel Moumen, Guangzhi Sun, Philip C Woodland

SpeechLLMs inherit decoder-layer redundancy from their base LLMs, allowing large decoder pruning with minimal ASR/speech-translation loss.

Empirically maps which decoder layers are redundant for speech and shows the pattern largely matches text-only redundancy, yielding a reusable pruning recipe across encoders, tasks, and languages. Layer-prune decoder blocks and measure performance (not just proxies) across two LLM families and ~1B–8B sizes; compare redundancy under text vs speech inputs; test post-pruning “healing”; validate across ASR vs speech translation, multiple encoders, and languages. Redundant layers under speech align with redundant layers under text; in ~7–8B models, ~40% of decoder layers can be removed while keeping strong ASR, with similar redundancy structure holding across translation, encoders, and languages (smaller models tolerate less pruning).

Do Speech Emphasis Models Generalize across Languages and Emotions? [\[arxiv\]](#)

Megan Wei, Deepali Aneja, Jiaqi Su, Yunyun Wang, Haonan Chen, Zeyu Jin

Emphasis detection doesn’t reliably transfer across languages/emotions; MMEE benchmarks what training actually yields robust prosody-based emphasis models.

Releases MMEE: a professionally recorded, 7-language, multi-emotion corpus with perceptual (3-level) emphasis labels, enabling systematic cross-lingual and cross-emotion generalization tests. Multi-annotator perceptual labeling; evaluate two emphasis models under cross-lingual, cross-emotion, multilingual-training, cross-dataset transfer, and varying data-scale settings to test whether emphasis cues learned are language-agnostic or language/style-specific. Monolingual models transfer poorly to distant languages; multilingual training substantially improves cross-lingual robustness. Cross-emotion transfer is somewhat more stable (notably across arousal levels) but still condition-dependent; transfer between synthetic and perceptual benchmarks suggests shared prosodic structure, and diversity of conditions can matter as much as dataset size.

Foundation Model Theory

The Curse of Multiple Mediators: Hidden Interaction Effects in Activation Patching [\[arxiv\]](#)

Sankaran Vaidyanathan, David Arbour, Aaron Mueller, Scott Niekum, David Jensen

Activation patching conflates component effects with hidden interactions, explaining why “importance” scores can be unstable and misleading.

Shows patching’s estimand includes mediator interaction terms in multi-mediator causal settings, so one-component patching is not a clean measure of standalone causal contribution. Formalize patching as causal mediation with multiple mediators; derive decomposition into direct, mediated, and interaction terms; analyze when interactions grow (nonlinear/non-affine regions, large clean–corrupt gaps) and how they decompose into pairwise/higher-order effects. On GPT-2 IOI, interaction terms explain observed patching failures: conditional components can be missed, others over-credited, and prompt-to-prompt instability arises from varying interactions; measuring interactions becomes a diagnostic and motivates group/combinatorial searches for faithful mechanisms.

LLM Evaluation

CELEUS: Certifiable and Efficient LLM Evaluation via E-Processes [\[arxiv\]](#)

Zhijian Zhou, Zesheng Ye, Zhaorun Chen, Bo Li, Feng Liu

CELEUS enables anytime-valid LLM evaluation with optional stopping, cutting human-graded samples roughly in half while keeping guaranteed coverage.

Combines e-process (optional-stopping-safe) confidence intervals with adaptive sampling and surrogate assistance, preserving statistical validity under repeated peeking and data-dependent stopping. Online evaluation: choose which items to label; use uncertainty-guided sampling to reduce variance; incorporate surrogate predictions for unlabeled items; construct conditionally unbiased per-step signals feeding an e-process to maintain always-valid CIs. Achieves target CI precision with ~54–62% fewer gold evaluations than prior certifiable baselines while maintaining anytime-valid coverage; theory shows near-parametric CI shrinkage (log factors) and motivates variance-optimal sampling.

Field Overview

Today’s batch is dominated by LLM/agent reliability and infrastructure: at least ~25 papers touch LLM agents, memory/world models, planning, and evaluation (e.g., memory-update gaps, clarification-aware search, long-horizon multimodal memory, world-model planning, agent benchmarks like Ko-WideSearch/DiscoBench/NormAct). A second dense cluster is efficiency/serving for large models—roughly ~15 papers on inference acceleration and deployment (KV-cache compression/eviction, sliding-window/full-attention hybrids, dynamic sparsity, MoE pruning, routing/scheduling, checkpointing). Safety/security/privacy is also unusually prominent (12–15): jailbreak/prompt-injection theory and attacks, guardrails, “unlearning” critiques and methods, tool-privacy benchmarks, and ecosystem-level risk for agentic coding. Outside core LLM work, there’s a noticeable time-series foundation/forecasting wave (10–12) plus a parallel audio/speech surge (10) spanning TTS, robustness, deepfake detection, and long-audio QA—suggesting multimodal reliability and deployment constraints are converging as a key emerging direction.