

Multilingual NLP

E-CONAN (Entailment, CONtradition And Neutral) Benchmarks: Arabic Textual Entailment and Natural Inference Datasets [\[arxiv\]](#)

Khlood AL Jallad, Nada Ghneim, Ghaida Rebdawi

Introduces a more diverse Arabic NLI benchmark suite that better stress-tests cross-dataset generalization than prior Arabic resources.

E-CONAN: two Arabic inference datasets built from mixed “naturalness” sources—translation, human-validated translation, pedagogical hand-crafted pairs, and rumor/news headlines—released as E-CONAN-2 (2-way RTE) and E-CONAN-3 (3-way NLI). Constructs sentence pairs from four pipelines, then evaluates 9 multilingual pretrained models zero-shot plus 5 LLMs on E-CONAN-3, with MARBERT as an Arabic-specific baseline; compares transfer vs ArNLI/XNLI and reports qualitative/quantitative error analysis. Shows E-CONAN’s diversity makes it a useful generalization benchmark (and a fine-tuning resource); provides broad zero-shot/LLM baselines and error analyses, arguing it offers a more robust assessment than XNLI/ArNLI (abstract reports no specific error-pattern conclusions).

Prompt Revision as a Source of Cultural Bias in Text-to-Image Systems [\[arxiv\]](#)

Aleksandra Urman, Elsa Lichtenegger, Salima Jaoua, Azza Bouleimen, Robin Forsberg, Corinna Hertweck, Stefania Ionescu, Nicolò Pagan, Anca Hannak, Joachim Baumann

*Hidden prompt-rewrite layers in text-to-image products can *cause* cultural stereotyping, so auditing only generated images misses a major bias source.*

Identifies prompt revision as a causal bias mechanism and introduces WORLDVIEW, a multilingual benchmark spanning 15 languages and 31 language–context pairings to measure how systems differentially “mark” cultures. Collects revised prompts from three deployed systems; measures (i) cultural marking, (ii) vocabulary collapse/flattening into repeated culture terms, and (iii) stereotypical signifiers; tests causality by feeding original vs revised prompts into models without revision layers. Prompt revision marks non-Western/non-Anglophone contexts far more than a US/English baseline, often collapsing diverse intents into narrow stereotyped terms; swapping only to the revised prompt increases stereotyped imagery, isolating the rewrite step as a previously undocumented bias source.

Multilingual in Name Only? Cultural and Linguistic Weaknesses of LLMs in Urdu [\[arxiv\]](#)

Farah Adeeba, Abdul Rafae Khan, Rajesh Bhatt, Hassan Sajjad

“Multilingual” LLMs still produce visibly broken, culturally off Urdu stories, and few-shot prompting doesn’t reliably fix the core issues.

Urdu-Stories: 93 Urdu stories from three LLMs (GPT-5.1, Qwen-3-Max, DeepSeek-3.1) with a human, nine-category error taxonomy covering linguistic, semantic, coherence, and cultural/context failures. Story-generation evaluation; manual annotation with nine labels; compares baseline prompting vs few-shot prompting to see which error types improve vs persist. Frequent grammar/semantic errors, coherence drift, and unnatural repetition; cultural shallowness and context mismatches remain pervasive even with few-shot prompting, indicating missing grounding/knowledge rather than simple instruction-following failures.

Cross-Lingual Clinical Annotation Projection as Constrained Text Generation: A Six-Language Study [\[arxiv\]](#)

Álvaro Rey-Blanes, Francisco J. Moreno-Barea, Francisco J. Veredas

Treating cross-lingual clinical label projection as constrained, text-preserving generation yields offset-exact spans that are actually usable for corpus building.

Reframes projection as “immutable text + inline tags,” preventing paraphrase/normalization so annotations deterministically map back to character offsets; validated outputs enable reliable multi-language corpus creation. LLM outputs the target document unchanged except for inserted Disease/Symptom/Procedure tags; deterministic post-check ensures tag-stripped text exactly matches the original, enabling exact offset reconstruction; compared against supervised and hybrid projection pipelines on six languages. On MultiClinAI, constrained direct projection is best and most consistent across all 6 languages & 3 entity types: GLM 5.2 ~0.92 mean Strict F1 over

18 settings; Gemma4:31B ~0.913; beats prior SOTA in every setting by ~0.056–0.151 Strict F1 and produces tens of thousands of offset-reconstructable mentions.

Multilingual Speech Processing

Beyond Word Error Rate: A Switch Aware Evaluation of ASR and Audio Language Models on English Yoruba Code-Switched Speech [\[arxiv\]](#)

Chibuzor Okocha, Christan Earl Grant

WER can hide the real failure in code-switched ASR: models break at EnglishYoruba switches, so switch-aware metrics are necessary.

A switch-aware evaluation suite for English–Yoruba code-switched speech, adding metrics like SETER, windowed switch error rates, language-specific error rates, and diacritic-insensitive WER; also characterizes non-transcription behaviors of audio LMs. Evaluates 11 systems (6 ASR, 5 audio LMs) on a fixed 2,000-utterance test set with a shared scoring pipeline; computes switch-localized and language-split metrics; checks audio LMs for translation, verbosity, and prompt leakage. Overall WER makes a top ASR model look tied with a leading audio LM, but switch-aware metrics show the audio LM is better at switches; Yoruba token recognition nearly collapses (~0.97 error for Yoruba tokens for most systems) with errors concentrated at switch points; some audio LMs also translate/add text or leak prompts, making them unreliable as exact transcribers.

X-AuT: Progressive Audio-Encoder Compression for Speech LLMs with Cross-Scale Distillation [\[arxiv\]](#)

Haojun Zhang, Yi Zou, Min Chen, Qize Yu, Lianrui Fan, Xini Ding, Hao Li, Shuchang Zhou, Xianming Liu, Shiyu Huang

X-AuT compresses speech-LLM audio encoders with minimal behavior drift by progressive pruning plus cross-scale distillation to preserve decoder compatibility.

A staged compression recipe for the audio tower of speech LLMs that avoids deletion/early-EOS failures from naive layer dropping by keeping the frozen LM decoder’s expected embedding distribution stable. Progressive pruning with behavioral probes to pick least-disruptive layer subsets; representation alignment + cross-scale distillation; scheduled student-policy supervision; trains only lightweight attention LoRA adapters (LM frozen) and uses transcript-consistency filtering plus data reweighting. On 10 Zh–En benchmarks (Qwen3-ASR-0.6B), 1816 layers improves macro error 5.61%→5.27%; 1814 yields 5.75% with ~20.7% fewer audio parameters; progressive pruning beats direct pruning (5.75% vs 6.73%), and a 1.7B teacher helps (5.55%) while self-distillation degrades (8.45%).

Foundation Model Theory

From Parameters to Answers: How LLMs Retrieve and Use Their Internal Knowledge [\[arxiv\]](#)

Wenkang Wei, Yuan Fang, Renhe Jiang, Hong Cheng, Xingtong Yu

Causal interventions separate “request routing” from “answer content” inside LLMs and show the handoff timing differs across model families.

Defines linear directions for request information (which entity/subquestion) and for answer-content candidates, then tests when each is merely detectable vs causally steering computation via layerwise interventions. Builds pair-conditioned and global request directions at the end-of-question state; constructs content “selection candidate” directions; intervenes on these components at chosen layers and measures downstream effects across Qwen/Llama/Gemma and answer types (nouns, adjectives, code). In Qwen, request info becomes detectable before it becomes causally effective, with a mid-layer window where routing interventions change later knowledge/content while content is still forming; in paired questions, dependence shifts from global request to content in later layers; Gemma partially matches this profile, while Llama lacks a sustained routing-effect window; some request variables (pair-conditioned) retain later causal influence even as global routing fades.

LLM Evaluation

HarvestBench: Measuring Whether LLM Agents Will Pay to Avoid Killing Animals [\[arxiv\]](#)

Jasmine Brazilek, Miles Tidmarsh, Matthias Endres, Anshuman Singh, Jeremiah Miller

*HarvestBench quantifies whether LLM agents will *pay* to avoid harming animals—and shows harm avoidance is highly instruction-fragile and not tied to capability.*

A fully automated, logged, decision-theoretic benchmark for side-effect avoidance: agents choose between killing an animal for free or paying fuel to avoid it while completing a harvest task. Two-tractor gridworld harvest task; rocks test competence, animals test side effects; varies briefing (moral vs neutral), avoidance price, and animal type; computes kill rates from actions (no LLM-judge scoring). Kill rates span ~0.4%–98.8% and are not monotonic with model strength; moral briefings keep most reasoning models <~6% kills, but neutral briefings push all >84%; models kill wild animals more than farmed, and small prompt changes can override the moral instruction.

Field Overview

Today’s batch is dominated by LLM agents + evaluation/infra work: at least ~25–30 papers touch agent definitions, long-horizon resilience/memory, multi-agent coordination, tool-use workflows, and agent benchmarking/auditing (e.g., resilience under accumulating challenge, update admission, incident registries, runtime harnesses, MCP/tool ecosystem sampling, reward-integrity instrumentation). A second major cluster is “trustworthiness” for LLMs—uncertainty/calibration, privacy, unlearning, hallucination, prompt-injection/security, and bias/low-resource language robustness—at least ~15–20 papers (e.g., privacy-utility in interactions, unlearning audits, prompt-injection detection, cultural bias from prompt revision, Urdu weaknesses, domain hallucination detection). Generative modeling is also heavily represented, especially diffusion/flow-matching control and efficiency (LoRA rank tradeoffs, DiT control via activation flow, schedule design, physical consistency eval, video reasoning) with ~8–12 papers. A notable emerging direction is “LLMs for formal/verified reasoning and deterministic correctness” (Lean verification loops, machine-checked proofs, deterministic math solvers, solver-informed distillation) plus multiple OR/optimization-via-LLM papers (~6–10), suggesting a push from fluent reasoning toward verifiable, tool-grounded reliability.