

Multilingual NLP

When the API Speaks the Wrong Language: Revisiting Post-Training for Multilingual Tool Use [\[arxiv\]](#)

Siddharth Chauhan, Thomas Butler, Abhishek Singhania, Pankaj Porwal, Honey Gupta

Multilingual tool use often fails because API arguments come out in the wrong language; targeted SFT fixes most of it, with RL adding small gains.

Defines and measures Argument Language Mismatch (ALM)—correct tool, semantically correct args, wrong/inconsistent language—and shows that explicit supervised post-training largely resolves it, challenging the assumption RL is required. Build a multilingual function-calling eval where success requires language-consistent arguments; compare SFT vs RL variants (including argument-aware rewards) and analyze “holding tool selection constant” to isolate argument-language improvements. SFT substantially improves argument language consistency and end-to-end call accuracy, often matching/beat RL when tool choice is controlled; RL (e.g., structured/GRPO-style rewards) yields incremental benefits mainly in harder generalization/multi-objective settings.

Language-Conditional Dequantization: Recovering What Quantization Steals from Non-English Languages [\[arxiv\]](#)

Nirmal Thomas

Aggressive quantization hurts non-English far more than English, but tiny per-language LoRA patches can recover most of the loss.

Shows INT3 GPTQ on ~3B LLMs disproportionately degrades non-English (especially non-Latin scripts) and introduces Language-Conditional Dequantization (LCD): per-language low-rank adapters that compensate quantization error post hoc. Start from an INT3-quantized model (e.g., Qwen2.5-3B, Llama-3.2-3B); train rank-2 LoRA adapters per language on that language’s text (~0.12% params/language, <20 minutes/GPU). Select adapter by input language at inference; analyze layer-localization of quantization damage. Non-English sees 2–4 $\times$ larger perplexity degradation than English under INT3; LCD closes ~70–83% of the non-Latin perplexity gap and recovers ~17–28% of the GlobalMMLU accuracy gap. Language-conditioned adapters beat language-agnostic fixes by ~3–9 points on distant languages; early-layer damage is harder to patch than late-layer damage.

Better Decomposition, Free Aggregation: A Synthesizer-Folding Framework for Multilingual Multi-Hop Question Answering [\[arxiv\]](#)

Yilin Wang, Yuchun Fan, Weidong Bao, Zili Wei, Shi Feng, Tong Xiao, Zhengtao Yu, Jingbo Zhu

Multilingual multi-hop QA can avoid translation-by-default by translating only when the model’s decomposition is unreliable.

Syfer reframes translation as a gated fallback in multilingual multi-hop RAG: attempt native-language decomposition/answering first, and switch to an English-assisted path only when decomposition quality is predicted to be poor. Generate a structured sub-question graph (“synthesizer”) with format constraints; run a decomposition-quality check. If pass: retrieve-and-answer in the target language and aggregate along the graph. If fail: translate with bilingual graph alignment and “fold” cross-lingual intermediate results back into a target-language answer. Across multiple languages, Syfer maintains competitive accuracy while reducing unnecessary translation/compute; results support that translation can add noise/erase cues, but is valuable as a targeted rescue when decomposition is weak, and that structured decomposition + checks reduces cascading multi-hop errors.

Structural Silence: When AI Infrastructure Fails Speakers of Underrepresented Languages [\[arxiv\]](#)

Avijit Roy, Proma Roy

Underperformance in underrepresented languages is often an upstream infrastructure problem, not just a modeling problem—shown via a Bengali end-to-end audit.

Recasts “low-resource” as structural silence across the pipeline (web presence, corpus sampling, tokenization, connectivity), arguing these compounding defaults create predictable inequity that model scaling alone won’t fix. Bengali case study quantifying: (1) web content share vs speaker share, (2) token allocation in major multilingual corpora, (3) tokenizer token-fertility penalties for Bengali script,

and (4) rural/urban connectivity gaps affecting real access to cloud AI tools. Bengali is <0.5% of web content despite ~4% of global population; major corpora show ~67:1 English:Bengali token deficit, worsened by higher tokenization fertility; low rural connectivity further blocks deployment—implying equity requires data priorities, tokenizer design, and offline-first delivery, not just bigger models.

Poly-Dialectal Neural Machine Translation System for Bangla Regional Dialects [\[arxiv\]](#)

Rakib Ullah, Ruhul Islam Rahul, Tanbir Ahmed

A single dialect-aware Bangla NMT model can translate among many regional dialects with little data, outperforming much larger multilingual baselines.

Builds a poly-dialectal, multi-directional Bangla dialect translation system and releases a large multi-dialect parallel corpus (51,531 sentence pairs), including expert-verified bidirectional data for five previously uncovered dialects. Fine-tune a BanglaT5-style seq2seq model for many dialect-pair directions; use DoRA (weight-decomposed low-rank adaptation) for parameter-efficient specialization; study cross-dialect transfer and scaling vs data size; demonstrate INT8 quantized web deployment. BanglaT5+DoRA reaches 29.26 BLEU / 57.26 chrF++ and outperforms NLLB-200 (615M) and mBART-50 (611M) on dialectal Bangla with better morphological coherence; scaling/transfer analyses suggest dialect coverage depends more on the right parallel signal than model size.

BavGround: A Benchmark for Regional Cultural Grounding and Dialect Competence in Bavarian [\[arxiv\]](#)

Jophin John, Michael Hoffmann, Jan Fillies, Michael A. Hedderich, Barbara Plank

BavGround enables protocol-aware testing of Bavarian dialect and regional cultural grounding, revealing consistent drops vs English/standard German and sensitivity to scoring method.

Introduces BavGround: 206 MCQ items $\times$ 3 languages (English/German/Bavarian) = 618 parallel instances across 8 cultural domains, designed to disentangle dialect difficulty from question difficulty and to test localized, source-grounded knowledge. Evaluate 15 open-weight instruction-tuned LLMs (7B–10B) plus one closed reference across all three language versions; compare multiple MCQ scoring protocols (letter, shuffled, option likelihood, parsing, semantic matching) to quantify protocol effects; exploratory checkpoint analysis for GENBA-10B. Scores drop when questions are in Bavarian and when they require localized source-grounded knowledge; evaluation protocol can materially change absolute scores and model rankings (notably for regionally adapted models). Continued pretraining can help some likelihood-based metrics but dialect competence remains comparatively weak.

Multilingual Speech Processing

DonorRank: Donor Language Selection for Low-Resource Cross-Lingual Speech Recognition [\[arxiv\]](#)

Akriti Dhasmana, Aarohi Srivastava, David Chiang

Donor-language choice for low-resource cross-lingual ASR can be learned as a ranking problem and beats common heuristics.

Proposes DonorRank, a learning-to-rank model that predicts which high-resource donor languages transfer best to a target language, emphasizing donor selection is conditional on the available donor pool (not a single rule like “closest language”). Train a ranker over (target, donor) pairs using relationship/resource features and a learning-to-rank objective; outputs an ordered donor list (not just top-1) to match practical “try top-k donors” workflows and enable feature analysis. On two multilingual speech corpora (Indic and African families), DonorRank improves donor selection over similarity-only or resource-only heuristics and shows which cues dominate depends on the donor set composition.

LLM Evaluation

Jagged Judges: Epistemic Stability Under Silence, Pressure, and Persistence [\[arxiv\]](#)

Justin Zhao, Himaghna Bhattacharjee, Hannah Korevaar, Bhaktipriya Radharapu, Khalid El-Arini

LLM judges are highly unstable under rephrasing and pushback, and mind-changes usually move them away from the correct

label.

Introduces the Wiggle Framework to evaluate judges as interactive systems, separating (i) prompt sensitivity, (ii) one-shot susceptibility, and (iii) multi-turn persuasion—showing that “gold-set accuracy once” misses key reliability failures. Probe the same judgment across three regimes: Mechanical Consistency (rewording), Single-turn Conviction (one opposing challenge), and Multi-turn Persistence (sustained dialogue with an adversarial LLM persuader). Tested 9 frontier models on 14 judging tasks; uses initial panel agreement (“jury majority strength”) to predict likely flips. Verdicts flip ~25–71% under single-turn pushback and ~62–91% under adversarial multi-turn persuasion; flips are typically net-corrupting vs ground truth, implying interactive pressure behaves like rhetorical capture rather than helpful deliberation.

Field Overview

Today’s batch is dominated by foundation-model “systems” work rather than new standalone architectures: at least ~25–35 papers on agentic workflows (AI scientists, long-horizon tool use, multi-agent orchestration) plus the infrastructure they require (memory, harnesses, routing, provenance, evaluation). A second major cluster is retrieval/RAG and memory for agents—roughly ~20 papers on multi-hop retrieval, stopping policies, embedding/retriever design, poisoning detection, caching, and long-term memory consolidation (e.g., Search-R1 stopping, GEM, RAGSieve, multiple “memory” benchmarks). Safety/trustworthiness/evaluation is similarly heavy (~20+): refusal robustness, uncertainty/calibration, benchmark contamination/wording effects, judge reliability, watermarking, political/cultural bias, and cross-lingual safety failures. A striking surprise is how large the audio/speech/music track is relative to typical days—well over 150 titles on TTS/ASR/audio LLMs, audio generation, deepfake detection, and audio benchmarks—suggesting a strong surge in “omni-modal” and speech-first agent directions alongside the usual LLM agent + RAG focus.