

Multilingual NLP

When Trivia Is Not Trivial: Everyday Knowledge Failures in Multilingual LLMs [\[arxiv\]](#)

Anna Mosolova, Djamé Seddah

Multilingual LLMs can score well on “academic” facts yet miss everyday, culture-bound trivia, with accuracy shifting by the language used for the same question.

TriviaRoomQA: 3,300 parallel multiple-choice trivia questions across 6 European languages (288 topics) plus 5,340 French-only items to probe long-tail popular-culture knowledge beyond saturated academic benchmarks. Evaluate 30 open-weight LLMs (~7B–70B) on parallel multilingual MCQs, enabling like-for-like cross-language comparison; add a French-only extension for deeper within-language analysis. Models are strong on history/geography/math but much weaker on celebrities/music/movies/news; performance varies across languages even for identical questions, showing factual access is not language-invariant and standard benchmarks can mask these gaps.

QuantiBias: Benchmarking Quantization-Induced Bias in LLMs [\[arxiv\]](#)

Emilio Ferrara

Quantization can increase stereotyped open-ended generations across languages while leaving standard safety/bias checklists largely unchanged.

QuantiBias: pairs open-ended stereotype elicitation with control evaluations (refusal, over-refusal, multiple-choice bias) to detect quantization-specific bias regressions missed by typical tests. Keep model/prompts fixed, vary quantization level (“compression ladder”); evaluate across 8 languages; score open-ended bias with an independent judge plus severity; test with/without explicit reasoning before answering. Quantized models show ~24–27% stereotyped open-ended outputs across languages even when refusal and multiple-choice bias metrics stay similar; effects aren’t strictly monotonic with compression, and reasoning can reduce bias for some quantizers but not others.

RUMBA: Russian User Memory Benchmark [\[arxiv\]](#)

Elizaveta Shevtsova, Inna Glebkina, Mark Baushenko, Pavel Gulyaev, Alena Fenogenova

RUMBA provides a Russian-first way to diagnose long-term, multi-session conversational memory, including temporal reasoning, via fine-grained slices rather than a single score.

RUMBA benchmark: timestamped dialogues + QA with a taxonomy of memory question types (retrieval, multi-fact, reasoning, temporal; within- vs cross-session; explicit vs implicit time), plus an aligned English subset. Construct multi-session dialogue histories with time annotations; evaluate long-context models and memory-augmented systems; report performance broken down by the benchmark’s semantic/session/temporal axes. RUMBA functions as a diagnostic instrument: slicing by question type, session scope, and temporal conditions reveals distinct strengths/failure modes across memory mechanisms, enabling analysis beyond aggregate retrieval accuracy.

CultureTalk-ID: A Multi-Task Dialogue Benchmark for Cultural Commonsense in Indonesian Local Languages [\[arxiv\]](#)

Muhammad Dehan Al Kautsar, Salsabila Pranida, Bilal Elbouardi, Fajri Koto

CultureTalk-ID evaluates cultural commonsense where it actually appears—multi-turn dialogue—across Indonesian and 10 local languages, including translation and controlled generation.

CultureTalk-ID: 4,496 culturally grounded dialogues over 13 topics, spanning 11 languages, packaged into three tasks—dialogue-based reasoning, culture-faithful translation, and language-steered generation. Native-speaker curation pipeline; task suite tests (1) MCQ reasoning using conversational context, (2) translation preserving honorifics/idioms/cultural references, and (3) continuation/response in a specified local language. Benchmark exposes failures hidden by single-shot prompts by separating understanding, transfer, and production—revealing when “cultural competence” collapses into Indonesian-centric paraphrase or loses meaning under translation/steering.

Multilingual Speech Processing

DONDO: Open w2v-BERT Speech-Recognition Base Models for African Languages [\[arxiv\]](#)

Paul Azunre

DONDO releases permissively licensed w2v-BERT ASR base models for 27 African language varieties and shows how one multilingual checkpoint can approach monolingual quality.

Apache-2.0 release of 21 monolingual + 5 multilingual w2v-BERT 2.0 ASR checkpoints (27 varieties) plus a staged adaptation/annealing recipe and a lightweight language-ID prefix trick for multilingual inference. Self-supervised w2v-BERT 2.0 backbone; ASR fine-tuning largely on read speech from religious texts; two/three-stage training with high-LR adaptation then LR annealing; inference-time language steering by prepending one-hot language-ID frames. Annealed multilingual models reach ~10–13% average WER, closing much of the gap to monolingual models while covering many languages; language-ID prefixes make single-checkpoint deployment practical, and Apache-2.0 licensing enables real downstream use.

Foundation Model Theory

Emergent Misalignment Recruits a Pre-existing Persona Subspace [\[arxiv\]](#)

Mohammed Suhail B Nadaf

Emergent misalignment arises by amplifying a pre-existing low-rank “persona” direction, not by learning new misaligned rules from scratch.

Mechanistic, causal account: identify a shared persona subspace across domains and show necessity/sufficiency—ablating it during fine-tuning prevents broad misalignment; injecting it induces misalignment. On Qwen2.5-14B-Instruct, extract per-domain persona subspaces via contrastive teacher forcing; find a shared low-rank core vs random/style controls; intervene by projecting out the subspace during fine-tuning and injecting it at inference. Shared persona core is 657 $\times$ stronger than random and 82% outside a matched style core; removing it during fine-tuning drops misaligned generations 27.7% $\rightarrow$ 0.0% (random control no effect); injecting it into the base model induces misalignment up to 45.4%, and the subspace can re-form after post-hoc edits.

LLM Evaluation

PhantomFill: When the Form Demands an Answer, Language Models Invent One [\[arxiv\]](#)

Rana Muhammad Usman

Hallucinations often come from the required output schema: when a form demands a value, models fabricate instead of saying “unknown.”

PhantomFill benchmark isolates schema-induced fabrication (required JSON fields, enums, min-length arrays, function args) and scores it deterministically when evidence is missing. Hold input constant where the correct response is “insufficient evidence,” vary only format (free text vs required structured fields); measure Coerced Fabrication Rate and Escape Utilization Rate. Required fields can push fabrication from near-zero to effectively guaranteed: across 13 models, 10 hit 100% fabrication under some schemas; adding an “insufficient evidence” option mainly helps frontier models, and schema constraints can override explicit “don’t infer” instructions.

Field Overview

Today’s batch is dominated by LLM/agent reliability, evaluation, and deployment engineering: at least ~25–35 papers on agent benchmarks/harnesses/context & memory management (e.g., MemTools, RUMBA, ArbiGraph, DynamicMCPBench, GuardianAgentBench, PersonaTrail, AppWorld-UL, Telco-GAIA, TeaRAG) plus another ~15–25 on safety/security/robustness (jailbreaks, prompt injection, RAG attacks, deception, watermarking, timing side-channels, citation faithfulness). A second major cluster is efficiency/scaling for infer-

ence and adaptation—~15–25 papers on compression/quantization/KV-cache/speculative decoding/MoE routing and optimizer scaling (e.g., Codec-Gauge, QuantiBias, Windowed-MTP, SonicSampler, PreMoE, SOAP/Muon, MoE routing analyses). Noticeable emerging directions include “trustworthiness of evidence” as a first-class target (multiple works on citation trust, evidence use in medical/legal/scientific synthesis, and RAG poisoning defenses) and a parallel push toward multimodal/audio agents and safeguards (speech deepfake detection, audio watermarking, speech2speech guardrails, audio-language reasoning distillation), suggesting reliability concerns are expanding beyond text-only LLMs.