

Multilingual NLP

Code-Switching Reveals Language Anchoring in Multilingual LLMs [\[arxiv\]](#)

Jeonghyun Park, Seunghyun Yoon, Yonghyun Jun, Hwanhee Lee

Code-switched QA fails because multilingual LLMs “anchor” their hidden states to one language frame; this anchoring is measurable and can be corrected at inference to recover F1.

Defines Anchor Bias, a geometric diagnostic linking internal language anchoring to code-switching degradation, and shows anchoring is a controllable failure mode rather than just data coverage noise. Create controlled, grammar-forced code-switched inputs; compute Anchor Bias by comparing code-switched hidden states to monolingual source/target counterparts; apply CANVAS steering during prefill to nudge states toward the source anchor direction. Across models, source-framed code-switching stays source-anchored and degrades less, while target-framed shifts target-ward and degrades more; CANVAS consistently restores QA F1 without retraining.

Enhancing Multilingual Reasoning via Steerable Model Merging [\[arxiv\]](#)

Zhuoran Li, Rui Xu, Jian Yang, Junnan Liu, Zhijun Chen, Qianren Mao, Hongcheng Guo, Jiaheng Liu, Likang Xiao, Ming Li, Xiaojie Wang

Steerable model merging adaptively blends a multilingual model and a reasoning model per input, improving multilingual reasoning over fixed merges.

ST-Merge addresses conflicts in standard merges by making the mixture input-dependent, so different queries can lean more on multilingual competence or reasoning skill as needed. A gated cross-attention module attends to signals from both source models and gates their contributions, producing a context-appropriate blend instead of a single static parameter merge. On four multilingual reasoning benchmarks covering 21 languages, ST-Merge consistently outperforms strong merging baselines, showing steerability yields better cross-lingual reasoning.

REDACT: A Systematically Controlled Multilingual Benchmark for Personal Information Detection [\[arxiv\]](#)

Guneesh Vats, Anubha Agrawal, Shikha Singhal, Ajita Dash, Praisson Selvaraj, Vidhan Jhavar, Ranga Prasad Chenna, Bharadwaj Y M G

REDACT is a controlled multilingual PII benchmark that varies “surface conditions” so you can pinpoint which contexts and disclosure forms break detectors, especially for high-sensitivity PII.

Introduces a designed (not scraped) benchmark spanning 25 languages/9 scripts with explicit control over conditions that drive PII failures, plus metadata to evaluate risk by disclosure form and GDPR-aligned sensitivity, not just entity type. Generate texts via a schema with nine axes (e.g., domain, density, code-switching, adjacency); use a strength-2 covering array to cover all pairwise condition combinations; annotate entities with disclosure status, disclosure form, and sensitivity tier. Evaluations show aggregate F1 can hide dangerous gaps: rule-based detection has extremely low recall on HIGH-sensitivity and non-verbatim disclosures, while LLM-based detectors are more robust; sensitivity-tier assignment is itself hardest, validating stratified evaluation.

When English Isn’t the Best Teacher: Source Language Effects in Cross-Lingual In-Context Learning [\[arxiv\]](#)

Fred Philippy, Siwen Guo, Jacques Klein, Tegawendé F. Bissyandé

In cross-lingual in-context learning, the “best source language” heuristics from fine-tuning often fail, and language confusion becomes a key blocker for generative tasks.

Large-scale evidence that supervised transfer predictors don’t reliably forecast cross-lingual ICL success, reopening source-language selection as an ICL-specific problem and highlighting language confusion as a practical failure mode. Systematic study varying tasks, models, and demo/eval language pairs: 7 tasks $\bowtie$ 6 multilingual models $\bowtie$ diverse languages; measure both task performance and language confusion (wrong/mixed output language). Fine-tuning-era rules of thumb do not consistently transfer to ICL; language confusion recurs, especially for generation, motivating new ICL-tailored heuristics for choosing demonstration languages.

Multilingual Speech Processing

UR-BERT: Scaling Text Encoders for Massively Multilingual TTS Through Universal Romanization and Speech Token Prediction [\[arxiv\]](#)

Sangmin Lee, Eekgyun Ahn, Woongjib Choi, Hong-Goo Kang

A single TTS text encoder can scale to hundreds of languages by Romanizing all scripts into one space and training the encoder to predict speech tokens, learning pronunciation without per-language G2P.

UR-BERT removes the main long-tail bottleneck in multilingual TTS—missing G2P/lexicons—via universal Romanization plus a speech-grounded objective, yielding one reusable encoder that transfers even to unseen languages. Map all input text to a shared Romanized form; train a BERT-like encoder with standard text objectives plus an auxiliary task that predicts discrete speech tokens from paired audio, forcing phonetic/alignment-relevant representations. Plugged into multilingual TTS, UR-BERT beats strong text-encoder baselines across languages and data regimes (notably low-resource) and generalizes to unseen languages, showing Romanization + speech-token prediction scales phonetic fidelity.

IndicContextEval: A Benchmark for Evaluating Context Utilisation in Audio Large Language Models Across 8 Indic Languages [\[arxiv\]](#)

Sakshi Joshi, Dhruv Subhash Rath, Sanskar Singh, Eldho Ittan George, R J Hari, Kaushal Bhogale, Mitesh M. Khapra

IndicContextEval tests whether AudioLLMs truly use provided text context (including wrong context) rather than just transcribing, across 8 Indic languages.

A benchmark that treats context as an intervention: by including adversarial incorrect entity prompts, it can distinguish context-following from context-ignoring behavior, which standard ASR accuracy can't reveal. ~56 hours of natural speech from hundreds of speakers; evaluate with a 7-level prompting ladder from minimal hints to rich metadata and entity lists (English/native script), plus adversarial prompts with incorrect entities; compare transcript shifts across prompt levels. Across five AudioLLMs, context sensitivity varies widely; adversarial prompts expose whether models are controllable (pulled toward provided entities) or largely invariant, showing single-prompt accuracy can mask lack of context utilization.

Foundation Model Theory

Output Vector Editing for Memorization Mitigation in Large Language Models [\[arxiv\]](#)

Ahmad Dawar Hakimi, Kaiwei Lei, Isabelle Augenstein, Hinrich Schütze

Mitigate memorization by editing a few MLP neurons' output vectors (what they write into the residual stream) instead of zeroing activations, sharply reducing regurgitation with less collateral damage.

Proposes output-vector editing as a more surgical privacy mitigation: redirect neuron write-directions that drive memorized continuations, and characterizes a boundary where some memorization requires attention-based interventions. Mine memorized sequences (notably on open OLMo-7B); attribute continuations to a small set of MLP neurons; solve a constrained optimization to minimally edit only those neurons' output vectors to steer away from memorized next tokens; for failures, ablate key attention heads. Across 360M–7B models (incl. OLMo-7B, Llama2-7B), achieves up to 87.9% suppression and 2.7 $\times$ better than activation ablation; an edit-mode ensemble covers 96.5% (single mode 81.5%); ~14% need attention-head ablation, recovering 60–64% of those cases.

Field Overview

Today's submissions are dominated by LLM agent systems and their deployment realities: at least ~25 papers on tool-using/long-horizon agents (memory systems like AtomMem/CoreMem/GateMem, multi-agent coordination/leadership, agent benchmarks like CEO-Bench/EComAgentBench/ORAgentBench, and agent governance such as prompt-injection defenses and policy-aware control planes). A second major cluster is inference/training efficiency for large models (roughly ~15 papers) spanning KV-cache/speculative

decoding/quantization (UltraQuant, JetFlow, token-ops optimization) and long-context attention variants (HydraHead, ConSA, Dual Dimensionality, Variable-Width Transformers). Safety, evaluation, and reliability is another heavy theme (15–20): LLM-as-a-judge validity/bias, calibration/uncertainty, privacy & memorization/unlearning, and red-teaming/jailbreak/pseudoscience resistance (PseudoBench, FFinRED, Anthropic red-team). The most surprising concentration is sheer volume in speech/audio foundation models and audio-language systems (well over 100 titles) covering full-duplex spoken agents, TTS/voice conversion, watermarking/deepfake detection, multilingual/low-resource ASR, and clinical speech biomarkers—suggesting “audio-first agents” and audio forensics are rapidly heating up alongside text-centric agent work.