

Multilingual NLP

Language Models are not Equally Robust to Non-Canonical Tokenization across Languages [\[arxiv\]](#)

Poulami Ghosh, Preethi Jyothi

Equivalent re-tokenizations of the same string can sharply degrade LLM performance in many languages; training on multiple tokenizations improves robustness.

Shows “tokenization invariance” is not multilingual: across 27 languages, non-canonical (but text-identical) tokenizations cause large, systematic drops tied to tokenizer fragmentation; proposes a simple LoRA + multi-tokenization augmentation fix that transfers cross-lingually. Generate alternative token sequences that decode to the exact same text as the canonical tokenizer output; evaluate instruction-tuned LLMs on 6 tasks while holding decoded text constant; relate drops to per-language token fragmentation; LoRA fine-tune on examples augmented with diverse tokenizations and re-evaluate. Average relative performance drops under non-canonical tokenization are large (23.7% Llama-3.1-8B, 11.4% Qwen3-8B, 9.9% Gemma-3-12B), worst in highly fragmented languages; LoRA on multi-tokenization data reduces the gap, with systematic diverse sampling best, and even English-only robustness training can generalize.

DenseOn with the LateOn: Fully Open Dense and Late-Interaction Models for Multilingual, Long-Context, and Code Search [\[arxiv\]](#)

Raphaël Sourty, Antoine Chaffin, Paulo Roberto Moura Junior, Amélie Chatelain

With fully open data/code, late-interaction retrieval matches strong English results and transfers to unseen languages/scripts better than single-vector dense retrieval.

Rebuilds a large-scale, end-to-end open retrieval pipeline and trains matched-scale dense (DenseOn) and ColBERT-style late-interaction (LateOn) models; cleanly demonstrates that late interaction is more robust beyond translate-trained languages, revealing an architectural advantage for multilingual transfer. Pretrain on hundreds of millions of public contrastive query–doc pairs; supervised fine-tune with hard negatives; train DenseOn (single embedding) vs LateOn (token-level late interaction) under matched supervision; multilingual study via translate-train into 8 languages on the same mmBERT-base backbone (mDenseOn vs mLateOn). On BEIR, both open models are top-tier for their size (LateOn slightly better); in multilingual evaluation, dense retrieval degrades much more outside translate-trained languages, while late interaction remains stronger on unseen languages and even unseen scripts, consistent with more language-agnostic token-level matching.

DialectLLM: A Dialect-Aware Dialog[ue] Generation Framework Beyond Standard American English [\[arxiv\]](#)

Jio Oh, Paul Vicinanza, Thomas Butler, Steven Euijong Whang, Dezhi Hong, Amani Namboori

Dialect-aware assistants need dialect-parallel dialogue and an asymmetry rule: understand user dialect, but usually don’t mirror its grammar in assistant replies.

Creates DialectLLM, a linguistically grounded framework to generate high-quality dialogues in 9 English dialects by controlling lexical, orthographic, and morphosyntactic features; finds assistant-side grammatical mirroring is often unnatural; releases DialectLLM-Bench to expose persistent model failures. Start from SAE dialogues and apply linguist-designed/validated transformations across vocabulary, spelling, and grammar; crucially apply morphosyntax asymmetrically (user uses dialect grammar; assistant stays mostly neutral with selective markers); human preference studies plus benchmarking on dialect ID and response appropriateness. Humans prefer DialectLLM dialogues for dialect naturalness in 98.8% of pairwise comparisons; assistant responses should avoid up to ~90% of dialect morphosyntactic features; DialectLLM-Bench (50k+ dialogues, 97k+ QA) shows 17 LLMs still <70% dialect ID accuracy (and <50% on some dialects), often collapsing dialects into “American/British.”

ML2B: Benchmarking LLMs on Cross-Lingual ML Pipeline Generation [\[arxiv\]](#)

Ekaterina Trofimova, Zosia Shamina, Maria Selifanova, Artem Zaitsev, Remi Savchuk, Maxim Minets, Daria Ozerova, Emil Sataev, Denis Zuenko, Andrey E. Ustyuzhanin

ML2B shows multilingual ML-pipeline code generation fails in task-specific ways; “good in language X” can’t be inferred from generic multilingual scores.

Introduces a realistic cross-lingual benchmark for end-to-end Kaggle-style pipeline generation: 35 competitions translated into 14 languages with integrity controls (private comps, network-isolated execution) to measure true task understanding and runnable pipeline construction, not memorization. Native-speaker ML-aware translations of competition specs; evaluate generated code by executability and achieved scores under a standardized protocol; include AutoGluon baseline; use private competitions and network isolation to reduce leakage; categorize failures into code bugs vs task misunderstanding. Cross-lingual degradation is not monotonic with language “resource level”; performance swings heavily by competition/task, with some language–task pairs holding up and others collapsing, implying bottlenecks often come from pipeline decision-making (data/metric/preprocessing/leakage) rather than general multilingual fluency.

Multilingual Speech Processing

Prosody-driven Jailbreaks in Audio LLMs: A Controlled Study and Mechanistic Analysis [\[arxiv\]](#)

Jiachen Qian, Junyu Li

Audio LLMs can be jailbroken by prosody alone—same words, different delivery—so transcript-only safety checks miss a major attack channel.

Defines and measures “prosody-only” jailbreaks: paralinguistic cues (panic/anger/fast/authority) can drive policy violations without changing text; introduces PJ-Break protocol and AdvAudio-Prosody (600 verified samples) to cleanly separate content from delivery and enable reproducible testing. Keep a fixed jailbreak transcript and render it in six controlled delivery presets; evaluate jailbreak success in a black-box setting (PJ-Break); build AdvAudio-Prosody with acoustic QC verifying intended prosodic changes; run ablations (same-voice pool, audio emotion vs emotional wording) to rule out confounds. On Qwen2-Audio, neutral delivery yields 4/95 successes, while Panic/Anger/Fast reach 38/95, 35/95, 32/95; the 6-query pool succeeds on 44/95 Qwen2-Audio seeds and 15/95 GPT-4o seeds, beating a matched-budget StyleBreak reimplementation (27/95) on Qwen2-Audio; emotional delivery audio (44/95) far outperforms emotional text alone (11/95).

Dissecting Sensitivity to Training Language in Self-Supervised Speech Learning Using Neural Audio Codec Tokens

[\[arxiv\]](#)

Daigo Takizawa, Tomohiko Nakamura, Samuele Cornell, William Chen, Satoru Fukayama, Shinji Watanabe

In codec-token SSL speech models, codec training language matters little; SSL pretraining language drives most cross-lingual sensitivity.

Disentangles where language dependence enters codec-token pipelines by independently varying codec training language vs SSL pretraining language; shows the codec is largely language-agnostic while the SSL stage learns language-specific structure that governs transfer. Two-stage controlled swaps: train codecs on different languages with SSL pretraining fixed, then fix the codec and vary SSL pretraining language; evaluate downstream tasks to attribute performance changes to codec vs SSL components. Swapping codec training language yields minimal downstream change, but swapping SSL pretraining language causes large, consistent shifts—implying one shared codec can be reused broadly, while multilingual robustness mainly requires aligning/adapting SSL pretraining data.

Foundation Model Theory

Steering Instruction Hierarchies at Inference Time [\[arxiv\]](#)

Siqi Zeng, Sewoong Lee, Han Zhao, Julia Hockenmaier

Instruction hierarchy (system > user) can be enforced at inference time by editing a few attention value vectors—no retraining required.

Proposes V-Steer, a mechanistic, training-free fix for role-conflict failures: identify attention heads where lower-priority spans dominate logit contributions, then reweight cached value (V) vectors so privileged instructions regain causal influence. After prefill, run head-wise direct logit attribution for the first next-token prediction to detect hierarchy-violating heads; apply in-place multiplicative edits to KV-cache V tensors at prompt positions (boost system/developer spans, suppress conflicting user/tool spans) only for those heads; minimal

overhead and compatible with fused attention. Primary constraint accuracy rises from $< \sim 18\%$ to as high as $\sim 92\%$ on role-conflict benchmarks, consistent across 7B–70B models; outperforms prompt-only baselines and is competitive with training-based fixes while adding negligible decoding-time cost.

LLM Evaluation

BayesAME: Bayesian Active Model Evaluation [\[arxiv\]](#)

Paula Cordero Encinar, Taylan Cemgil, Arnaud Doucet, Virginia Aglietti, Silvia Chiappa

BayesAME cuts benchmark cost by actively selecting items and stopping once uncertainty is low, using priors from historical model results.

Recasts evaluation as sequential Bayesian inference with automatic coreset sizing: leverage correlations with past models as a prior, choose the next most-informative items, and stop when estimates stabilize—yielding cheaper yet uncertainty-aware evaluation. Cluster items by historical behavior; place a correlated prior over group “abilities” for the new model; sequentially pick items via expected information gain, update the posterior with observed scores (optionally using continuous signals like log-likelihood), and stop when stability + uncertainty thresholds are met; extend to jointly evaluating multiple new models. Achieves target accuracy/confidence with fewer evaluated items than sequential baseline methods; active (non-random) selection reduces uncertainty faster; using continuous signals (e.g., log-likelihood) further improves sample efficiency, making evaluation both cheaper and more statistically explicit.

Field Overview

Today’s batch is dominated by LLM agents + evaluation/safety work: at least ~ 25 – 35 papers on agentic systems (interfaces like AgentGUI, long-horizon task benchmarks like TREK/OmegaUse-OfficeVal/SecRespond, multi-agent debate/coordination, and workflow optimization/cost-aware tool use), with a particularly strong subcluster on agent memory (filesystem/graph memory stores, Forget-Bench/IFCMemoryBench, memory poisoning like MemSecBench, and RAG+memory hybrids like CMT-RAG). Retrieval-Augmented Generation is another clear hotspot (at least ~ 10 – 15 papers) spanning scaling studies (“Which RAG Paradigm Wins at Scale?”), evidence coverage/uncertainty, poisoning defenses (RAGuard), and enterprise serving/caching (FinCacheServe), suggesting the field is shifting from “does RAG help?” to “how do we make it reliable, economical, and attack-resistant?”. Safety/alignment and adversarial robustness form a second major pillar (at least ~ 15 – 25 papers) including red teaming/jailbreaks (GPT-Red, prosody-driven audio jailbreaks), bias audits (regional/gender/disability), backdoors/poisoning detection (ToxScreen, Lilith), and multi-turn/state-dependent safety risk forecasting. A notable emerging direction is audio-first foundation modeling and audio security (roughly ~ 10 – 15 papers): full-duplex speech agents/ASR, audio deepfake/forgery detection, and music generation/detection benchmarks (MMAC, Qwen-Audio-3.0), indicating multimodal safety is expanding beyond vision into speech/music.