

Multilingual NLP

MameLoshnLM: Yiddish Language Model and Evaluation Benchmark [\[arxiv\]](#)

Uri Katz, Omer Goldman, Tomasz Limisiewicz, Reut Tsarfaty, Noah A. Smith

Clean, language-faithful Yiddish data plus targeted continued pretraining beats relying on noisy “multilingual web” signal for true Yiddish competence.

Releases a full Yiddish LM stack: MameLoshnLM (Llama 3.1 8B continued-pretrained), Oytser (curated Yiddish pretraining corpus), and Kashes (multi-task Yiddish benchmark). Diagnoses a key failure mode for low-resource languages: web-scale “multilingual” data is often misidentified/MT/noisy, teaching wrong lexical/morphological regularities. Continue pretraining Llama 3.1 8B on high-precision Yiddish (Oytser). Build Kashes to test translation plus morphology/syntax-sensitive tasks (analysis, IE, understanding). Compare to similarly sized open baselines and analyze whether learned patterns match Yiddish-specific morphology/lexicon. On Kashes, MameLoshnLM outperforms similar-scale open baselines across tasks and shows more Yiddish-faithful lexical/morphological behavior, supporting the claim that data fidelity (not just quantity) is decisive for low-resource multilingual training.

Different Perturbations, Different Mechanisms: Understanding Continued Pre-training for Zero-Shot Dialect Robustness [\[arxiv\]](#)

Aarohi Srivastava, David Chiang

Synthetic-noise continued pretraining improves zero-shot dialect robustness, but different perturbations work via different internal mechanisms.

Provides a controlled comparison of multiple perturbation-based CPT recipes and links similar accuracy gains to distinct mechanisms: some perturbations increase dialect–standard representational alignment (invariance), others improve input “repair” at prediction time. Continued pretraining of a multilingual LLM under six synthetic perturbation conditions (incl. character noise). Zero-shot evaluation on nine dialect tasks (German/Italian/Arabic) plus checks on standard-variety performance. Mechanism probes: representation alignment and behavioral signatures of invariance vs repair. Character-noise CPT is the most consistently beneficial, improving dialect task performance while largely preserving standard-language accuracy; analyses show comparable gains can arise from different internal adaptations, so perturbation choice should match the dialect shift type.

RP-OPSD: Reasoning-Pivot-Guided On-Policy Self-Distillation for Multilingual Reasoning Transfer [\[arxiv\]](#)

Xinye Wang, Junxiao Liu, Shujian Huang

Multilingual reasoning transfer improves when distillation targets the few trajectory-steering “pivot” decisions rather than all tokens equally.

Introduces RP-OPSD: on-policy self-distillation that detects reasoning pivots (subgoal/operation/state-update decisions) and concentrates teacher pressure there, reframing cross-lingual reasoning transfer as controlling key decisions, not supervising surface text. Student generates target-language rollouts. Two teacher views score the same rollout: one privileged with an English reference solution, one without. Tokens where the two teacher distributions diverge most are treated as pivots; distillation loss is upweighted on these tokens using the privileged view as anchor. Across math reasoning benchmarks in 17 languages, RP-OPSD beats strong multilingual reasoning baselines and prior OPSD objectives; gains track increased supervision on pivot-like tokens rather than language-specific surface realization.

Task-Conditional Flow Matching for Balanced Multilingual Text Embedding Adaptation [\[arxiv\]](#)

Tirth Bhatt, Naren Kumar S, Mayank Singh

Multilingual embedding adaptation improves when objectives are task-conditional and training is stabilized to preserve the base embedding geometry.

Proposes Task-Conditional Flow Matching (TCFM): use Flow Matching for translation-style distribution alignment, but different objectives for retrieval/classification/pair-classification. Adds teacher-guided representation preservation plus a staged curriculum to re-

duce drift/forgetting. Route training by task type: Flow Matching for translation alignment; standard task-appropriate losses for retrieval/classification variants. Regularize toward a teacher/base model to preserve geometry, and train in three stages from stable signals to harder multi-task mixing. On the Indic Massive Text Embedding Benchmark, TCFM improves performance broadly across multilingual embedding tasks without the usual tradeoffs; Flow Matching helps specifically for translation alignment, while teacher-preservation + curriculum make gains stable and general across model families.

Multilingual Speech Processing

FormBharo: Designing and Evaluating a Voice Agent for Conversational Form Filling in Rural India [\[arxiv\]](#)

Aman Dalmia, Sanskriti Midha, Jigar Doshi

A deployable Hindi phone voice agent can fill benefit forms reliably by combining LLM flexibility with strict rule-based control and end-to-end evaluation under real speech noise.

Builds and pilots FormBharo, a conversational form-filling voice agent for low-income Hindi-speaking mothers, and releases FormVoiceAgentBench for reproducible end-to-end evaluation under realistic acoustic variability. Argues pipeline-level evaluation is essential under latency/cost constraints and ASR errors. Phone-call, multi-turn dialogue to collect structured fields. LLMs handle understanding/generation, but deterministic validation + flow control enforce constraints and choose next questions. Evaluate components (ASR/IE/generation) and full form-completion; benchmark uses human-recorded Hindi audio and thousands of simulated calls. Using real ASR transcripts can reduce form completion by ~41 points vs clean transcripts; rule-based controls recover many extraction errors so smaller/cheaper models can match or beat frontier models on end-to-end completion. High turn-level IE (e.g., 99.8% on clean text) does not guarantee best overall completion; no model dominates accuracy/cost/latency, so they select via Pareto-style weighting.

Breaking the Curse of Multilinguality in Many-to-Many Speech-to-Text Translation via a Resource-Aware Mixture of Speech Encoders [\[arxiv\]](#)

Yexing Du, Kaiyuan Liu, Youcheng Pan, Bo Yang, Chengpeng Fu, Yu Wang, Ming Liu

Many-to-many speech translation can avoid low-resource “crowding out” by routing languages through a resource-aware mixture of speech encoders while protecting high-resource performance.

Introduces MSRT/MoSE: replace a single shared speech encoder with a routed mixture specialized by resource regime. Key design: a frozen expert preserves high-resource representations; a trainable expert adapts for medium/low-resource, reducing destructive interference without abandoning a unified multilingual system. Language router selects an encoder expert per utterance. One expert is frozen (high-resource anchor), another is trainable (adaptation capacity). Train with a five-stage curriculum to align speech/text with limited paired data, targeting effectiveness with ~10 hours paired S2TT per language. Across 45 languages and all 45E44 directions, the mixture-of-encoders improves low-resource performance while maintaining high-resource quality; the 4B model reaches SOTA and beats larger baselines, indicating the gain comes from reduced cross-lingual interference, not just scale.

Foundation Model Theory

Subliminal Learning is Non-Semantic Distillation [\[arxiv\]](#)

Ethan Hadley, Eren Gultepe

Subliminal learning transfers bias through non-semantic, weight-linked structure in synthetic data, and students can inherit both the bias and the intervention style that created it.

Shows subliminal transfer is not purely semantic: weight-level structure matters, and distillation can transmit the *mechanism* of bias induction (e.g., steering vs prompting). Expands the threat model by demonstrating steering vectors can generate subliminal data. Controlled distillation experiments varying bias source (prompting, fine-tuning, steering) and teacher/student weight structure. Add Gaussian noise to weights to test sensitivity. Analyze student activations after steered vs prompted subliminal data; test whether gradients from steered data align with teacher steering directions. Gaussian weight noise increases subliminal transfer (~1.9E Gemma, ~1.3E Llama), implicating non-semantic weight structure. Steering-generated subliminal data works, and students trained on it show

steering-like internal signatures; gradients correlate linearly with teacher steering vectors, suggesting an auditing/detection handle.

Field Overview

Today's list is dominated by LLM agent reliability and evaluation: at least ~25–35 papers on tool-using/long-horizon agents, skill libraries, and debugging/auditing (e.g., SearchAuditor, TRAJDEBUG, OrchestraBench, SkillTrace/SkillZip/SkillHEX/SkillMemo, DreamGuard, CodeGrep, “Bitter Lesson of Tool Calling,” prompt-side playbook transfer). A second major cluster is RAG and grounding—roughly ~10–15 papers on RAG failure modes, traceability, privacy/PII leakage, and neuro-symbolic/agentic retrieval (e.g., triple-robustness GraphRAG analysis, multilingual RAG privacy audit, NeSy-RAG, Align-RAG/TS-RAG, “Beyond Top-K” retrieval). There's also a strong safety/governance thread (~10+), spanning jailbreak/guardrails, sycophancy, double-blind review threats, unlearning/privacy filters, and agent authorization/zero-trust signing (e.g., Mood Matters jailbreaks, harmful sycophancy detection, GROM unlearning, AISPA prompt auditing, Hardware Keystores for agent signing). A notable emerging direction is “self-evolving” agents and on-policy self-distillation/post-training methods (~10–15) showing up across reasoning, multilingual transfer, and agent RL (OPSD/OPD variants, DASH, Hyper-ES, AgentOPSD, When Self-Evolution Backfires/Trajectory Poisoning), suggesting the field is shifting from static assistants toward continuously improving, auditable agent systems.