

Multilingual NLP

Reinforcement Learning Elicits Contextual Learning of Unseen Language Translation [\[arxiv\]](#)

Hanxu Hu, Zdenk najdr, Pinzhen Chen, Jannis Vamvas, Rico Sennrich

Reinforcement learning can teach an LLM a reusable “read the grammar in the prompt, then translate” skill for truly unseen languages.

Frames unseen-language translation with in-prompt linguistic descriptions as a meta-skill and shows RL elicits that strategy more reliably than SFT or vanilla in-context learning, which tend to memorize or ignore the description. RL over translation episodes where prompts include rich linguistic context (morphology/syntax/lexicon); reward is only final-output chrF, pushing the model to exploit the description to maximize outcomes across tasks. RL-trained models outperform strong ICL and SFT baselines on completely unseen languages despite a lightweight reward, with analyses indicating behavior shifts toward consistently using the provided grammar/vocabulary.

A Komi-Yazva–Russian Parallel Corpus and Evaluation Protocol for Zero- and Few-Shot LLM Translation [\[arxiv\]](#)

Petr Parshakov

A first KomiYazva–Russian parallel corpus plus a leakage-aware protocol that makes zero/few-shot LLM MT evaluation credible with only hundreds of sentences.

Releases 457 aligned sentence pairs from 74 narratives with story IDs and an evaluation recipe (story-level CV, deterministic few-shot retrieval, strict failure handling, multiple metrics + judges) to avoid leakage and fragile conclusions. Split by story (not sentence) for cross-validation; run zero-shot prompts and deterministic retrieval-based few-shot prompts from the training fold; explicitly count wrong-language/refusal/malformed outputs; report reference metrics and human/judge assessments with story-level uncertainty. LLMs can translate KomiYazvaRussian meaningfully, but results are highly model/prompt sensitive; retrieval-based few-shot reliably beats zero-shot with diminishing returns beyond a small context, and metric/failure accounting can change rankings—motivating the protocol as much as the data.

"Chi nas dal soch el sent de legn" – Auditing Text Corpora for Lombard [\[arxiv\]](#)

Edoardo Signoroni, Pavel Rychlý

Most “Lombard web data” is mislabeled or boilerplate, and the usable remainder is dialect/orthography-skewed—so scraping more can worsen bias.

Manual, variety-aware audit of popular Lombard corpora showing dataset size and language-ID labels are unreliable proxies for usable, representative training data in a dialect continuum. Human-in-the-loop inspection of monolingual/parallel corpora to quantify mis-ID (e.g., Italian), templated boilerplate, and junk; then analyze the valid subset’s orthographies and regional variety coverage. Headline corpus volumes shrink sharply after filtering; remaining Lombard is dominated by Western varieties and competing spelling conventions with Eastern underrepresented, implying that naive scaling entrenches the wrong distribution and misleads evaluation.

Multilingual Speech Processing

OpenSTBench: Beyond Semantic Evaluation for Speech Translation [\[arxiv\]](#)

Yanjie An, Yuxiang Zhao, Yichi Zhang, Qixi Zheng, Yujie Tu, Keqi Deng, Kai Yu, Xie Chen

A single benchmark to compare speech translation systems across meaning, speech quality, and timing—even when outputs differ (text vs speech; offline vs streaming).

OpenSTBench standardizes formats and protocols so heterogeneous ST systems can be evaluated side-by-side on semantic, acoustic, and temporal dimensions instead of via incompatible pipelines. Unifies S2TT and S2ST, offline and streaming outputs, then jointly scores translation quality, speech quality, speaker/emotion/paralinguistic fidelity, temporal consistency, and latency to produce a multi-

axis system profile. Across representative systems, strong translation scores often coexist with large deficits in speech quality and/or temporal behavior, exposing trade-offs that semantic-only evaluation hides and making comparisons reproducible across paradigms.

Benchmarking Speech-to-Speech Translation Models [\[arxiv\]](#)

Alkis Koudounas, Hayato Futami, Quentin Jodelet, Osamu Take, Shinji Watanabe, Emiru Tsunoo

COMPASS makes speech-to-speech translation evaluation reproducible and shows single-metric rankings can be badly wrong.

Introduces COMPASS: an offline S2ST benchmark with 46 metrics across eight dimensions, enabling comparable, multi-dimensional evaluation and revealing architecture-dependent trade-offs. Compute 46 metrics over 1,248 model–language configs (FLEURS/CVSS; cascaded and end-to-end; 10 language pairs); use correlation filtering to select 10 metrics per direction (XEN vs ENX) to cut cost while preserving rankings. Naturalness/speaker preservation can vary by >30% while translation quality shifts only a few points, so leaderboards can mis-rank systems; 10-metric subsets preserve rankings well (Spearman >0.80) with ~2.5E speedup, and human studies show generic MOS predictors miss preferences while best domain metrics correlate strongly (0.90).

Foundation Model Theory

Where does Absolute Position come from in decoder-only Transformers? [\[arxiv\]](#)

Valeria Ruscio, Umberto Nanni, Fabrizio Silvestri

Decoder-only RoPE models still encode absolute position because of two “leaks”: causal-mask softmax normalization and a position-0 residual anchor read by sink heads.

Provides a mechanistic, predictive account of absolute-position signals in ostensibly relative-position RoPE decoders, attributing them to mask-induced normalization effects plus a BOS/position-0 residual trajectory broadcast forward. Derives how the causal mask makes the softmax denominator depend on absolute query index; analyzes position-0 residual dynamics (self-only attention) and sink-reading heads; validates via attention-variant comparisons and BOS-swapping interventions. Most absolute-position behavior decomposes into (i) guaranteed mask/normalization dependence and (ii) a model-dependent position-0 residual fingerprint; NTK scaling dampens the residual component, sliding-window amplifies it, and swapping BOS removes ~40% of that residual component early—supporting causality.

LLM Evaluation

LLMs Can Leak Training Data But Do They Want To? A Propensity-Aware Evaluation of Memorization in LLMs

[\[arxiv\]](#)

Gianluca Barmina, Peter Schneider-Kamp, Lukas Galke Poech

Memorization risk should measure not just what an LLM can be forced to leak, but what it tends to leak under normal prompts.

PropMe converts existing memorization detectors into propensity-aware metrics (typical-prompt leakage) alongside capability metrics (prefix-attack extractability), paired with SimpleTrace for deterministic corpus attribution. Evaluate the same memorization scoring under (1) adversarial prefix continuation prompts to maximize extraction and (2) non-adversarial prompt distributions to estimate everyday leakage; SimpleTrace attributes verbatim/near-verbatim spans via indexed matching. On Comma and DFM Decoder over Common Pile and Dynaword (two languages), capability is high under prefix attacks but propensity remains low under ordinary prompts; continued pretraining (DFM from Comma) can reduce both, so audits should report both numbers.

Field Overview

Today’s batch is dominated by foundation-model work, especially LLM agents, memory, and evaluation: at least ~25–35 papers focus on

long-horizon agents (persistent memory, tool planning/replanning, collaboration benchmarks, agent safety/guardrails, and agent-serving systems like KV-cache/sparse attention). A second major cluster is audio/speech foundation models and audio generation: well over ~150 titles cover speech/audio LLMs, tokenizers/codecs, TTS/music/audio-video generation, and a parallel surge in audio deepfake detection/jailbreaks/watermarking (dozens of papers). Reinforcement learning for post-training and test-time scaling is another clear hotspot (at least ~15–25 papers on GRPO/RLVR variants, credit assignment, rollout budgeting, and reward hacking/judge issues), often explicitly tied to agent reliability. Notable emerging directions include diffusion language models (multiple papers on masked/diffusion LMs and decoding) and a surprisingly dense set of “agent infrastructure” papers (routing, speculative decoding, KV reuse, compression) treating deployment constraints as first-class research problems.