

Multilingual NLP

Improving Mental Health Screening and Early Risk Detection in Spanish [\[arxiv\]](#)

Andreu Casamayor-Segarra, Vicent Ahuir, Antonio Molina-Marco, Lluís-F. Hurtado

Earlier, more reliable Spanish mental-health risk detection comes from pairing domain-adapted Spanish LMs with a re-labeling scheme that teaches when evidence becomes sufficient.

Adds (1) Spanish foundation models further pre-trained on mental-health-relevant text and (2) Incremental Context Expansion (ICE), which converts user-level labels into early-detection supervision by inferring the earliest “turning point” in a post timeline. From each user’s chronological posts and final label, ICE creates prefix histories and auto-relabels them by selecting the earliest prefix that justifies the final label; models are then fine-tuned on these ICE samples to optimize accuracy under minimal delay. Across three Spanish screening/early-risk benchmarks, domain adaptation + ICE consistently lowers detection latency without hurting overall quality, showing much early-warning performance is lost when training only on full histories; models are released publicly.

DialectLLM: A Dialect-Aware Dialog[ue] Generation Framework Beyond Standard American English [\[arxiv\]](#)

Jio Oh, Paul Vicinanza, Thomas Butler, Steven Euijong Whang, Dezhi Hong, Amani Namboori

LLMs still struggle with everyday English dialects, and dialect-aware dialogue needs linguist-grounded transformations plus restraint in assistant imitation to avoid forced/stereotyped dialect.

Creates a large dialect-parallel dialogue framework for nine dialects using native-linguist-authored rules and introduces DialectLLM-Bench to test dialect ID and dialect-conditioned response generation; argues assistants should reproduce only a small subset of dialect morphosyntax (up to 90% should not be mirrored). Start from SAE dialogues, apply validated transformations across lexicon, spelling, and morphosyntax to generate meaning-preserving dialect variants; treat user vs. assistant differently (limited assistant morphosyntax); evaluate models on identification and constrained generation with human naturalness checks. Across 17 LLMs, even frontier models stay <70% overall and <50% on some dialects (e.g., Canadian English), often collapsing dialects into US/UK labels; humans prefer DialectLLM outputs over prior approaches for dialect naturalness (98.8% pairwise), and the data also serves as scalable post-training material.

MathNet: a Global Multimodal Benchmark for Mathematical Reasoning and Retrieval [\[arxiv\]](#)

Shaden Alshammari, Kevin Wen, Abrar Zainal, Mark Hamilton, Navid Safaei, Sultan Albarakati, William T. Freeman, Antonio Torralba

MathNet is a large multilingual, multimodal Olympiad-math benchmark that separately measures solving, true-equivalence retrieval, and retrieval-augmented solving—exposing retrieval as the bottleneck for math RAG.

Builds a 17-language, multimodal Olympiad problem set with expert solutions and human-curated pairs of mathematically equivalent/structurally similar problems, enabling rigorous evaluation of math-aware retrieval beyond surface similarity. Three tracks: (1) direct problem solving, (2) retrieval of equivalent/structurally aligned problems using expert-curated relevance, and (3) RAG solving with analysis of sensitivity to retrieval quality. Frontier models are not saturated (e.g., 78.4% Gemini-3.1-Pro; 69.3% GPT-5); embedding retrieval often fails to find truly equivalent problems; RAG can add large gains but is highly retrieval-quality dependent (e.g., DeepSeek-V3.2-Speciale up to ~+12% to best overall), making math retrieval the key limiter.

AHA-Memes: A Fine-Grained Multimodal Benchmark for Understanding Hate in Arabic Memes [\[arxiv\]](#)

Mohamed Bayan Kmainasi, Ali Ezzat Shahroor, Abul Hasnat, Md. Rafiul Biswas, Wajdi Zaghoulani, Firoj Alam

AHA-Memes provides the first large, fine-grained benchmark for hateful Arabic memes and establishes broad baselines across text, vision, and multimodal models.

Releases a 5k manually labeled Arabic meme dataset with multi-label hate taxonomy framed as attack strategies, plus ~66k silver-labeled memes, along with guidelines and evaluation scripts to standardize progress. Collect and annotate memes with fine-grained multi-label hate categories; benchmark text-only, image-only, late-fusion multimodal, and vision-language models under zero-shot, few-shot, and fine-tuning settings. Provides baseline results across unimodal and multimodal families and surfaces culturally grounded challenges

where straightforward model applications fall short; the paper’s main outcome is a shared dataset/taxonomy/eval pipeline rather than a single claimed SOTA margin.

Multilingual Speech Processing

Zero-Shot Face-to-Speech Synthesis via Latent Space Adaptation of a Style-Diffusion TTS Model [\[arxiv\]](#)

Carlos Muñoz-Romero, Jose A. Gonzalez-Lopez

A single face image can drive zero-shot, identity-consistent speech by learning a small facestyle mapping into a frozen diffusion TTS model, and it transfers cross-lingually.

Introduces a lightweight “face adapter” that maps face-recognition embeddings into StyleTTS2’s speaker/style latent, avoiding end-to-end TTS retraining while enabling face-conditioned voice synthesis. Face image face encoder embedding small adapter (with mild tuning of top face-encoder blocks) StyleTTS2 style code speech; StyleTTS2 stays frozen and the adapter is trained on paired face–speech data. On unseen LRS3 identities, synthesis is highly natural (UTMOS ~3.7–4.0, reported above their ground-truth 3.61) and identity-consistent (retrieval above chance); an English-trained adapter produces fluent Spanish without retraining, suggesting language-agnostic speaker traits are captured.

DualAnchor: Preserving Language Priors and Improving Lexical Fidelity in Gloss-Free Sign Language Translation

[\[arxiv\]](#)

Hongbin Zhang, Junhao Liu, Xuefeng Bai, Youcheng Pan, Yang Xiang, Kehai Chen

DualAnchor improves gloss-free sign-language translation by explicitly preserving an LLM’s fluency prior while adding token-level video–text grounding for lexical fidelity.

Identifies two failures in LLM-based SLT—language-prior degradation and weak lexical grounding—and proposes DualAnchor with two training “anchors” to address them: Token-level Prior Anchoring (TPA) and Optimal Transport Alignment (OTA). TPA regularizes the multimodal decoder’s next-token distribution toward a frozen LLM teacher given the same prefix; OTA uses entropy-regularized partial optimal transport (Sinkhorn, cosine cost) to softly align video tokens with text content tokens, allowing unmatched tokens/words. On PHOENIX-2014T and CSL-Daily, DualAnchor outperforms prior gloss-free LLM-based baselines; analysis attributes fluency gains to TPA and reduced lexical errors to OTA, showing separate mechanisms are needed for “write well” and “say what you saw.”

Field Overview

Today’s batch is dominated by LLM agents and the infrastructure to make them reliable: at least ~25–35 papers on agent evaluation/benchmarks and workflow harnesses (e.g., ORCA-bench, HANDBOOK.md, OmegaUse-OfficeVal, ClawTrack, SecRespond, StealthBench, OSReward, SimpleWikiSearch), plus another ~15–25 on agent memory (ChronoMem, MemTxn, Memory Decoder at Scale, ForgetBench, filesystem/graph-native memory, memory poisoning like MemSecBench). A second major cluster is retrieval/RAG and evidence traceability—roughly ~15–20 papers spanning agentic RAG reliability (LayerRAG-Bench), graph/structured RAG (GLM-RAG), mutable-doc serving (FinCacheServe), and claim–evidence ledgers/citation auditing (LEDGERMIND, Evidence-Ledger Adjudication, SourceMinds). Efficiency/post-training is also heavily represented (~20+): quantization/pruning/low-bit inference (WIDE, LightRot, GyRot, Flat Score Amplified Failures), KV-cache/long-context tricks (Recall Before You Rank, Back from the Future, Red-Knot), and RLVR/OPD-style post-training methods (LEEPS, LSPO, TAPO, Flux-OPD, Lightning OPD 2.0). A notable emerging direction is “evaluation skepticism” and measurement science—multiple papers explicitly question LLM-as-judge, benchmark composability/perishability, and score validity (e.g., Position: Evaluation Scores Are Perishable Knowledge Claims; When benchmark inferences do not compose; Rethinking LLM-Judged Helpfulness; Reviewer scores not comparable), alongside a smaller but visible safety/security cluster around deception, prompt injection, and red-teaming (Can Agents Deceive?, Even More Deception, GPT-Red, prompt-injection defenses).