

Multilingual NLP

TalkFa: A Unified Benchmark for Farsi Dialogue Generation and Understanding [\[arxiv\]](#)

Neda Jamshidi, Kamyar Zeinalipour, Fahimeh Akbari, Monica Bianchini, Marco Maggini, Marco Gori

TalkFa unifies high-quality Farsi dialogue generation + understanding tasks and shows automatic metrics can overrate models vs GPT-4.1 judging.

Packages three validated Farsi dialogue datasets into one benchmark with strong native-speaker QC; demonstrates a measurement pitfall: common automatic dialogue metrics can substantially overestimate quality relative to GPT-4.1-as-judge. Combine WIKI-FADIAL (Wikipedia-grounded generation), DAILYDIALOG-FA (acts+emotions), PLAYDIAL-FA (sentiment). LLM-assisted drafting with multi-stage native review; experiments with LLaMA/Mistral variants, LoRA fine-tuning, and classification models; compare auto metrics vs GPT-4.1 judgments. LoRA improves generation, and 25–50% of training data recovers >90% of gains. Best understanding models: FABERT (dialogue acts), LoRA-Mistral-7B (emotion), Mistral-24B (sentiment). Auto metrics overestimate quality vs GPT-4.1; zero-shot frontier LLMs still struggle on TalkFa.

CroCo: Cross-Lingual Contrastive Preference Tuning on Self-Generations [\[arxiv\]](#)

Mike Zhang, Ali Basirat, Desmond Elliott

CroCo aligns multilingual LLM behavior using only English preference data by ranking the model’s own non-English outputs and tuning on those rankings.

Turns English-only preference supervision into cross-lingual alignment: use an English-trained reward model (with multilingual backbone) to rank same-language self-generations, then preference-tune without needing per-language preference labels and without wiping SFT skills. Sample multiple on-policy responses per prompt across languages; score with an English-preference-trained multilingual reward model; form chosen/rejected pairs and train with offline contrastive/DPO-style preference tuning (within-language or mixed-language). English-trained reward rankings transfer: tuned models improve broadly across 14+ languages. Judges prefer tuned over base in 28/30 open-ended comparisons (15 languages). Gains depend on on-policy self-generations; off-policy data weakens benefits, and online optimization doesn’t beat the offline approach; avoids catastrophic forgetting.

BioELX: Context-Aware Cross-lingual Biomedical Entity Linking without Task-Specific Supervision [\[arxiv\]](#)

Yi Wang, Corina Dima, Liangyu Zhong, Steffen Staab

BioELX achieves strong cross-lingual biomedical entity linking with no labeled BEL data by fixing alias bias in retrieval and using mention-anchored LLM reranking for context.

Identifies two blockers—English-skewed alias supervision and context hurting alias-trained retrievers—and proposes a retrieve–rerank pipeline: expand cross-lingual alias coverage for retrieval, then apply context only in an LLM reranker explicitly anchored to the target mention span. Stage 1: continue-train SapBERT_multi on Wikidata-mined cross-lingual alias pairs to improve multilingual candidate retrieval. Stage 2: LLM reranker with mention-marked prompting scores candidate entity descriptions conditioned on the marked span in context. On 4 cross-lingual BEL benchmarks, Recall@1 improves by ~5–18 points over prior best without task-specific BEL labels. Context helps most in reranking (not retrieval), and mention-anchoring is key to correct disambiguation behavior.

MultiGhostBench: A Multilingual Benchmark for Long-Form LLM-Generated Text Attribution under Distribution Shifts [\[arxiv\]](#)

Matteo Greco, Anudeex Shetty, Andrea Tagarelli, Jey Han Lau

MultiGhostBench is a multilingual, book-length benchmark for LLM text attribution designed to measure robustness under domain/author/language shifts.

Moves attribution evaluation from short English i.i.d. snippets to realistic forensic conditions: 928 long synthetic books across languages/scripts, with explicit stress tests for domain shift, unseen generators, and cross-language transfer. Generate 928 books from 5 LLMs in 6 languages/3 scripts (~59K words avg). Define train/test splits for domain, author (generator), and language shifts. Bench-

mark transformer detectors and statistical/fingerprint methods under each shift. No method dominates under shifts; performance drops markedly out-of-distribution. Transformer detectors retain some cross-language generator signal (language-pair dependent), while statistical/fingerprint methods degrade more across languages/scripts—showing “in-domain English” success doesn’t imply robust attribution.

Bridging Latent Reasoning and Target-Language Generation via Retrieval-Transition Heads [\[arxiv\]](#)

Shaswat Patel, Vishvesh Trivedi, Yue Han, Yihuai Hong, Eunsol Choi

Retrieval-Transition Heads are a small set of attention heads that causally steer multilingual models from latent reasoning into the requested output language.

Identifies a distinct head type beyond standard “retrieval heads”: Retrieval-Transition Heads (RTHs) that control the switch from language-agnostic internal reasoning to target-language surface generation, especially for multilingual chain-of-thought. Analyze attention heads in multilingual LLMs: show many retrieval heads are shared across languages; define RTHs via coupling to output-language choice; validate causality by masking candidate heads at inference and measuring degradation vs masking ordinary retrieval heads. Masking RTHs harms multilingual QA/reasoning far more than masking retrieval heads across MMLU-ProX, MGSM, MLQA, XQuAD and across Qwen-2.5 and Llama-3.1, with the largest drops on chain-of-thought—pinpointing a manipulable choke point for language control.

Multilingual Speech Processing

VoiceLongMemEval: Do Assistants Remember How You Sounded? [\[arxiv\]](#)

Ramit Pahwa, Parivesh Priye, Apoorva Beedu

VLME tests long-term voice-assistant memory for how users sounded (emotion/prosody/events), not just what they said.

Introduces VoiceLongMemEval, where questions depend on paralinguistic cues intentionally unrecoverable from transcripts; adds adversarial filtering so text-only LMs cannot solve items, making the benchmark genuinely diagnostic for audio-channel memory. Multi-turn long-horizon dialogues with paralinguistic annotations; questions require recalling these cues. A 3-stage adversarial gate removes items solvable from transcript alone. Evaluate transcript-only, transcript+paralinguistic “text track,” transcript+evidence hints, and audio-native models. Transcript-only models show a consistent “affect gap.” Adding paralinguistic metadata boosts accuracy by ~0.09–0.38; adding evidence hints reaches ~0.61–0.69. Audio-native models beat transcript-only (~0.354–0.412 vs ~0.325), and ASR-centric pipelines erase key signals VLME measures.

VAANI Noise Event Dataset: A curated spontaneous speech dataset annotated with timestamps for noise events [\[arxiv\]](#)

Pavan Kumar J, Agneeth Basu, Pranav Bhat, Sujith Pulikodan, Suryansh Shukla, Nihar Desai Prasanta K. Ghosh

VAANI adds timestamped real-world noise-event labels to spontaneous multilingual speech, enabling training/eval for overlapping speech+noise conditions that break deployed ASR.

Provides a rare supervision type: start/end timestamps for overlapping background noise events in in-the-wild recordings, with a compact 7-class taxonomy, spanning 105 languages—bridging the gap between synthetic mixtures and clean speech corpora. Annotate Project VAANI field recordings with human-labeled temporal spans for noise events (including overlap with speech); use a 7-category noise taxonomy and QC to ensure consistent boundaries and labels. Delivers a missing benchmark: authentic co-occurring speech+noise with span-level timing at massive multilingual scale. Compared to MUSAN/AudioSet/DESED/CHiME/WHAM!/noisy-ASR sets, it uniquely combines real overlap, timestamps, and broad language coverage—enabling event-aware robust ASR/enhancement training and evaluation.

LLM Evaluation

Incremental Pooled LLM Evaluation for Cost-Effective Retrieval Model Selection [\[arxiv\]](#)

Max Nelson, Hanoz Bhathena, Aviral Joshi, Saket Sharma

Reuse LLM relevance judgments via incremental pooling to evaluate evolving RAG retrievers cheaply with near-gold ranking fidelity.

Adapts classic IR pooling to LLM judging and makes it incremental: maintain a shared judged doc pool across retriever candidates; when a new retriever is tested, label only newly retrieved docs, enabling consistent comparisons without re-labeling past work. For a fixed query set, store all previously retrieved docs + LLM qrels. For each new system, add only unseen retrieved docs for LLM judging, then rescore all systems on the accumulated qrels; use bootstrap/uncertainty to compare pairwise orderings robustly. Across 4 benchmarks/11 systems, pooled-LLM rankings track gold closely; with uncertainty, 97% of pairwise orderings match gold. In a financial-news QA deployment (62 configs), 65–80% judgment reuse yields up to 4.9€ lower evaluation cost.

Field Overview

Today’s batch is dominated by LLM agent reliability/safety/evaluation work: at least ~25 papers on agent scaffolding, long-horizon planning/credit assignment, memory (persistent memory failures/poisoning, routing/topology for multi-agent systems), and deployment realism (e.g., evaluation awareness, monitoring without internal signals, enterprise readiness). A second major cluster is retrieval-grounding and evidence discipline—roughly ~15 papers on RAG/multi-hop QA, evidence sufficiency/coverage, retrieval model selection, and retrieval attacks/poisoning (including code RAG), plus several KG-centric hypothesis discovery/completion efforts. Efficiency and model surgery is another heavy theme (~15+): LoRA/PEFT variants and initialization, pruning/quantization (2-bit/FP4/ternary), KV-cache/attention optimizations, and depth/layer merging—often explicitly tied to on-device or production constraints. Notable emerging directions include audio/speech + privacy/security (10 papers: low-resource ASR, audio grounding benchmarks, TTS membership inference, privacy firewalls) and a visible push toward culturally/linguistically grounded evaluation beyond English (8–10 papers: Indic/Farsi/Romanian/Dutch/Cantonese, cultural memes/pragmatics/bias).