

Multilingual NLP

ADAGE: A Language-Agnostic Pipeline for Analogical Reasoning Evaluation [\[arxiv\]](#)

Ahmed Haj Ahmed, Alvin Grissom II

Translation-based “multilingual reasoning” benchmarks can inflate performance; ADAGE builds native, culture-grounded analogy tests that reveal real cross-cultural gaps.

ADAGE replaces the standard “translate an English benchmark” recipe with a language-agnostic pipeline where native speakers author culturally valid analogies (e.g., proverb-like abstractions) from scratch, using LLMs only for drafting/scale and humans as the authority. They release new non-translated benchmarks in Arabic, Amharic, and Japanese. Native speakers curate source cultural material and define valid analogical mappings; LLMs generate candidate questions/options; native review filters unnatural phrasing, ambiguity, and culturally off analogies. The result is translation-free, difficulty-controlled analogy evaluation grounded in each language’s own abstractions. Across 14 open-weight models, accuracy drops by ~12–52 points versus English when evaluated on the native Arabic/Amharic/Japanese sets, reshuffling conclusions about which models “reason well.” Translation-based tests systematically overestimate multilingual reasoning transfer.

The Cross-Domain Generalization Cost of Offensive Language Detection [\[arxiv\]](#)

Ruixing Ren, Junhui Zhao, Xiaoke Sun, Qiuping Li

Offensive-language detectors fail in transfer mostly due to dataset/label mismatch, and fixing target performance has a measurable “source accuracy” price tag.

They decompose transfer loss into dataset-shift vs language-shift components and argue adaptation must be scored jointly on target gains and source-task forgetting. They provide joint-training strategies that expose a controllable Pareto frontier between multilingual improvement and source preservation. Zero-shot loss decomposition (e.g., OLIDMLMA) isolates dataset vs language effects. Few-shot adaptation compares continued fine-tuning vs cold-start to separate true adaptation from initialization advantage, and measures post-adaptation source-task damage. Joint training uses temperature-based sampling and replay to trade off target gains vs forgetting. Dataset shift dominates zero-shot degradation. Continued fine-tuning yields unstable, large forgetting—4–9% more source-task damage than replay-based joint training. Joint strategies trade ~3.2–4.1 source points for +8.1 to +42.6 target gains, making adaptation an explicit budgeted decision.

Echoes Across Vietnam’s Highlands, Delta, and Coast: A Multilingual Corpus for Cham, Khmer, and Tay-Nung [\[arxiv\]](#)

Anh Trac Duc Dinh, Khang Nhat Hoang Vo, Vinh Cong Doan, Tai Tien Ta, Khoa Duc Anh Lam

CKTN provides the first multi-task benchmark for Cham, Khmer, and TayNung and shows models can “improve” via script/tokenization shortcuts without learning meaning.

They release CKTN (continued pretraining + classification + summary-to-document retrieval) for three Vietnamese minority languages and highlight a key pitfall: mixed scripts/standardization let multilingual models win on surface cues, making common adaptation signals misleading. They propose a script-aware adaptation recipe to block these shortcuts. Diagnose severe tokenization fragmentation in existing multilingual encoders; expand vocabulary to better cover scripts/orthography; use calibrated replaced-token pretraining so the discriminator can’t rely on trivial script mismatch, forcing contextual/semantic learning. Lower LM loss and strong overlap-heavy retrieval can coexist with poor semantic generalization. Their script-aware adaptation reduces fragmentation and yields the best category classification among tested models, demonstrating that surface-overlap retrieval metrics are not reliable proxies for understanding in mixed-script low-resource settings.

Efficient Multilingual Reasoning Transfer via Progressive Code-Switching [\[arxiv\]](#)

Zhijun Wang, Junxiao Liu, Hao Zhou, Hao-Ran Wei, Baosong Yang, Shujian Huang

Progressive Code-Switching transfers English reasoning to other languages by gradually increasing target-language usage inside the chain-of-thought, using only cheap translation.

PCS enables multilingual reasoning without teacher-generated target-language rationales or external judge scoring. Key idea: preserve reasoning skill by smoothing the transition from English CoT to target-language CoT via a curriculum over code-switching intensity. Stage 1 SFT on mixed traces created by translating only some English reasoning steps. Stage 2 RL with step-level language-consistency rewards, gradually raising the required target-language ratio until reasoning is fully in the target language. Across multiple reasoning benchmarks and five diverse languages, PCS closes much of the English-target reasoning gap while increasing true target-language reasoning consistency (not just translated final answers), maintaining competitive accuracy without expensive supervision.

Multilingual Speech Processing

MoLGE: Mixture of Language Group Experts for Efficient Scaling of Massively Multilingual Speech Recognition

[[arxiv](#)]

Sangmin Lee, Woojin Chung, Woongjib Choi, Hong-Goo Kang

MoLGE scales ASR to hundreds of languages by specializing small expert modules per language group (not per language), avoiding capacity dilution.

MoLGE combats the “curse of multilinguality” with group-level experts plus hierarchical LoRA that targets acoustic vs linguistic/orthographic components separately. It treats language grouping as a design variable and analyzes how grouping choices affect outcomes. Start from a speech self-supervised backbone; attach expert modules shared by language clusters and route examples by cluster. Add structured (hierarchical) LoRA adapters aligned to acoustic vs linguistic parts. Compare linguistically motivated vs data-driven grouping strategies. On a 495-language benchmark, MoLGE outperforms dense multilingual baselines with only modest added trainable parameters, recovering performance otherwise lost to capacity dilution. Grouping materially affects both phonetic and orthographic modeling, implying “similarity” for ASR depends on sound systems and writing conventions.

DONDO: Open w2v-BERT Speech-Recognition Base Models for African Languages [[arxiv](#)]

Paul Azunre, Naafi Ibrahim, Joel Budu, Lawrence Adu-Gyamfi

DONDO releases permissively licensed w2v-BERT ASR base models for African languages and shows a single multilingual checkpoint can approach monolingual accuracy with staged fine-tuning plus language conditioning.

They publish 21 monolingual and 5 multilingual w2v-BERT 2.0 ASR base models (27 varieties) under Apache-2.0. Core idea: staged learning-rate fine-tuning plus an explicit language-ID prefix lets one multilingual model behave like many specialized systems; they leverage license-clear, consistent read-speech data (religious texts). Fine-tune w2v-BERT 2.0 on transcribed read speech. For multilingual: high LR adaptation then LR annealing to recover accuracy. Condition inference by prepending prefix frames encoding a one-hot language ID, steering decoding without separate heads. Annealed multilingual models reach ~10–13% average WER, closing most of the monolingual gap while covering many languages in one checkpoint. High-impact practical result: openly released Apache-2.0 base checkpoints enable legal downstream fine-tuning/deployment for language communities totaling ~100M L1 speakers.

Foundation Model Theory

Through the Bottleneck: How Multi-head Latent Attention Separates Content from Position in Language Models

[[arxiv](#)]

Dhruvil S, Fenil Sojitra, Ravirajsinh Chauhan

Multi-head Latent Attention’s shared low-rank bottleneck reshapes transformer circuits by separating content from position and concentrating key computations into specific layers.

First mechanistic interpretability study of DeepSeek-style MLA: the shared cKV bottleneck acts as a content channel while positional information is handled elsewhere, causing recognizable circuits (e.g., induction) to relocate and concentrate across layers. Train a 114M MLA transformer (web/code/math) then fine-tune on TinyStories; analyze cKV with SVD/rank, linear probes for content vs position, head taxonomy for induction-like behavior, and disruption-attribution to localize causal importance. The cKV bottleneck preserves entity/content extremely well (~98% retention) while largely discarding position. Induction heads concentrate into one layer (Layer

12), and a “semantic hub” layer (Layer 15) shows highest effective rank and disruption importance. Bottleneck capacity is underused (~46%), suggesting room for further compression or explanation.

LLM Evaluation

Codifying the Judge: Scalable Evaluation via Program Distillation [\[arxiv\]](#)

Tzu-Heng Huang, Shengqi Qiu, Frederic Sala

LLM-judge evaluation can be mostly replaced by a distilled committee of executable programs, with LLM fallback only for uncertain cases.

Program distillation compresses an LLM judge into transparent, editable programmatic judges; PAJAMA aggregates a committee and routes ambiguous items to an LLM, cutting cost while retaining quality. Program verdicts also serve as cheap labels for downstream reward modeling. Synthesize multiple scoring/ranking programs that take prompt + candidate (and optional references) and output scores/preferences; aggregate committee outputs; use agreement/confidence to escalate hard cases to an LLM judge. Use program labels as rewards to train reward models. Program committees reach ~parity with a 13B-class LLM judge across datasets/model families and improve the accuracy–throughput tradeoff via selective escalation. Reward models trained on program labels outperform those trained on proprietary LLM labels on RewardBench while using ~100× fewer API calls.

Field Overview

Today’s batch is dominated by LLM/agent reliability, safety, and evaluation work: at least ~40–60 titles focus on hallucination detection, chain-of-thought faithfulness/unfaithfulness, prompt-injection/jailbreak defenses, red-teaming limits, and “reliability beyond accuracy” (e.g., D-Score, Reasoning Denoiser, Semalith, Same Question Different Answers, CoT unfaithfulness, red-team validity). A second major cluster is agentic systems + RAG + memory/tooling (roughly ~30–50): active/agentic RAG, evidence attribution/citations, memory contamination/consistency gates, workflow synthesis, tool-call risk control, and enterprise/DB agents (e.g., CAGE, TriShield-RAG, ConsistencyGate, Keep It InMind, DBA-Bench, AgentKVShift, SpecBox). Efficiency/serving for long-context and deployment is also heavily represented (~25–40), especially KV-cache compression/eviction, sparse attention, quantization, and on-device/mobile inference (LOCKS, HiKV, DynaCalKV, MixQuant, MM-ShiftKV, FBLayout, ELMOD). A notable emerging direction is the strong multilingual/low-resource emphasis (at least ~20–30) spanning Indic/African languages, tokenization “tax,” multilingual ASR/diarization, and culturally grounded datasets—plus a surprisingly large audio/music thread (~15–25) covering TTS, deepfake detection, audio codecs/vocoders, and music generation/source separation.