

Multilingual NLP

BURMESE-SAN: Burmese NLP Benchmark for Evaluating Large Language Models [\[arxiv\]](#)

Thura Aung, Jann Railey Montalan, Jian Gang Ngui, Peerat Limkonchotiawat

A native-speaker-built Burmese benchmark shows Burmese LLM performance depends more on data coverage and tuning than on sheer model size.

Releases BURMESE-SAN, a realistic Burmese evaluation suite (not translation-artifact-heavy) spanning understanding, reasoning, and generation, plus a public leaderboard for consistent tracking. Seven tasks—QA, sentiment, toxicity, causal reasoning, NLI, summarization, MT—curated with native-speaker emphasis on naturalness; evaluate a range of open and commercial LLMs under a unified protocol and report results on the leaderboard. Model size is not the main driver: models with better Burmese/regional data and instruction tuning make large gains even when smaller, implying low-resource progress comes from coverage/adaptation strategy rather than scaling alone.

Brain-LLM Alignment Tracks Training Data, Not Typology [\[arxiv\]](#)

Dongxin Guo, Jikun Wu, Siu Ming Yiu

Brain-LLM alignment advantages track a model’s dominant training language, not an inherent English privilege; remaining gaps reflect typology and tokenization.

Multilingual fMRI alignment study (English/Chinese/French) using the same narrative and language-dominant model comparisons, including an architecture-matched Chinese- vs English-dominant pair, to isolate training-language effects; then quantifies residual typology/tokenization impacts. Fit encoding models from layer-wise LLM representations to fMRI responses (112 participants) in the language network while processing Le Petit Prince across languages; compare alignment across models/languages/regions; analyze typological distance effects and tokenizer “fertility” effects on best-layer shifts. Alignment reverses with training dominance: a Chinese-dominant model aligns best to Chinese brains and worst to English, opposite an architecture-matched English-dominant model; beyond dominance, typological distance hurts alignment more in syntax-linked regions (e.g., IFG), and tokenization fertility explains ~60% of cross-language best-layer shifts.

Structure-Guided Entity Resolution: Fine-Tuning LLMs for Robust Name Matching in Complex Linguistic Contexts

[\[arxiv\]](#)

Shivam Chourasia, Hitesh Kapoor, Nilesh Patil

Name matching becomes far more robust when an LLM is first taught name structure, then trained to decide matches.

Introduces Structure-Guided Entity Resolution (SGER), a two-stage curriculum that learns internal name components (given/family/initials/honorific ordering, transliteration behavior) before binary entity matching, improving robustness on messy multilingual KYC-style data; validated in a large production setting. Two-phase fine-tuning: (1) supervised name-structure understanding/parsing to induce a structured representation; (2) downstream fine-tune for same-person vs different-person classification on name pairs. On 50k held-out real Indian name pairs, achieves 99.02% accuracy and 0.994 F1, beating GPT-4o few-shot and single-stage fine-tuning; reported deployed at Dream11 (250M+ users), indicating production-grade stability.

Multilingual Knowledge Transfer under Data Constraints via Lexical Interventions [\[arxiv\]](#)

Anastasiia Sedova, Natalie Schluter, Skyler Seto, Maartje ter Hoeve

Cross-lingual transfer under data scarcity can be boosted by lightly mixing translated target-language words into English pretraining text—no parallel corpora required.

Proposes LINK, a data-only lexical intervention that couples English-learned knowledge to target-language tokens by replacing a small fraction of English words with dictionary translations, creating informative mixed contexts that bind knowledge to low-resource lexical forms. During standard pretraining, randomly substitute selected English words with bilingual-dictionary translations at a chosen ratio; train normally on the resulting code-mixed stream to encourage shared representations and better target-language knowledge access. Across 8 target languages and 5 model sizes, yields consistent target-language gains (notably on knowledge/reasoning tasks) and can

reach baseline performance with up to ~20% less training, supporting the claim that lexical coupling—not more target text—is the key bottleneck.

Multilingual Speech Processing

Convex Low-resource Accent-Robust Language Detection in Speech Recognition [\[arxiv\]](#)

Miria Feng, William Tan, Mert Pilanci

Accent-robust language ID in truly low-resource settings can be achieved by replacing fragile fine-tuning with a convex, globally solvable classifier with margin-based stability guarantees.

Proposes Convex Language Detection (CLD): a convex language-ID head on frozen speech embeddings that avoids small-data overfitting, trains to a global optimum, and comes with a certified decision-stability interpretation via margin robustness to bounded feature perturbations (accent/dialect shift). Train a convex margin-based classifier on fixed speech representations; solve efficiently with an ADMM optimizer implemented in JAX with multi-GPU support; relate learned margin to provable stability under bounded feature perturbations. Maintains high accuracy in low-resource, dialect-shifted conditions (~97–98%), outperforming typical fine-tuning behavior; robustness is explained/controlled via the margin-based stability certificate and is practical due to fast ADMM training.

Benchmarking Commercial ASR Systems on Code-Switching Speech: Arabic, Persian, and German [\[arxiv\]](#)

Sajjad Abdoli, Ghassan Al-Sumaidae, Clayton W. Taylor, Ahmad ElShiekh, Ahmed Rashad

A public code-switching ASR benchmark shows WER can greatly overstate system gaps when transliteration differs but meaning matches; semantic metrics help.

Releases a code-switching dataset for Arabic(2 dialect groups)-English, Persian-English, and German-English; demonstrates why WER alone is misleading and pairs it with BERTScore to separate orthography/transliteration variation from semantic errors; includes a cost-efficient data selection pipeline. Select 300 samples per pair via heuristic filtering plus an LLM ensemble (GPT-4o + Gemini 1.5 Pro) to confirm code-switching, cutting LLM costs ~91%; evaluate five commercial ASR systems with WER and BERTScore; analyze difficulty strata and embedding-based semantic proximity. WER and BERTScore agree on system ranking for Arabic/Persian pairs (Kendall's $\tau = 1.0$) but WER inflates apparent performance gaps by ~30% due to penalizing meaning-preserving transliterations; ElevenLabs Scribe v2 is best overall (13.2% WER, 0.936 BERTScore).

Field Overview

Today's batch is dominated by foundation-model engineering and evaluation: at least ~25–35 papers on LLM/agent reliability (red-teaming & jailbreaks, influence ops, watermarking/deepfake detection, privacy/unlearning, benchmark gaming/evaluation awareness, and calibration/uncertainty), plus another ~20–30 on agentic systems (multi-agent coordination, memory/context management, tool-use protocols, self-evolving skills, and long-horizon serving). A second major cluster is retrieval/RAG and structured grounding (10–15) spanning chunking/context compaction, KG/LaTeX/document RAG, dense retrieval/embeddings, and law/finance/science benchmarks—often framed as “verifiability” and evidence dependence rather than raw accuracy. On the modeling side, there's a noticeable diffusion/flow-matching resurgence beyond images (10–15) including diffusion language models, diffusion policies for robotics, and RL post-training for diffusion/flow models, alongside systems work on efficiency (KV-cache compression, quantization/MoE serving, GPU kernel generation, checkpointing). A surprising emerging direction is mechanistic/representation interpretability tied to neuroscience and sparse autoencoders (6–10) (brain-LLM alignment, SAE-based steering, attribution contracts), suggesting interpretability is shifting from toy analyses to scalable tooling and cross-lingual/biological validation.