

Multilingual NLP

An Investigation of Translationese in the Generations of Multilingual Large Language Models [\[arxiv\]](#)

Maria Valentini, Téa Wright, Julisa Granados, Eliana Colunga, Katharina von der Wense

Defines an evaluation pipeline to test whether multilingual LLM outputs exhibit translationese, and whether any signal matches human translation artifacts across languages.

Reframes “LLM translationese” as a measurable empirical question and contributes a structured assessment: compare MLLM generations to non-translated and human-written/translated baselines, and diagnose whether any translation-like signature is human-like or model-specific. Apply established translationese indicators to outputs from multilingual LLMs in five languages; use high-accuracy classifiers as aggregate detectors plus feature-level analyses (e.g., variance/feature differences). Add human annotations for German and Spanish as an extra evaluation signal. The paper reports an assessment and feature-based characterization of translationese-like patterns in MLLM generations; the abstract does not claim prevalence, direction, or downstream impact, only that classifiers/feature analyses and limited human judgments are used to examine distinguishing cues.

There is No Theoretical Curse of Multilinguality For Embedding Space Structure [\[arxiv\]](#)

Niyati Bafna, Neha Verma, Vilém Zouhar, Philipp Koehn, David Yarowsky

Shows there’s no inherent geometric “curse of multilinguality”: even strong cross-lingual alignment constraints can be satisfied with embedding dimension growing only logarithmically in the number of languages.

Formalizes “perfect multilinguality” with explicit structure-preservation and alignment conditions, then proves the minimal embedding dimension needed scales as $O(\log L)$, implying observed multilingual degradation is not a fundamental representational/geometric necessity. Define two multilinguality conditions capturing monolingual structure + consistent cross-lingual alignment; analyze the capacity question “smallest d for L languages,” and prove constructive/lower–upper bounds yielding logarithmic scaling; include a small empirical sanity check. Main theorem: under their strong definition, required embedding dimension grows only like $\log(\text{number of languages})$. Conclusion: any practical “curse” likely comes from data imbalance, interference, or optimization—not unavoidable embedding-space geometry.

Thinking in a Low-Resource Language: What SFT Builds, What RL Fixes, What Accuracy Cannot See [\[arxiv\]](#)

Ayoub Kirouane, Christos Petrocheilos

Demonstrates you can make frontier models produce readable reasoning in a low-resource language without changing benchmark accuracy; the real gains are controllability and auditability.

Separates final-answer accuracy from “legible, steerable reasoning in the user’s language,” showing SFT and RL can drastically change the latter while accuracy stays noisy/flat; introduces six length-robust behavioral metrics plus experimental controls (pre-registration, random-reward RL). Measure baseline: models rarely produce Greek reasoning traces even when prompted. Apply SFT to induce Greek reasoning; evaluate via gated metrics (language-of-thought adherence, channel separation, formatting, grammaticality, capability). Then apply RL with verifiable rewards to fix specific defects (format fallback, channel leakage, override obedience) and compare to random-reward control. Accuracy is dominated by seed noise (~7.7 points), masking training effects. Behavior shifts are large: base models show 0/1000 Greek traces; SFT yields ~98% Greek reasoning with preserved ability. RL nearly eliminates format fallback (24%→2.5%) and leakage (3.5%→0%), and improves “think in English” override by ~9 points; random-reward control stays flat.

What Tokens are Learned when Tokenization is Optimized Jointly with Language Modeling? [\[arxiv\]](#)

Saketh Reddy Vemula, Parameswari Krishnamurthy

Jointly learned tokenization produces qualitatively different token “units” (varying by method and language) that can lower perplexity while remaining competitive on downstream tasks.

A typology-aware comparison showing “tokenizer optimization” is not monolithic: different joint schemes yield very different vocabularies, linked to language morphology/script, and these vocabularies can still transfer in BERT-style pretrain/finetune settings. Compare

two joint tokenization families vs fixed-tokenizer baselines across 18 languages. SSLM-style methods learn contextually useful segmentations (often morpheme-like); H-Nets favor byte/computational efficiency (longer tokens, low overlap with subwords). Analyze overlap/length/dynamics and evaluate as pretokenization for BERT-style models via perplexity + downstream tasks. Joint optimization changes token structure fundamentally: SSLMs trend toward morphologically aligned, prediction-efficient units; H-Nets drift toward byte-efficient long tokens with minimal overlap to standard vocabularies. Agglutinative languages show more dynamic segmentation. Despite mismatch, SSLM pretokenization consistently reduces perplexity and keeps downstream performance competitive.

Multilingual Speech Processing

Speak in Context: Multilingual ASR with Speech Context Alignment via Contrastive Learning [\[arxiv\]](#)

Yuchen Zhang, Haralambos Mouratidis, Ravi Shekhar

Builds modular multilingual context-aware ASR by pairing frozen pretrained components with contrastive alignment between speech and context, yielding consistent gains.

A multilingual ASR framework that treats dialogue history/biasing words as first-class inputs and adds a principled speech–context contrastive objective, while keeping a frozen speech encoder and decoder-only LM for modularity. Connect frozen speech encoder to frozen decoder-only LM via a lightweight projection; feed structured context prompts (history, bias lists) into the LM; add contrastive learning to align speech and contextual representations in a shared space. On >1,500 hours of conversational speech across 11 languages and 5 English dialects, context improves ASR consistently, and contrastive alignment adds further gains across context types, for >5% aggregate improvement.

Language Family Matters: Evaluating LLM-Based ASR Across Linguistic Boundaries [\[arxiv\]](#)

Yuchen Zhang, Ravi Shekhar, Haralambos Mouratidis

For LLM-based multilingual ASR, sharing the speech-to-LLM connector within language families reduces parameters and often improves cross-domain robustness versus per-language connectors.

Challenges per-language adapter training by arguing the connector is mainly an acousticLLM-space mapping that can be shared among related languages; proposes a simple deployment strategy: one connector per language family, reused across family languages. Freeze speech encoder and pretrained LLM; train only a lightweight connector. Group languages by family and train a single connector on pooled family data; at inference, any family language uses the same connector (sharing driven by an external linguistic prior). Family-shared connectors substantially cut trainable parameters while matching or improving ASR quality, with the clearest gains in cross-domain generalization (e.g., curatedcrowdsourced speech). Suggests the connector learns reusable family-level correspondences rather than brittle language-specific mappings.

Foundation Model Theory

Geometric and Behavioral Stratification in Transformer Residual Streams [\[arxiv\]](#)

Nelson Guda

Anchoring residual-stream analysis to the model’s current predicted-token direction reveals a thin, decisive “prediction interface” plus a large complementary subspace that is behaviorally essential but variance-invisible.

Introduces the content-defined “prediction direction” (unembedding of the currently predicted token) as an internal reference axis; shows residual streams stratify into a narrow prediction-proximal band concentrating readout-relevant structure and a prediction-distal complement that grows with scale, explaining why variance-first views miss key organization. Across 18 transformers (dense/MoE; base/instruct; ~7B–120B), define per-position prediction-direction anchors; analyze geometry relative to this anchor and run causal perturbations at varying “distances” from it to test behavioral importance, contrasting with PCA/variance-based analyses. Consistent stratification: a scale-invariant, prediction-proximal band is disproportionately critical, while the distal complement expands with model size. Prediction direction is near-orthogonal to top-variance PCs, so PCA misses it, especially with heterogeneous prompts. Perturbing closest directions causes rapid divergence/task-frame shifts; perturbing farther tiers degrades more slowly—showing the complement

can be weakly readout-aligned yet causally necessary for stable behavior.

LLM Evaluation

Judge, Retrieve, or Abstain: Uncertainty-Guarded LLM Judging with Provable Risk Guarantees [\[arxiv\]](#)

Sher Badshah, Ali Emami, Hassan Sajjad

Turns an LLM judge into a selective system that judges, retrieves evidence, or abstains, with finite-sample control of false discovery rate (FDR) among accepted verdicts at a user-set level.

A practical, reference-free judging framework with a formal, user-tunable reliability guarantee: accept verdicts only when calibrated uncertainty says it's safe, otherwise escalate to retrieval or abstain, while controlling FDR on the accepted set (not informal confidence). Two-stage pipeline with two calibrated acceptance thresholds learned on a held-out calibration set: (1) parametric judge outputs verdict + uncertainty; accept if below threshold. Else (2) retrieval-augmented judging; accept if below a second threshold. Thresholds use finite-sample Clopper–Pearson intervals, and the guarantee composes through the routing scheme. Across open-domain QA benchmarks and judge sizes, the system meets the target FDR bound with high probability while achieving higher coverage than single-mode baselines by using retrieval only when needed; provable risk control and practical throughput can coexist for reference-free objective judging.

Field Overview

Today's list is dominated by LLM/agent reliability and governance work: at least ~25–35 papers on agentic systems (multi-agent workflows, harnesses, long-horizon browser/GUI agents, skill generation/memory, and “deep research” benchmarks like WANDR/StartupBench), often paired with safety controls (runtime governance, guardrails, prompt-injection/RAG safety, memory leakage, jailbreak/ablation defenses). A second major cluster is evaluation/uncertainty/calibration (roughly ~20+), including LLM-as-judge risk guarantees, rubric interference, conditional/cheap-signal evaluation, leakage audits, and selective prediction/conformal methods across domains (clinical, fraud, time series). There's also a noticeable systems-and-efficiency thread (~15–25) focused on inference/serving and compression (KV-cache paging/migration, mixed precision attention, quantization, MoE routing, GPU kernel optimization/PTXBench/KernelArc, “serve LLaMA-70B on \$60 GPUs”), plus a strong multimodal/audio-speech pocket (~10–15) spanning MLLM uncertainty/safety, emotion across speech/faces, deepfake speech detection, and music/audio-language benchmarks. A surprising emerging direction is the “agent harness” as a first-class research object (Agent Lightning, LEGO-RL, HarnessRisk, workspace/versioning, provisioning), suggesting the field is shifting from model-only improvements to end-to-end operational scaffolding and auditability.