

Multilingual NLP

Ladders in Chaos: When, How, (and Perhaps Why) Does Test-Time Scaling Improve LLM Machine Translation [\[arxiv\]](#)

Di Wu, Sergey Troshin, Christof Monz, Antske Fokkens, Vlad Niculae

Test-time scaling in MT isn't free: sequential self-refinement boosts fluency, but at high budgets it can erode faithfulness as extra target-side context steers the model off-source.

Disentangles parallel (i.i.d. Best-of-N) vs sequential (candidates conditioned on prior attempts) scaling and shows sequential changes the candidate distribution: more natural outputs, but a non-monotonic fluency–accuracy tradeoff at larger inference budgets; human eval + ablations point to target-context as the driver. Compare parallel sampling+selection vs sequential self-improvement chains across budgets; use human ratings that separate fluency/naturalness from accuracy/faithfulness; ablate target-side context construction and temperature to test robustness and mechanism. Sequential scaling is more sample-efficient and reaches a higher ceiling than parallel, but accuracy can drop as budget grows even while fluency improves; ablations tie gains (and drift) to added target-side context and its design.

OmniFusion: Simultaneous Multilingual Multimodal Translations via Modular Fusion [\[arxiv\]](#)

Sai Koneru, Matthias Huck, Jan Niehues

OmniFusion fuses a multimodal perception model with a translation LLM to do low-latency simultaneous multilingual translation that can use audio and images when available.

Proposes a modular, jointly trained fusion of a pretrained multimodal foundation model and a translation-focused LLM to avoid cascade drawbacks and enable end-to-end multimodal simultaneous translation. Connects multiple-layer hidden states from Omni 2.5-7B into SeedX PPO-7B (not just final features) and trains end-to-end; supports speechtext, speech+imagetext, and text+imagetext translation modes. Reports effective use of audio/visual context, ~1s lower latency vs ASRMT cascades in simultaneous speech translation, and improved overall translation quality (per abstract).

XHotpotQA: A Benchmark for Cross-Lingual Knowledge Composition in Multi-Hop Question Answering [\[arxiv\]](#)

Iman Barati, Arash Ghafouri, Behrouz Minaei-Bidgoli

XHotpotQA forces multi-hop QA to cross language boundaries mid-reasoning, revealing failures that translation-to-one-language benchmarks hide.

Creates a HotpotQA-style benchmark where question, bridge evidence, answer evidence, and distractors can be in different languages, represented with evidence-dependency roles and sentence-level supporting-fact supervision for diagnosis. Controlled language-role assignments per instance; supplied-candidate setting (gold paragraphs + distractors) to isolate reading/composition from retrieval; evaluates selector vs reader under mismatches (including different scripts) using support labels. Largest drops occur at language interfaces: full question–evidence mismatch reduces answer F1 by ~10–16; different-script evidence drops ~12–24; selector drops are small (~1.7–1.8), implicating multilingual reading/composition as the bottleneck.

When Tokenizers Fail: Byte-Level Chunking for Zero-Shot Transfer to Low-Resource Languages [\[arxiv\]](#)

Sanjeev Kumar, Atsuki Yamaguchi, Nikolaos Aletras

Gets byte-level robustness for low-resource transfer without training a full byte LM by learning byte chunks aligned to a frozen subword LM, with light boundary supervision.

Hybrid “byte-to-chunk + frozen subword LM” framework that removes brittle tokenizer effects: learn word-aligned byte chunks while distilling/aligning them into the frozen LM’s representation space. Hierarchical byte encoder dynamically chunks UTF-8; initialize/anchor with frozen subword representations; train with chunk-alignment loss to match subword-derived targets; add lightweight POS supervision to encourage linguistically sensible boundaries. Improves word-level morphology tasks across six languages over subword-tokenized transfer baselines, with up to +13.3% POS tagging gain, without massive byte-level pretraining.

One Form to Transfer Them All: Pretraining Multilingual Language Models Beyond Native Orthography [\[arxiv\]](#)

Muge Zhang, Aaron Jencks, Krishna Badikela, Yulia Tsvetkov, Sachin Kumar

For cross-script transfer in multilingual decoder-only LMs, romanize during pretraining: it creates shared surface patterns that scaling can exploit better than native scripts or IPA.

Controlled pretraining study isolating representation choice (native orthography vs IPA vs romanization) and showing script equalization is a primary driver of cross-lingual transfer, not a minor preprocessing tweak. Pretrain 467M/709M/1.03B autoregressive multilingual models on eight languages (four related pairs) under three representations; evaluate in-language and transfer (including unseen languages); test post-hoc romanization finetuning of native-text models. Romanized pretraining yields best transfer; the advantage over native orthography grows with model size; IPA usually beats native but trails romanization; post-hoc romanization finetuning can hurt covered languages and only marginally helps missing-script cases—romanization must shape pretraining/tokenizer stats.

Multilingual Speech Processing

Phoneme- and Word-Level Metrics Using Self-Supervised Speech Representations for Forced Alignment Evaluation

[\[arxiv\]](#)

V. S. D. S. Mahesh Akavarapu, Michael Daniel, Gerhard Jäger

Reference-free forced-alignment evaluation is possible: SSL speech models can score whether phoneme/word boundaries are acoustically consistent, avoiding human timestamps.

Defines two scalable, multilingual alignment QA metrics—PCMI (phoneme-level) and WACS (word-level)—that use self-supervised speech representations to assess alignment quality without ground-truth boundaries; released as tooling. PCMI: mutual information between aligned phoneme labels and unsupervised clusters of SSL frame embeddings. WACS: consistency of SSL segments for repeated words using DTW to handle duration variation. Requires only audio, transcript, and alignment. Metrics degrade under random/systematic alignment perturbations; across 85 FLEURS languages they consistently separate better/worse aligners; correlate strongly with timestamp-based quality on 45 DoReCo languages, supporting validity as reference-free proxies.

Foundation Model Theory

How Do Linear Probes Emerge? A Circuit-Tracing Framework with Concept-Targeted Attribution [\[arxiv\]](#)

Vedant Palit, Florent Draye, Terry Jingchen Zhang, Bernhard Schölkopf, Zhijing Jin

Concept-Targeted Attribution turns linear probes into traceable circuits, showing probe mechanisms can be causally distinct from the circuits that drive next-token outputs.

Introduces CTA: attribute not to a logit, but to alignment with a probe direction in the residual stream, yielding probe-specific attribution graphs with predictive structure and causal separability from logit circuits. Builds transcoder-style attribution graphs (via Cross-Layer Transcoders) targeting probe scores (dot product with probe direction); analyzes global graph stats and per-prompt sparse components; validates with targeted ablations of probe-relevant vs logit-relevant features. Graph features predict probe accuracy across concept types (corr ~0.91, R² ~0.84); ablations cleanly separate mechanisms—removing probe features lowers concept scores with little effect on tokens, while removing logit features flips tokens ~92–100% with probe scores largely unchanged.

LLM Evaluation

Rating the Raters: Rasch Measurement Theory for LLM Evaluation [\[arxiv\]](#)

Pratik S. Sachdeva, Nathan Boudol

Using Rasch measurement models exposes LLM rater severity, miscalibration, and instability that simple agreement/correlation

metrics miss.

Applies many-facet Rasch theory to LLM-as-rater evaluation, explicitly separating item difficulty from rater effects (severity, scale use, consistency) and other facets (e.g., order), yielding interpretable bias diagnostics. Fit many-facet Rasch models to ordinal ratings from nine LLMs on Measuring Hate Speech; analyze severity/leniency, item-level calibration, order effects, target-identity sensitivity, and category usage patterns. LLMs differ substantially as raters despite similar aggregate scores: systematic harsh/lenient biases, item-specific miscalibration, order sensitivity, identity effects, and differing threshold/scale usage—showing why rater choice and calibration matter.

Field Overview

Today's batch is dominated by LLM/agent engineering and governance: at least ~35–45 papers touch agentic workflows (tool use, memory/context management, GUI/computer-use agents, multi-agent coordination, harness/OS layers like String/CrabOS/Logos, and agent RL/credit assignment such as VICT/HARTS/RTPO), with a noticeable sub-cluster on evaluation realism/benchmarks for agents (e.g., RealSWE, mobile assistants, MAP accessibility planning, LoopArena, PCFBench). A second major theme is efficiency for deployment—roughly ~15–20 papers on inference acceleration and memory (speculative decoding/tree drafting, KV-cache eviction theory, sliding-window vs linear attention, quantization incl. NVFP4/bit-width allocation/hybrid precision, output-embedding bandwidth, energy accounting). Safety/security/privacy is another heavy concentration (~15–25): prompt injection and RAG poisoning/defenses (LongPIBench, CamoDocs, CAITLYN, Semantic Overlays), moderation/watermarking/AIGC detection (OpenStamp, semantic watermarking, stylometry), plus privacy/unlearning and context exfiltration (AIM, GRACE, ContextLeak, DP audits). Emerging directions include “evidence-grounded abstention/verification” for RAG and agents (Knowing Before Answering, Twin Worlds, HALT, verifier-instrumented credit tracing) and a parallel rise in multimodal/speech evaluation and robustness (audio-visual conflict, speech evidence gating, prosody transfer), suggesting the community is shifting from raw capability gains toward controllable, auditable, and cost-aware agent deployment.