

Multilingual NLP

Are Multilingual Models Actually Improving? Isolating True Cross-Lingual Transfer [\[arxiv\]](#)

Prasoon Bajpai, Eleftheria Briakou, Colin Cherry, Preethi Jyothi, Vihari Piratla

Many reported “multilingual gains” mostly reflect better source-language accuracy; HAT isolates genuine cross-lingual transfer.

Shows standard transfer metrics are confounded by source-language difficulty and introduces Hardness Adjusted Transfer (HAT) to factor that out, revising claims about scaling and small-model transfer. Estimate each item’s source-language hardness and normalize target-language performance against it, so transfer is measured as doing unusually well in the target given how hard the same content is in the source; apply across models/sizes/benchmarks. With HAT, small models no longer look inherently bad at transfer; scaling yields smaller true transfer gains than raw curves suggest; nonetheless, model generations still show real transfer progress over time.

Beyond ‘One Language, One Script’: Quantifying Orthographic Bias in Multilingual VLMs with PuMVR [\[arxiv\]](#)

Prabhjot Singh, Bhushan Pawar, Madhu Reddiboina

Multilingual VLMs can fail the same language when written in a different script; PuMVR makes this orthographic bias measurable.

Introduces PuMVR (Punjabi visual reasoning) with parallel items in Gurmukhi/Shahmukhi/Roman and proposes Script Consistency Rate (SCR) to expose script-specific brittleness hidden by average accuracy. 375 image-reasoning tasks replicated across three scripts; evaluate 10 VLMs with accuracy, Script Gap (between-script deltas), and SCR (requires consistent success across scripts); compare reasoning traces across scripts. Models show Script Gaps up to 16 points and SCR as low as 24.8%; images raise absolute accuracy but don’t remove relative script bias, and reasoning trajectories can diverge purely due to orthography.

First-Token Broadcasters: Mechanistic Origins of Language Identity and Distributed Robustness in Transformers

[\[arxiv\]](#)

Arjun Pillai, Christian Hoang, Anjelo Jann Laroza

Language choice is often controlled by a few attention heads that lock onto the first prompt token and broadcast language identity forward.

Defines LIHA to causally locate language-identity control; finds “first-token broadcaster” heads with outsized influence and shows structured, layer-wise redundancy; instruction tuning can relocate/localize this circuit. Ablate each attention head and measure language switch rate on 2,700 prompt–language pairs (7 languages); inspect attention patterns for persistent first-token focus; test compensation by re-running ablations and tracking which heads take over; compare base vs instruct models. In GPT-2, a small set of heads (notably L6H1) strongly drives switching and matches the broadcaster pattern; compensation comes predictably from higher layers; in Qwen2.5-1.5B, instruction tuning concentrates control early (layer 0) versus diffuse control in the base model, with similar early localization for non-Latin scripts.

Phonemes to the Rescue: Multilingual Tokenization Based on International Phonetic Alphabet [\[arxiv\]](#)

Milan Miletic, Julie Kallini, Ekaterina Shutova

IPA-based tokenization reduces script-driven inequities by mapping languages into a shared phonetic symbol space before subword learning.

Argues the tokenizer is a key source of multilingual unfairness and shows that phonemizing into IPA before training subword vocabularies improves segmentation quality and cross-script/language transfer. Train matched subword tokenizers on (a) raw multilingual text vs (b) IPA-converted text across 24 languages/14 scripts; compare segmentation quality and generalization to unseen languages/scripts. IPA tokenizers consistently improve tokenization quality—largest on non-Latin scripts—and generalize better to unseen languages and even unseen scripts due to reusable merges over a compact shared inventory.

Multilingual Speech Processing

Adding Robust Code-Switching Capabilities to High Performance Multilingual ASR [\[arxiv\]](#)

Enes Yavuz Ugan, Alexander Waibel

You can add strong code-switching ASR without hurting monolingual accuracy via a constrained, parameter-efficient adaptation.

Proposes Bayesian factorized adaptation to integrate code-switching behavior into a high-quality multilingual ASR model while avoiding catastrophic interference from standard fine-tuning. Learn a small “code-switching add-on” (factorized update) under a Bayesian prior that anchors parameters near the pretrained solution unless code-switched evidence demands change; train with limited (synthetic) code-switched data. Cuts errors on code-switched words by 32.87% and improves overall WER by 5.31% while keeping monolingual performance essentially unchanged.

Interleaved Speech Language Models Latently Work In Text [\[arxiv\]](#)

Talia Sternberg, Gallil Maimon, Yossi Adi

Interleaved speech–text LMs often internally form a latent transcript—briefly “thinking in text”—while processing speech. Mechanistically shows that, even without explicit ASR training, interleaved SLMs make the correct written word decodable at intermediate layers, suggesting an implicit transcription step used for next-token prediction. Logit-lens probing across layers at speech positions to see when the correct text token becomes high-probability; track subsequent shift to text-like next-word prediction then back to speech-token generation; compare training/initialization variants. For up to 77% of analyzed data, the correct written word appears among top text-token candidates at some intermediate layer; interleaving data and text-LM initialization strengthen this effect, which correlates with better spoken-knowledge performance.

Foundation Model Theory

Factual Retrieval in LLMs Is a Redundant, Distributed and Non-Contiguous Process [\[arxiv\]](#)

Hail Hochman, Natalie Shapira, Yoav Goldberg

Factual recall is implemented by redundant, non-contiguous layer subsets, so “where a fact lives” is not a single localized block.

Introduces “attribute-computation paths” and an iterative patching procedure to find minimal layer sets sufficient for entityattribute transformation, showing multiple alternative routes for the same fact. Activation patching between clean (correct) and corrupted runs; iteratively search/shrink to minimal layer subsets that restore the correct attribute; analyze contiguity and multiplicity of sufficient subsets across many queries. In LLaMA 3.1 8B and Qwen3 8B, paths often skip layers (non-contiguous) and multiple distinct minimal layer subsets can recover the same fact, evidencing true redundancy and explaining why localized editing often fails.

Field Overview

Today’s submissions are dominated by agentic LLM systems and their failure modes: at least ~40–60 papers cluster around long-horizon agents (memory/compaction, tool use, routing, harnesses, and benchmarks like PlanBench-XL, EnterpriseClawBench, MacAgentBench, ChainWorld, CLI-Universe), plus a similarly large safety/governance/security cluster (jailbreak detection, prompt injection, memory poisoning, guardrails, privacy, citation hallucinations, legal/medical reliability). A second major theme is efficiency/serving/compression for deployment (KV-cache/quantization/speculative decoding/edge inference/energy costs)—roughly ~25–40 papers spanning prompt/RAG compression, low-rank/quantization, scheduling, and energy modeling. Two notable “surprising” concentrations: (1) a very large audio/speech wave (TTS, codecs, ASR hallucinations, deepfake detection/watermarking, audio-language models)—easily ~40+ papers; and (2) a strong push toward verifiable evaluation and process-level rewards (PRMs/RLVR, conformal/OOD rejection, deterministic eval replacements for LLM-as-judge), suggesting the community is shifting from raw capability gains to measurement, auditing, and

controllable reliability.