

Multilingual NLP

DiM³: Bridging Multilingual and Multimodal Models via Direction- and Magnitude-Aware Merging [\[arxiv\]](#)

Zijing Wang, Mingyang Wang, Ercong Nie, Yongkang Liu, Shi Feng, Mengjie Zhao, Daling Wang, Xiaocui Yang, Hinrich Schütze

DiM₃ makes an English-centric multimodal model multilingual with no new multimodal data by merging a multilingual “delta” into the language backbone without breaking vision-language skills.

Shows multilingual gains can come from injecting the multilingual fine-tuning update into a multimodal model, but only with a merge rule that handles conflicts between multilingual vs multimodal parameter changes; proposes a training-free, per-parameter composition to preserve both. Given a shared base LLM, compute deltas to (a) a multilingual-tuned LLM and (b) a multimodal-tuned LLaVA/Qwen-VL-style model (vision encoder/projector fixed). DiM₃ combines deltas per parameter using direction (alignment) and magnitude to reinforce compatible updates and damp/choose between conflicting ones. Across LLaVA-family and Qwen-based multimodal models over 57 languages, DiM₃ boosts multilingual text and vision-language performance over the original multimodal model and standard merging baselines, while largely retaining general multimodal ability; even improves already-multilingual multimodal models. Analysis suggests mid-layer representations become more cross-lingually aligned while upper layers keep task structure.

Direct Translation between Sign Languages [\[arxiv\]](#)

Zetian Wu, Bowen Xie, Wuyang Meng, Milan Gautam, Stefan Lee, Liang Huang

Direct sign-to-sign translation is feasible and better than sign-text-sign cascades by creating synthetic sign–sign pairs via back-translation.

Addresses the lack of parallel sign-language video pairs by synthesizing sign–sign training data from existing sign–text corpora, enabling a single multilingual model to translate between sign languages without text as an intermediate. Use textsign models to back-translate text into another sign language, forming pseudo-parallel sign–sign pairs. Jointly train an mBART-style multilingual encoder–decoder for both textsign and signsign across ASL/CSL/DGS. Direct signsign beats cascades in quality and latency: ~20% lower DTW-aligned MPJPE, ~50% higher BLEU-4 via signtext back-evaluation, and ~2.3 $\times$ faster inference; similar trends hold on limited real cross-lingual sign data.

Do LLMs Know What Luxembourgish Borrows? Probing Lexical Neology in Low-Resource Multilingual Models [\[arxiv\]](#)

Nina Hosseini-Kivanani

Multilingual LLMs poorly detect Luxembourgish borrowings unless given structured lexical evidence; small knowledge-graph prompts sharply improve donor-language classification.

Creates LexNeo-Bench for token-level native vs borrowed (French/German/English) labeling and shows failures are largely due to missing structured lexical/morphological context; knowledge-graph prompting supplies that context and closes much of the gap. 3,050 labeled tokens from Luxembourgish news (LuxBorrow). Probe multilingual LLMs on 4-way donor classification and a binary borrowed-vs-native proxy; retrieve an instance-specific subgraph (donor cues, orthography/morphology, related lexemes) and insert it into the prompt. Without context, models are only slightly above chance on 4-way classification (~25–35%); with KG prompting, accuracy jumps to ~71–81% and size matters less, implying information access/structure is the bottleneck. The binary “innovation” proxy remains sensitive to prompting and still difficult.

Dictionary Insertion Prompting for Multilingual Reasoning on Multilingual Large Language Models [\[arxiv\]](#)

Hongyuan Lu, Zixuan Li, Wai Lam

Dictionary Insertion Prompting boosts multilingual reasoning by interleaving English glosses inside non-English prompts, letting English-dominant LLMs reason in their strongest space.

Proposes DIP, a minimal prompting trick that outperforms adding the same dictionary content as a separate glossary block, suggesting local grounding of English cues is key for multilingual understanding + reasoning. Select words via a bilingual dictionary and insert

English translations inline next to source-language tokens; compare to prepend/append glossary variants. Build multilingual reasoning sets by translating English datasets with NLLB and validating via back-translation plus some manual checks. DIP improves multilingual reasoning across many languages (reported from 10 up to 200 FLORES languages depending on dataset), and inline insertion consistently beats equivalent front/back glossary placement, supporting the claim that context-attached glosses better anchor meaning for downstream reasoning.

Building Arabic NLP from the Ground Up: Twenty Years of Lessons, Failures, and Open Problems [\[arxiv\]](#)

Wajdi Zaghoulani

Two decades of Arabic NLP show the main blockers are often socio-institutional—data, incentives, communities—not just models or linguistic complexity.

A practitioner retrospective that distills “counterintuitive lessons” and concrete failures, reframing Arabic NLP progress as a socio-technical project shaped by coordination, incentives, and deployment realities. Narrative analysis across two phases: early infrastructure/resource building and later social-media/computational social science work; organizes evidence as lessons learned plus failure case studies. Argues the hardest problems are social/institutional/epistemic, supported by three lessons (dataset building is social; shared-task communities can matter more than tasks; CSS needs skills NLP training omits) and three failures (depression corpus not adopted clinically; spreading effort across too many shared tasks; assuming MSA resources transfer to dialects).

Multilingual Speech Processing

SCRIBE: Diagnostic Evaluation and Rich Transcription Models for Indic ASR [\[arxiv\]](#)

Kavya Manohar, Arghya Bhattacharya, Kush Juvekar, Kumarmanas Nethil

SCRIBE replaces blunt WER with Indic-aware, user-cost-aligned ASR diagnostics, revealing error types (entities, numerals, punctuation) that matter most.

Introduces an evaluation framework that (i) avoids unfair WER penalties from sandhi/agglutination merges/splits and (ii) reports error categories tied to correction effort; releases benchmarks and open “rich transcription” ASR models for Hindi, Malayalam, Kannada. Sandhi-tolerant alignment plus categorical scoring (lexical, punctuation, numeral, domain-entity), including domain vocabulary injection to track critical terms; uses an LLM-assisted pipeline to curate/label rich transcripts and benchmarks. SCRIBE’s breakdown matches expert notions of impactful errors better than WER, reduces false penalties from valid merges/splits, and exposes cases where similar WER hides severe numeral/entity corruption; released resources enable reproducible, more realistic optimization for Indic ASR.

Field Overview

Today’s batch is dominated by LLM/agent post-training and evaluation: at least ~25–35 papers on RLVR/RLHF/DPO-style alignment (e.g., GRPO variants, token credit assignment, reward hacking, verifier calibration) plus another ~20+ on agent benchmarks, long-horizon workflows, and memory systems (MemGym, DecisionBench, OpenComputer, Terminal-World, routing/scheduling). A second major cluster is efficiency for deployment—quantization/KV-cache/attention and serving infrastructure—with ~20+ papers spanning static/mobile quantization, KV-cache compression, speculative decoding, and WebGPU/browser inference. Safety/reliability is also heavily represented (~15–25 papers) across jailbreak/prompt-injection defenses, hallucination auditing (including RAG/GraphRAG grounding and evidence tracing), unlearning/privacy, and AI-generated text detection. Notable emerging directions include diffusion/flow-based language modeling and “one/few-step” generation (FlowLM, PulseCol) and a surprisingly large audio/spoken-dialogue push (full-duplex speech models, audio LLM attacks, long-form audio understanding), suggesting multimodal agents are becoming a first-class focus rather than an add-on.