

Multilingual NLP

SomaliWeb v1: A Quality-Filtered Somali Web Corpus with a Matched Tokenizer and a Public Language-Identification Benchmark [\[arxiv\]](#)

Khalid Yusuf Dahir

SomaliWeb v1 turns noisy “Somali in web dumps” into a reproducible Somali-first stack: cleaned corpus, matched tokenizer, and a public LID benchmark.

Releases a quality-filtered Somali web corpus (~303M tokens), a Somali-trained 16K BPE tokenizer, and a language-ID benchmark, showing upstream duplication/encoding/boilerplate issues can dominate low-resource data quality. Aggregate Somali from HPLT v2, CC100, and Somali Wikipedia; apply a six-stage pipeline targeting exact duplicates, mojibake, and near-duplicates (Jaccard thresholding); train a 16K BPE tokenizer on the cleaned distribution; benchmark multiple production LID systems on Somali. Even “cleaned” sources remain heavily flawed: HPLT v2 Somali has 17.3% exact duplicates, 56.1% docs with mojibake, and 10.7% near-duplicates after dedup (=0.80). The Somali BPE-16K yields 40.2% fewer tokens than c1100k_base on FLORES-200 Somali devtest, indicating much better tokenization efficiency (no downstream gains claimed yet).

A Data-Efficient Path to Multilingual LLMs: Language Expansion via Post-training PARAM Δ Integration into Upcycled MoE [\[arxiv\]](#)

Hao Zhou, Tianhao Li, Zhijun Wang, Shuaijie She, Linjuan Wu, Hao-Ran Wei, Baosong Yang, Jiajun Chen, Shujian Huang

You can expand an LLM to new languages without redoing costly alignment by isolating languages in MoE experts and transferring alignment as a post-training parameter delta.

Avoids the usual “CPT then re-align” cost and merge trade-offs by upcycling a dense model into MoE (reducing cross-language weight conflict) and then grafting an alignment delta onto the multilingual CPT model. Upcycle dense base MoE; run multilingual continued pre-training to learn new languages; instead of full alignment, expand and integrate a post-training parameter delta (Δ_{post}) into the MoE-structured CPT model to transfer instruction-following behavior. Across base models and different post-training deltas, the MoE+ approach outperforms compute- or parameter-matched baselines, improving new-language performance while preserving original capabilities—where data-free merging typically degrades one side.

Mixture of Experts for Low-Resource LLMs [\[arxiv\]](#)

Ori Bar Joseph, Smadar Arvatz, Noam Kayzer, Dan Revital, Sarel Weinberger

Multilingual MoE LLMs can “collapse” expert routing for low-resource languages in deep layers; balanced bilingual continual pre-training restores routing diversity and boosts performance.

Identifies a layer-localized, measurable routing pathology (deep-layer entropy collapse) for underrepresented languages and shows it’s fixable; proposes routing entropy/specialization as practical diagnostics tied to downstream quality. Probe expert-selection distributions per layer in two MoE models (Qwen3-30B-A3B; Nemotron-3-Nano-30B-A3B) for English vs Hebrew/Japanese; quantify with routing entropy and specialization metrics; compare interventions: balanced bilingual continual pre-training vs supervised fine-tuning. Hebrew shows sharp deep-layer routing collapse (tokens funnel into few experts) unlike English; balanced bilingual CPT substantially reverses collapse (higher entropy, more shared experts) while SFT only partially helps. Similar signatures appear for Japanese, and routing recovery correlates with downstream benchmark gains.

Why Do Safety Guardrails Degrade Across Languages? [\[arxiv\]](#)

Max Zhang, Ameen Patel, Sang T. Truong, Sanmi Koyejo

Apparent multilingual safety drops often reflect measurement confounds; a multi-group IRT model separates true guardrail weakness from prompt and language effects.

Replaces raw Jailbreak Success Rate with a decomposed model of refusals: language-agnostic robustness, prompt difficulty, language-wide difficulty, and promptClanguage gaps capturing genuine cross-lingual vulnerabilities. Fit a multi-group Item Response Theory

model to refusal/compliance outcomes over (model config, prompt, language); validate near-1D latent “refusal ability” via factor analysis; analyze gap outliers with native-speaker checks for mistranslation/concept mismatch; evaluate predictive power on MultiJail (1.9M rows, 61 configs, 10 languages). After decomposition, “low-resource is always less safe” fails: for 22 configurations, English is more vulnerable than some low-resource languages once factors are separated. Cross-lingual gaps cluster in categories like physical harm (e.g., Theft/Weapons) and lower-resource languages; severe mistranslations create extreme outliers. The model predicts refusals well (AUC ~0.94), outperforming simpler baselines.

Multilingual Speech Processing

WASIL: In-the-Wild Arabic Spoken Interactions with LLMs [\[arxiv\]](#)

Zien Sheikh Ali, Hamdy Mubarak, Soon-Gyo Jung, Hunzalah Hassan Bhatti, Firoj Alam, Shammur Absar Chowdhury

WASIL provides real Arabic spoken-to-LLM interactions with feedback and answerability labels, enabling clean separation of ASR-caused failures from inherently unanswerable turns.

Releases an in-the-wild Arabic voice-assistant dataset (audio, ASR, responses, likes/dislikes) plus answerability annotations, addressing the common misdiagnosis that user dissatisfaction is mainly ASR error. Collect spoken turns with audio, ASR hypotheses, and assistant responses; obtain low-cost gold transcripts via multi-ASR agreement + human post-editing; label answerability (answerable/ambiguous/unsupported-a-request); propose reference-free evaluation comparing outputs from ASR vs gold transcripts using multiple LLM judges. Releases 8,529 labeled turns (14.2% dislikes) plus a 2,000-turn test set spanning MSA and four dialects. The dataset design shows dislikes can stem from ambiguity/unsupported/non-request turns even with perfect transcripts, and enables controlled measurement of gains from better ASR vs better dialogue/refusal handling.

Sometin Beta Pass Notin (SBPN): Improving Multilingual ASR for Nigerian Languages via Knowledge Distillation

[\[arxiv\]](#)

Sewade Ogun

SBPN is an open multilingual ASR model for major Nigerian languages, trained with distillation plus pseudo-labeling to cut WER and beat multilingual baselines.

Introduces and releases SBPN for Yorùbá, Hausa, Igbo, Nigerian Pidgin, and Nigerian English, with a practical two-stage recipe combining teacher distillation, language-specific LM conditioning, and iterative pseudo-labeled training. Stage 1: distill from monolingual ASR teachers into one multilingual student, guided by language-specific N-gram LMs. Stage 2: iterative self-training—generate pseudo-labels on extra audio and retrain to refine recognition. Achieves ~29% average relative WER reduction vs monolingual baselines and outperforms prior multilingual ASR on Common Voice and Fleurs. Releases SBPN-Base (120M) and SBPN-Large (600M) models.

Foundation Model Theory

FishBack: Pullback Fisher Geometry for Optimal Activation Steering in Transformers [\[arxiv\]](#)

Sihan Wang, Jiayi Zhao

Activation steering should respect the model’s own output-sensitive geometry; pullback Fisher gives a closed-form steering direction with fewer side effects than Euclidean tweaks.

Recasts steering as “minimal output-distribution distortion” by measuring activation changes with a Fisher metric pulled back from the softmax through downstream layers, unifying prior steering methods as crude metric approximations. Define a desired first-order change in an output-level concept; compute the pullback Fisher metric via the downstream Jacobian; take the metric-preconditioned (closed-form) minimum-distortion direction and apply iteratively. Derive a layer-wise recursive metric decomposition to interpret ActAdd/CAA/ITI as approximations. On GPT-2 the pullback Fisher metric is far from identity (>97% relative spectral-norm difference) and effectively lower-rank; Fisher-optimal steering achieves the same morphology concept increase with ~1.3–2.5 $\times$ lower KL drift than Euclidean gradient ascent and ~1.5 $\times$ better than CAA at matched concept probability. A spectral “cost ratio” diagnostic predicts when prior methods waste effort.

Field Overview

Today's batch is dominated by agentic LLM systems and their evaluation: at least ~25–35 papers focus on multi-agent workflows, skill libraries/lifecycles, memory, and realistic agent benchmarks (e.g., CHI-Bench, PROTEA, STT-Arena, SaaS-Bench, ShopGym, SocialMemBench/GroupMemBench/LongMINT, SkillsVote/SkillSmith). A second major cluster is reliability/safety for deployed LLMs—hallucination detection and RAG trustworthiness (HalluScore, PARALLAX, ConflictRAG, TRACE, QuCo-RAG), plus prompt-injection/jailbreak and agent security ("AI Agents May Always Fall for Prompt Injections", multilingual jailbreaking, Trust No Tool, Trojan Hippo/ShadowMerge memory attacks), totaling roughly ~20+ papers. Systems/efficiency is also heavily represented (~15–25): long-context attention/KV-cache management and quantization/pruning/routing (KVDrive, CompactAttention, ProxyKV, TriAxialKV, OSCAR, GAMMA, HyDRA), alongside diffusion language models and RLVR/on-policy distillation for reasoning (~10–15; e.g., DACA-GRPO, RLVR in knowledge domains, early-exit/CoT compression). A surprising non-LLM hotspot is audio/music generation and deepfake detection (Stable Audio 3, WavFlow, MusicDET, multiple ASR/TTS and spoofing papers), forming a sizable ~10–15-paper cluster that rivals some core NLP subtopics.