

Multilingual NLP

Reasoning about In-Context Samples for Machine-Translation [\[arxiv\]](#)

Maxime Bouthors, Josep Crego, François Yvon

MT improves when the LLM explicitly extracts reusable source–target fragments from in-context examples before translating.

Proposes fragment-based reasoning over exemplars: treat retrieved in-context pairs as a resource to mine aligned phrase fragments that then guide the final translation; distills this behavior from a teacher via silver fragments/drafts. Retrieve similar parallel exemplars; force an intermediate step that extracts aligned source–target fragments relevant to the input; condition translation on these fragments; train by distilling teacher-produced fragment annotations and drafts into a smaller model. Across Qwen3 variants, six languages, and multiple domains (up to five per language), fragment-guided translation consistently beats standard k-shot prompting and a simple drafting baseline.

Cross-Lingual Alignment Without Joint Training: Do Monolingual Language Models Converge on Universal Representations? [\[arxiv\]](#)

Ej Zhou, Suchir Salhan, Catherine Arnett, Anna Korhonen

Independently trained monolingual LMs often learn hidden-state spaces that can be linearly rotated into each other, enabling cross-lingual transfer without joint training.

Separates multilingual alignment from multilingual training: demonstrates that a single linear map learned from parallel data aligns representations across separately trained models—and that the alignment is functional, not just correlational. Run parallel sentences through each monolingual LM; fit a Procrustes rotation between residual-stream activations; measure alignment across layers/scales/language pairs; test causality via activation patching (rotate donor activations and insert into recipient). Linear alignability strengthens with larger models/more data/closer languages; rotated activation patching can flip a recipient model’s factual cloze answers toward the donor’s, showing the mapped vectors carry causal semantic content.

Vowel Signs Are Not Letters: A Pre-tokenization Ceiling on Multilingual Tokenizer Fertility [\[arxiv\]](#)

Sajal Regmi, Siddhartha Pudasaini, Chetan Phakami Pun

A common pre-tokenizer regex forces abugida scripts to split at vowel marks, creating an unfixable over-tokenization ceiling; making it mark-aware improves Nepali LM perplexity at equal compute.

Identifies a structural tokenizer bug in HuggingFace ByteLevel: defining “word” as `\p{L}+` ignores combining marks (`\p{M}`), so BPE can never merge across vowel-sign boundaries; formalizes a training-free fertility floor and shows a simple regex fix removes it. Analyze how pre-tokenization constrains BPE merges; derive a lower bound on tokens/word from forced splits at combining marks; train controlled tokenizer pairs differing only in letter-only vs mark-aware regex; train matched LMs to isolate perplexity impact. Abugida languages show large forced fertility (up to ~9 tokens/word in Thai) while non-abugida scripts stay at 1.00x; observed fertility matches the predicted floor; mark-aware tokenization yields measurable Nepali bits-per-byte gains even versus a compute-boosted broken tokenizer.

Lost in Compression: A Controlled Cross-Lingual Audit of Extractive Prompt Compressors [\[arxiv\]](#)

Mantas Lukauskas

English-trained extractive prompt compressors can erase non-English context, sometimes making models worse than using no context despite saving tokens.

Provides a controlled 10-language, 5-script audit across 11 target LLMs showing compression is not language-neutral; attributes failures to English-only supervision by contrasting learned compressors, deterministic baselines, and a multilingual-trained compressor; proposes translate-then-compress as a safer workaround. Use fully parallel content across languages; apply multiple compressors (learned English-supervised, multilingual, and deterministic) with budget-matching in each target model’s tokenizer; sweep keep-rates and long-context settings; measure retained utility vs token savings. Large cross-lingual transfer gaps: at 0.33 keep-rate, English retains much

more usable context while some languages (e.g., Lithuanian, Chinese) collapse to near-empty utilization; deterministic baselines and multilingual training avoid the collapse; aggressive learned compression can drop to no-context (or worse) performance, while translate-then-compress often preserves utility at ~half the token cost.

Multilingual Speech Processing

Mapping Written Words to Spoken Words in a Different Language Using Only Visual Grounding [\[arxiv\]](#)

Gabriel Pirlogeanu, Dan Oneata, Horia Cucu, Herman Kamper

Using images as weak supervision, they learn to spot and localize Hindi spoken words from English text queries—no transcripts and no end-to-end speech model.

Shows a simple, data-frugal alignment recipe can replace heavy multimodal training: image tags (e.g., “dog”) weakly select Hindi utterances likely containing the concept, and recurring aligned acoustic patterns reveal the word segment. Generate English tags/captions for each image; for each keyword, collect associated Hindi audios; align utterances pairwise using self-supervised speech features; pool alignment evidence to surface consistent segments; add negative (unrelated) utterances to suppress generic false matches. On keyword spotting/localization, the alignment+pooling approach outperforms a prior attention-based multimodal model; adding negatives further improves results, supporting that many errors come from frequent non-word fragments.

AfriSwitch: A Benchmark for In-the-Wild African Code-Switched Speech Recognition [\[arxiv\]](#)

Gabriel Zencha Ashungafac, Busayo Awobade, Tobi Olatunji

AfriSwitch provides in-the-wild African code-switched ASR evaluation and shows current multilingual ASR performs poorly without Africa-targeted training.

Releases a 61.36-hour human-transcribed benchmark spanning 16 African languages/varieties with code-switch annotations (English spans, per-utterance CMI, switch-point counts), highlighting that switching frequency and mixture balance are distinct dimensions. Collect natural bilingual conversational speech with human transcripts; add structured code-switch metadata (English span tags, CMI, switch counts); benchmark five multilingual ASR systems zero-shot; analyze how mixing properties relate to errors. Zero-shot ASR is weak: best system averages 35.93% WER and no system gets <24% WER on any language; performance tracks Africa-targeted training/adaptation more than model size or nominal language coverage.

Foundation Model Theory

Circuit Condensation: Post-Training that Concentrates a Behavior’s Causal Circuit [\[arxiv\]](#)

Sai Adith Senthil Kumar

Post-training can concentrate a behavior into a much smaller causal circuit, making mechanistic explanations easier to inspect and verify.

Introduces Circuit Condensation: iteratively prune weakly attributing edges and train a small adapter so the remaining edges alone reproduce the behavior, effectively relocating causal responsibility into a compact subgraph. Loop: score edges via attribution, prune candidates, then train a low-rank adapter with the base model frozen to match original behavior using only surviving edges; accept cuts only if target behavior and general capability are preserved; verify circuits with ablations (including exhaustive subset tests when feasible). Produces much smaller circuits than frozen pruning/search: smaller in 30/32 settings, ~8 $\times$ average and up to 316 $\times$ reduction; without weight updates circuits stay larger in 29/32, implying true computation relocation; condensed IOI circuits isolate known attention heads and closely track the original model’s next-token distribution (including its errors).

LLM Evaluation

Which Metrics Save the Most Human Annotation? Prediction-Powered Evaluation and Meta-Evaluation [\[arxiv\]](#)

Automatic metrics can be used as variance reducers—not replacements—to cut human judging while keeping system comparisons unbiased to human labels.

Introduces prediction-powered evaluation for non-verifiable tasks and a meta-evaluation measure, Prediction-Powered Saving Ratio (PPSR), that ranks metrics by how many human annotations they actually save for a fixed statistical goal. Compute metric scores on many items and human judgments on a subset; use prediction-powered inference to debias/correct the metric with the labeled subset while leveraging full-coverage metric scores; provide parametric/nonparametric estimators and analyze paired vs unpaired designs; define PPSR from resulting annotation savings. On WMT datasets, prediction-powered evaluation substantially reduces required human labels while remaining human-grounded and unbiased; PPSR yields more practical, stable metric rankings than correlation-style meta-evals by directly measuring annotation savings.

Field Overview

Today's batch is dominated by LLM/agent reliability and evaluation: at least ~25–35 papers on agent benchmarks, tool-use reliability, harness/runtime governance, and LLM-as-a-judge issues (e.g., AgentJudgeBench, DuMateBench, BTS-AgentBench, ADeptS-Bench, Invocation-Level Reliability, Five Primitives for Governing Agents, verdict staleness, tool-output-as-command). A second major cluster is factuality/hallucination and abstention—roughly ~12–18 papers spanning doubt signals, RAG hallucination diagnostics, evidence-grounded verification, and surveys (e.g., “Can a Model Catch Its Own Hallucinations...”, PoP hallucination detection, “Why RAGs Hallucinate”, hallucination lifecycle survey, ProvenanceGuard/TriShieldRAG). Efficiency/inference engineering is also heavily represented (~10–15 papers) with speculative decoding, diffusion LMs/MLLMs decoding, KV-cache compression, pruning/quantization, and MoE compression (TreeGraft, Affix Cache, TwinKV, LowRankArena, PACE, ClusterAttention). A notable emerging direction is multilingual/cultural and fairness auditing across modalities (~10–15 papers), including tokenization ceilings, cross-platform fairness, code-switch ASR, and cultural narrative homogenization—plus a surprisingly large audio/voice-agent thread (~8–12 papers) around audio-language models, streaming audio-video generation, and speech-first agent training (AudioSpan, SpeechGym, StreamAV-Bench).