

Multilingual NLP

Vision-Language Models are Fragile Multilingual Associators [\[arxiv\]](#)

Ritabrata Chakraborty, Rajat Subhra Chakraborty, Shivakumara Palaiahnakote, Angelo Cangelosi, Umapada Pal

VLMs often lose correct entity–attribute bindings when you switch languages, and the paper traces this to a shifted/weakened internal binding computation—not just an accuracy drop.

Defines multilingual “binding” as stable entity–attribute linking across language changes, and introduces M^2BIND to test it both behaviorally (task success) and mechanistically (whether the same internal signals remain causally necessary). M^2BIND varies context language and query language across multiple languages/scripts to force cross-lingual carryover of associations; evaluates task metrics plus causal probing/interventions on internal representations to localize binding-relevant layers and measure their causal effect on decisions. Cross-family/script switches can sharply collapse binding accuracy; internally, binding-related computation shifts later and its causal strength weakens under harder multilingual settings, while closely related languages preserve bindings better—implying the binding mechanism itself degrades under multilingual input.

Steering the Language Axis: From Linear Decodability to Causal Control [\[arxiv\]](#)

Arnav Srivastav

A low-dimensional “language axis” in hidden states is not just decodable—it can be used as a causal control knob to switch a model’s output language.

Moves from correlation to causation: PCA-derived language directions reliably steer generation language, and removing that component makes models revert to a default, implying language choice is implemented as a compact, manipulable feature in specific layers. Extract language axes via PCA on hidden states by target language; during generation, add (steer) or remove (ablate) the axis at chosen layers; compare to equal-norm random directions; sweep layers/language pairs across models (e.g., Qwen 3.5-2B, Llama-3.2-1B-Instruct) with ~1.26M FLORES-200 generations. Axis steering flips output language (including cross-script) while random directions barely do; layer sensitivity differs by pair (e.g., EnglishChinese steers later than EnglishSpanish); ablating the signal often collapses outputs back to English, suggesting an English “default basin.”

Don’t Want Your LLM to Recommend Nuclear Strike? Try Asking It in Japanese [\[arxiv\]](#)

Rian Touchent (ALMAAnaCH)

Changing the language a model reasons in can flip catastrophic-violence recommendations, so English-only safety tests can badly misestimate real risk.

Shows a high-stakes cross-lingual alignment effect: Japanese can strongly suppress nuclear-strike recommendations in some frontier models, and a key manipulation separates input language from reasoning language to pinpoint the driver. Single-turn game-theoretic nuclear-strike advisor vignettes with identical strategic structure/amoral framing across languages; test nine models from six providers; measure “launch rates” across scenario types; mechanism test: English prompt + explicit instruction to reason in Japanese; analyze rationales for framing shifts. Claude models show large drops with Japanese (e.g., Sonnet 4.6: unnecessary strikes 40%0%, contested 93%17%) with little change when strikes are strategically rational; Gemini Pro 3.1 also drops (53%13%); instructing Japanese reasoning inside an English prompt cuts contested launches (93%37%), indicating reasoning language drives the effect and elicits moral framing absent from the prompt.

Multilingual Speech Processing

Comparative Analysis of Multilingual Pre-trained Models for Nepali Automatic Speech Recognition [\[arxiv\]](#)

Suman Paudel, Sarbin Sayami

For Nepali ASR, language-family-relevant pretraining can match huge models on in-domain WER, and CTC models can deliver similar accuracy at far lower latency.

First controlled, efficiency-aware comparison of major multilingual pretrained ASR models for Nepali under a unified fine-tuning recipe, reporting both accuracy (WER/CER) and deployment cost (RTF) across multiple test sets to expose accuracy–latency–robustness trade-offs. Fine-tune six pretrained ASR models spanning CTC SSL encoders (XLSR-53, IndicWav2Vec, MMS-1B), autoregressive encoder-decoder (Whisper variants), and Conformer-CTC; keep data (OpenSLR SLR54 ~165h), preprocessing/splits, and tuning protocol consistent; evaluate on OpenSLR, FLEURS, Common Voice with WER/CER + RTF. Whisper-Large-v3-Turbo and IndicWav2Vec tie on in-domain WER (14.76% vs 14.89%), showing family-relevant pretraining can substitute for scale; CTC decoding is up to 29× faster than Whisper at similar accuracy; MMS-1B degrades least out-of-domain on FLEURS, suggesting scale mainly buys domain-shift robustness.

Foundation Model Theory

Information Abundance Paradox: Long-Context Training Undermines Parametric Knowledge [\[arxiv\]](#)

Arda Uzunoglu, Benjamin Van Durme, Daniel Khashabi

Training with ever-more helpful long context can reduce what models store in weights, making them worse when context is missing or misleading.

Formalizes the Information Abundance Paradox: beyond an intermediate context length, long-context training can improve context use yet degrade parametric recall/robustness, supported by an optimization/mechanistic account tied to where learning pressure flows in the network. Train models with varying context availability/length in pretraining and SFT; evaluate both with-support and closed-book/no-context settings to detect non-monotonic effects; analyze training dynamics showing abundant context favors “cheaper” attention-based solutions over MLP-based storage; use causal component interventions to test whether attention-heavy computation increases context reliance. Longer-context training yields gains up to a midpoint, then harms closed-book knowledge (e.g., multiple-choice QA) and increases fragility when context is removed or adversarial; gradients shift from MLPs toward attention as context becomes more informative, and causal tests support this shift contributing to increased context dependence at inference.

LLM Evaluation

Fast A/B/n Testing: Exact Multi-Policy Comparison via Tree-Coupled Feedback Sharing [\[arxiv\]](#)

Yuxiao Wen

You can evaluate many adaptive bandit policies “as if” run separately while often paying near one trajectory’s reward cost, by coupling policies to share feedback when they choose the same actions.

An exact multi-policy A/B/n design for history-dependent contextual-bandit policies that preserves each policy’s standalone trajectory distribution while enabling reward sharing via controlled dependence, yielding unbiased comparisons with far fewer reward queries. At each round, arrange the J policies in a tree and apply maximal couplings on edges so endpoints match actions with highest possible probability; matched components share one reward sample, mismatches trigger extra queries; derive cost identity $N(T) = T + \sum_{t,e} D_{t,e}$ linking extra queries to cumulative tree-edge total variation; argue myopic minimum-spanning-tree choice is optimal among trees. Reward queries drop from JT to $\sim T$ plus a mismatch penalty that shrinks as policies’ action distributions converge; induced correlation can also reduce variance of pairwise contrasts; experiments (reward-model eval, MCQ LM eval, adaptive search) show better cost–precision than independent rollouts.

Field Overview

Today’s batch is dominated by LLM agents and their infrastructure: at least ~25–35 papers touch agentic workflows (memory layers like MindMemOS/FluctlightDB/EgoMonth, multi-agent coordination/communication like StateBridge/BoardroomAI/MARC, and long-

horizon evaluation such as SteerBench-Work, ARAC, Beyond Final Scores, QuoteBench). A second major cluster is safety/governance and evaluation of alignment/judging (roughly ~15–25), including multilingual safety failures (e.g., “asking in Japanese”), research integrity/provenance, watermarking, rule compliance, and critiques of alignment as dual-use/censorship tooling. Efficiency/serving is also heavily represented (~10–15) with KV-cache virtualization/compaction (vToken, thought-aware compaction), speculative/edge inference (SPADE), transformer inference refactors (Dual-Flow Transformers), and diffusion acceleration/caching (GeoCache, cache reuse policy). A notable emerging direction is “process-level” reasoning diagnostics—constraint satisfaction/constraint influence, reasoning-trace evaluation (Reasoning Jury), search-efficiency probes (TsuGO), numeracy limits, and activation/causal control—suggesting the community is shifting from final-answer scores to mechanistic and governance-aware reliability metrics.