

## Multilingual NLP

---

### FrameBench: A Language Understanding Benchmark Based on Frame Semantics [\[arxiv\]](#)

Chihiro Yano, Ryohei Sasano

*FrameBench tests whether LLMs infer the implicit situation (“frame”) a verb evokes from context, in both English and Japanese.*

Introduces a multilingual, frame-semantics diagnostic: minimal context shifts where the same verb maps to different frames, grounded in FrameNet-style resources and validated by native speakers. Multiple-choice frame identification for target verbs; English/Japanese item creation via generation+verification, filtered with native-speaker judgments to ensure human-consistent frame labels. Small models struggle with context-sensitive frame disambiguation, while several large models exceed reported human reference scores; the benchmark cleanly separates weak/strong models across English and Japanese.

### Lost in Reordering: Structural Sensitivity of Multilingual LLMs under Semantics-Preserving Perturbations [\[arxiv\]](#)

Karthika Nhayakkat, Rajat Verma, Maharaj Brahma, Vetcha Gnana Mahesh, Maunendra Sankar Desarkar, Ganesh Ramakrishnan, Rohit Saluja

*Multilingual LLMs’ reasoning in Hindi/Malayalam is brittle to meaning-preserving reordering and voice changes, exposing weak compositional/structural robustness.*

IndicReStruct: GSM8K-style problems rewritten with constituent reordering and activepassive transforms to isolate structure from meaning; adds mechanistic localization of where reordering disrupts reasoning. Evaluate 6 multilingual LLMs on original vs. perturbed Hindi/Malayalam problems under multiple prompting setups; analyze errors; use residual-stream activation patching (cleancorrupted) across layers to identify where fixes restore accuracy. Accuracy drops consistently under structural perturbations; models often mis-bind entities/quantities after reordering/voice changes. Patching mid-layer activations restores performance most, suggesting the key structure-invariant representations are formed/disrupted in intermediate layers.

### Contextual Tamil Spelling and Grammar Correction Using Progressively Fine-Tuned Sequence-to-Sequence Transformers [\[arxiv\]](#)

Karthikeyan A, Jaya Nirmala S, Sangeetha Sivanesan, Indhu R, Pranav Kumar, Bharat Jude Johnson, Vishnu Ram

*Tamil correction improves sharply with a staged seq2seq curriculum: learn typos first, then contextual grammar, then increasingly complex sandhi.*

Progressive fine-tuning for mT5-small/mBART-50 across error types (surface noise contextual grammarsingle-boundary sandhimulti-site sandhi), supported by a synthetic noisy-clean corpus and a balanced diagnostic set. End-to-end seq2seq correction on ~657k synthetic pairs spanning 10 error categories; four-stage curriculum (v2-v5) on the same backbone; evaluate top-1 exact match on a disjoint 1,000-sentence diagnostic set plus identity (do-nothing) accuracy. Best model (mBART-50 v5) reaches 69.3% exact match; sandhi is strong (87.5%) while subject-verb agreement remains weak (43.5%). Curriculum drives the gains: agreement rises from ~1% to >50% when contextual grammar is introduced; sandhi goes 0%87.5% with multi-site examples. Higher correction recall can reduce identity accuracy. Tamil-LLaMA-7B-Instruct only modestly beats copy baseline without supervision.

### Typological Feature Prediction with Large Language Models: An In-Context Learning Approach [\[arxiv\]](#)

Qianwen Wang, York Hay Ng, Aditya Khan, En-Shiun Annie Lee

*LLMs predict typological features far better when given in-context evidence from related and nearby languages, and their rationales usually track that evidence.*

Recasts typology prediction as evidence-based in-context learning using phylogenetic and geographic “neighbor” feature tables, improving accuracy and making explanations checkable against provided evidence. Prompts built from URIEL+ features and Glottolog metadata; compare zero-shot feature guessing vs. prompts augmented with family/tree and geographic neighbor feature values; collect rationales and check alignment with shown evidence. Zero-shot is not competitive, indicating LLMs’ memorized typology is unreliable. With neighbor evidence, the LLM substantially outperforms prior baselines without sacrificing low-resource languages, and rationales

are typically consistent with the provided neighbor cues.

## Multilingual Speech Processing

---

### Alignment-Free Text-Audiobox for Voice Dubbing and Full-Duplex Dialogue Synthesis [\[arxiv\]](#)

Sanyuan Chen, Min-Jae Hwang, Sho Inoue, Anna Sun, Bokai Yu, David Kant, Dongmin Hyun, Dorian Desblancs, Gregory Antonovsky, Oleg Repin, Peng-Jen Chen, Xutai Ma, Zehai Tu, Juan Pino, Wei-Ning Hsu

*A single large latent diffusion model can do cross-lingual dubbing and full-duplex (overlapping) dialogue without forced alignments by generating in a highly compressed audio latent space.*

Text-Audiobox unifies dubbing and interactive dialogue in one alignment-free system; the key idea is compact, high-fidelity audio latents plus scale, letting cross-attention learn timing implicitly instead of using duration/alignment modules. Latent diffusion Transformer over DAC-VAE latents (48kHz/25Hz); text embeddings via cross-attention; 3B model pretrained with flow-matching on 480k hours, then fine-tuned for dubbing, full-duplex, and emotion-conditioned dialogue; long-form via multi-diffusion and candidate reranking. Improves dubbing on prosody match, speaker similarity, naturalness, and “shareability” vs. strongest internal baseline; for full-duplex, stays closer to human behavior (interruptions/backchannels) especially in long-form; emotion conditioning measurably improves emotion alignment and perceived quality.

### VoxPrivacy: A Benchmark for Evaluating Interactional Privacy of Speech Language Models [\[arxiv\]](#)

Yuxiang Wang, Hongyu Liu, Dekun Chen, Xueyao Zhang, Zhizheng Wu

*Speech LMs often fail speaker-aware privacy in multi-user settings, leaking one user’s context to another; VoxPrivacy measures this and shows targeted fine-tuning can reduce leaks.*

Defines and benchmarks “interactional privacy” (what to say depends on who is speaking); releases VoxPrivacy (bilingual, multi-speaker) plus a large training set and shows privacy can improve without major robustness loss. 32-hour bilingual benchmark with three tiers: follow secrecy instructions, conditional disclosure by speaker, and proactive privacy inference; evaluate 9 SLMs and a human-recorded Real-VoxPrivacy subset; mitigate by fine-tuning on a new 4,000-hour speaker-conditioned privacy dataset. On conditional privacy, most open models are near chance; closed models still struggle on proactive inference. Failures persist on real human speech. Fine-tuning on the 4,000-hour set materially improves privacy behavior while keeping general robustness stable.

## Foundation Model Theory

---

### A Circuit for Plural Reference: How LLMs Represent and Retrieve Singular and Plural Entities [\[arxiv\]](#)

Anh Danh, Rick Nouwen, Massimo Poesio

*Plural pronoun resolution in LLMs is partly implemented by a small, causally testable attention-head circuit that builds a plural “group” from multiple singular mentions and drives “they” vs. singular pronouns.*

Provides a circuit-level account of plural reference: heads that encode entity/coreference info, detect when mentions should be grouped, and route a grouped representation to downstream antecedent/pronoun selection—validated with causal interventions. Controlled coreference prompts requiring plural antecedents; identify candidate heads via attention patterns (pronoun mentions, conjunct linking) and test necessity/sufficiency with activation patching and ablations across the proposed multi-step computation. A small set of heads forms a plural-reference circuit; intervening on them predictably shifts pronoun choice. The model’s pluralization follows human-like cues (ontological similarity, explicit “and”), implying sensitivity to both world knowledge and syntax.

## LLM Evaluation

---

### ObserverBench: Testing Mechanistic Estimates for Intervention and Control [\[arxiv\]](#)

Vijay Erramilli

*ObserverBench shows interpretability “observers” should be judged by decision loss under real intervention/control contracts, not just estimation metrics like MSE/AUROC.*

Defines a contract-based benchmark where observers drive constrained actions (edits, steering, triage); highlights that accurate estimates can still yield bad interventions once coupled to a decision rule and limited action set. For each task: fix model, observer information boundary, allowed actions, decision rule, eval distribution, and loss; report estimation accuracy alongside action-induced loss; instantiate across circuit intervention-effect prediction/selection and monitoring/triage settings. Repeated estimate–action mismatches: better effect prediction doesn’t reliably yield lower-loss interventions, while observers trained on action loss choose better actions despite worse pure accuracy. AUROC can mis-rank monitors vs. deployment loss; “best” info sources vary by model. Sparse SAE readouts underperform layer-matched dense controls in their Qwen panels (with noted caveats).

## Field Overview

---

Today’s list is dominated by LLM agent engineering and post-training: at least ~25 papers on harness/prompt evolution, long-horizon memory, tool-use protocols, and agent evaluation (e.g., harness optimization, memory retrieval/validation, terminal/GUI agents, multi-agent debate/monitoring). A second major cluster is efficiency for deployment—roughly ~15 papers on KV-cache compression/eviction, speculative decoding, quantization (FP4/W4A4), and on-device/streaming inference (LeanStream, GrowPage, Random Attention, FlashAttention-4). Safety/measurement is also unusually prominent (10–15): multilingual jailbreak robustness, refusal circuits/representational alignment, deception detection, watermarking/auditing (including RAG watermarking), and multiple critiques of LLM-as-a-judge reliability and rubric artifacts. Finally, there’s a noticeable multimodal + speech surge (15–20) spanning full-duplex voice agents, ASR/TTS/OCR, audio deepfake detection/traceability, and multimodal benchmarks (DocVQA, medical VQA/MM shortcuts), suggesting an emerging push to make agents “real-time” and accountable across modalities rather than text-only.