
General Information

Detailed information about the lecture, tutorials and homework assignments can be found on the lecture website¹. Solutions have to be submitted to Moodle². Make sure your uploaded documents are readable. Blurred images will be rejected. Use Piazza³ to ask questions and discuss with your fellow students.

Assignment 12.1 (L) What the fact

Consider the following function definitions:

```
let rec fact n = match n with 0 -> 1
  | n -> n * fact (n-1)

let rec fact_aux x n = match n with 0 -> x
  | n -> fact_aux (n*x) (n-1)

let fact_iter = fact_aux 1
```

Assume that all expressions terminate. Show that

$$\text{fact_iter } n = \text{fact } n$$

holds for all non-negative inputs $n \in \mathbb{N}_0$.

Suggested Solution 12.1

We show that $\text{fact_iter } n = \text{fact } n$, resp. that $\text{fact_aux } 1 \ n = \text{fact } n$ by induction on n .

- Base case: $n = 0$

$$\begin{aligned} & \text{fact_aux } 1 \ 0 \\ \stackrel{f.a}{=} & \text{match } 0 \text{ with } 0 \rightarrow 1 \mid n \rightarrow \text{fact_aux } (n*1) \ (n-1) \\ \stackrel{\text{match}}{=} & 1 \\ \stackrel{\text{match}}{=} & \text{match } 0 \text{ with } 0 \rightarrow 1 \mid n \rightarrow n * \text{fact } (n-1) \\ \stackrel{\text{fact}}{=} & \text{fact } 0 \end{aligned}$$

¹<https://www.in.tum.de/i02/lehre/wintersemester-1819/vorlesungen/functional-programming-and-verification/>

²<https://www.moodle.tum.de/course/view.php?id=44932>

³<https://piazza.com/tum.de/fall2018/in0003/home>

- Inductive step: We assume `fact_aux 1 n = fact n` holds for an input $n \geq 0$. Now we try to prove that it also holds for $n + 1$:

```

fact_aux 1 (n+1)
 $\stackrel{f\_a}{=}$  match n+1 with 0 -> 1 | n -> fact_aux (n*1) (n-1)
 $\stackrel{match}{=}$  fact_aux ((n+1)*1) ((n+1)-1)
 $\stackrel{arith}{=}$  fact_aux (n+1) n
    our proof fails here
= (n+1) * fact n
 $\stackrel{arith}{=}$  (n+1) * fact ((n+1)-1)
 $\stackrel{match}{=}$  match n+1 with 0 -> 1 | n -> n * fact (n-1)
 $\stackrel{fact}{=}$  fact (n+1)

```

We fail, because we cannot use the induction hypothesis to rewrite one side into the other. The reason is that our hypothesis holds only for the special case where `x` is exactly 1. Since the value of argument `x` changes between recursive calls, we have to state (and prove) a more general equality between the two sides that holds for arbitrary `x`. It is easy to see that `x` is used as an accumulator here and the function simply multiplies the factorial of `n` onto its initial value. Thus, for an arbitrary `x`, `fact_aux x n` computes $x * n!$. In order for the other side to compute the exact same value, we have also have to multiply by the initial value of `x`:

```
fact_aux acc n = acc * fact n
```

Now, we try to prove this by induction on `n`:

- Base case: `n = 0`

```

fact_aux acc 0
 $\stackrel{f\_a}{=}$  match 0 with 0 -> acc | n -> fact_aux (n*acc) (n-1)
 $\stackrel{match}{=}$  acc
 $\stackrel{arith}{=}$  acc * 1
 $\stackrel{match}{=}$  acc * match 0 with 0 -> 1 | n -> n * fact (n-1)
 $\stackrel{fact}{=}$  acc * fact 0

```

- Inductive step: We assume `fact_aux acc n = acc * fact n` holds for an input

$n \geq 0$. Now, we show that it holds for $n + 1$ as well:

```

fact_aux acc (n+1)
 $\stackrel{f.a}{=}$  match n+1 with 0 -> acc | n -> fact_aux (n*acc) (n-1)
 $\stackrel{match}{=}$  fact_aux ((n+1)*acc) ((n+1)-1)
 $\stackrel{arith}{=}$  fact_aux ((n+1)*acc) n
 $\stackrel{I.H.}{=}$  (n+1) * acc * fact n
 $\stackrel{arith}{=}$  acc * (n+1) * fact ((n+1)-1)
 $\stackrel{match}{=}$  acc * match n+1 with 0 -> 1 | n -> n * fact (n-1)
 $\stackrel{fact}{=}$  acc * fact (n+1)

```

This proof succeeds, as we can now make use of the (more general) induction hypothesis. \square

Assignment 12.2 (L) Arithmetic 101

Let these functions be defined:

```

let rec summa l = match l with [] -> 0
                  | h::t -> h + summa t

```

```

let rec sum l a = match l with [] -> a
                  | h::t -> sum t (h+a)

```

```

let rec mul i j a = if i <= 0 then a
                    else mul (i-1) j (j+a)

```

Prove that, under the assumption that all expressions terminate, for arbitrary l and $c \geq 0$ it holds that:

$$\text{mul } c \text{ (sum } l \text{ 0) 0} = c * \text{summa } l$$

Suggested Solution 12.2

Both `sum` and `mul` use an accumulator in their tail recursive implementation. Thus, we have to generalize the claim to:

$$\text{mul } c \text{ (sum } l \text{ acc1) acc2} = \text{acc2} + c * (\text{acc1} + \text{summa } l)$$

First we prove a lemma by induction on the length n of the list l :

Lemma 1: `sum l acc1 = acc1 + summa l`

- Base case: `l = []`

```

sum [] acc1
 $\stackrel{sum}{=}$  match [] with [] -> acc1 | h::t -> sum t (h+acc1)
 $\stackrel{match}{=}$  acc1
 $\stackrel{match}{=}$  acc1 + match [] with [] -> 0 | h::t -> h + summa t
 $\stackrel{summa}{=}$  acc1 + summa []

```

- Inductive step: We assume $\text{sum } l \text{ acc1} = \text{acc1} + \text{summa } l$ holds for a list xs of length $n \geq 0$. Now, we show that it then also holds for a list $x::xs$ of length $n + 1$:

```

      sum (x::xs) acc1
    ==sum match x::xs with [] -> acc1 | h::t -> sum t (h+acc1)
    ==match sum xs (x+acc1)
    ==I.H. x + acc1 + summa xs
    ==comm acc1 + x + summa xs
    ==match acc1 + match x::xs with [] -> 0 | h::t -> h + summa t
    ==summa acc1 + summa (x::xs)

```

Next, we prove the initial statement by induction on c :

- Base case: $c = 0$

```

      mul 0 (sum l acc1) acc2
    ==mul if 0 <= 0 then acc2 else mul (0-1) (sum l acc1) ((sum l acc1)+acc2)
    ==if acc2
    ==arith acc2 + 0 * (acc1 + summa l)

```

- Inductive step: We assume the statement holds for a $c \geq 0$. Now, we show that it also holds for $c + 1$:

```

      mul (c+1) (sum l acc1) acc2
    ==mul if c+1 <= 0 then acc2 else mul c (sum l acc1) ((sum l acc1) + acc2)
    ==if mul c (sum l acc1) ((sum l acc1) + acc2)
    ==I.H. (sum l acc1) + acc2 + c * (acc1 + summa l)
    ==comm acc2 + c * (acc1 + summa l) + (sum l acc1)
    ==L.1 acc2 + c * (acc1 + summa l) + (acc1 + summa l)
    ==Distr acc2 + (c+1) * (acc1 + summa l)

```

This proves the statement. □

Assignment 12.3 (L) Counting nodes

A binary tree and two functions to count the number of nodes in such a tree are defined as follows:

```

type tree = Node of tree * tree | Empty

let rec nodes t = match t with Empty -> 0

```

```

| Node (l,r) -> 1 + (nodes l) + (nodes r)

let rec count t =
  let rec aux t a = match t with Empty -> a
    | Node (l,r) -> aux r (aux l (acc+1))
  in
  aux t 0

```

Prove or disprove the following statement for arbitrary trees t :

$$\text{nodes } t = \text{count } t$$

Suggested Solution 12.3

The statement holds. First, we show that $\text{nodes } t = \text{aux } t \ 0$ or, more precisely, the generalized statement $\text{acc} + \text{nodes } t = \text{aux } t \ \text{acc}$ holds. We prove by induction on the structure of trees:

- Base case: $t = \text{Empty}$

$$\begin{aligned}
 & \text{acc} + \text{nodes } \text{Empty} \\
 \stackrel{\text{nodes}}{=} & \text{acc} + \text{match } \text{Empty} \text{ with } \text{Empty} \rightarrow 0 \\
 & \quad | \text{Node } (l,r) \rightarrow 1 + (\text{nodes } l) + (\text{nodes } r) \\
 \stackrel{\text{match}}{=} & \text{acc} \\
 \stackrel{\text{match}}{=} & \text{match } \text{Empty} \text{ with } \text{Empty} \rightarrow \text{acc} \\
 & \quad | \text{Node } (l,r) \rightarrow \text{aux } r \ (\text{aux } l \ (\text{acc}+1)) \\
 \stackrel{\text{aux}}{=} & \text{aux } \text{Empty} \ \text{acc}
 \end{aligned}$$

- Inductive step: Assume the above equivalence holds for two trees a and b . Now, we show that it then also holds for a tree $\text{Node } (a, b)$:

$$\begin{aligned}
 & \text{acc} + \text{nodes } (\text{Node } (a,b)) \\
 \stackrel{\text{nodes}}{=} & \text{acc} + \text{match } \text{Node } (a,b) \text{ with } \text{Empty} \rightarrow 0 \\
 & \quad | \text{Node } (l,r) \rightarrow 1 + (\text{nodes } l) + (\text{nodes } r) \\
 \stackrel{\text{match}}{=} & \text{acc} + 1 + (\text{nodes } a) + (\text{nodes } b) \\
 \stackrel{I.H.}{=} & \text{aux } b \ (\text{acc} + 1 + \text{nodes } a) \\
 \stackrel{I.H.}{=} & \text{aux } b \ (\text{aux } a \ (\text{acc}+1)) \\
 \stackrel{\text{match}}{=} & \text{match } \text{Node } (a,b) \text{ with } \text{Empty} \rightarrow \text{acc} \mid \text{Node } (l,r) \rightarrow \text{aux } r \ (\text{aux } l \ (\text{acc}+1)) \\
 \stackrel{\text{aux}}{=} & \text{aux } (\text{Node } (a,b)) \ \text{acc}
 \end{aligned}$$

Finally, we show:

$$\text{nodes } t \stackrel{\text{arith}}{=} 0 + \text{nodes } t \stackrel{\text{theor}}{=} \text{aux } t \ 0 \stackrel{\text{count}}{=} \text{count } t$$

□

Assignment 12.4 (H) Len or nlen?

[5 Points]

The following functions are defined:

```

let rec nlen n l = match l with [] -> 0
  | h::t -> n + nlen n t

let rec fold_left f a l = match l with [] -> a
  | h::t -> fold_left f (f a h) t

let rec map f l = match l with [] -> []
  | h::t -> f h :: map f t

let (+) a b = a + b

```

Show that the statement

$$\text{nlen } n \text{ l} = \text{fold_left } (+) \text{ 0 (map (fun _ -> n) l)}$$

holds for arbitrary l and n . Assume that all expressions do terminate.

Assignment 12.5 (H) Fun with fold

[8 Points]

Given are the following functions with semantics as usual:

```

let rec fl f a l = match l with [] -> a
  | x::xs -> fl f (f a x) xs
let rec fr f l a = match l with [] -> a
  | x::xs -> f x (fr f xs a)
let rec rev_map f l a = match l with [] -> a
  | x::xs -> rev_map f xs (f x :: a)
let (+) a b = a + b

```

Prove that, if all expressions terminate, the statement

$$\text{fl } (+) \text{ 0 (rev_map (fun x -> x * 2) l [])} = \text{fr (fun x a -> a + 2 * x) l 0}$$

holds for all inputs l .

Assignment 12.6 (H) Trees

[7 Points]

Once again, we define binary trees and some functions for them:

```
type tree = Empty | Node of int * tree * tree

let rec fl f a l = match l with [] -> a
  | x::xs -> fl f (f a x) xs

let rec app l1 l2 = match l1 with [] -> l2
  | x::xs -> x::app xs l2

let rec tf f b t = match t with Empty -> b
  | Node (x, l, r) -> f (tf f b l) x (tf f b r)

let rec to_list t = match t with Empty -> []
  | Node (x, l, r) -> app (to_list l) (x::to_list r)

let add3 a b c = a + b + c
let (+) a b = a + b
```

Assume all expressions terminate, then proof for all trees t :

$$\text{fl } (+) \ 0 \ (\text{to_list } t) = \text{tf } \text{add3 } 0 \ t$$

Hint: If you get stuck during your proof, try to formulate additional equalities that help to reach your goal. Don't forget to prove them, however!