FinLit Launch Guide: every step, in order

You will create three free accounts (Neon, MongoDB Atlas, Render), paste five values, and press Deploy: about 60 minutes of your time plus 15 minutes of waiting. Everything costs 0 for now.

Never type a password, key or token into a chat. Secrets go only into the Render, Neon, Atlas and GitHub pages named below. Screen labels on those websites may differ slightly from these words; the order of actions is the same.

Before you start

Have these ready:

1. **Your GitHub login.** Render will sign in with it.
2. **A NEW FinEdge API key** from your FinEdge dashboard. The old key was shown in an earlier chat, so do not reuse it. Keep the new one in a password manager or a private note.
3. **An email address** you check (for Neon, MongoDB Atlas and Render).
4. **One password for the administrator account**: 10+ characters and not containing the part of your email before the @. It also opens the blog/CMS tools: there is only one sign-in.
5. **About 60 minutes.**

What you will create:

Where	What it holds	Cost
Neon	The main database: members, plans, company data	Free
MongoDB Atlas	The blog, portfolio page and contact forms	Free (M0)
Render	Runs the website and both back ends in one service, plus a free cache	Free
GitHub (your repo)	Holds the code; Render builds from it	Free

The code is already in your repository `pranshukesavmishra/finlit-platform`, branch `main`, including the company's back end in the `site-api` folder. You do not upload anything.

What it costs

Everything below is 0 today. The last column says when you would start paying; nothing is charged unless you choose a paid plan yourself. Limits were read from each provider's own pages on 18 October 2026; Render's pricing page showed no prices, so none is quoted for Render.

Service	Used for	Cost now	When you would need to pay
Render, free web service + free Redis	The whole site	0	When you need it to never sleep or need more memory: choose a paid instance (see Render's pricing page)
Neon, free Postgres	Members, plans, company data	0	If data passes 1 GB, or monthly compute passes 100 compute-hours (about 400 awake hours)
MongoDB Atlas, M0 free	Blog, portfolio, forms	0	If data passes 512 MB
UptimeRobot, free (optional)	Backup keep-awake check	0	Free plan: 50 monitors, checks every 5 minutes
Resend, free	Sign-up and contact emails	0	Free plan: 100 emails a day, 3,000 a month
Google AI Studio, free tier	FinLit AI chat	0	If the free daily quota is not enough
Domain finlitventures.com	Your own address	Ask your registrar	When the company signs off. Price depends on the registrar; check before buying

---

Step 1. Create the main database (Neon)

Neon gives a free Postgres database that does not expire (Render's own free database is deleted after 30 days, so it is not used).

1. Open https://neon.com and click **Sign up**. Choose **Continue with GitHub** (or Google).
2. When it asks you to create a project, enter: **Project name** `finlit`, **Postgres version** 16, **Region** AWS Asia Pacific (Singapore). Click **Create**.
3. On the project dashboard click **Connect**.
4. In the box that opens, switch **Connection pooling** OFF. The address in the string must not contain the word `-pooler`.
5. Click the copy button on the connection string. It looks like `postgresql://neondb_owner:XXXX@ep-something.ap-southeast-1.aws.neon.tech/neondb?sslmode=require`.
6. Paste it into a private note and name it **DATABASE_URL**. You paste it into Render in Step 4.

What you should see: a project page with the Connect button and an empty database. Nothing to build: the website creates its own tables the first time it starts.

Free plan (from Neon's own pages): 1 GB of data, 100 compute-hours a month, it sleeps after 5 idle minutes, and the free plan has no time limit.

Step 2. Create the blog database (MongoDB Atlas)

This holds the blog, the portfolio page and the contact forms. If the company already runs a live MongoDB with its blog content, ask them for that connection string and use it instead: the existing posts then appear.

1. Open https://www.mongodb.com/cloud/atlas and click **Try Free**. Sign up with Google or an email.
2. Create a cluster: choose the **M0 Free** plan, provider AWS, region Mumbai (or Singapore), name it `Cluster0`, click **Create**.
3. In the security step, create a database user: username `finlit`, click **Autogenerate Secure Password**, copy that password into your private note, click **Create User**.
4. Go to **Network Access** in the left menu, click **Add IP Address**, choose **Allow Access From Anywhere** (`0.0.0.0/0`), click **Confirm**. This is needed because Render's addresses change.
5. Go to **Database** in the left menu, click **Connect** on your cluster, choose **Drivers**, and copy the string that starts with `mongodb+srv://`.
6. In your private note, replace `<password>` in that string with the password from step 3. Name the result **MONGO_URL**.

What you should see: the cluster listed as running, one database user, and `0.0.0.0/0` under Network Access. The website creates its collections itself.

Free plan (from MongoDB's pages): 512 MB of data. A free cluster is paused after 30 days with no connections at all; the site connects every few minutes, so this will not happen while it is running.

Step 3. Create the Render account and start the deploy

Render runs the whole site as one free service. Render gives each workspace about 750 free hours a month, which covers one service running all month and not two, so create **only this one free service** in the workspace.

1. Open https://render.com and click **Get Started**. Choose **GitHub** and authorize Render.
2. On the Render dashboard click **New +**, then **Blueprint**.
3. Under **Connect a repository** find `pranshukesavmishra/finlit-platform`. If it is not listed, click **Configure account** and give Render access to that repository.
4. Click **Connect** next to it. Leave the branch as `main`. Give the blueprint any name, for example `finlit`.
5. Render reads the file `render.yaml` and lists two items: **finlit** (web service, Free) and **finlit-redis** (Key Value, Free). Below them it asks for five values. Keep this page open and go to Step 4.

What you should see: both items marked Free, no database in the list (the database comes from Neon), and five empty value boxes.

Step 4. Paste the five values Render asks for

Type or paste each value into its box on the Blueprint page, then click **Apply** (or **Deploy Blueprint**). Render hides secret values after you save.

Name	What it is	Where it comes from
`FINEDGE_API_KEY`	Market data for every company	A NEW key from your FinEdge dashboard
`DATABASE_URL`	The main database	Step 1: the Neon string, pooling OFF
`MONGO_URL`	The blog database	Step 2: the Atlas string with your real password
`ADMIN_EMAIL`	Your administrator login	Your own email address
`ADMIN_PASSWORD`	Your administrator password	You choose: 10+ characters, not containing the part of your email before the @

Render creates three more values for you, so do not type them: `SECRET_KEY`, `DEMO_PASSWORD` (the password of the demo accounts) and `CMS_JWT_SECRET` (the key that lets your normal administrator sign-in open the blog tools). Both halves of the site run in the same service, so they share `CMS_JWT_SECRET` automatically.

`SITE_API_URL` is not needed: the blog back end runs inside the same service and is found automatically. Set it only if the blog back end is ever hosted somewhere else.

What you should see: after Apply, a page with the service `finlit` and a build log scrolling.

Step 5. Wait until it says Live, then open the site

1. Watch the **Logs** tab. The first build takes about 8 to 12 minutes because it builds the website and two Python environments.
2. When the service status turns **Live**, click the address under the service name: `https://finlit-xxxx.onrender.com`.
3. To read the demo password: service **Environment** tab, find `DEMO_PASSWORD`, click the eye icon.

What you should see: the FinLit home page. Companies appear in the background: the 10 largest within a couple of minutes, then about 60 a minute up to 1,500 companies. The Screener page shows the count growing.

The first visit after the site has been idle takes about a minute to wake: that is normal on the free plan.

Step 6. Sign in for the first time, one account type at a time

Every account signs in at `/login`. There is no separate admin password form: `/admin/login` now just forwards you to `/login`.

Account	Email	Password	What you should see after signing in
Demo Basic	`demo-basic@finlit-demo.com`	`DEMO_PASSWORD`	The dashboard with a Basic badge. Scores are locked on company pages
Demo Silver	`demo-silver@finlit-demo.com`	`DEMO_PASSWORD`	The dashboard with a Silver badge. FinLit scores and watchlists are open
Demo Gold	`demo-gold@finlit-demo.com`	`DEMO_PASSWORD`	The dashboard with a Gold badge. Everything is open, including the Score screener
A new visitor	Any email, using **Create account** on the sign-in page	Their own	"Your account is ready", then they sign in. They start on Basic
You, the administrator	The `ADMIN_EMAIL` you typed	The `ADMIN_PASSWORD` you typed	See below

First administrator sign-in, once only:

1. Sign in at `/login` with your administrator email and password.
2. You are taken to **Account, Security**. Click to set up the authenticator app. Scan the picture with Google Authenticator, Microsoft Authenticator or Authy, type the 6-digit code, and confirm. Administrators must use this.
3. From now on, signing in asks for the 6-digit code after the password.
4. Open `/admin` (type it after your site address, for example `https://finlit-xxxx.onrender.com/admin`). The blog and content tools open at once, with no second password. The members, plans and data-health screen is at `/console`.
5. Change your password under **Account**, then delete `ADMIN_PASSWORD` in Render (service, Environment, delete the variable).

If `/admin` says the content tools are not connected, or the server answers `cms_not_configured`, the value `CMS_JWT_SECRET` is missing or shorter than 32 characters: add or regenerate it in the Environment tab, save, and let Render redeploy.

If a new member says they cannot sign in and the email service is not on yet, open `/console`, find them under members, and click **Confirm email**.

Step 7. Keep the free site awake

A free Render service goes to sleep after 15 minutes without visitors and takes about a minute to wake. Sleeping also pauses the background data jobs. Two free pingers prevent this. Use both: the second is the backup for the first.

7a. GitHub pinger (already in the code).

1. Open your repository on GitHub, then **Settings**, **Secrets and variables**, **Actions**, tab **Variables**.
2. Click **New repository variable**. Name: `SITE_URL`. Value: your Render address, like `https://finlit-xxxx.onrender.com` (no slash at the end). Click **Add variable**.
3. Open the **Actions** tab, click **Keep the free server awake**, then **Run workflow**.

You should see a green tick. After that it calls `/api/ping` every 10 minutes. GitHub runs scheduled jobs on a best-effort basis, so a few minutes of delay is normal.

7b. UptimeRobot (backup).

1. Open https://uptimerobot.com and click **Register** (free).
2. Click **Add New Monitor**. Monitor Type: **HTTP(s)**. Friendly Name: `FinLit`. URL: `https://finlit-xxxx.onrender.com/api/ping`. Monitoring Interval: 5 minutes.
3. Click **Create Monitor**.

You should see the monitor turn green (Up). The free plan allows 50 monitors with 5-minute checks and can email you when the site is down.

The address `/api/ping` is used on purpose: it never touches the database, so these pings do not use up Neon's free compute hours.

Why only one service: 750 free hours cover about 744 hours in a 31-day month. If you ever create a second free web service in the same Render workspace, both would be suspended before the month ends. Do not.

Step 8. Back up the databases every week

Free plans keep little or no backup history, so keep your own. This takes 5 minutes once a week; put a reminder in your phone. Do it on your own computer.

1. Install two tools once: the PostgreSQL client tools (`pg_dump`, version 16 or newer) and the MongoDB Database Tools (`mongodump`). If `mongodump` is missing, the script skips MongoDB.
2. In your terminal, inside the folder of the repository, run these four lines (use your own values from Steps 1 and 2; the passphrase is a long sentence you will remember):

```
export NEON_URL='postgresql://...your Neon string...'
export MONGO_URL='mongodb+srv://...your Atlas string...'
export BACKUP_PASSPHRASE='a long sentence only you know'
./scripts/backup.sh ~/finlit-backups
```

1. You get one encrypted file, for example `finlit-2026-10-25.tgz.enc` (about 8 MB at 160 companies). Copy it to a private place: a private Google Drive or OneDrive folder, or an external disk. Never put it in the GitHub repository: it contains member data. Delete copies older than 8 weeks. Store the passphrase in a password manager.

2. In MongoDB Atlas, also open your cluster, then **Backup**, and switch on backups: free clusters keep up to four daily snapshots.

To restore into an empty database: `openssl enc -d -aes-256-cbc -pbkdf2 -in finlit-DATE.tgz.enc | tar -xz -C restore`, then `pg_restore --no-owner -d "$NEON_URL" restore/postgres.dump` and `mongorestore --uri="$MONGO_URL" --archive=restore/mongo.archive --gzip`. The backup and restore of the main database were tested end to end: a restored copy had the same members and scores as the original.

Step 9. Switch on the chat and the market ticker (optional)

In Render open the service, **Environment** tab, **Add Environment Variable**, type the name and value, **Save Changes**. Render redeploys in about 2 minutes each time.

Name	Switches on	Where to get the value
`GEMINI_API_KEY`	The FinLit AI chat bubble	https://aistudio.google.com/apikey, click **Create API key**, copy it
`UPSTOX_ACCESS_TOKEN`	The NIFTY ticker strip at the top	Your Upstox developer account. The token expires every day, so the strip hides itself when it has expired

What you should see: the chat bubble answers a question instead of saying it is unavailable.

Step 10. Real emails (needs your own domain)

Sign-up confirmation, password reset and contact emails can only reach other people from an email address on a domain you have verified. Until then, the three demo accounts are the way in for demos, and a new visitor's account is confirmed the moment they create it (the setting `AUTO_VERIFY_EMAIL`). Resend's free plan allows 100 emails a day and 3,000 a month.

1. Buy or use the domain `finlitventures.com`. You need access to its DNS settings at your domain registrar.
2. Open https://resend.com, **Sign up**, then **Domains**, **Add Domain**, enter `finlitventures.com`.
3. Resend shows a few DNS records (names and values). Add each one in your registrar's DNS page exactly as shown, then click **Verify DNS Records** in Resend. It can take from a few minutes to a day. The domain must show **Verified**.
4. In Resend open **API Keys**, **Create API Key**, permission **Sending access**, copy the key (it is shown once).
5. In Render, **Environment**, add or change: `MAIL_MODE` = `resend`, `RESEND_API_KEY` = the key, `MAIL_FROM` = `FinLit <hello@finlitventures.com>`, `SENDER_EMAIL` = `hello@finlitventures.com`, `CONTACT_RECIPIENT_EMAIL` = the address where contact forms should arrive. Delete `AUTO_VERIFY_EMAIL`. Save.

What you should see: creating a new account now shows "Check your email", and the confirmation link arrives from your domain. The contact form delivers to your recipient

address.

Step 11. Move to finlitventures.com after sign-off

Do this only when the company has approved the site. Everything before it works on the Render address.

1. In Render open the service, **Settings**, **Custom Domains**, **Add Custom Domain**. Add `finlitventures.com`, then add `www.finlitventures.com` the same way.
2. Render shows the DNS records to add. Add them in your registrar's DNS page exactly as shown, then click **Verify** in Render. Render issues the secure certificate by itself; wait until it says **Certificate issued**.
3. In Render, **Environment**, set these values and **Save Changes**:

Name	Value
`ENVIRONMENT`	`production`
`PUBLIC_SITE_URL`	`https://finlitventures.com`
`CORS_ORIGINS`	`https://finlitventures.com,https://www.finlitventures.com`
`ALLOWED_HOSTS`	`finlitventures.com,www.finlitventures.com,finlit-xxxx.onrender.com`
`MAIL_MODE`, `RESEND_API_KEY`, `MAIL_FROM`	As in Step 10

Keep your Render address (for example `finlit-xxxx.onrender.com`, without https://) at the end of `ALLOWED_HOSTS`: Render's health checks and the keep-awake pings use it.

1. Delete `AUTO_VERIFY_EMAIL`, `DEMO_PASSWORD` and `ADMIN_PASSWORD`. In `/console` set the three demo accounts to Disabled.
2. Tell the engineer who maintains the repository when you reach this step: the lines `ENVIRONMENT` and `AUTO_VERIFY_EMAIL` in `render.yaml` need changing too, so that Render does not put the old values back at its next sync.

Production mode refuses to start unless every setting is safe. If the service does not come up, open **Logs**: the first line says `Unsafe production configuration:` followed by exactly what is wrong.

What you should see: `https://finlitventures.com` shows the same site with a padlock, and sign-up sends real confirmation emails.

Rotating the FinEdge key later

1. In your FinEdge dashboard create a new key and revoke the old one.

2. In Render open the service, **Environment**, click `FINEDGE_API_KEY`, paste the new key, **Save Changes**.
3. Render redeploys in about 2 minutes. Open the Screener: companies keep loading.
4. Never paste a key into a chat, an email or a file in the repository.

If something goes wrong

Open the service in Render and read the **Logs** tab first. Lines starting with `[site-api]` come from the blog back end.

What you see	Likely cause	What to do
The build fails	A typo or a temporary download problem	Click **Manual Deploy**, **Deploy latest commit**. If it fails again, copy the last 30 lines of the log and send them to the engineer
The site shows a spinner or an error for a minute	The free service was asleep	Wait 60 seconds and reload. Step 7 prevents this
The Screener is empty	The company load has not run yet, or `DATABASE_URL` is wrong	Wait 5 minutes. In Logs look for a database error. Re-copy the Neon string with pooling OFF
Database errors mentioning `-pooler` or prepared statements	The pooled Neon string was used	Use the direct string (Step 1, pooling OFF)
Blog, portfolio or forms are empty, or Logs show Mongo errors	`MONGO_URL` is wrong or Atlas does not allow `0.0.0.0/0`	Re-check Step 2 items 3, 4 and 6
`/admin` sends you to Account, Security	The authenticator app is not set up yet	Finish Step 6
The server answers `cms_not_configured`	`CMS_JWT_SECRET` is missing or shorter than 32 characters	Add it in Environment and save
Administrator sign-in refused	Wrong password, or the password contains your email name	Set a new `ADMIN_PASSWORD` in Environment and redeploy, then sign in again
The chat says it is unavailable	No `GEMINI_API_KEY`	Step 9
Company data stops updating	Render suspended the service for the month, or FinEdge limits were reached	Check the Render dashboard banner. Only one free service may run in the workspace
Neon says the compute allowance is used	Background jobs kept the database awake	In Render Environment add `QUOTES_EVERY_MINUTES` = `10`, and look at the Neon usage page

What needs a person (cannot be done by the software)

What	Who	When
Rotate the FinEdge key (the old key was exposed)	You, in the FinEdge dashboard and Render	Before launch
Create the Neon, MongoDB Atlas and Render accounts and paste the values	You	Steps 1 to 4
Buy the domain and verify it with Resend (DNS records)	You, with the registrar	After sign-off
Legal review of the Terms, Privacy notice and research disclosures	The company's legal adviser	Before launch
Payments (Razorpay or similar)	The company and an engineer: not built yet. Until then an administrator grants plans in `/console` after a member requests one	When the company decides
Weekly backup (Step 8)	You	Every week
Refresh the Upstox token, if the ticker is wanted	Whoever owns the Upstox account	Daily