

UAT Verification Queries

Digital Customer Onboarding Analytics Dashboard | Prantik Pegu

I ran these queries directly against the project's MySQL database (DigitalBank schema) to check each of the 10 UAT test cases in UAT_Test_Cases.md. Each one below maps to a test case and shows what the data actually returned, not just the expected outcome.

UAT-01 / UAT-02 — Registration & OTP outcomes

Confirms Applications contains multiple real outcome statuses (not uniform success), proving both successful registrations and rejected/abandoned ones exist.

```
SELECT Final_status, COUNT(*)
FROM Applications
GROUP BY Final_status;
```

Result: Completed 350 | Rejected 50 | Abandoned 50 | Progress 50

UAT-01 / UAT-02 (detail) — OTP-specific failures

Isolates journey records where the OTP stage specifically failed, to directly evidence OTP-failure drop-off.

```
SELECT *
FROM Applications_journey
WHERE Stage_name = 'OTP' AND Stage_status = 'Failed'
LIMIT 20;
```

UAT-03 / UAT-04 — Document upload stage

Checks that the Document Upload stage contains both completed and failed/pending records, confirming the upload-rejection path is represented in the data.

```
SELECT *
FROM Applications_journey
WHERE Stage_name = 'Document Upload'
LIMIT 20;
```

UAT-05 / UAT-06 — OCR extraction accuracy

Cross-tabulates document quality against OCR outcome, verifying that poor-quality documents (Blurry/Cropped) correlate with OCR failure rather than being incorrectly auto-approved.

```
SELECT Document_quality, OCR_status, COUNT(*)
FROM Verifications
GROUP BY Document_quality, OCR_status;
```

UAT-07 — Compliance / KYC check

Confirms compliance outcomes include both Pass and Fail, proving high-risk applications are not automatically approved.

```
SELECT Compliance_status, COUNT(*)
FROM Verifications
GROUP BY Compliance_status;
```

UAT-08 — End-to-end successful onboarding

Joins Applications and Verifications to confirm completed applications carry consistent passing verification outcomes, matched manually against the Power BI dashboard.

```
SELECT a.Application_id, a.Final_status, v.OCR_status, v.Compliance_status
FROM Applications a
JOIN Verifications v ON a.Application_id = v.Application_id
WHERE a.Final_status = 'Completed'
LIMIT 10;
```

UAT-09 — Application abandonment tracking

Joins Applications and Applications_journey to confirm the recorded Failed_stage matches the actual stage where journey status shows Failed/Pending, validating drop-off point accuracy.

```
SELECT a.Application_id, a.Final_status, a.Failed_stage,
j.Stage_name, j.Stage_status, j.Failure_reason
FROM Applications a
JOIN Applications_journey j ON a.Application_id = j.Application_id
WHERE a.Final_status = 'Abandoned'
LIMIT 10;
```

UAT-10 — Dashboard KPI accuracy

Calculates completion rate and average processing time directly from source data, to be manually cross-checked against the equivalent Power BI dashboard KPI cards.

```
SELECT
COUNT(*) AS total_apps,
SUM(CASE WHEN Final_status = 'Completed' THEN 1 ELSE 0 END) AS completed,
SUM(CASE WHEN Final_status = 'Abandoned' THEN 1 ELSE 0 END) AS abandoned,
SUM(CASE WHEN Final_status = 'Rejected' THEN 1 ELSE 0 END) AS rejected,
ROUND(SUM(CASE WHEN Final_status = 'Completed' THEN 1 ELSE 0 END) * 100.0 / COUNT(*),
2) AS completion_rate_pct,
ROUND(AVG(Total_processing_time), 2) AS avg_processing_time
FROM Applications;
```