

Assignment No.7

Student Name:	Prarthana Kumbhar
Branch:	Computer Engineering
Division:	SY I
PRN:	B25CE2014

Problem Statement:

Web Crawling:

A. Breadth First Search (BFS): Application: Indexing web pages for search engines. Example: A web crawler uses BFS to visit web pages systematically, starting from a seed URL and exploring links level by level. Nodes represent web pages. Edges represent hyperlinks. BFS ensures that pages at the same "depth" (distance from the starting page) are visited before moving to deeper levels. Write a program to simulate the indexing of web pages for a search engine using a Breadth-First Search (BFS) algorithm.

Program:

```
#include<iostream>
#define MAX 10

int queue[MAX], front = -1, rear = -1; int
visited[MAX] = {0}; int adj[MAX][MAX]; //
adjacency matrix

void enqueue(int v) { if (rear == MAX - 1)
    printf("Queue Overflow\n");
    else { if (front == -1)
        front = 0;
        queue[++rear] = v;
    } }
int dequeue() { if (front == -1 || front >
rear)
    return -1;
    return queue[front++];
} void bfs(int start, int n) {

    enqueue(start); visited[start] = 1;
    printf("\nIndexing pages starting from: %d\n", start);

    while (front <= rear) {
        int v = dequeue();
```

```


printf("Indexed page: %d\n", v);

for (int i = 0; i < n; i++) {
    if (adj[v][i] == 1 && !visited[i]) {
        enqueue(i); visited[i] = 1;
    }
}
}
} int main() { int n, e, from, to,
start;
printf("Enter number of web pages (max 10): "); scanf("%d", &n);

printf("\nEnter number of hyperlinks: ");
scanf("%d", &e);
// initialize adjacency matrix for (int i
= 0; i < n; i++) for (int j = 0; j < n;
j++) adj[i][j] = 0;
printf("\nEnter links (from to):\n"); for (int i = 0; i
< e; i++) {
    scanf("%d %d", &from, &to); adj[from][to] = 1;
}
printf("\nEnter seed/start page number: "); scanf("%d",
&start); bfs(start, n);
return 0;
}

```

Output:



```

C:\WINDOWS\SYSTEM32\cmd.exe
Enter number of web pages (max 10): 6

Enter number of hyperlinks: 5

Enter links (from to):
0 1
0 2
1 4
2 3
3 5

Enter seed/start page number: 0

Indexing pages starting from: 0
Indexed page: 0
Indexed page: 1
Indexed page: 2
Indexed page: 4
Indexed page: 3
Indexed page: 5

-----
(program exited with code: 0)

Press any key to continue . . .

```

B. Depth First Search (DFS): Application: Web crawlers use DFS to explore web pages systematically, following links and indexing content for search engines. Write a simple program to index web pages using Depth First Search (DFS). The program should simulate a web graph where pages are represented as nodes and hyperlinks as edges.

Program

```
#include <stdio.h> #define MAX 10 int
adj[MAX][MAX]; // adjacency matrix int visited[MAX];
// visited array
void dfs(int v, int n) { visited[v] = 1;
    printf("\n Indexed page: %d", v);

    for (int i = 0; i < n; i++) { if (adj[v][i] == 1 &&
        !visited[i]) { dfs(i, n);
        }
    }
}

int main() { int n, e, from, to,
    start;

    printf("Enter number of web pages (max 10): "); scanf("%d",
    &n); printf("\nEnter number of hyperlinks: ");
    scanf("%d", &e);
    // Initialize adjacency matrix for (int i
    = 0; i < n; i++) for (int j = 0; j < n; j++)
    adj[i][j] = 0;

    printf("\nEnter links (from to):\n");
    for (int i = 0; i < e; i++) {
        scanf("%d %d", &from, &to);
        adj[from][to] = 1;
    }
    printf("\nEnter seed (start) page number: "); scanf("%d", &start);
    printf("\n\nStarting DFS web crawling from page: %d\n", start); dfs(start, n); return 0;
}
```

Output:

```
C:\WINDOWS\SYSTEM32\cmd  ×  +  v
Enter number of web pages (max 10): 6
Enter number of hyperlinks: 5
Enter links (from to):
1 2
1 4
2 3
4 6
5 6

Enter seed/start page number: 1

Indexing pages starting from: 1
Indexed page: 1
Indexed page: 2
Indexed page: 4
Indexed page: 3

-----
(program exited with code: 0)

Press any key to continue . . .
```