ERP PROJECT

Aryaman Chaudhary : 2024118

Prarthna Sharma : 2024427

How to run:

1. Project Setup

- Download or clone the ERP project folder.
- Open it in IntelliJ, Eclipse, or VS Code.
- Make sure MySQL Connector/J is added to the project libraries.

2. Database Configuration The system uses two databases:

- authdb — login accounts
- erpdb — ERP data (courses, timetable, grades, registrations, settings)

3. Open file 'erp/data/DBConnection.java' and update the following to make a connection to database on your device:

- JDBC URL
- Username
- Password

4. Creating and importing SQL data:

- Open MYSQL Command Line Client (enter user password)
- Or run MYSQL on terminal ("mysql -u root -p")
- Download the files with .sql extension into a safe and easy to access directory.
- Import the files into MYSQL :
- Use command : USE authdb;
- Use command : SOURCE auth_backup.sql;
- Use command : USE erpdb;
- Use command : SOURCE erp_backup.sql;

5. 4. Verify Required Tables

authdb:

- users_auth

erpdb:

- users
- courses

- timetable
- registrations
- grades
- final_grades
- settings (maintenance mode)

Check with command : SHOW TABLES;

6. Run program:

From your IDE select LoginFrame.java and click run.

From terminal use commands:

- change directory to wherever you have saved the files (cd)
- use command : “javac LoginFrame.java;”
- use command : “java LoginFrame;”

7. Login:

- Admin logs in using the account inserted in users_auth.
- Students log in using accounts with role STUDENT.
- Instructors log in using accounts with role INSTRUCTOR.

8. Maintenance Mode

- Admin toggles maintenance in AdminDashboard.
- Value stored in erpdb.settings.
- Student dashboards read the value and disable registration & dropping when ON.
- Instructor dashboards read the value and disable grading when ON.
-

9. Common Errors:

- “Failed to open referenced table” → Missing foreign key target table.
- “Access denied” → Wrong DB credentials in DBConnection.
- Images not loading → Check resource path under /erp/ui/.
- Hash mismatch → Ensure bcrypt hash matches typed password.