

```
In [3]: #importing libs
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
```

```
In [4]: class NaiveBayesClassifier(object):

    def __init__(self):
        pass

    #Input: X - features of a trainset
    #        y - labels of a trainset
    def fit(self, X, y):
        self.X_train = X
        self.y_train = y

        self.no_of_classes = np.max(self.y_train) + 1

    #This is our function to calculate all nodes/samples in our radius
    def euclidianDistance(self, Xtest, Xtrain):
        return np.sqrt(np.sum(np.power((Xtest - Xtrain), 2)))

    #our main function is predict
    #All calculation is done by using our test or new samples
    #There are 4 steps to be performed:
    # 1. calculate Prior probability. Ex.  $P(A) = \text{No\_of\_elements\_of\_one\_class} / \text{total\_no\_of\_samples}$ 
    # 2. calculate Margin probability  $P(X) = \text{No\_of\_elements\_in\_radius} / \text{total\_no\_of\_samples}$ 
    # 3. calculate Likelihood  $(P(X|A) = \text{No\_of\_elements\_of\_current\_class} / \text{total\_no\_of\_samples})$ 
    # 4. calculate Posterior probability:  $P(A|X) = (P(X|A) * P(A)) / P(X)$ 
    # NOTE: Do these steps for all clases in dataset!
    #
    #Inputs: X - test dataset
    #        radius - this parameter is how big circle is going to be around our new datapoint, default = 2
    def predict(self, X, radius=0.4):
        pred = []

        #Creating list of numbers of elements for each class in trainset
        members_of_class = []
        for i in range(self.no_of_classes):
            counter = 0
            for j in range(len(self.y_train)):
                if self.y_train[j] == i:
```

```

        counter += 1
        members_of_class.append(counter)

#Entering the process of prediction
    for t in range(len(X)):
        #Creating empty list for every class probability
        prob_of_classes = []
        #looping through each class in dataset
        for i in range(self.no_of_classes):

            #1. step > Prior probability  $P(\text{class}) = \text{no\_of\_elements\_of\_that\_class} / \text{total\_no\_of\_elements}$ 
            prior_prob = members_of_class[i]/len(self.y_train)

            #2. step > Margin probability  $P(X) = \text{no\_of\_elements\_in\_radius} / \text{total\_no\_of\_elements}$ 
            #NOTE: In the same loop collecting information for
            3. step as well

            inRadius_no = 0
            #counter for how many points are from the current class in circle
            inRadius_no_current_class = 0

            for j in range(len(self.X_train)):
                if self.euclidianDistance(X[t], self.X_train[j]) < radius:

                    inRadius_no += 1
                    if self.y_train[j] == i:
                        inRadius_no_current_class += 1

            #Computing, margin probability
            margin_prob = inRadius_no/len(self.X_train)

            #3. step > Likelihood  $P(X|\text{current\_class}) = \text{no\_of\_elements\_in\_circle\_of\_current\_class} / \text{total\_no\_of\_elements}$ 
            likelihood = inRadius_no_current_class/len(self.X_train)

            #4. step > Posterior Probability > formula from Bayes theorem:  $P(\text{current\_class} | X) = (\text{likelihood} * \text{prior\_prob}) / \text{margin\_prob}$ 

            post_prob = (likelihood * prior_prob)/margin_prob
            prob_of_classes.append(post_prob)

            #Getting index of the biggest element (class with the biggest probability)
            pred.append(np.argmax(prob_of_classes))

    return pred

```

```
In [5]: def accuracy(y_tes, y_pred):
        correct = 0
        for i in range(len(y_pred)):
            if(y_tes[i] == y_pred[i]):
                correct += 1
        return (correct/len(y_tes))*100
```

```
In [2]: #Testing Breast Cancer dataset
def breastCancerTest():
    # Importing the dataset
    dataset = pd.read_csv('breastCancer.csv')
    dataset.replace('?', 0, inplace=True)
    dataset = dataset.applymap(np.int64)
    X = dataset.iloc[:, 1:-1].values
    y = dataset.iloc[:, -1].values
    #This part is necessary because of NUMBER of features part of a
lgo
    #and in this dataset classes are marked with 2 and 4
    y_new = []
    for i in range(len(y)):
        if y[i] == 2:
            y_new.append(0)
        else:
            y_new.append(1)
    y_new = np.array(y_new)

    # Splitting the dataset into the Training set and Test set
    from sklearn.cross_validation import train_test_split
    X_train, X_test, y_train, y_test = train_test_split(X, y, test_
size = 0.25, random_state = 0)

    #Testing my Naive Bayes Classifier
    NB = NaiveBayesClassifier()
    NB.fit(X_train, y_train)

    y_pred = NB.predict(X_test, radius=8)

    #sklearn
    from sklearn.naive_bayes import GaussianNB
    NB_sk = GaussianNB()
    NB_sk.fit(X_train, y_train)

    sk_pred = NB_sk.predict(X_test)

    print("Accuracy for my Naive Bayes Classifier: ", accuracy(y_te
st, y_pred), "%")
    print("Accuracy for sklearn Naive Bayes Classifier: ",accuracy(
y_test, sk_pred), "%")
```

In [7]: `breastCancerTest()`

Accuracy for my Naive Bayes Classifier: 96.57142857142857 %

Accuracy for sklearn Naive Bayes Classifier: 95.42857142857143 %