LAB ASSIGNMENT 15.2

Lab 15 – Backend API Development: Creating RESTful Services with AI

Name: A.V.Prasad

Rollno:2503A52400

Batch-14

## Task 1: Setup FastAPI Backend

### 2. Prompt :

Create a basic FastAPI app with a root GET endpoint that returns a welcome message.


### 3. Code

```
from fastapi import FastAPI

app = FastAPI()

@app.get("/")
def read_root():
    """Return a welcome message."""
    return {"message": "Welcome to AI-powered FastAPI"}
```

### 4. Output




### 5. Justification

FastAPI creates the backend application. The GET endpoint at / returns a welcome message and confirms that the server is running.

## Task 2: API – Create and Read Items

### 2. Prompt (Small)

Add GET and POST endpoints to retrieve and create items using a Python list.

### 3. Code

```
items = []


@app.get("/items")
def get_items():
    """Return all stored items."""
    return items

@app.post("/items")
```

```
def add_item(item: dict):
    """Add an item to the list."""
    items.append(item)
    return {"message": "Item created", "item": item}
```

### 4. Output

GET /items :




POST /items :




5. Justification

The GET endpoint displays the items in the list. The POST endpoint accepts an item as JSON, stores it in the list, and returns a confirmation message.

## Task 3: Update Existing Item

### 2. Prompt (Small)

Create a PUT endpoint that updates an item by its zero-based index and reports when the item is not found.


### 3. Code

```
@app.put("/items/{index}")
def update_item(index: int, item: dict):
    """Update an item at the given index."""
    if index < 0 or index >= len(items):
        raise HTTPException(status_code=404, detail="Item not found")
```

```
    items[index] = item
    return {"message": "Item updated", "item": item}
```

### 4. Output

PUT /items:




### 5. Justification

The PUT endpoint replaces the item at the specified index. It returns a 404 error if the index does not refer to an existing item.

## Task 4: Delete Item

### 2. Prompt (Small)

Create a DELETE endpoint that removes an item by its index and returns the deleted item.


### 3. Code

```
@app.delete("/items/{index}")
def delete_item(index: int):
    """Delete an item at the given index."""
    if index < 0 or index >= len(items):
        raise HTTPException(status_code=404, detail="Item not found")
```

```
    removed = items.pop(index)
    return {"message": "Item removed", "item": removed}
```

### 4. Output

DELETE /items/0:




### 5. Justification

The DELETE endpoint removes the selected item from the list and returns the removed item. Invalid indexes produce a 404 error.

## Task 5: Add Auto-Generated Documentation

### 2. Prompt (Small)

Add comments, docstrings, endpoint summaries, and Swagger documentation to the FastAPI endpoints.

### 3. Code

```
from fastapi import FastAPI, HTTPException

app = FastAPI(
    title="Items CRUD API",
    description="API for creating, reading, updating, and deleting items",
    version="1.0.0"
)

@app.get("/items", summary="Get all items")
```


```
def get_items():
    """Return all items stored in memory."""
    return items

@app.post("/items", summary="Create an item")
def add_item(item: dict):
    """Create and return a new item."""
    items.append(item)
    return {"message": "Item created", "item": item}
```

Add summaries and docstrings to the PUT and DELETE endpoints in the same way.

### 4. Output

Run the server and open:




Swagger UI displays the available endpoints, HTTP methods, descriptions, and request body fields.

### 5. Justification

FastAPI reads endpoint definitions, type hints, summaries, and docstrings to generate interactive Swagger documentation automatically. The /docs page helps users test the API without needing a separate API client.

## Complete Program Note

For a single runnable program, combine the endpoint code from Tasks 1–4 in one main.py file. Include the imports at the top: from fastapi import FastAPI, HTTPException. Define app = FastAPI() and items = [] only once. Task 5 documentation metadata can be added to that same FastAPI instance.

Run the completed program with: uvicorn main:app --reload

Note: The item list is temporary storage. Its contents are cleared when the server restarts.